



TEST DATA OF SUCS3243R3

Regulated DC Power Supply
Mar 23, 2005

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Hayato Nakatsubo
Hayato Nakatsubo Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Figure of Testing Circuitry	18

(Final Page 18)

COSEL

Model	SUCS3243R3	Temperature	25°C																																																																															
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																															
Object	_____																																																																																	
1. Graph		2. Values																																																																																
<p>The graph plots Input Current [A] on the y-axis (0.00 to 0.50) against Input Voltage [V] on the x-axis (0 to 50). Three data series are shown: Load 100% (triangles), Load 50% (squares), and Load 0% (circles). All series show a sharp increase in current from 0V to approximately 10V, followed by a gradual decrease. A slanted line is drawn through the origin, representing the rated input voltage range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>9.2</td><td>0.013</td><td>0.152</td><td>0.005</td></tr> <tr><td>9.6</td><td>0.013</td><td>0.146</td><td>0.302</td></tr> <tr><td>12.0</td><td>0.012</td><td>0.114</td><td>0.228</td></tr> <tr><td>16.0</td><td>0.011</td><td>0.086</td><td>0.166</td></tr> <tr><td>18.0</td><td>0.010</td><td>0.078</td><td>0.150</td></tr> <tr><td>20.0</td><td>0.010</td><td>0.070</td><td>0.132</td></tr> <tr><td>24.0</td><td>0.011</td><td>0.060</td><td>0.111</td></tr> <tr><td>28.0</td><td>0.011</td><td>0.053</td><td>0.096</td></tr> <tr><td>32.0</td><td>0.012</td><td>0.048</td><td>0.085</td></tr> <tr><td>36.0</td><td>0.014</td><td>0.045</td><td>0.077</td></tr> <tr><td>40.0</td><td>0.015</td><td>0.043</td><td>0.071</td></tr> <tr><td>42.4</td><td>0.015</td><td>0.042</td><td>0.069</td></tr> <tr><td>44.0</td><td>0.015</td><td>0.041</td><td>0.067</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	9.2	0.013	0.152	0.005	9.6	0.013	0.146	0.302	12.0	0.012	0.114	0.228	16.0	0.011	0.086	0.166	18.0	0.010	0.078	0.150	20.0	0.010	0.070	0.132	24.0	0.011	0.060	0.111	28.0	0.011	0.053	0.096	32.0	0.012	0.048	0.085	36.0	0.014	0.045	0.077	40.0	0.015	0.043	0.071	42.4	0.015	0.042	0.069	44.0	0.015	0.041	0.067	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
4.0	0.000	0.000	0.000																																																																															
8.0	0.000	0.000	0.000																																																																															
9.2	0.013	0.152	0.005																																																																															
9.6	0.013	0.146	0.302																																																																															
12.0	0.012	0.114	0.228																																																																															
16.0	0.011	0.086	0.166																																																																															
18.0	0.010	0.078	0.150																																																																															
20.0	0.010	0.070	0.132																																																																															
24.0	0.011	0.060	0.111																																																																															
28.0	0.011	0.053	0.096																																																																															
32.0	0.012	0.048	0.085																																																																															
36.0	0.014	0.045	0.077																																																																															
40.0	0.015	0.043	0.071																																																																															
42.4	0.015	0.042	0.069																																																																															
44.0	0.015	0.041	0.067																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SUCS3243R3	Temperature 25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry Figure A																																																			
Object	<hr/>																																																				
1.Graph	<p style="text-align: center;"> △ Input Volt. 18V □ Input Volt. 24V ○ Input Volt. 36V </p>																																																				
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.010</td><td>0.011</td><td>0.014</td></tr> <tr><td>0.12</td><td>0.037</td><td>0.030</td><td>0.026</td></tr> <tr><td>0.24</td><td>0.064</td><td>0.050</td><td>0.039</td></tr> <tr><td>0.36</td><td>0.091</td><td>0.070</td><td>0.051</td></tr> <tr><td>0.48</td><td>0.119</td><td>0.090</td><td>0.064</td></tr> <tr><td>0.60</td><td>0.148</td><td>0.111</td><td>0.078</td></tr> <tr><td>0.66</td><td>0.163</td><td>0.121</td><td>0.084</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.010	0.011	0.014	0.12	0.037	0.030	0.026	0.24	0.064	0.050	0.039	0.36	0.091	0.070	0.051	0.48	0.119	0.090	0.064	0.60	0.148	0.111	0.078	0.66	0.163	0.121	0.084	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.00	0.010	0.011	0.014																																																		
0.12	0.037	0.030	0.026																																																		
0.24	0.064	0.050	0.039																																																		
0.36	0.091	0.070	0.051																																																		
0.48	0.119	0.090	0.064																																																		
0.60	0.148	0.111	0.078																																																		
0.66	0.163	0.121	0.084																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.


COSEL

Model	SUCS3243R3	Temperature 25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry Figure A																																																			
Object	_____	_____																																																			
1. Graph																																																					
<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																					
2. Values																																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.19</td> <td>0.26</td> <td>0.49</td> </tr> <tr> <td>0.12</td> <td>0.66</td> <td>0.73</td> <td>0.93</td> </tr> <tr> <td>0.24</td> <td>1.14</td> <td>1.20</td> <td>1.39</td> </tr> <tr> <td>0.36</td> <td>1.63</td> <td>1.68</td> <td>1.85</td> </tr> <tr> <td>0.48</td> <td>2.14</td> <td>2.17</td> <td>2.32</td> </tr> <tr> <td>0.60</td> <td>2.66</td> <td>2.66</td> <td>2.80</td> </tr> <tr> <td>0.66</td> <td>2.92</td> <td>2.92</td> <td>3.05</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Input Power [W]			18[V]	24[V]	36[V]	0.00	0.19	0.26	0.49	0.12	0.66	0.73	0.93	0.24	1.14	1.20	1.39	0.36	1.63	1.68	1.85	0.48	2.14	2.17	2.32	0.60	2.66	2.66	2.80	0.66	2.92	2.92	3.05	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																				
	18[V]	24[V]	36[V]																																																		
0.00	0.19	0.26	0.49																																																		
0.12	0.66	0.73	0.93																																																		
0.24	1.14	1.20	1.39																																																		
0.36	1.63	1.68	1.85																																																		
0.48	2.14	2.17	2.32																																																		
0.60	2.66	2.66	2.80																																																		
0.66	2.92	2.92	3.05																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

COSEL

Model	SUCS3243R3
Item	Efficiency (by Input Voltage)
Object	_____

1. Graph


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
16	72.0	74.3
18	71.5	74.7
20	70.8	74.7
24	69.0	74.4
30	65.4	73.0
36	61.1	70.8
40	57.9	69.0
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.


coSEL

Model	SUCS3243R3	Temperature 25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry Figure A																																																			
Object	<hr/>																																																				
1.Graph	—△— Input Volt. 18V -□--- Input Volt. 24V -○--- Input Volt. 36V																																																				
	<p>The graph shows efficiency increasing with load current for all input voltages. The 18V curve is the highest, followed by 24V, and then 36V. A slanted line on the graph indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>18[V] (%)</th> <th>24[V] (%)</th> <th>36[V] (%)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.12</td><td>59.9</td><td>54.4</td><td>42.6</td></tr> <tr><td>0.24</td><td>69.3</td><td>66.1</td><td>56.9</td></tr> <tr><td>0.36</td><td>72.6</td><td>70.8</td><td>64.1</td></tr> <tr><td>0.48</td><td>74.1</td><td>73.1</td><td>68.2</td></tr> <tr><td>0.60</td><td>74.5</td><td>74.3</td><td>70.6</td></tr> <tr><td>0.66</td><td>74.6</td><td>74.6</td><td>71.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	18[V] (%)	24[V] (%)	36[V] (%)	0.00	-	-	-	0.12	59.9	54.4	42.6	0.24	69.3	66.1	56.9	0.36	72.6	70.8	64.1	0.48	74.1	73.1	68.2	0.60	74.5	74.3	70.6	0.66	74.6	74.6	71.5	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	18[V] (%)	24[V] (%)	36[V] (%)																																																		
0.00	-	-	-																																																		
0.12	59.9	54.4	42.6																																																		
0.24	69.3	66.1	56.9																																																		
0.36	72.6	70.8	64.1																																																		
0.48	74.1	73.1	68.2																																																		
0.60	74.5	74.3	70.6																																																		
0.66	74.6	74.6	71.5																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.12</td><td>59.9</td><td>54.4</td><td>42.6</td></tr> <tr><td>0.24</td><td>69.3</td><td>66.1</td><td>56.9</td></tr> <tr><td>0.36</td><td>72.6</td><td>70.8</td><td>64.1</td></tr> <tr><td>0.48</td><td>74.1</td><td>73.1</td><td>68.2</td></tr> <tr><td>0.60</td><td>74.5</td><td>74.3</td><td>70.6</td></tr> <tr><td>0.66</td><td>74.6</td><td>74.6</td><td>71.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	0.12	59.9	54.4	42.6	0.24	69.3	66.1	56.9	0.36	72.6	70.8	64.1	0.48	74.1	73.1	68.2	0.60	74.5	74.3	70.6	0.66	74.6	74.6	71.5	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.00	-	-	-																																																		
0.12	59.9	54.4	42.6																																																		
0.24	69.3	66.1	56.9																																																		
0.36	72.6	70.8	64.1																																																		
0.48	74.1	73.1	68.2																																																		
0.60	74.5	74.3	70.6																																																		
0.66	74.6	74.6	71.5																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Note: Slanted line shows the range of the rated load current.																																																					

COSEL

Model	SUCS3243R3
Item	Line Regulation
Object	+3.3V0.6A

1.Graph




Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	3.303	3.301
18	3.303	3.301
20	3.303	3.301
24	3.303	3.301
30	3.303	3.301
36	3.303	3.301
40	3.303	3.301
--	-	-
--	-	-

COSEL

Model	SUCS3243R3	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+3.3V0.6A																																																					
1.Graph	<p style="text-align: center;"> △ Input Volt. 18V - - - □ - - - Input Volt. 24V - - ○ - - Input Volt. 36V </p>  <p>The graph plots Output Voltage [V] on the Y-axis (3.22 to 3.36) against Load Current [A] on the X-axis (0.0 to 0.6). Three data series are shown for input voltages of 18V, 24V, and 36V. All series show a flat output voltage of approximately 3.30V across the entire load current range. A slanted line is drawn through the data points, representing the rated load current range.</p>																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>3.304</td><td>3.304</td><td>3.305</td></tr> <tr><td>0.12</td><td>3.304</td><td>3.304</td><td>3.304</td></tr> <tr><td>0.24</td><td>3.303</td><td>3.303</td><td>3.303</td></tr> <tr><td>0.36</td><td>3.302</td><td>3.302</td><td>3.302</td></tr> <tr><td>0.48</td><td>3.302</td><td>3.302</td><td>3.302</td></tr> <tr><td>0.60</td><td>3.301</td><td>3.301</td><td>3.301</td></tr> <tr><td>0.66</td><td>3.301</td><td>3.301</td><td>3.301</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	3.304	3.304	3.305	0.12	3.304	3.304	3.304	0.24	3.303	3.303	3.303	0.36	3.302	3.302	3.302	0.48	3.302	3.302	3.302	0.60	3.301	3.301	3.301	0.66	3.301	3.301	3.301	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	3.304	3.304	3.305																																																			
0.12	3.304	3.304	3.304																																																			
0.24	3.303	3.303	3.303																																																			
0.36	3.302	3.302	3.302																																																			
0.48	3.302	3.302	3.302																																																			
0.60	3.301	3.301	3.301																																																			
0.66	3.301	3.301	3.301																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	<p>Slanted line shows the range of the rated load current.</p>																																																					


COSEL

COSEL

Model	SUCS3243R3
Item	Ripple Voltage (by Load Current)
Object	+3.3V0.6A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.00	3	3
0.12	4	3
0.24	5	5
0.36	7	6
0.48	12	7
0.60	16	9
0.66	19	11
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

COSEL


Model SUCS3243R3

Item Ripple-Noise

Object +3.3V0.6A

Temperature 25°C
Testing Circuitry Figure B


1.Graph



Measured by 100 MHz Oscilloscope.
 Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

2.Values


Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.00	7	7
0.12	8	8
0.24	9	9
0.36	12	11
0.48	16	13
0.60	21	14
0.66	24	16
--	-	-
--	-	-
--	-	-
--	-	-



COSEL

Model	SUCS3243R3
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V0.6A

1. Graph




Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	15	23
-40	15	22
-20	14	21
0	13	19
25	10	14
55	6	10
60	6	10
--	-	-
--	-	-
--	-	-
--	-	-

COSEL


Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	3.286	3.287	3.288
-40	3.294	3.295	3.295
-20	3.299	3.299	3.300
0	3.301	3.301	3.302
25	3.301	3.301	3.301
55	3.298	3.298	3.298
60	3.298	3.297	3.297
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUCS3243R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V0.6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current : 0 - 0.6A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	36	0	3.305	± 6	± 0.2
Minimum Voltage	-40	18	0.6	3.294		

COSEL

Model	SUCS3243R3	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+3.3V0.6A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.304</td></tr> <tr><td>0.5</td><td>3.302</td></tr> <tr><td>1.0</td><td>3.302</td></tr> <tr><td>2.0</td><td>3.302</td></tr> <tr><td>3.0</td><td>3.302</td></tr> <tr><td>4.0</td><td>3.301</td></tr> <tr><td>5.0</td><td>3.301</td></tr> <tr><td>6.0</td><td>3.301</td></tr> <tr><td>7.0</td><td>3.301</td></tr> <tr><td>8.0</td><td>3.301</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	3.304	0.5	3.302	1.0	3.302	2.0	3.302	3.0	3.302	4.0	3.301	5.0	3.301	6.0	3.301	7.0	3.301	8.0	3.301
Time since start [H]	Output Voltage [V]																								
0.0	3.304																								
0.5	3.302																								
1.0	3.302																								
2.0	3.302																								
3.0	3.302																								
4.0	3.301																								
5.0	3.301																								
6.0	3.301																								
7.0	3.301																								
8.0	3.301																								

COSEL


Model SUCS3243R3

Item Rise and Fall Time

Object +3.3V0.6A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

[mS]


Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	1.0	1.1	0.1	0.6
100 %		0.1	1.0	1.1	0.1	0.3



COSEL

Model	SUCS3243R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V0.6A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	7.0	8.7
-40	6.9	8.8
-20	6.8	9.0
0	6.6	9.1
25	6.5	9.3
55	6.6	9.6
60	6.7	9.7
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	SUCS3243R3
Item	Overcurrent Protection
Object	+3.3V0.6A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
3.30	0.60	0.60	0.60
3.14	1.08	1.09	1.09
2.97	1.10	1.11	1.10
2.64	1.14	1.13	1.11
2.31	1.17	1.15	1.12
1.98	1.21	1.17	1.12
1.65	1.23	1.18	1.11
1.32	1.25	1.17	1.09
0.99	1.25	1.14	1.04
0.66	1.21	1.08	0.96
0.33	1.05	0.87	0.83
0.00	1.12	0.88	0.82




Figure A




Figure B (Ripple and Ripple noise Characteristic)