

Temperature increase of main components

Model: SUCS/SUCW1005


1. Conditions

- (1) Input :DC 4.5 - 9 [V]
 (2) Output :Rated output
 (3) Cooling method :Convection cooling
 (4) Mounting method :Shown as Fig.1.1

2. Result

Table 2.1 Temperature increase of main components

No.	Parts name	Symbol No.	Increase (ΔT)						Rated temp. [°C]	Reference
			[deg]							
			3.3V	5V	12V	15V	±12V	±15V		
1	Switching Transistor	TR31	53	51	49	46	47	43	150	Junction Temp.
2	Transformer	T11	60	53	55	50	51	49	155	
3	Rectifying MOS-FET	TR51	60	48	—	—	—	—	150	Junction Temp.
4	Rectifying Diode	D52	58	47	51	48	38	34	150	Junction Temp.
5	Photocoupler	PC11	47	42	43	39	35	31	125	Junction Temp.
6	Input Choke Coil	L11	47	44	45	40	42	38	120	
7	Output Choke Coil	L51	45	42	34	28	29	27	120	
8	Output Capacitor	C51	50	42	39	34	33	31	125	
9	Power Control IC	IC11	43	42	41	38	40	36	150	
10	Current Transformer	T12	43	41	41	37	38	33	155	
11										
12										
13										
14										
15										
16										
17										
18										
19										
20										



(Side view)

Fig.1.1 Mounting method
(Normal position)