

TEST DATA OF SUCW1R50512

Regulated DC Power Supply
Sep 14, 2004

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Masahiro Shima
Masahiro Shima Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

COSEL

Model	SUCW1R50512
Item	Input Current (by Input Voltage)
Object	<p>1.Graph</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>

 Temperature 25°C
 Testing Circuitry Figure A


2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0	0.000	0.000	0.000
1.7	0.000	0.000	0.000
2.0	0.000	0.000	0.000
2.5	0.086	0.826	0.811
3.0	0.074	0.455	0.848
3.2	0.071	0.434	0.841
4.0	0.061	0.300	0.639
4.5	0.057	0.264	0.530
5.0	0.054	0.238	0.457
6.0	0.049	0.199	0.368
7.0	0.045	0.171	0.314
8.0	0.041	0.152	0.274
9.0	0.039	0.138	0.243
10.0	0.038	0.128	0.221
-	-	-	-
-	-	-	-

COSEL

Model	SUCW1R50512	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Current (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph	<p style="text-align: center;"> Input Volt. 4.5V Input Volt. 5V Input Volt. 9V </p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 4.5V [A]</th> <th>Input Volt. 5V [A]</th> <th>Input Volt. 9V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.057</td><td>0.053</td><td>0.039</td></tr> <tr><td>20</td><td>0.137</td><td>0.124</td><td>0.080</td></tr> <tr><td>40</td><td>0.220</td><td>0.199</td><td>0.120</td></tr> <tr><td>60</td><td>0.311</td><td>0.278</td><td>0.160</td></tr> <tr><td>80</td><td>0.399</td><td>0.354</td><td>0.200</td></tr> <tr><td>100</td><td>0.510</td><td>0.443</td><td>0.242</td></tr> <tr><td>110</td><td>0.559</td><td>0.491</td><td>0.263</td></tr> </tbody> </table>			Load Ration [%]	Input Volt. 4.5V [A]	Input Volt. 5V [A]	Input Volt. 9V [A]	0	0.057	0.053	0.039	20	0.137	0.124	0.080	40	0.220	0.199	0.120	60	0.311	0.278	0.160	80	0.399	0.354	0.200	100	0.510	0.443	0.242	110	0.559	0.491	0.263																			
Load Ration [%]	Input Volt. 4.5V [A]	Input Volt. 5V [A]	Input Volt. 9V [A]																																																			
0	0.057	0.053	0.039																																																			
20	0.137	0.124	0.080																																																			
40	0.220	0.199	0.120																																																			
60	0.311	0.278	0.160																																																			
80	0.399	0.354	0.200																																																			
100	0.510	0.443	0.242																																																			
110	0.559	0.491	0.263																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.057</td><td>0.053</td><td>0.039</td></tr> <tr><td>20</td><td>0.137</td><td>0.124</td><td>0.080</td></tr> <tr><td>40</td><td>0.220</td><td>0.199</td><td>0.120</td></tr> <tr><td>60</td><td>0.311</td><td>0.278</td><td>0.160</td></tr> <tr><td>80</td><td>0.399</td><td>0.354</td><td>0.200</td></tr> <tr><td>100</td><td>0.510</td><td>0.443</td><td>0.242</td></tr> <tr><td>110</td><td>0.559</td><td>0.491</td><td>0.263</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.057	0.053	0.039	20	0.137	0.124	0.080	40	0.220	0.199	0.120	60	0.311	0.278	0.160	80	0.399	0.354	0.200	100	0.510	0.443	0.242	110	0.559	0.491	0.263	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0	0.057	0.053	0.039																																																			
20	0.137	0.124	0.080																																																			
40	0.220	0.199	0.120																																																			
60	0.311	0.278	0.160																																																			
80	0.399	0.354	0.200																																																			
100	0.510	0.443	0.242																																																			
110	0.559	0.491	0.263																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			


COSEL

Model	SUCW1R50512																																																				
Item	Input Power (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																			
Object	_____																																																				
1.Graph																																																					
—▲— Input Volt. 4.5V - -□--- Input Volt. 5V - -○--- Input Volt. 9V		2.Values																																																			
																																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>9[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.25</td> <td>0.27</td> <td>0.35</td> </tr> <tr> <td>20</td> <td>0.61</td> <td>0.63</td> <td>0.72</td> </tr> <tr> <td>40</td> <td>0.99</td> <td>1.00</td> <td>1.08</td> </tr> <tr> <td>60</td> <td>1.38</td> <td>1.38</td> <td>1.44</td> </tr> <tr> <td>80</td> <td>1.80</td> <td>1.77</td> <td>1.80</td> </tr> <tr> <td>100</td> <td>2.26</td> <td>2.20</td> <td>2.17</td> </tr> <tr> <td>110</td> <td>2.50</td> <td>2.42</td> <td>2.35</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Ration [%]	Input Power [W]			4.5[V]	5[V]	9[V]	0	0.25	0.27	0.35	20	0.61	0.63	0.72	40	0.99	1.00	1.08	60	1.38	1.38	1.44	80	1.80	1.77	1.80	100	2.26	2.20	2.17	110	2.50	2.42	2.35	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																				
	4.5[V]	5[V]	9[V]																																																		
0	0.25	0.27	0.35																																																		
20	0.61	0.63	0.72																																																		
40	0.99	1.00	1.08																																																		
60	1.38	1.38	1.44																																																		
80	1.80	1.77	1.80																																																		
100	2.26	2.20	2.17																																																		
110	2.50	2.42	2.35																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

COSEL

Model	SUCW1R50512
Item	Efficiency (by Input Voltage)
Object	_____

1.Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
4.0	67.1	64.1
4.5	67.3	68.9
5.0	67.6	71.3
6.0	67.0	73.0
7.0	66.2	73.5
8.0	65.1	73.2
9.0	63.6	72.8
9.5	62.9	72.3
-	-	-

COSEL

Model	SUCW1R50512
Item	Efficiency (by Load Current)
Object	

1.Graph

Load Ration [%]	Input Volt. 4.5V	Input Volt. 5V	Input Volt. 9V
20	53.5	52.2	46.0
40	64.6	64.3	59.4
60	69.0	69.5	66.3
80	70.5	71.5	70.4
100	70.0	72.1	72.9
110	69.4	71.8	73.8

Temperature 25°C
Testing Circuitry Figure A

2.Values


Load Ration [%]	Efficiency [%]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0	-	-	-
20	53.5	52.2	46.0
40	64.6	64.3	59.4
60	69.0	69.5	66.3
80	70.5	71.5	70.4
100	70.0	72.1	72.9
110	69.4	71.8	73.8
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	SUCW1R50512
Item	Line Regulation
Object	+12V0.065A

1.Graph

---□--- Load 50%
—△— Load 100%



Temperature 25°C
Testing Circuitry Figure A


2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.0	12.168	12.038
4.5	12.156	12.038
5.0	12.148	12.038
6.0	12.138	12.037
7.0	12.132	12.037
8.0	12.128	12.037
9.0	12.125	12.037
9.5	12.124	12.037
-	-	-

Object	-12V0.065A
--------	------------

1.Graph

---□--- Load 50%
—△— Load 100%



2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.0	-12.165	-12.031
4.5	-12.152	-12.031
5.0	-12.142	-12.031
6.0	-12.132	-12.031
7.0	-12.125	-12.031
8.0	-12.121	-12.030
9.0	-12.118	-12.030
9.5	-12.117	-12.030
-	-	-

Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	SUCW1R50512	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+12V0.065A																																																					
1.Graph	<p>Input Volt. 4.5V Input Volt. 5V Input Volt. 9V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.419</td><td>12.420</td><td>12.422</td></tr> <tr><td>0.010</td><td>12.248</td><td>12.238</td><td>12.216</td></tr> <tr><td>0.020</td><td>12.203</td><td>12.193</td><td>12.167</td></tr> <tr><td>0.030</td><td>12.165</td><td>12.156</td><td>12.132</td></tr> <tr><td>0.040</td><td>12.130</td><td>12.123</td><td>12.102</td></tr> <tr><td>0.050</td><td>12.095</td><td>12.090</td><td>12.076</td></tr> <tr><td>0.060</td><td>12.057</td><td>12.056</td><td>12.050</td></tr> <tr><td>0.065</td><td>12.037</td><td>12.038</td><td>12.038</td></tr> <tr><td>0.072</td><td>12.011</td><td>12.015</td><td>12.022</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	12.419	12.420	12.422	0.010	12.248	12.238	12.216	0.020	12.203	12.193	12.167	0.030	12.165	12.156	12.132	0.040	12.130	12.123	12.102	0.050	12.095	12.090	12.076	0.060	12.057	12.056	12.050	0.065	12.037	12.038	12.038	0.072	12.011	12.015	12.022	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.000	12.419	12.420	12.422																																																			
0.010	12.248	12.238	12.216																																																			
0.020	12.203	12.193	12.167																																																			
0.030	12.165	12.156	12.132																																																			
0.040	12.130	12.123	12.102																																																			
0.050	12.095	12.090	12.076																																																			
0.060	12.057	12.056	12.050																																																			
0.065	12.037	12.038	12.038																																																			
0.072	12.011	12.015	12.022																																																			
-	-	-	-																																																			
-	-	-	-																																																			
Object	-12V0.065A	2.Values																																																				
1.Graph	<p>Input Volt. 4.5V Input Volt. 5V Input Volt. 9V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.400</td><td>-12.401</td><td>-12.403</td></tr> <tr><td>0.010</td><td>-12.241</td><td>-12.231</td><td>-12.208</td></tr> <tr><td>0.020</td><td>-12.196</td><td>-12.186</td><td>-12.160</td></tr> <tr><td>0.030</td><td>-12.160</td><td>-12.150</td><td>-12.126</td></tr> <tr><td>0.040</td><td>-12.125</td><td>-12.117</td><td>-12.096</td></tr> <tr><td>0.050</td><td>-12.089</td><td>-12.084</td><td>-12.070</td></tr> <tr><td>0.060</td><td>-12.051</td><td>-12.050</td><td>-12.044</td></tr> <tr><td>0.065</td><td>-12.032</td><td>-12.032</td><td>-12.031</td></tr> <tr><td>0.072</td><td>-12.004</td><td>-12.009</td><td>-12.015</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	-12.400	-12.401	-12.403	0.010	-12.241	-12.231	-12.208	0.020	-12.196	-12.186	-12.160	0.030	-12.160	-12.150	-12.126	0.040	-12.125	-12.117	-12.096	0.050	-12.089	-12.084	-12.070	0.060	-12.051	-12.050	-12.044	0.065	-12.032	-12.032	-12.031	0.072	-12.004	-12.009	-12.015	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.000	-12.400	-12.401	-12.403																																																			
0.010	-12.241	-12.231	-12.208																																																			
0.020	-12.196	-12.186	-12.160																																																			
0.030	-12.160	-12.150	-12.126																																																			
0.040	-12.125	-12.117	-12.096																																																			
0.050	-12.089	-12.084	-12.070																																																			
0.060	-12.051	-12.050	-12.044																																																			
0.065	-12.032	-12.032	-12.031																																																			
0.072	-12.004	-12.009	-12.015																																																			
-	-	-	-																																																			
-	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL



COSEL




COSEL

Model SUCW1R50512

Item Ripple Voltage (by Load Current)

Object +12V0.065A

1. Graph



Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form

Temperature 25°C
Testing Circuitry Figure B


2. Values

Load Ration [%]	Ripple Voltage [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0	1	1
20	1	1
40	1	1
60	2	1
80	2	1
100	4	1
110	5	2
-	-	-
-	-	-
-	-	-
-	-	-

COSEL

Model	SUCW1R50512
Item	Ripple Voltage (by Load Current)
Object	-12V0.065A

1.Graph



Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

Temperature 25°C
Testing Circuitry Figure B


2.Values

Load Ration [%]	Ripple Voltage [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0	2	2
20	2	2
40	2	2
60	2	2
80	3	2
100	4	2
110	5	3
-	-	-
-	-	-
-	-	-
-	-	-

COSEL

Model	SUCW1R50512
Item	Ripple-Noise
Object	+12V0.065A

1.Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
Testing Circuitry Figure B


2.Values

Load Ration [%]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0	3	3
20	3	3
40	3	3
60	4	3
80	4	3
100	6	4
110	7	4
-	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	SUCW1R50512
Item	Ripple-Noise
Object	-12V0.065A

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
Testing Circuitry Figure B

2. Values


Load Ration [%]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0	4	4
20	4	5
40	4	5
60	5	5
80	5	5
100	6	5
110	7	5
-	-	-
-	-	-
-	-	-
-	-	-

COSEL

Model	SUCW1R50512
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.065A

1.Graph


---□--- Load 50%
—△— Load 100%



Object -12V0.065A

1.Graph

---□--- Load 50%
—△— Load 100%



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	6
-40	3	5
-20	2	5
0	1	3
25	1	2
55	1	2
60	1	2
-	-	-
-	-	-
-	-	-
-	-	-

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	4	5
-40	4	5
-20	4	4
0	3	3
25	2	3
55	2	2
60	2	2
-	-	-
-	-	-
-	-	-
-	-	-

COSEL

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
-60	12.046	12.046	12.046
-40	12.052	12.052	12.051
-20	12.053	12.053	12.052
0	12.049	12.048	12.048
25	12.038	12.038	12.037
55	12.019	12.017	12.016
60	12.015	12.014	12.013
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
-60	-12.039	-12.041	-12.039
-40	-12.045	-12.047	-12.045
-20	-12.047	-12.047	-12.046
0	-12.043	-12.043	-12.041
25	-12.032	-12.031	-12.030
55	-12.011	-12.011	-12.009
60	-12.007	-12.007	-12.005
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



Model	SUCW1R50512	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.065A (AVR 2) : 0 - 0.065A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$


$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+12V0.065A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	0	9	0	12.439	±212	±1.8
Minimum Voltage	55	9	0.065	12.016		

Object	-12V0.065A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	0	9	0	-12.418	±205	±1.7
Minimum Voltage	55	9	0.065	-12.009		


COSEL

Model	SUCW1R50512
Item	Time Lapse Drift
Object	+12V0.065A
1.Graph	
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V Load 100%</p>	
Object	

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	12.040
0.5	12.032
1.0	12.032
2.0	12.031
3.0	12.031
4.0	12.030
5.0	12.030
6.0	12.030
7.0	12.029
8.0	12.031




2.Values

Time since start [H]	Output Voltage [V]
0.0	-12.038
0.5	-12.030
1.0	-12.031
2.0	-12.030
3.0	-12.030
4.0	-12.029
5.0	-12.029
6.0	-12.029
7.0	-12.029
8.0	-12.030

COSEL

Model	SUCW1R50512	Temperature Testing Circuitry 25°C Figure A
Item	Rise and Fall Time	
Object	+12V0.065A	


1. Graph




2. Values

[mS]

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	3.3	3.4	0.1	3.6
100 %		0.1	3.6	3.7	0.1	1.8




COSEL

COSEL

Model	SUCW1R50512
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.065A

1.Graph

---□--- Load 50%
—△— Load 100%



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.3	3.1
-40	2.4	3.1
-20	2.3	3.2
0	2.4	3.3
25	2.5	3.3
55	2.5	3.4
60	2.5	3.4
-	-	-
-	-	-
-	-	-
-	-	-

Object	-12V0.065A
--------	------------

1.Graph

---□--- Load 50%
—△— Load 100%





2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.2	3.0
-40	2.2	3.0
-20	2.2	3.1
0	2.3	3.2
25	2.3	3.2
55	2.4	3.3
60	2.4	3.3
-	-	-
-	-	-
-	-	-
-	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	SUCW1R50512	Temperature	25°C
Item	Overcurrent Protection	Testing Circuitry	Figure A
Object	+12V0.065A		
1.Graph	 <p>Input Volt. 4.5V Input Volt. 5V Input Volt. 9V</p>	2.Values	
Object	-12V0.065A	Output Voltage [V]	Load Current [A]
1.Graph	 <p>Input Volt. 4.5V Input Volt. 5V Input Volt. 9V</p>	2.Values	
Note: Slanted line shows the range of the rated load current.		Output Voltage [V]	Load Current [A]
		Input Volt. 4.5V	Input Volt. 5V
		Input Volt. 9V	
		12.0	0.07
		11.4	0.12
		10.8	0.13
		9.6	0.15
		8.4	0.18
		7.2	0.20
		6.0	0.23
		4.8	0.25
		3.6	0.27
		2.4	0.29
		1.2	0.30
		0.0	0.28
		12.0	0.07
		11.4	0.12
		10.8	0.13
		9.6	0.15
		8.4	0.18
		7.2	0.20
		6.0	0.23
		4.8	0.25
		3.6	0.27
		2.4	0.29
		1.2	0.30
		0.0	0.28
		12.0	0.07
		11.4	0.12
		10.8	0.13
		9.6	0.15
		8.4	0.18
		7.2	0.20
		6.0	0.23
		4.8	0.25
		3.6	0.27
		2.4	0.29
		1.2	0.30
		0.0	0.28
		12.0	0.07
		11.4	0.12
		10.8	0.13
		9.6	0.15
		8.4	0.18
		7.2	0.20
		6.0	0.23
		4.8	0.25
		3.6	0.27
		2.4	0.29
		1.2	0.30
		0.0	0.28

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)