

TEST DATA OF SUCW1R52415

Regulated DC Power Supply
Sep 28, 2004

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Masahiro Shima
Masahiro Shima Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

COSEL

Model	SUCW1R52415																																																																									
Item	Input Current (by Input Voltage)																																																																									
Object	_____																																																																									
1.Graph																																																																										
<p>The graph plots Input Current [A] on the y-axis (0.00 to 0.30) against Input Voltage [V] on the x-axis (0 to 40). Three data series are shown: Load 100% (triangles), Load 50% (squares), and Load 0% (circles). A slanted line at approximately 12.5V marks the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.031</td><td>0.204</td><td>0.181</td></tr> <tr><td>8.4</td><td>0.029</td><td>0.182</td><td>0.212</td></tr> <tr><td>12.0</td><td>0.020</td><td>0.092</td><td>0.171</td></tr> <tr><td>16.0</td><td>0.017</td><td>0.071</td><td>0.127</td></tr> <tr><td>18.0</td><td>0.016</td><td>0.063</td><td>0.113</td></tr> <tr><td>20.0</td><td>0.015</td><td>0.057</td><td>0.101</td></tr> <tr><td>24.0</td><td>0.014</td><td>0.049</td><td>0.086</td></tr> <tr><td>28.0</td><td>0.013</td><td>0.043</td><td>0.074</td></tr> <tr><td>32.0</td><td>0.012</td><td>0.038</td><td>0.066</td></tr> <tr><td>36.0</td><td>0.012</td><td>0.035</td><td>0.060</td></tr> <tr><td>40.0</td><td>0.012</td><td>0.033</td><td>0.055</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.031	0.204	0.181	8.4	0.029	0.182	0.212	12.0	0.020	0.092	0.171	16.0	0.017	0.071	0.127	18.0	0.016	0.063	0.113	20.0	0.015	0.057	0.101	24.0	0.014	0.049	0.086	28.0	0.013	0.043	0.074	32.0	0.012	0.038	0.066	36.0	0.012	0.035	0.060	40.0	0.012	0.033	0.055	Temperature 25°C Testing Circuitry Figure A																	
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																							
0	0.000	0.000	0.000																																																																							
4.0	0.000	0.000	0.000																																																																							
8.0	0.031	0.204	0.181																																																																							
8.4	0.029	0.182	0.212																																																																							
12.0	0.020	0.092	0.171																																																																							
16.0	0.017	0.071	0.127																																																																							
18.0	0.016	0.063	0.113																																																																							
20.0	0.015	0.057	0.101																																																																							
24.0	0.014	0.049	0.086																																																																							
28.0	0.013	0.043	0.074																																																																							
32.0	0.012	0.038	0.066																																																																							
36.0	0.012	0.035	0.060																																																																							
40.0	0.012	0.033	0.055																																																																							
2.Values																																																																										
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.031</td><td>0.204</td><td>0.181</td></tr> <tr><td>8.4</td><td>0.029</td><td>0.182</td><td>0.212</td></tr> <tr><td>12.0</td><td>0.020</td><td>0.092</td><td>0.171</td></tr> <tr><td>16.0</td><td>0.017</td><td>0.071</td><td>0.127</td></tr> <tr><td>18.0</td><td>0.016</td><td>0.063</td><td>0.113</td></tr> <tr><td>20.0</td><td>0.015</td><td>0.057</td><td>0.101</td></tr> <tr><td>24.0</td><td>0.014</td><td>0.049</td><td>0.086</td></tr> <tr><td>28.0</td><td>0.013</td><td>0.043</td><td>0.074</td></tr> <tr><td>32.0</td><td>0.012</td><td>0.038</td><td>0.066</td></tr> <tr><td>36.0</td><td>0.012</td><td>0.035</td><td>0.060</td></tr> <tr><td>40.0</td><td>0.012</td><td>0.033</td><td>0.055</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.031	0.204	0.181	8.4	0.029	0.182	0.212	12.0	0.020	0.092	0.171	16.0	0.017	0.071	0.127	18.0	0.016	0.063	0.113	20.0	0.015	0.057	0.101	24.0	0.014	0.049	0.086	28.0	0.013	0.043	0.074	32.0	0.012	0.038	0.066	36.0	0.012	0.035	0.060	40.0	0.012	0.033	0.055	-	-	-	-	-	-	-	-	-	-	-	-
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0	0.000	0.000	0.000																																																																							
4.0	0.000	0.000	0.000																																																																							
8.0	0.031	0.204	0.181																																																																							
8.4	0.029	0.182	0.212																																																																							
12.0	0.020	0.092	0.171																																																																							
16.0	0.017	0.071	0.127																																																																							
18.0	0.016	0.063	0.113																																																																							
20.0	0.015	0.057	0.101																																																																							
24.0	0.014	0.049	0.086																																																																							
28.0	0.013	0.043	0.074																																																																							
32.0	0.012	0.038	0.066																																																																							
36.0	0.012	0.035	0.060																																																																							
40.0	0.012	0.033	0.055																																																																							
-	-	-	-																																																																							
-	-	-	-																																																																							
-	-	-	-																																																																							


Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SUCW1R52415	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Current (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph	<p style="text-align: center;"> —△— Input Volt. 18V ---□--- Input Volt. 24V ---○--- Input Volt. 36V </p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18V [A]</th> <th>24V [A]</th> <th>36V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.016</td><td>0.014</td><td>0.012</td></tr> <tr><td>20</td><td>0.035</td><td>0.028</td><td>0.021</td></tr> <tr><td>40</td><td>0.054</td><td>0.042</td><td>0.031</td></tr> <tr><td>60</td><td>0.074</td><td>0.056</td><td>0.040</td></tr> <tr><td>80</td><td>0.093</td><td>0.071</td><td>0.050</td></tr> <tr><td>100</td><td>0.112</td><td>0.085</td><td>0.059</td></tr> <tr><td>110</td><td>0.123</td><td>0.092</td><td>0.064</td></tr> </tbody> </table>			Load Ration [%]	18V [A]	24V [A]	36V [A]	0	0.016	0.014	0.012	20	0.035	0.028	0.021	40	0.054	0.042	0.031	60	0.074	0.056	0.040	80	0.093	0.071	0.050	100	0.112	0.085	0.059	110	0.123	0.092	0.064																			
Load Ration [%]	18V [A]	24V [A]	36V [A]																																																			
0	0.016	0.014	0.012																																																			
20	0.035	0.028	0.021																																																			
40	0.054	0.042	0.031																																																			
60	0.074	0.056	0.040																																																			
80	0.093	0.071	0.050																																																			
100	0.112	0.085	0.059																																																			
110	0.123	0.092	0.064																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.016</td><td>0.014</td><td>0.012</td></tr> <tr><td>20</td><td>0.035</td><td>0.028</td><td>0.021</td></tr> <tr><td>40</td><td>0.054</td><td>0.042</td><td>0.031</td></tr> <tr><td>60</td><td>0.074</td><td>0.056</td><td>0.040</td></tr> <tr><td>80</td><td>0.093</td><td>0.071</td><td>0.050</td></tr> <tr><td>100</td><td>0.112</td><td>0.085</td><td>0.059</td></tr> <tr><td>110</td><td>0.123</td><td>0.092</td><td>0.064</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			18[V]	24[V]	36[V]	0	0.016	0.014	0.012	20	0.035	0.028	0.021	40	0.054	0.042	0.031	60	0.074	0.056	0.040	80	0.093	0.071	0.050	100	0.112	0.085	0.059	110	0.123	0.092	0.064	—	-	-	-	—	-	-	-	—	-	-	-	—	-	-	-
Load Ration [%]	Input Current [A]																																																					
	18[V]	24[V]	36[V]																																																			
0	0.016	0.014	0.012																																																			
20	0.035	0.028	0.021																																																			
40	0.054	0.042	0.031																																																			
60	0.074	0.056	0.040																																																			
80	0.093	0.071	0.050																																																			
100	0.112	0.085	0.059																																																			
110	0.123	0.092	0.064																																																			
—	-	-	-																																																			
—	-	-	-																																																			
—	-	-	-																																																			
—	-	-	-																																																			

COSEL

Model	SUCW1R52415
Item	Input Power (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ration [%]	Input Power [W]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0	0.29	0.33	0.42
20	0.63	0.67	0.77
40	0.97	1.01	1.11
60	1.32	1.35	1.45
80	1.67	1.70	1.79
100	2.03	2.05	2.14
110	2.21	2.22	2.31
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

COSEL

Model	SUCW1R52415																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	_____	_____																																
1. Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (30 to 80) against Input Voltage [V] on the x-axis (10 to 40). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>16</td><td>67.8</td><td>75.4</td></tr> <tr><td>18</td><td>67.0</td><td>75.3</td></tr> <tr><td>20</td><td>66.4</td><td>75.3</td></tr> <tr><td>24</td><td>65.2</td><td>74.6</td></tr> <tr><td>30</td><td>63.0</td><td>73.3</td></tr> <tr><td>36</td><td>60.4</td><td>71.4</td></tr> <tr><td>40</td><td>57.9</td><td>69.8</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	16	67.8	75.4	18	67.0	75.3	20	66.4	75.3	24	65.2	74.6	30	63.0	73.3	36	60.4	71.4	40	57.9	69.8								
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
16	67.8	75.4																																
18	67.0	75.3																																
20	66.4	75.3																																
24	65.2	74.6																																
30	63.0	73.3																																
36	60.4	71.4																																
40	57.9	69.8																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>67.8</td><td>75.4</td></tr> <tr><td>18</td><td>67.0</td><td>75.3</td></tr> <tr><td>20</td><td>66.4</td><td>75.3</td></tr> <tr><td>24</td><td>65.2</td><td>74.6</td></tr> <tr><td>30</td><td>63.0</td><td>73.3</td></tr> <tr><td>36</td><td>60.4</td><td>71.4</td></tr> <tr><td>40</td><td>57.9</td><td>69.8</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	67.8	75.4	18	67.0	75.3	20	66.4	75.3	24	65.2	74.6	30	63.0	73.3	36	60.4	71.4	40	57.9	69.8	-	-	-	-	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
16	67.8	75.4																																
18	67.0	75.3																																
20	66.4	75.3																																
24	65.2	74.6																																
30	63.0	73.3																																
36	60.4	71.4																																
40	57.9	69.8																																
-	-	-																																
-	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL


Model SUCW1R52415

Item Efficiency (by Load Current)

Object _____

1. Graph

- ▲ — Input Volt. 18V
- - □ - - Input Volt. 24V
- - ○ - - Input Volt. 36V

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Ration [%]	Efficiency [%]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0	-	-	-
20	49.8	46.9	40.9
40	63.5	61.1	55.7
60	69.7	67.9	63.5
80	73.2	72.0	68.2
100	75.4	74.5	71.3
110	76.1	75.5	72.6
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

COSEL

Model SUCW1R52415		Temperature 25°C Testing Circuitry Figure A																																	
Item Line Regulation																																			
Object +15V0.05A																																			
1.Graph		2.Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>15.252</td><td>15.142</td></tr> <tr><td>18</td><td>15.245</td><td>15.142</td></tr> <tr><td>20</td><td>15.239</td><td>15.143</td></tr> <tr><td>24</td><td>15.233</td><td>15.143</td></tr> <tr><td>30</td><td>15.227</td><td>15.143</td></tr> <tr><td>36</td><td>15.224</td><td>15.143</td></tr> <tr><td>40</td><td>15.223</td><td>15.142</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	15.252	15.142	18	15.245	15.142	20	15.239	15.143	24	15.233	15.143	30	15.227	15.143	36	15.224	15.143	40	15.223	15.142	-	-	-	-	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
16	15.252	15.142																																	
18	15.245	15.142																																	
20	15.239	15.143																																	
24	15.233	15.143																																	
30	15.227	15.143																																	
36	15.224	15.143																																	
40	15.223	15.142																																	
-	-	-																																	
-	-	-																																	
Object -15V0.05A		2.Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>-15.266</td><td>-15.158</td></tr> <tr><td>18</td><td>-15.258</td><td>-15.158</td></tr> <tr><td>20</td><td>-15.253</td><td>-15.158</td></tr> <tr><td>24</td><td>-15.246</td><td>-15.157</td></tr> <tr><td>30</td><td>-15.241</td><td>-15.157</td></tr> <tr><td>36</td><td>-15.238</td><td>-15.156</td></tr> <tr><td>40</td><td>-15.237</td><td>-15.157</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	-15.266	-15.158	18	-15.258	-15.158	20	-15.253	-15.158	24	-15.246	-15.157	30	-15.241	-15.157	36	-15.238	-15.156	40	-15.237	-15.157	-	-	-	-	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
16	-15.266	-15.158																																	
18	-15.258	-15.158																																	
20	-15.253	-15.158																																	
24	-15.246	-15.157																																	
30	-15.241	-15.157																																	
36	-15.238	-15.156																																	
40	-15.237	-15.157																																	
-	-	-																																	
-	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL


Model	SUCW1R52415	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V0.05A																																																					
1.Graph		2.Values																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15.460</td><td>15.463</td><td>15.461</td></tr> <tr><td>0.008</td><td>15.330</td><td>15.317</td><td>15.308</td></tr> <tr><td>0.016</td><td>15.285</td><td>15.272</td><td>15.261</td></tr> <tr><td>0.024</td><td>15.248</td><td>15.237</td><td>15.228</td></tr> <tr><td>0.032</td><td>15.216</td><td>15.206</td><td>15.199</td></tr> <tr><td>0.040</td><td>15.183</td><td>15.177</td><td>15.173</td></tr> <tr><td>0.048</td><td>15.150</td><td>15.149</td><td>15.148</td></tr> <tr><td>0.050</td><td>15.143</td><td>15.142</td><td>15.142</td></tr> <tr><td>0.055</td><td>15.121</td><td>15.125</td><td>15.127</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	15.460	15.463	15.461	0.008	15.330	15.317	15.308	0.016	15.285	15.272	15.261	0.024	15.248	15.237	15.228	0.032	15.216	15.206	15.199	0.040	15.183	15.177	15.173	0.048	15.150	15.149	15.148	0.050	15.143	15.142	15.142	0.055	15.121	15.125	15.127	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	15.460	15.463	15.461																																																			
0.008	15.330	15.317	15.308																																																			
0.016	15.285	15.272	15.261																																																			
0.024	15.248	15.237	15.228																																																			
0.032	15.216	15.206	15.199																																																			
0.040	15.183	15.177	15.173																																																			
0.048	15.150	15.149	15.148																																																			
0.050	15.143	15.142	15.142																																																			
0.055	15.121	15.125	15.127																																																			
-	-	-	-																																																			
-	-	-	-																																																			
Object		2.Values																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-15.484</td><td>-15.487</td><td>-15.488</td></tr> <tr><td>0.008</td><td>-15.343</td><td>-15.332</td><td>-15.324</td></tr> <tr><td>0.016</td><td>-15.298</td><td>-15.284</td><td>-15.275</td></tr> <tr><td>0.024</td><td>-15.262</td><td>-15.249</td><td>-15.241</td></tr> <tr><td>0.032</td><td>-15.229</td><td>-15.219</td><td>-15.212</td></tr> <tr><td>0.040</td><td>-15.197</td><td>-15.191</td><td>-15.186</td></tr> <tr><td>0.048</td><td>-15.166</td><td>-15.163</td><td>-15.161</td></tr> <tr><td>0.050</td><td>-15.158</td><td>-15.157</td><td>-15.156</td></tr> <tr><td>0.055</td><td>-15.137</td><td>-15.139</td><td>-15.141</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-15.484	-15.487	-15.488	0.008	-15.343	-15.332	-15.324	0.016	-15.298	-15.284	-15.275	0.024	-15.262	-15.249	-15.241	0.032	-15.229	-15.219	-15.212	0.040	-15.197	-15.191	-15.186	0.048	-15.166	-15.163	-15.161	0.050	-15.158	-15.157	-15.156	0.055	-15.137	-15.139	-15.141	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	-15.484	-15.487	-15.488																																																			
0.008	-15.343	-15.332	-15.324																																																			
0.016	-15.298	-15.284	-15.275																																																			
0.024	-15.262	-15.249	-15.241																																																			
0.032	-15.229	-15.219	-15.212																																																			
0.040	-15.197	-15.191	-15.186																																																			
0.048	-15.166	-15.163	-15.161																																																			
0.050	-15.158	-15.157	-15.156																																																			
0.055	-15.137	-15.139	-15.141																																																			
-	-	-	-																																																			
-	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL


Model SUCW1R52415

Item Dynamic Load Response

Object +15V0.05A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 24 V
Cycle 100 mSMin. Load (0A) \longleftrightarrow
Load 100% (0.05A)


200mV/div



2ms/div

Min. Load (0A) \longleftrightarrow
Load 50% (0.025A)


200mV/div



2ms/div


Load 50% (0.025A) \longleftrightarrow
Load 100% (0.05A)

200mV/div



2ms/div

COSEL




COSEL

Model	SUCW1R52415
Item	Ripple Voltage (by Load Current)
Object	+15V0.05A

Temperature 25°C
Testing Circuitry Figure B

1.Graph

—△— Input Volt. 18V
---○--- Input Volt. 36V



2.Values

Load Ration [%]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0	1	2
20	1	2
40	2	2
60	2	2
80	3	2
100	3	2
110	4	2
-	-	-
-	-	-
-	-	-
-	-	-

Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	SUCW1R52415
Item	Ripple Voltage (by Load Current)
Object	-15V0.05A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Ration [%]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0	1	2
20	2	2
40	3	2
60	3	2
80	3	2
100	3	2
110	3	2
-	-	-
-	-	-
-	-	-
-	-	-

Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.




Fig.Complex Ripple Wave Form


COSEL

Model	SUCW1R52415																																					
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																				
Object	+15V0.05A																																					
1.Graph		2.Values																																				
	<p>—△— Input Volt. 18V - -○- - Input Volt. 36V</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 18 [V] [mV]</th> <th>Input Volt. 36 [V] [mV]</th> </tr> </thead> <tbody> <tr><td>0</td><td>4</td><td>4</td></tr> <tr><td>20</td><td>4</td><td>4</td></tr> <tr><td>40</td><td>4</td><td>4</td></tr> <tr><td>60</td><td>4</td><td>4</td></tr> <tr><td>80</td><td>4</td><td>4</td></tr> <tr><td>100</td><td>5</td><td>4</td></tr> <tr><td>110</td><td>5</td><td>5</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Volt. 18 [V] [mV]	Input Volt. 36 [V] [mV]	0	4	4	20	4	4	40	4	4	60	4	4	80	4	4	100	5	4	110	5	5	-	-	-	-	-	-	-	-	-	-	-	-	
Load Ration [%]	Input Volt. 18 [V] [mV]	Input Volt. 36 [V] [mV]																																				
0	4	4																																				
20	4	4																																				
40	4	4																																				
60	4	4																																				
80	4	4																																				
100	5	4																																				
110	5	5																																				
-	-	-																																				
-	-	-																																				
-	-	-																																				
-	-	-																																				
	<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below.</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																					

COSEL

Model	SUCW1R52415
Item	Ripple-Noise
Object	-15V0.05A

1. Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
Testing Circuitry Figure B


2. Values

Load Ration [%]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0	5	5
20	5	5
40	5	6
60	5	6
80	5	6
100	6	6
110	6	6
--	--	--
--	--	--
--	--	--
--	--	--

COSEL

Model	SUCW1R52415
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.05A

1. Graph




Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	2	3
-40	2	3
-20	2	2
0	2	2
25	2	2
55	2	2
60	2	2
—	—	—
—	—	—
—	—	—
—	—	—

1. Graph




2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	3
-40	3	3
-20	3	3
0	2	2
25	2	2
55	2	2
60	2	2
—	—	—
—	—	—
—	—	—
—	—	—

Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	15.077	15.077	15.077
-40	15.105	15.105	15.105
-20	15.124	15.124	15.124
0	15.136	15.136	15.136
25	15.142	15.142	15.142
55	15.138	15.137	15.137
60	15.136	15.135	15.135
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	-15.090	-15.090	-15.090
-40	-15.119	-15.118	-15.118
-20	-15.137	-15.137	-15.136
0	-15.150	-15.149	-15.149
25	-15.157	-15.156	-15.155
55	-15.154	-15.152	-15.151
60	-15.151	-15.151	-15.149
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated ambient temperature.




Model	SUCW1R52415	Testing Circuitry Figure A				
Item	Output Voltage Accuracy					
1. Output Voltage Accuracy						
<p>This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.</p> <p>Temperature : -40 - 55°C Input Voltage : 18 - 36V Load Current (AVR 1) : 0 - 0.05A (AVR 2):0 - 0.05A</p> <p>* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$</p> <p>* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$</p>						
2. Values						
Object		+15V0.05A				
Item	Temperature [°C]	Input Voltage[V]	Output	Output Voltage Accuracy		
			Current[A]	Voltage[V]	Value [mV] Ration [%]	
Maximum Voltage	25	24	0	15.459	±177	±1.2
Minimum Voltage	-40	36	0.05	15.105		
Object		-15V0.05A				
Item	Temperature [°C]	Input Voltage[V]	Output	Output Voltage Accuracy		
			Current[A]	Voltage[V]	Value [mV] Ration [%]	
Maximum Voltage	25	36	0	-15.485	±184	±1.2
Minimum Voltage	-40	36	0.05	-15.118		

COSEL


Model	SUCW1R52415
Item	Time Lapse Drift
Object	+15V0.05A

1.Graph



Input Volt. 24V
Load 100%

Object -15V0.05A



Input Volt. 24V
Load 100%

Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	15.141
0.5	15.142
1.0	15.142
2.0	15.143
3.0	15.143
4.0	15.144
5.0	15.143
6.0	15.142
7.0	15.141
8.0	15.140

2.Values

Time since start [H]	Output Voltage [V]
0.0	-15.161
0.5	-15.164
1.0	-15.165
2.0	-15.165
3.0	-15.166
4.0	-15.166
5.0	-15.166
6.0	-15.165
7.0	-15.164
8.0	-15.162

COSEL


Model SUCW1R52415

Item Rise and Fall Time

Object +15V0.05A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

[mS]

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	4.6	4.7	0.2	2.0
100 %		0.1	4.9	5.0	0.1	1.0



COSEL


Model SUCW1R52415

Item Rise and Fall Time

Object -15V0.05A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

[mS]

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	4.6	4.7	0.2	2.0
100 %		0.1	4.9	5.0	0.1	1.0




COSEL

Model	SUCW1R52415
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.05A

1.Graph

---□--- Load 50%
—△— Load 100%



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	9.2	9.5
-40	8.9	9.6
-20	8.7	9.7
0	8.5	9.9
25	8.2	10.1
55	8.0	10.5
60	8.0	10.6
-	-	-
-	-	-
-	-	-
-	-	-

Object	-15V0.05A
--------	-----------

1.Graph

---□--- Load 50%
—△— Load 100%



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	9.1	9.4
-40	8.9	9.5
-20	8.6	9.6
0	8.4	9.8
25	8.1	10.1
55	7.9	10.4
60	7.9	10.5
-	-	-
-	-	-
-	-	-
-	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	SUCW1R52415	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection																																																									
Object	+15V0.05A																																																									
1.Graph	<p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p>	2.Values																																																								
			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.05</td><td>0.05</td><td>0.05</td></tr> <tr><td>14.3</td><td>0.12</td><td>0.12</td><td>0.10</td></tr> <tr><td>13.5</td><td>0.13</td><td>0.12</td><td>0.11</td></tr> <tr><td>12.0</td><td>0.15</td><td>0.14</td><td>0.13</td></tr> <tr><td>10.5</td><td>0.17</td><td>0.16</td><td>0.14</td></tr> <tr><td>9.0</td><td>0.19</td><td>0.18</td><td>0.16</td></tr> <tr><td>7.5</td><td>0.21</td><td>0.19</td><td>0.18</td></tr> <tr><td>6.0</td><td>0.23</td><td>0.21</td><td>0.19</td></tr> <tr><td>4.5</td><td>0.25</td><td>0.22</td><td>0.20</td></tr> <tr><td>3.0</td><td>0.26</td><td>0.23</td><td>0.21</td></tr> <tr><td>1.5</td><td>0.27</td><td>0.23</td><td>0.22</td></tr> <tr><td>0.0</td><td>0.28</td><td>0.25</td><td>0.25</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			18[V]	24[V]	36[V]	15.0	0.05	0.05	0.05	14.3	0.12	0.12	0.10	13.5	0.13	0.12	0.11	12.0	0.15	0.14	0.13	10.5	0.17	0.16	0.14	9.0	0.19	0.18	0.16	7.5	0.21	0.19	0.18	6.0	0.23	0.21	0.19	4.5	0.25	0.22	0.20	3.0	0.26	0.23	0.21	1.5	0.27	0.23	0.22	0.0	0.28	0.25	0.25
Output Voltage [V]	Load Current [A]																																																									
	18[V]	24[V]	36[V]																																																							
15.0	0.05	0.05	0.05																																																							
14.3	0.12	0.12	0.10																																																							
13.5	0.13	0.12	0.11																																																							
12.0	0.15	0.14	0.13																																																							
10.5	0.17	0.16	0.14																																																							
9.0	0.19	0.18	0.16																																																							
7.5	0.21	0.19	0.18																																																							
6.0	0.23	0.21	0.19																																																							
4.5	0.25	0.22	0.20																																																							
3.0	0.26	0.23	0.21																																																							
1.5	0.27	0.23	0.22																																																							
0.0	0.28	0.25	0.25																																																							
Object	-15V0.05A	2.Values																																																								
1.Graph	<p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-15.00</td><td>0.05</td><td>0.05</td><td>0.05</td></tr> <tr><td>-14.25</td><td>0.12</td><td>0.12</td><td>0.10</td></tr> <tr><td>-13.50</td><td>0.13</td><td>0.13</td><td>0.11</td></tr> <tr><td>-12.00</td><td>0.15</td><td>0.14</td><td>0.13</td></tr> <tr><td>-10.50</td><td>0.17</td><td>0.16</td><td>0.14</td></tr> <tr><td>-9.00</td><td>0.19</td><td>0.18</td><td>0.16</td></tr> <tr><td>-7.50</td><td>0.21</td><td>0.19</td><td>0.18</td></tr> <tr><td>-6.00</td><td>0.23</td><td>0.21</td><td>0.19</td></tr> <tr><td>-4.50</td><td>0.25</td><td>0.22</td><td>0.20</td></tr> <tr><td>-3.00</td><td>0.26</td><td>0.23</td><td>0.21</td></tr> <tr><td>-1.50</td><td>0.27</td><td>0.23</td><td>0.22</td></tr> <tr><td>0.00</td><td>0.29</td><td>0.25</td><td>0.25</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			18[V]	24[V]	36[V]	-15.00	0.05	0.05	0.05	-14.25	0.12	0.12	0.10	-13.50	0.13	0.13	0.11	-12.00	0.15	0.14	0.13	-10.50	0.17	0.16	0.14	-9.00	0.19	0.18	0.16	-7.50	0.21	0.19	0.18	-6.00	0.23	0.21	0.19	-4.50	0.25	0.22	0.20	-3.00	0.26	0.23	0.21	-1.50	0.27	0.23	0.22	0.00	0.29	0.25	0.25
Output Voltage [V]	Load Current [A]																																																									
	18[V]	24[V]	36[V]																																																							
-15.00	0.05	0.05	0.05																																																							
-14.25	0.12	0.12	0.10																																																							
-13.50	0.13	0.13	0.11																																																							
-12.00	0.15	0.14	0.13																																																							
-10.50	0.17	0.16	0.14																																																							
-9.00	0.19	0.18	0.16																																																							
-7.50	0.21	0.19	0.18																																																							
-6.00	0.23	0.21	0.19																																																							
-4.50	0.25	0.22	0.20																																																							
-3.00	0.26	0.23	0.21																																																							
-1.50	0.27	0.23	0.22																																																							
0.00	0.29	0.25	0.25																																																							

Note: Slanted line shows the range of the rated load current.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)