

TEST DATA OF SUCW1R54812

Regulated DC Power Supply
Sep 29, 2004

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Masahiro Shima
Masahiro Shima Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

COSEL

Model	SUCW1R54812	Temperature Testing Circuitry	25°C Figure A
Item	Input Current (by Input Voltage)		
Object	—		
1. Graph		<p>Input Current [A]</p> <p>Input Voltage [V]</p> <ul style="list-style-type: none"> — ▲ — Load 100% --- ■ --- Load 50% --- ○ --- Load 0% 	
			2. Values
Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0	0.000	0.000	0.000
8.0	0.000	0.000	0.000
16.0	0.000	0.000	0.000
21.6	0.010	0.056	0.121
24.0	0.009	0.048	0.099
33.0	0.008	0.035	0.067
36.0	0.007	0.032	0.061
40.0	0.007	0.029	0.055
48.0	0.006	0.025	0.045
60.0	0.006	0.021	0.037
70.0	0.005	0.018	0.032
76.0	0.005	0.017	0.030
80.0	0.005	0.017	0.029
—	-	-	-
—	-	-	-
—	-	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SUCW1R54812	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
<p>Graph showing Input Current [A] vs Load Ration [%] for Model SUCW1R54812 at 25°C. The graph plots Input Current [A] on the y-axis (0.00 to 0.10) against Load Ration [%] on the x-axis (0 to 120). Three curves are shown for Input Voltages: 36V (solid line with triangles), 48V (dashed line with squares), and 76V (dash-dot line with circles). All curves show a linear increase in input current as load ratio increases.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.007</td><td>0.006</td><td>0.005</td></tr> <tr><td>20</td><td>0.017</td><td>0.014</td><td>0.010</td></tr> <tr><td>40</td><td>0.028</td><td>0.021</td><td>0.015</td></tr> <tr><td>60</td><td>0.038</td><td>0.029</td><td>0.020</td></tr> <tr><td>80</td><td>0.049</td><td>0.037</td><td>0.025</td></tr> <tr><td>100</td><td>0.061</td><td>0.045</td><td>0.030</td></tr> <tr><td>110</td><td>0.067</td><td>0.049</td><td>0.033</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.007	0.006	0.005	20	0.017	0.014	0.010	40	0.028	0.021	0.015	60	0.038	0.029	0.020	80	0.049	0.037	0.025	100	0.061	0.045	0.030	110	0.067	0.049	0.033	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	0.007	0.006	0.005																																																			
20	0.017	0.014	0.010																																																			
40	0.028	0.021	0.015																																																			
60	0.038	0.029	0.020																																																			
80	0.049	0.037	0.025																																																			
100	0.061	0.045	0.030																																																			
110	0.067	0.049	0.033																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			


COSEL

Model	SUCW1R54812	Temperature Testing Circuitry	25°C Figure A																														
Item	Input Power (by Load Current)																																
Object	_____																																
1.Graph		2.Values																															
<p>The graph plots Input Power [W] on the y-axis (0.0 to 5.0) against Load Ration [%] on the x-axis (0 to 120). Three data series are shown: Input Volt. 36V (solid line with open triangle markers), Input Volt. 48V (dashed line with open square markers), and Input Volt. 76V (dash-dot line with open circle markers). All three series show a positive linear correlation between input power and load ratio.</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 36V [W]</th> <th>Input Volt. 48V [W]</th> <th>Input Volt. 76V [W]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.26</td> <td>0.29</td> <td>0.40</td> </tr> <tr> <td>20</td> <td>0.62</td> <td>0.66</td> <td>0.78</td> </tr> <tr> <td>40</td> <td>0.99</td> <td>1.02</td> <td>1.15</td> </tr> <tr> <td>60</td> <td>1.36</td> <td>1.39</td> <td>1.51</td> </tr> <tr> <td>80</td> <td>1.74</td> <td>1.76</td> <td>1.87</td> </tr> <tr> <td>100</td> <td>2.12</td> <td>2.14</td> <td>2.24</td> </tr> <tr> <td>110</td> <td>2.32</td> <td>2.33</td> <td>2.43</td> </tr> </tbody> </table>		Load Ration [%]	Input Volt. 36V [W]	Input Volt. 48V [W]	Input Volt. 76V [W]	0	0.26	0.29	0.40	20	0.62	0.66	0.78	40	0.99	1.02	1.15	60	1.36	1.39	1.51	80	1.74	1.76	1.87	100	2.12	2.14	2.24	110	2.32	2.33	2.43
Load Ration [%]	Input Volt. 36V [W]	Input Volt. 48V [W]	Input Volt. 76V [W]																														
0	0.26	0.29	0.40																														
20	0.62	0.66	0.78																														
40	0.99	1.02	1.15																														
60	1.36	1.39	1.51																														
80	1.74	1.76	1.87																														
100	2.12	2.14	2.24																														
110	2.32	2.33	2.43																														
<p>The graph plots Input Power [W] on the y-axis (0.0 to 5.0) against Load Ration [%] on the x-axis (0 to 120). Three data series are shown: Input Volt. 36V (solid line with open triangle markers), Input Volt. 48V (dashed line with open square markers), and Input Volt. 76V (dash-dot line with open circle markers). All three series show a positive linear correlation between input power and load ratio.</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 36V [W]</th> <th>Input Volt. 48V [W]</th> <th>Input Volt. 76V [W]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.26</td> <td>0.29</td> <td>0.40</td> </tr> <tr> <td>20</td> <td>0.62</td> <td>0.66</td> <td>0.78</td> </tr> <tr> <td>40</td> <td>0.99</td> <td>1.02</td> <td>1.15</td> </tr> <tr> <td>60</td> <td>1.36</td> <td>1.39</td> <td>1.51</td> </tr> <tr> <td>80</td> <td>1.74</td> <td>1.76</td> <td>1.87</td> </tr> <tr> <td>100</td> <td>2.12</td> <td>2.14</td> <td>2.24</td> </tr> <tr> <td>110</td> <td>2.32</td> <td>2.33</td> <td>2.43</td> </tr> </tbody> </table>		Load Ration [%]	Input Volt. 36V [W]	Input Volt. 48V [W]	Input Volt. 76V [W]	0	0.26	0.29	0.40	20	0.62	0.66	0.78	40	0.99	1.02	1.15	60	1.36	1.39	1.51	80	1.74	1.76	1.87	100	2.12	2.14	2.24	110	2.32	2.33	2.43
Load Ration [%]	Input Volt. 36V [W]	Input Volt. 48V [W]	Input Volt. 76V [W]																														
0	0.26	0.29	0.40																														
20	0.62	0.66	0.78																														
40	0.99	1.02	1.15																														
60	1.36	1.39	1.51																														
80	1.74	1.76	1.87																														
100	2.12	2.14	2.24																														
110	2.32	2.33	2.43																														

COSEL

Model	SUCW1R54812
Item	Efficiency (by Input Voltage)
Object	—

1. Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
33	69.1	75.1
36	68.6	75.2
40	67.9	75.0
48	66.7	74.7
55	65.4	74.1
60	64.7	73.5
70	62.1	72.0
76	60.6	71.0
80	59.5	70.3

COSEL

Model	SUCW1R54812	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Efficiency [%]</p> <p>Load Ration [%]</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 36V - ■ - Input Volt. 48V - ○ - Input Volt. 76V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>52.8</td><td>50.0</td><td>42.2</td></tr> <tr><td>40</td><td>65.2</td><td>63.1</td><td>56.2</td></tr> <tr><td>60</td><td>70.5</td><td>69.0</td><td>63.6</td></tr> <tr><td>80</td><td>73.4</td><td>72.3</td><td>68.0</td></tr> <tr><td>100</td><td>74.9</td><td>74.4</td><td>71.0</td></tr> <tr><td>110</td><td>75.5</td><td>75.1</td><td>72.0</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	20	52.8	50.0	42.2	40	65.2	63.1	56.2	60	70.5	69.0	63.6	80	73.4	72.3	68.0	100	74.9	74.4	71.0	110	75.5	75.1	72.0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	-	-	-																																																			
20	52.8	50.0	42.2																																																			
40	65.2	63.1	56.2																																																			
60	70.5	69.0	63.6																																																			
80	73.4	72.3	68.0																																																			
100	74.9	74.4	71.0																																																			
110	75.5	75.1	72.0																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			


COSEL

Model SUCW1R54812

Item Line Regulation

Object +12V0.065A

1.Graph


Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
33	12.240	12.117
36	12.233	12.115
40	12.227	12.115
48	12.218	12.115
55	12.213	12.114
60	12.211	12.114
70	12.209	12.113
76	12.207	12.113
80	12.206	12.113

Object -12V0.065A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
33	-12.246	-12.117
36	-12.239	-12.118
40	-12.233	-12.119
48	-12.225	-12.118
55	-12.222	-12.119
60	-12.220	-12.120
70	-12.216	-12.120
76	-12.214	-12.120
80	-12.213	-12.119

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SUCW1R54812	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V0.065A																																																					
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>																																																					
<p>Output Voltage [V]</p> <p>Load Current [A]</p>			2.Values																																																			
Object	-12V0.065A																																																					
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>			2.Values																																																		
<p>Output Voltage [V]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.529</td><td>12.525</td><td>12.512</td></tr> <tr><td>0.010</td><td>12.340</td><td>12.326</td><td>12.317</td></tr> <tr><td>0.020</td><td>12.283</td><td>12.264</td><td>12.253</td></tr> <tr><td>0.030</td><td>12.243</td><td>12.227</td><td>12.215</td></tr> <tr><td>0.040</td><td>12.206</td><td>12.193</td><td>12.183</td></tr> <tr><td>0.050</td><td>12.171</td><td>12.161</td><td>12.154</td></tr> <tr><td>0.060</td><td>12.134</td><td>12.130</td><td>12.127</td></tr> <tr><td>0.065</td><td>12.116</td><td>12.115</td><td>12.113</td></tr> <tr><td>0.072</td><td>12.092</td><td>12.095</td><td>12.096</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	12.529	12.525	12.512	0.010	12.340	12.326	12.317	0.020	12.283	12.264	12.253	0.030	12.243	12.227	12.215	0.040	12.206	12.193	12.183	0.050	12.171	12.161	12.154	0.060	12.134	12.130	12.127	0.065	12.116	12.115	12.113	0.072	12.092	12.095	12.096	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	12.529	12.525	12.512																																																			
0.010	12.340	12.326	12.317																																																			
0.020	12.283	12.264	12.253																																																			
0.030	12.243	12.227	12.215																																																			
0.040	12.206	12.193	12.183																																																			
0.050	12.171	12.161	12.154																																																			
0.060	12.134	12.130	12.127																																																			
0.065	12.116	12.115	12.113																																																			
0.072	12.092	12.095	12.096																																																			
-	-	-	-																																																			
-	-	-	-																																																			
<p>Output Voltage [V]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.550</td><td>-12.542</td><td>-12.533</td></tr> <tr><td>0.010</td><td>-12.350</td><td>-12.339</td><td>-12.330</td></tr> <tr><td>0.020</td><td>-12.290</td><td>-12.275</td><td>-12.262</td></tr> <tr><td>0.030</td><td>-12.249</td><td>-12.234</td><td>-12.223</td></tr> <tr><td>0.040</td><td>-12.211</td><td>-12.199</td><td>-12.190</td></tr> <tr><td>0.050</td><td>-12.174</td><td>-12.167</td><td>-12.161</td></tr> <tr><td>0.060</td><td>-12.137</td><td>-12.134</td><td>-12.133</td></tr> <tr><td>0.065</td><td>-12.118</td><td>-12.118</td><td>-12.120</td></tr> <tr><td>0.072</td><td>-12.093</td><td>-12.098</td><td>-12.103</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	-12.550	-12.542	-12.533	0.010	-12.350	-12.339	-12.330	0.020	-12.290	-12.275	-12.262	0.030	-12.249	-12.234	-12.223	0.040	-12.211	-12.199	-12.190	0.050	-12.174	-12.167	-12.161	0.060	-12.137	-12.134	-12.133	0.065	-12.118	-12.118	-12.120	0.072	-12.093	-12.098	-12.103	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	-12.550	-12.542	-12.533																																																			
0.010	-12.350	-12.339	-12.330																																																			
0.020	-12.290	-12.275	-12.262																																																			
0.030	-12.249	-12.234	-12.223																																																			
0.040	-12.211	-12.199	-12.190																																																			
0.050	-12.174	-12.167	-12.161																																																			
0.060	-12.137	-12.134	-12.133																																																			
0.065	-12.118	-12.118	-12.120																																																			
0.072	-12.093	-12.098	-12.103																																																			
-	-	-	-																																																			
-	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						


COSEL

coSEL



Model SUCW1R54812

Item Dynamic Load Response


Object -12V0.065A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 48 V
Cycle 100 mSMin. Load (0A) \longleftrightarrow
Load 100% (0.065A)



200mV/div

Min. Load (0A) \longleftrightarrow
Load 50% (0.0325A)

200mV/div

Load 50% (0.0325A) \longleftrightarrow
Load 100% (0.065A)

200mV/div



COSEL


Model SUCW1R54812

Item Ripple Voltage (by Load Current)

Object +12V0.065A

1. Graph

—▲— Input Volt. 36V
 -○--- Input Volt. 76V



Measured by 100 MHz Oscilloscope.
 Ripple Voltage is shown as p-p in the figure below.

Ripple [mVp-p]






Fig. Complex Ripple Wave Form

Temperature 25°C
 Testing Circuitry Figure B

2. Values

Load Ration [%]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0	1	1
20	1	1
40	2	1
60	2	1
80	3	2
100	3	2
110	4	2
-	-	-
-	-	-
-	-	-
-	-	-

COSEL


Model	SUCW1R54812	Temperature 25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry Figure B																																						
Object	-12V0.065A																																							
1. Graph																																								
<p style="text-align: center;"> Input Volt. 36V Input Volt. 76V </p> 																																								
2. Values																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>2</td><td>3</td></tr> <tr><td>20</td><td>3</td><td>3</td></tr> <tr><td>40</td><td>3</td><td>3</td></tr> <tr><td>60</td><td>3</td><td>3</td></tr> <tr><td>80</td><td>3</td><td>3</td></tr> <tr><td>100</td><td>3</td><td>3</td></tr> <tr><td>110</td><td>5</td><td>3</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0	2	3	20	3	3	40	3	3	60	3	3	80	3	3	100	3	3	110	5	3	-	-	-	-	-	-	-	-	-	-	-	-
Load Ration [%]	Ripple Voltage [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0	2	3																																						
20	3	3																																						
40	3	3																																						
60	3	3																																						
80	3	3																																						
100	3	3																																						
110	5	3																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below.</p> <p style="text-align: center;">Ripple [mVp-p]</p> 																																								
<p>Fig.Complex Ripple Wave Form</p>																																								

COSEL

Model	SUCW1R54812
Item	Ripple-Noise
Object	+12V0.065A

1.Graph

—△— Input Volt. 36V
 -○--- Input Volt. 76V



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
 Testing Circuitry Figure B


2.Values

Load Ration [%]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0	3	3
20	3	3
40	4	4
60	4	4
80	5	4
100	6	5
110	7	5
-	-	-
-	-	-
-	-	-
-	-	-

COSEL

Model	SUCW1R54812
Item	Ripple-Noise
Object	-12V0.065A

1. Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
Testing Circuitry Figure B

2. Values

Load Ration [%]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0	5	5
20	5	5
40	6	6
60	6	6
80	6	6
100	7	7
110	8	7
-	-	-
-	-	-
-	-	-
-	-	-


COSEL

Model	SUCW1R54812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.065A
1.Graph	
<p style="text-align: center;">Input Volt. 48V</p>	

Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	2	5
-40	2	4
-20	2	4
0	1	3
25	1	2
55	1	2
60	1	2
-	-	-
-	-	-
-	-	-
-	-	-



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	4	4
-40	3	3
-20	3	3
0	3	3
25	3	3
55	2	2
60	2	2
-	-	-
-	-	-
-	-	-
-	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

<p>Model SUCW1R54812</p> <p>Item Ambient Temperature Drift</p> <p>Object +12V0.065A</p>	Testing Circuitry Figure A																																																					
	2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.106</td><td>12.104</td><td>12.102</td></tr> <tr><td>-40</td><td>12.116</td><td>12.115</td><td>12.113</td></tr> <tr><td>-20</td><td>12.122</td><td>12.121</td><td>12.118</td></tr> <tr><td>0</td><td>12.122</td><td>12.120</td><td>12.118</td></tr> <tr><td>25</td><td>12.113</td><td>12.112</td><td>12.110</td></tr> <tr><td>55</td><td>12.098</td><td>12.096</td><td>12.094</td></tr> <tr><td>60</td><td>12.095</td><td>12.093</td><td>12.091</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-60	12.106	12.104	12.102	-40	12.116	12.115	12.113	-20	12.122	12.121	12.118	0	12.122	12.120	12.118	25	12.113	12.112	12.110	55	12.098	12.096	12.094	60	12.095	12.093	12.091	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
-60	12.106	12.104	12.102																																																			
-40	12.116	12.115	12.113																																																			
-20	12.122	12.121	12.118																																																			
0	12.122	12.120	12.118																																																			
25	12.113	12.112	12.110																																																			
55	12.098	12.096	12.094																																																			
60	12.095	12.093	12.091																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
1.Graph																																																						
Object -12V0.065A		2.Values																																																				
1.Graph		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.103</td><td>-12.105</td><td>-12.108</td></tr> <tr><td>-40</td><td>-12.115</td><td>-12.116</td><td>-12.119</td></tr> <tr><td>-20</td><td>-12.121</td><td>-12.123</td><td>-12.125</td></tr> <tr><td>0</td><td>-12.122</td><td>-12.123</td><td>-12.125</td></tr> <tr><td>25</td><td>-12.116</td><td>-12.116</td><td>-12.117</td></tr> <tr><td>55</td><td>-12.101</td><td>-12.101</td><td>-12.101</td></tr> <tr><td>60</td><td>-12.098</td><td>-12.098</td><td>-12.099</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-60	-12.103	-12.105	-12.108	-40	-12.115	-12.116	-12.119	-20	-12.121	-12.123	-12.125	0	-12.122	-12.123	-12.125	25	-12.116	-12.116	-12.117	55	-12.101	-12.101	-12.101	60	-12.098	-12.098	-12.099	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
-60	-12.103	-12.105	-12.108																																																			
-40	-12.115	-12.116	-12.119																																																			
-20	-12.121	-12.123	-12.125																																																			
0	-12.122	-12.123	-12.125																																																			
25	-12.116	-12.116	-12.117																																																			
55	-12.101	-12.101	-12.101																																																			
60	-12.098	-12.098	-12.099																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
Note: Slanted line shows the range of the rated ambient temperature.																																																						



Model	SUCW1R54812	Testing Circuitry Figure A				
Item	Output Voltage Accuracy					
1. Output Voltage Accuracy						
<p>This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.</p> <p>Temperature : -40 - 55°C Input Voltage : 36 - 76V Load Current (AVR 1) : 0 - 0.065A (AVR 2) : 0 - 0.065A</p> <p>* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$</p> <p>* Output Voltage Accuracy (Ratio) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$</p>						
2. Values						
Object		+12V0.065A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	36	0	12.525	±216	±1.8
Minimum Voltage	55	76	0.065	12.094		
Object		-12V0.065A	Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	36	0	-12.546	±223	±1.9
Minimum Voltage	55	76	0.065	-12.101		

COSEL

Model	SUCW1R54812
Item	Time Lapse Drift
Object	+12V0.065A
1.Graph	
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>	
Object	

Temperature	25°C
Testing Circuitry	Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	12.122
0.5	12.117
1.0	12.117
2.0	12.117
3.0	12.117
4.0	12.118
5.0	12.118
6.0	12.117
7.0	12.117
8.0	12.117

Object	-12V0.065A
1.Graph	

2.Values

Time since start [H]	Output Voltage [V]
0.0	-12.133
0.5	-12.128
1.0	-12.128
2.0	-12.128
3.0	-12.128
4.0	-12.129
5.0	-12.128
6.0	-12.128
7.0	-12.129
8.0	-12.129

COSEL


Model SUCW1R54812

Item Rise and Fall Time


Object +12V0.065A

Temperature 25°C
Testing Circuitry Figure A

1. Graph




Input Volt. 36 V



2. Values

[mS]

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	3.5	3.6	0.2	1.3
100 %		0.1	3.7	3.8	0.1	0.6




COSEL

Model	SUCW1R54812
Item	Rise and Fall Time
Object	-12V0.065A


Temperature 25°C
Testing Circuitry Figure A

1. Graph





2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.1	3.5	3.6	0.2	1.3	
100 %		0.1	3.7	3.8	0.1	0.6	



COSEL

Model SUCW1R54812 Item Minimum Input Voltage for Regulated Output Voltage Object +12V0.065A		Testing Circuitry Figure A																																							
1.Graph		2.Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>16.3</td><td>19.3</td></tr> <tr><td>-40</td><td>16.3</td><td>19.7</td></tr> <tr><td>-20</td><td>15.8</td><td>20.3</td></tr> <tr><td>0</td><td>15.3</td><td>20.8</td></tr> <tr><td>25</td><td>15.3</td><td>21.3</td></tr> <tr><td>55</td><td>15.8</td><td>21.8</td></tr> <tr><td>60</td><td>15.8</td><td>22.3</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	16.3	19.3	-40	16.3	19.7	-20	15.8	20.3	0	15.3	20.8	25	15.3	21.3	55	15.8	21.8	60	15.8	22.3	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	16.3	19.3																																							
-40	16.3	19.7																																							
-20	15.8	20.3																																							
0	15.3	20.8																																							
25	15.3	21.3																																							
55	15.8	21.8																																							
60	15.8	22.3																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
Object -12V0.065A		2.Values																																							
1.Graph		2.Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>15.9</td><td>18.8</td></tr> <tr><td>-40</td><td>15.8</td><td>19.2</td></tr> <tr><td>-20</td><td>15.3</td><td>19.7</td></tr> <tr><td>0</td><td>14.8</td><td>20.3</td></tr> <tr><td>25</td><td>14.8</td><td>20.8</td></tr> <tr><td>55</td><td>15.3</td><td>21.3</td></tr> <tr><td>60</td><td>15.3</td><td>21.8</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	15.9	18.8	-40	15.8	19.2	-20	15.3	19.7	0	14.8	20.3	25	14.8	20.8	55	15.3	21.3	60	15.3	21.8	-	-	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	15.9	18.8																																							
-40	15.8	19.2																																							
-20	15.3	19.7																																							
0	14.8	20.3																																							
25	14.8	20.8																																							
55	15.3	21.3																																							
60	15.3	21.8																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									

COSEL

Model	SUCW1R54812	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection																																																									
Object	+12V0.065A																																																									
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>	2.Values																																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.07</td><td>0.07</td><td>0.07</td></tr> <tr><td>11.4</td><td>0.15</td><td>0.14</td><td>0.13</td></tr> <tr><td>10.8</td><td>0.15</td><td>0.15</td><td>0.14</td></tr> <tr><td>9.6</td><td>0.18</td><td>0.17</td><td>0.16</td></tr> <tr><td>8.4</td><td>0.20</td><td>0.19</td><td>0.18</td></tr> <tr><td>7.2</td><td>0.22</td><td>0.21</td><td>0.20</td></tr> <tr><td>6.0</td><td>0.24</td><td>0.23</td><td>0.22</td></tr> <tr><td>4.8</td><td>0.27</td><td>0.25</td><td>0.23</td></tr> <tr><td>3.6</td><td>0.29</td><td>0.27</td><td>0.25</td></tr> <tr><td>2.4</td><td>0.31</td><td>0.29</td><td>0.26</td></tr> <tr><td>1.2</td><td>0.33</td><td>0.29</td><td>0.27</td></tr> <tr><td>0.0</td><td>0.35</td><td>0.31</td><td>0.30</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	12.0	0.07	0.07	0.07	11.4	0.15	0.14	0.13	10.8	0.15	0.15	0.14	9.6	0.18	0.17	0.16	8.4	0.20	0.19	0.18	7.2	0.22	0.21	0.20	6.0	0.24	0.23	0.22	4.8	0.27	0.25	0.23	3.6	0.29	0.27	0.25	2.4	0.31	0.29	0.26	1.2	0.33	0.29	0.27	0.0	0.35	0.31	0.30	
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
12.0	0.07	0.07	0.07																																																							
11.4	0.15	0.14	0.13																																																							
10.8	0.15	0.15	0.14																																																							
9.6	0.18	0.17	0.16																																																							
8.4	0.20	0.19	0.18																																																							
7.2	0.22	0.21	0.20																																																							
6.0	0.24	0.23	0.22																																																							
4.8	0.27	0.25	0.23																																																							
3.6	0.29	0.27	0.25																																																							
2.4	0.31	0.29	0.26																																																							
1.2	0.33	0.29	0.27																																																							
0.0	0.35	0.31	0.30																																																							
Object	-12V0.065A	2.Values																																																								
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.07</td><td>0.07</td><td>0.07</td></tr> <tr><td>-11.4</td><td>0.15</td><td>0.14</td><td>0.13</td></tr> <tr><td>-10.8</td><td>0.15</td><td>0.15</td><td>0.14</td></tr> <tr><td>-9.6</td><td>0.18</td><td>0.17</td><td>0.16</td></tr> <tr><td>-8.4</td><td>0.20</td><td>0.19</td><td>0.18</td></tr> <tr><td>-7.2</td><td>0.22</td><td>0.21</td><td>0.20</td></tr> <tr><td>-6.0</td><td>0.24</td><td>0.23</td><td>0.21</td></tr> <tr><td>-4.8</td><td>0.27</td><td>0.25</td><td>0.23</td></tr> <tr><td>-3.6</td><td>0.29</td><td>0.27</td><td>0.25</td></tr> <tr><td>-2.4</td><td>0.31</td><td>0.29</td><td>0.26</td></tr> <tr><td>-1.2</td><td>0.32</td><td>0.29</td><td>0.27</td></tr> <tr><td>0.0</td><td>0.34</td><td>0.31</td><td>0.29</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-12.0	0.07	0.07	0.07	-11.4	0.15	0.14	0.13	-10.8	0.15	0.15	0.14	-9.6	0.18	0.17	0.16	-8.4	0.20	0.19	0.18	-7.2	0.22	0.21	0.20	-6.0	0.24	0.23	0.21	-4.8	0.27	0.25	0.23	-3.6	0.29	0.27	0.25	-2.4	0.31	0.29	0.26	-1.2	0.32	0.29	0.27	0.0	0.34	0.31	0.29	
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
-12.0	0.07	0.07	0.07																																																							
-11.4	0.15	0.14	0.13																																																							
-10.8	0.15	0.15	0.14																																																							
-9.6	0.18	0.17	0.16																																																							
-8.4	0.20	0.19	0.18																																																							
-7.2	0.22	0.21	0.20																																																							
-6.0	0.24	0.23	0.21																																																							
-4.8	0.27	0.25	0.23																																																							
-3.6	0.29	0.27	0.25																																																							
-2.4	0.31	0.29	0.26																																																							
-1.2	0.32	0.29	0.27																																																							
0.0	0.34	0.31	0.29																																																							

Note: Slanted line shows the range of the rated load current.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)