



TEST DATA OF SUS10243R3 SUCS10243R3

Regulated DC Power Supply
Mar 28, 2005

Approved by : *Tetsuo Sugimori*
Tetsuo Sugimori Design Manager

Prepared by : *Yoshimichi Hirokawa*
Yoshimichi Hirokawa Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) 1
 2.Input Current (by Load Current) 2
 3.Input Power (by Load Current) 3
 4.Efficiency (by Input Voltage) 4
 5.Efficiency (by Load Current) 5
 6.Line Regulation 6
 7.Load Regulation 7
 8.Dynamic Load Response 8
 9.Ripple Voltage (by Load Current) 9
 10.Ripple-Noise 10
 11.Ripple Voltage (by Ambient Temperature) 11
 12.Ambient Temperature Drift 12
 13.Output Voltage Accuracy 13
 14.Time Lapse Drift 14
 15.Rise and Fall Time 15
 16.Minimum Input Voltage for Regulated Output Voltage 16
 17.Overcurrent Protection 17
 18.Figure of Testing Circuitry 18

(Final Page 18)



Model		SUS10243R3/SUCS10243R3		Temperature	25°C																																																																															
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																															
Object		_____																																																																																		
1. Graph			—△— Load 100% - - - □ - - Load 50% - · - ○ - · - Load 0%	2. Values																																																																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>12.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>12.4</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>16.0</td><td>0.023</td><td>0.329</td><td>0.648</td></tr> <tr><td>18.0</td><td>0.024</td><td>0.294</td><td>0.574</td></tr> <tr><td>20.0</td><td>0.024</td><td>0.264</td><td>0.510</td></tr> <tr><td>24.0</td><td>0.024</td><td>0.222</td><td>0.428</td></tr> <tr><td>28.0</td><td>0.025</td><td>0.194</td><td>0.371</td></tr> <tr><td>32.0</td><td>0.025</td><td>0.175</td><td>0.327</td></tr> <tr><td>36.0</td><td>0.026</td><td>0.158</td><td>0.294</td></tr> <tr><td>40.0</td><td>0.027</td><td>0.146</td><td>0.268</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	8.0	0.001	0.001	0.001	12.0	0.001	0.001	0.001	12.4	0.001	0.001	0.001	16.0	0.023	0.329	0.648	18.0	0.024	0.294	0.574	20.0	0.024	0.264	0.510	24.0	0.024	0.222	0.428	28.0	0.025	0.194	0.371	32.0	0.025	0.175	0.327	36.0	0.026	0.158	0.294	40.0	0.027	0.146	0.268	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
4.0	0.000	0.000	0.000																																																																																	
8.0	0.001	0.001	0.001																																																																																	
12.0	0.001	0.001	0.001																																																																																	
12.4	0.001	0.001	0.001																																																																																	
16.0	0.023	0.329	0.648																																																																																	
18.0	0.024	0.294	0.574																																																																																	
20.0	0.024	0.264	0.510																																																																																	
24.0	0.024	0.222	0.428																																																																																	
28.0	0.025	0.194	0.371																																																																																	
32.0	0.025	0.175	0.327																																																																																	
36.0	0.026	0.158	0.294																																																																																	
40.0	0.027	0.146	0.268																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
Note: Slanted line shows the range of the rated input voltage.																																																																																				



Model		SUS10243R3/SUCS10243R3		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1. Graph		<p>—△— Input Volt. 18V</p> <p>- -□- - Input Volt. 24V</p> <p>- -○- - Input Volt. 36V</p>		2. Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.023</td><td>0.024</td><td>0.026</td></tr> <tr><td>0.52</td><td>0.127</td><td>0.103</td><td>0.078</td></tr> <tr><td>1.04</td><td>0.235</td><td>0.183</td><td>0.131</td></tr> <tr><td>1.56</td><td>0.351</td><td>0.267</td><td>0.185</td></tr> <tr><td>2.08</td><td>0.459</td><td>0.352</td><td>0.241</td></tr> <tr><td>2.60</td><td>0.577</td><td>0.437</td><td>0.299</td></tr> <tr><td>2.86</td><td>0.638</td><td>0.475</td><td>0.326</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.023	0.024	0.026	0.52	0.127	0.103	0.078	1.04	0.235	0.183	0.131	1.56	0.351	0.267	0.185	2.08	0.459	0.352	0.241	2.60	0.577	0.437	0.299	2.86	0.638	0.475	0.326	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0.00	0.023	0.024	0.026																																																					
0.52	0.127	0.103	0.078																																																					
1.04	0.235	0.183	0.131																																																					
1.56	0.351	0.267	0.185																																																					
2.08	0.459	0.352	0.241																																																					
2.60	0.577	0.437	0.299																																																					
2.86	0.638	0.475	0.326																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		SUS10243R3/SUCS10243R3		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 18V - - - □ - - Input Volt. 24V - · - ○ - · - Input Volt. 36V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.43</td><td>0.59</td><td>0.94</td></tr> <tr><td>0.52</td><td>2.31</td><td>2.48</td><td>2.83</td></tr> <tr><td>1.04</td><td>4.23</td><td>4.42</td><td>4.74</td></tr> <tr><td>1.56</td><td>6.30</td><td>6.41</td><td>6.69</td></tr> <tr><td>2.08</td><td>8.35</td><td>8.43</td><td>8.68</td></tr> <tr><td>2.60</td><td>10.44</td><td>10.46</td><td>10.76</td></tr> <tr><td>2.86</td><td>11.53</td><td>11.51</td><td>11.76</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.43	0.59	0.94	0.52	2.31	2.48	2.83	1.04	4.23	4.42	4.74	1.56	6.30	6.41	6.69	2.08	8.35	8.43	8.68	2.60	10.44	10.46	10.76	2.86	11.53	11.51	11.76	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0.00	0.43	0.59	0.94																																																					
0.52	2.31	2.48	2.83																																																					
1.04	4.23	4.42	4.74																																																					
1.56	6.30	6.41	6.69																																																					
2.08	8.35	8.43	8.68																																																					
2.60	10.44	10.46	10.76																																																					
2.86	11.53	11.51	11.76																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		SUS10243R3/SUCS10243R3																																	
Item		Efficiency (by Input Voltage)																																	
Object		Temperature 25°C Testing Circuitry Figure A																																	
1.Graph		2.Values																																	
<p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>81.7</td><td>81.8</td></tr> <tr><td>18</td><td>81.2</td><td>82.5</td></tr> <tr><td>20</td><td>81.2</td><td>82.7</td></tr> <tr><td>24</td><td>81.1</td><td>82.4</td></tr> <tr><td>30</td><td>77.9</td><td>81.4</td></tr> <tr><td>36</td><td>75.3</td><td>80.1</td></tr> <tr><td>40</td><td>73.8</td><td>79.2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	16	81.7	81.8	18	81.2	82.5	20	81.2	82.7	24	81.1	82.4	30	77.9	81.4	36	75.3	80.1	40	73.8	79.2	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
16	81.7	81.8																																	
18	81.2	82.5																																	
20	81.2	82.7																																	
24	81.1	82.4																																	
30	77.9	81.4																																	
36	75.3	80.1																																	
40	73.8	79.2																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



Model SUS10243R3/SUCS10243R3		Temperature 25°C Testing Circuitry Figure A																																																				
Item Efficiency (by Load Current)																																																						
Object _____																																																						
1.Graph <ul style="list-style-type: none"> —△— Input Volt. 18V - - -□- - Input Volt. 24V - · -○- · - Input Volt. 36V 		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.52</td><td>75.1</td><td>69.9</td><td>61.2</td></tr> <tr><td>1.04</td><td>81.8</td><td>78.3</td><td>73.0</td></tr> <tr><td>1.56</td><td>82.3</td><td>80.9</td><td>77.5</td></tr> <tr><td>2.08</td><td>82.7</td><td>82.0</td><td>79.6</td></tr> <tr><td>2.60</td><td>82.6</td><td>82.5</td><td>80.2</td></tr> <tr><td>2.86</td><td>82.2</td><td>82.4</td><td>80.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	0.52	75.1	69.9	61.2	1.04	81.8	78.3	73.0	1.56	82.3	80.9	77.5	2.08	82.7	82.0	79.6	2.60	82.6	82.5	80.2	2.86	82.2	82.4	80.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	-	-	-																																																			
0.52	75.1	69.9	61.2																																																			
1.04	81.8	78.3	73.0																																																			
1.56	82.3	80.9	77.5																																																			
2.08	82.7	82.0	79.6																																																			
2.60	82.6	82.5	80.2																																																			
2.86	82.2	82.4	80.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						



<p>Model SUS10243R3/SUCS10243R3</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>Item Line Regulation</p>																																		
<p>Object +3.3V2.6A</p>																																		
<p>1. Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>16</td><td>3.308</td><td>3.298</td></tr> <tr><td>18</td><td>3.308</td><td>3.299</td></tr> <tr><td>20</td><td>3.308</td><td>3.300</td></tr> <tr><td>24</td><td>3.308</td><td>3.301</td></tr> <tr><td>30</td><td>3.308</td><td>3.302</td></tr> <tr><td>36</td><td>3.308</td><td>3.302</td></tr> <tr><td>40</td><td>3.308</td><td>3.303</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	3.308	3.298	18	3.308	3.299	20	3.308	3.300	24	3.308	3.301	30	3.308	3.302	36	3.308	3.302	40	3.308	3.303	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
16	3.308	3.298																																
18	3.308	3.299																																
20	3.308	3.300																																
24	3.308	3.301																																
30	3.308	3.302																																
36	3.308	3.302																																
40	3.308	3.303																																
--	-	-																																
--	-	-																																




Model	SUS10243R3/SUCS10243R3
Item	Load Regulation
Object	+3.3V2.6A

Temperature 25°C
Testing Circuitry Figure A

1. Graph

- △— Input Volt. 18V
- Input Volt. 24V
- Input Volt. 36V



Note: Slanted line shows the range of the rated load current.


2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.00	3.313	3.313	3.314
0.52	3.311	3.311	3.311
1.04	3.309	3.309	3.310
1.56	3.306	3.307	3.307
2.08	3.303	3.304	3.305
2.60	3.299	3.300	3.302
2.86	3.296	3.299	3.300
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-




COSEL			
Model	SUS10243R3/SUCS10243R3	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+3.3V2.6A		


Input Volt. 24 V
Cycle 100 mS



Min. Load (0A) ←→
Load 100% (2.6A)




200µs/div




200µs/div

Min. Load (0A) ←→
Load 50% (1.3A)




200µs/div




200µs/div

Load 50% (1.3A) ←→
Load 100% (2.6A)



200µs/div



200µs/div



Model		SUS10243R3/SUCS10243R3		Temperature 25°C Testing Circuitry Figure B																																						
Item		Ripple Voltage (by Load Current)																																								
Object		+3.3V2.6A																																								
1. Graph			2. Values																																							
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>2</td></tr> <tr><td>0.52</td><td>5</td><td>6</td></tr> <tr><td>1.04</td><td>8</td><td>8</td></tr> <tr><td>1.56</td><td>13</td><td>12</td></tr> <tr><td>2.08</td><td>16</td><td>15</td></tr> <tr><td>2.60</td><td>21</td><td>15</td></tr> <tr><td>2.86</td><td>22</td><td>16</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.00	2	2	0.52	5	6	1.04	8	8	1.56	13	12	2.08	16	15	2.60	21	15	2.86	22	16	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Ripple Voltage [mV]																																									
	Input Volt. 18 [V]	Input Volt. 36 [V]																																								
0.00	2	2																																								
0.52	5	6																																								
1.04	8	8																																								
1.56	13	12																																								
2.08	16	15																																								
2.60	21	15																																								
2.86	22	16																																								
-	-	-																																								
-	-	-																																								
-	-	-																																								
-	-	-																																								
Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.																																										
Fig. Complex Ripple Wave Form																																										



<p>Model SUS10243R3/SUCS10243R3</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +3.3V2.6A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 18V - -○- - Input Volt. 36V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.52</td><td>18</td><td>16</td></tr> <tr><td>1.04</td><td>26</td><td>23</td></tr> <tr><td>1.56</td><td>32</td><td>30</td></tr> <tr><td>2.08</td><td>40</td><td>35</td></tr> <tr><td>2.60</td><td>48</td><td>40</td></tr> <tr><td>2.86</td><td>55</td><td>43</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.00	5	5	0.52	18	16	1.04	26	23	1.56	32	30	2.08	40	35	2.60	48	40	2.86	55	43	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.00	5	5																																						
0.52	18	16																																						
1.04	26	23																																						
1.56	32	30																																						
2.08	40	35																																						
2.60	48	40																																						
2.86	55	43																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
<p>Fig.Complex Ripple Noise Wave Form</p>																																								



Model		SUS10243R3/SUCS10243R3																																					
Item		Ripple Voltage (by Ambient Temp.)																																					
Object		+3.3V2.6A																																					
1.Graph		Testing Circuitry Figure B																																					
<p> ---□--- Load 50% ---△--- Load 100% </p> <p style="text-align: center;">Input Volt. 24V</p>		2.Values																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>26</td><td>36</td></tr> <tr><td>-40</td><td>22</td><td>33</td></tr> <tr><td>-20</td><td>17</td><td>26</td></tr> <tr><td>0</td><td>14</td><td>22</td></tr> <tr><td>25</td><td>11</td><td>18</td></tr> <tr><td>55</td><td>9</td><td>15</td></tr> <tr><td>60</td><td>10</td><td>15</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	26	36	-40	22	33	-20	17	26	0	14	22	25	11	18	55	9	15	60	10	15	-	-	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																						
	Load 50%	Load 100%																																					
-60	26	36																																					
-40	22	33																																					
-20	17	26																																					
0	14	22																																					
25	11	18																																					
55	9	15																																					
60	10	15																																					
-	-	-																																					
-	-	-																																					
-	-	-																																					
-	-	-																																					
<p>Measured by 100 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																							



Model		SUS10243R3/SUCS10243R3		Testing Circuitry Figure A																																																				
Item		Ambient Temperature Drift																																																						
Object		+3.3V2.6A																																																						
1. Graph		—△— Input Volt. 18V	24V	2. Values																																																				
		- - □ - - Input Volt. 24V	36V																																																					
		- · - ○ - · - Input Volt. 36V																																																						
<p>Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: right;">Load 100%</p>																																																								
				<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>3.281</td><td>3.283</td><td>3.285</td></tr> <tr><td>-40</td><td>3.286</td><td>3.289</td><td>3.291</td></tr> <tr><td>-20</td><td>3.291</td><td>3.294</td><td>3.296</td></tr> <tr><td>0</td><td>3.296</td><td>3.298</td><td>3.299</td></tr> <tr><td>25</td><td>3.298</td><td>3.300</td><td>3.301</td></tr> <tr><td>55</td><td>3.299</td><td>3.301</td><td>3.302</td></tr> <tr><td>60</td><td>3.299</td><td>3.301</td><td>3.302</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	3.281	3.283	3.285	-40	3.286	3.289	3.291	-20	3.291	3.294	3.296	0	3.296	3.298	3.299	25	3.298	3.300	3.301	55	3.299	3.301	3.302	60	3.299	3.301	3.302	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
-60	3.281	3.283	3.285																																																					
-40	3.286	3.289	3.291																																																					
-20	3.291	3.294	3.296																																																					
0	3.296	3.298	3.299																																																					
25	3.298	3.300	3.301																																																					
55	3.299	3.301	3.302																																																					
60	3.299	3.301	3.302																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																								



COSEL		
Model	SUS10243R3/SUCS10243R3	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+3.3V2.6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 36V

Load Current : 0 - 2.6A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	36	0	3.314	±14	±0.4
Minimum Voltage	-40	18	2.6	3.286		



COSEL																									
Model	SUS10243R3/SUCS10243R3	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+3.3V2.6A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.297</td></tr> <tr><td>0.5</td><td>3.298</td></tr> <tr><td>1.0</td><td>3.298</td></tr> <tr><td>2.0</td><td>3.298</td></tr> <tr><td>3.0</td><td>3.298</td></tr> <tr><td>4.0</td><td>3.298</td></tr> <tr><td>5.0</td><td>3.297</td></tr> <tr><td>6.0</td><td>3.297</td></tr> <tr><td>7.0</td><td>3.297</td></tr> <tr><td>8.0</td><td>3.297</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	3.297	0.5	3.298	1.0	3.298	2.0	3.298	3.0	3.298	4.0	3.298	5.0	3.297	6.0	3.297	7.0	3.297	8.0	3.297
Time since start [H]	Output Voltage [V]																								
0.0	3.297																								
0.5	3.298																								
1.0	3.298																								
2.0	3.298																								
3.0	3.298																								
4.0	3.298																								
5.0	3.297																								
6.0	3.297																								
7.0	3.297																								
8.0	3.297																								




Model	SUS10243R3/SUCS10243R3	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+3.3V2.6A		



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		5.1	0.6	5.7	0.2	0.4
100 %		5.0	0.7	5.7	0.1	0.2


[mS]





Model	SUS10243R3/SUCS10243R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V2.6A

Testing Circuitry Figure A



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	11.9	12.5
-40	11.7	12.3
-20	11.6	11.6
0	11.3	11.5
25	11.1	11.1
55	11.0	11.0
60	11.0	10.9
-	-	-
-	-	-
-	-	-
-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model SUS10243R3/SUCS10243R3		Temperature 25°C Testing Circuitry Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+3.3V2.6A																																																								
<p>1.Graph</p> <p> Input Volt. 18V Input Volt. 24V Input Volt. 36V </p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>3.30</td><td>2.89</td><td>2.93</td><td>2.96</td></tr> <tr><td>3.14</td><td>3.98</td><td>4.20</td><td>4.13</td></tr> <tr><td>2.97</td><td>4.16</td><td>4.41</td><td>4.36</td></tr> <tr><td>2.64</td><td>4.43</td><td>4.73</td><td>4.63</td></tr> <tr><td>2.31</td><td>4.65</td><td>4.86</td><td>4.71</td></tr> <tr><td>1.98</td><td>4.74</td><td>4.96</td><td>4.70</td></tr> <tr><td>1.65</td><td>4.81</td><td>4.99</td><td>4.61</td></tr> <tr><td>1.32</td><td>4.89</td><td>5.05</td><td>4.46</td></tr> <tr><td>0.99</td><td>5.03</td><td>5.11</td><td>4.14</td></tr> <tr><td>0.66</td><td>5.31</td><td>4.96</td><td>3.83</td></tr> <tr><td>0.33</td><td>5.26</td><td>4.83</td><td>3.57</td></tr> <tr><td>0.00</td><td>4.99</td><td>4.66</td><td>3.25</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	3.30	2.89	2.93	2.96	3.14	3.98	4.20	4.13	2.97	4.16	4.41	4.36	2.64	4.43	4.73	4.63	2.31	4.65	4.86	4.71	1.98	4.74	4.96	4.70	1.65	4.81	4.99	4.61	1.32	4.89	5.05	4.46	0.99	5.03	5.11	4.14	0.66	5.31	4.96	3.83	0.33	5.26	4.83	3.57	0.00	4.99	4.66	3.25
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																						
3.30	2.89	2.93	2.96																																																						
3.14	3.98	4.20	4.13																																																						
2.97	4.16	4.41	4.36																																																						
2.64	4.43	4.73	4.63																																																						
2.31	4.65	4.86	4.71																																																						
1.98	4.74	4.96	4.70																																																						
1.65	4.81	4.99	4.61																																																						
1.32	4.89	5.05	4.46																																																						
0.99	5.03	5.11	4.14																																																						
0.66	5.31	4.96	3.83																																																						
0.33	5.26	4.83	3.57																																																						
0.00	4.99	4.66	3.25																																																						




Figure A




Figure B (Ripple and Ripple noise Characteristic)