

TEST DATA OF SUS1R54812

Regulated DC Power Supply
Sep 28, 2004

Approved by : Tetsuo Sugimori
Tetsuo Sugimori Design Manager

Prepared by : Masahiro Shima
Masahiro Shima Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Figure of Testing Circuitry	18

(Final Page 18)



Model		SUS1R54812		Temperature		25°C																																																																								
Item		Input Current (by Input Voltage)		Testing Circuitry		Figure A																																																																								
Object		_____																																																																												
1. Graph				2. Values																																																																										
<p>Legend: —△— Load 100% - - □ - - Load 50% - - ○ - - Load 0%</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>21.6</td><td>0.006</td><td>0.054</td><td>0.120</td></tr> <tr><td>24.0</td><td>0.006</td><td>0.044</td><td>0.095</td></tr> <tr><td>33.0</td><td>0.005</td><td>0.032</td><td>0.063</td></tr> <tr><td>36.0</td><td>0.005</td><td>0.030</td><td>0.057</td></tr> <tr><td>40.0</td><td>0.005</td><td>0.027</td><td>0.051</td></tr> <tr><td>48.0</td><td>0.004</td><td>0.023</td><td>0.043</td></tr> <tr><td>60.0</td><td>0.004</td><td>0.019</td><td>0.035</td></tr> <tr><td>70.0</td><td>0.005</td><td>0.017</td><td>0.030</td></tr> <tr><td>76.0</td><td>0.005</td><td>0.017</td><td>0.029</td></tr> <tr><td>80.0</td><td>0.006</td><td>0.016</td><td>0.028</td></tr> <tr><td>88.0</td><td>0.007</td><td>0.016</td><td>0.026</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	21.6	0.006	0.054	0.120	24.0	0.006	0.044	0.095	33.0	0.005	0.032	0.063	36.0	0.005	0.030	0.057	40.0	0.005	0.027	0.051	48.0	0.004	0.023	0.043	60.0	0.004	0.019	0.035	70.0	0.005	0.017	0.030	76.0	0.005	0.017	0.029	80.0	0.006	0.016	0.028	88.0	0.007	0.016	0.026	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																													
	Load 0%	Load 50%	Load 100%																																																																											
0	0.000	0.000	0.000																																																																											
8.0	0.000	0.000	0.000																																																																											
16.0	0.000	0.000	0.000																																																																											
21.6	0.006	0.054	0.120																																																																											
24.0	0.006	0.044	0.095																																																																											
33.0	0.005	0.032	0.063																																																																											
36.0	0.005	0.030	0.057																																																																											
40.0	0.005	0.027	0.051																																																																											
48.0	0.004	0.023	0.043																																																																											
60.0	0.004	0.019	0.035																																																																											
70.0	0.005	0.017	0.030																																																																											
76.0	0.005	0.017	0.029																																																																											
80.0	0.006	0.016	0.028																																																																											
88.0	0.007	0.016	0.026																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																														



Model SUS1R54812		Temperature 25°C Testing Circuitry Figure A																																																				
Item Input Current (by Load Current)																																																						
Object _____																																																						
1.Graph		2.Values																																																				
<p> —△— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V </p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.005</td><td>0.004</td><td>0.005</td></tr> <tr><td>0.020</td><td>0.013</td><td>0.010</td><td>0.009</td></tr> <tr><td>0.040</td><td>0.020</td><td>0.016</td><td>0.012</td></tr> <tr><td>0.060</td><td>0.028</td><td>0.022</td><td>0.016</td></tr> <tr><td>0.080</td><td>0.036</td><td>0.028</td><td>0.020</td></tr> <tr><td>0.100</td><td>0.045</td><td>0.034</td><td>0.023</td></tr> <tr><td>0.120</td><td>0.053</td><td>0.040</td><td>0.027</td></tr> <tr><td>0.130</td><td>0.058</td><td>0.043</td><td>0.029</td></tr> <tr><td>0.143</td><td>0.064</td><td>0.047</td><td>0.031</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	0.005	0.004	0.005	0.020	0.013	0.010	0.009	0.040	0.020	0.016	0.012	0.060	0.028	0.022	0.016	0.080	0.036	0.028	0.020	0.100	0.045	0.034	0.023	0.120	0.053	0.040	0.027	0.130	0.058	0.043	0.029	0.143	0.064	0.047	0.031	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	0.005	0.004	0.005																																																			
0.020	0.013	0.010	0.009																																																			
0.040	0.020	0.016	0.012																																																			
0.060	0.028	0.022	0.016																																																			
0.080	0.036	0.028	0.020																																																			
0.100	0.045	0.034	0.023																																																			
0.120	0.053	0.040	0.027																																																			
0.130	0.058	0.043	0.029																																																			
0.143	0.064	0.047	0.031																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						



Model		SUS1R54812		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.17</td><td>0.21</td><td>0.39</td></tr> <tr><td>0.020</td><td>0.45</td><td>0.48</td><td>0.66</td></tr> <tr><td>0.040</td><td>0.72</td><td>0.76</td><td>0.93</td></tr> <tr><td>0.060</td><td>1.00</td><td>1.03</td><td>1.20</td></tr> <tr><td>0.080</td><td>1.28</td><td>1.31</td><td>1.47</td></tr> <tr><td>0.100</td><td>1.57</td><td>1.59</td><td>1.74</td></tr> <tr><td>0.120</td><td>1.86</td><td>1.87</td><td>2.02</td></tr> <tr><td>0.130</td><td>2.01</td><td>2.02</td><td>2.15</td></tr> <tr><td>0.143</td><td>2.20</td><td>2.20</td><td>2.33</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	0.17	0.21	0.39	0.020	0.45	0.48	0.66	0.040	0.72	0.76	0.93	0.060	1.00	1.03	1.20	0.080	1.28	1.31	1.47	0.100	1.57	1.59	1.74	0.120	1.86	1.87	2.02	0.130	2.01	2.02	2.15	0.143	2.20	2.20	2.33	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.000	0.17	0.21	0.39																																																					
0.020	0.45	0.48	0.66																																																					
0.040	0.72	0.76	0.93																																																					
0.060	1.00	1.03	1.20																																																					
0.080	1.28	1.31	1.47																																																					
0.100	1.57	1.59	1.74																																																					
0.120	1.86	1.87	2.02																																																					
0.130	2.01	2.02	2.15																																																					
0.143	2.20	2.20	2.33																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		SUS1R54812		Temperature 25°C																																	
Item		Efficiency (by Input Voltage)		Testing Circuitry Figure A																																	
Object		_____																																			
1.Graph			2.Values																																		
<p>---□--- Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>73.6</td><td>77.9</td></tr> <tr><td>36</td><td>73.1</td><td>78.0</td></tr> <tr><td>40</td><td>72.5</td><td>77.9</td></tr> <tr><td>48</td><td>71.3</td><td>77.6</td></tr> <tr><td>55</td><td>69.6</td><td>76.9</td></tr> <tr><td>60</td><td>68.0</td><td>76.2</td></tr> <tr><td>70</td><td>64.4</td><td>74.1</td></tr> <tr><td>76</td><td>62.0</td><td>72.7</td></tr> <tr><td>80</td><td>60.3</td><td>71.7</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	33	73.6	77.9	36	73.1	78.0	40	72.5	77.9	48	71.3	77.6	55	69.6	76.9	60	68.0	76.2	70	64.4	74.1	76	62.0	72.7	80	60.3	71.7
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
33	73.6	77.9																																			
36	73.1	78.0																																			
40	72.5	77.9																																			
48	71.3	77.6																																			
55	69.6	76.9																																			
60	68.0	76.2																																			
70	64.4	74.1																																			
76	62.0	72.7																																			
80	60.3	71.7																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					




Model	SUS1R54812
Item	Efficiency (by Load Current)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1. Graph

- △— Input Volt. 36V
- - □ - - Input Volt. 48V
- - ○ - - Input Volt. 76V



Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.000	-	-	-
0.020	54.8	51.0	37.3
0.040	67.1	64.1	52.3
0.060	72.3	70.3	60.5
0.080	75.2	73.5	65.7
0.100	76.7	75.8	69.2
0.120	77.7	77.2	71.7
0.130	78.0	77.6	72.7
0.143	78.2	78.1	73.8
-	-	-	-
--	-	-	-



Model SUS1R54812		Temperature 25°C Testing Circuitry Figure A																																
Item	Line Regulation																																	
Object	+12V0.13A																																	
1. Graph <div style="text-align: right;"> ---□--- Load 50% ---△--- Load 100% </div> <p style="text-align: center;">Input Voltage [V]</p>		2. Values <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>12.002</td><td>12.001</td></tr> <tr><td>36</td><td>12.001</td><td>12.000</td></tr> <tr><td>40</td><td>12.002</td><td>12.001</td></tr> <tr><td>48</td><td>12.002</td><td>12.000</td></tr> <tr><td>55</td><td>12.002</td><td>12.000</td></tr> <tr><td>60</td><td>12.002</td><td>12.000</td></tr> <tr><td>70</td><td>12.002</td><td>12.000</td></tr> <tr><td>76</td><td>12.002</td><td>12.000</td></tr> <tr><td>80</td><td>12.002</td><td>12.000</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	12.002	12.001	36	12.001	12.000	40	12.002	12.001	48	12.002	12.000	55	12.002	12.000	60	12.002	12.000	70	12.002	12.000	76	12.002	12.000	80	12.002	12.000
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	12.002	12.001																																
36	12.001	12.000																																
40	12.002	12.001																																
48	12.002	12.000																																
55	12.002	12.000																																
60	12.002	12.000																																
70	12.002	12.000																																
76	12.002	12.000																																
80	12.002	12.000																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		




<table border="1"> <tr> <td>Model</td> <td>SUS1R54812</td> </tr> <tr> <td>Item</td> <td>Load Regulation</td> </tr> <tr> <td>Object</td> <td>+12V0.13A</td> </tr> </table>		Model	SUS1R54812	Item	Load Regulation	Object	+12V0.13A	Temperature 25°C Testing Circuitry Figure A																																													
Model	SUS1R54812																																																				
Item	Load Regulation																																																				
Object	+12V0.13A																																																				
<p>1.Graph</p> <p> —△— Input Volt. 36V - - - □ - - - Input Volt. 48V - · - ○ - · - - Input Volt. 76V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.003</td><td>12.003</td><td>12.006</td></tr> <tr><td>0.020</td><td>12.003</td><td>12.003</td><td>12.004</td></tr> <tr><td>0.040</td><td>12.002</td><td>12.002</td><td>12.003</td></tr> <tr><td>0.060</td><td>12.002</td><td>12.002</td><td>12.002</td></tr> <tr><td>0.080</td><td>12.002</td><td>12.002</td><td>12.002</td></tr> <tr><td>0.100</td><td>12.002</td><td>12.001</td><td>12.002</td></tr> <tr><td>0.120</td><td>12.001</td><td>12.001</td><td>12.001</td></tr> <tr><td>0.130</td><td>12.001</td><td>12.001</td><td>12.001</td></tr> <tr><td>0.143</td><td>12.001</td><td>12.000</td><td>12.000</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	12.003	12.003	12.006	0.020	12.003	12.003	12.004	0.040	12.002	12.002	12.003	0.060	12.002	12.002	12.002	0.080	12.002	12.002	12.002	0.100	12.002	12.001	12.002	0.120	12.001	12.001	12.001	0.130	12.001	12.001	12.001	0.143	12.001	12.000	12.000	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.000	12.003	12.003	12.006																																																		
0.020	12.003	12.003	12.004																																																		
0.040	12.002	12.002	12.003																																																		
0.060	12.002	12.002	12.002																																																		
0.080	12.002	12.002	12.002																																																		
0.100	12.002	12.001	12.002																																																		
0.120	12.001	12.001	12.001																																																		
0.130	12.001	12.001	12.001																																																		
0.143	12.001	12.000	12.000																																																		
--	-	-	-																																																		
--	-	-	-																																																		




Model	SUS1R54812	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.13A		

Input Volt. 48 V
Cycle 100 mS




Min. Load (0A) ←→
Load 100% (0.13A)

100mV/div




2ms/div



2ms/div

Min. Load (0A) ←→
Load 50% (0.065A)

100mV/div




2ms/div



2ms/div

Load 50% (0.065A) ←→
Load 100% (0.13A)

100mV/div



2ms/div



2ms/div



Model		SUS1R54812		Temperature 25°C Testing Circuitry Figure B																																			
Item		Ripple Voltage (by Load Current)																																					
Object		+12V0.13A																																					
1. Graph			2. Values																																				
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>3</td><td>3</td></tr> <tr><td>0.026</td><td>3</td><td>3</td></tr> <tr><td>0.052</td><td>3</td><td>4</td></tr> <tr><td>0.078</td><td>3</td><td>4</td></tr> <tr><td>0.104</td><td>4</td><td>4</td></tr> <tr><td>0.130</td><td>4</td><td>4</td></tr> <tr><td>0.143</td><td>4</td><td>4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.000	3	3	0.026	3	3	0.052	3	4	0.078	3	4	0.104	4	4	0.130	4	4	0.143	4	4	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																						
	Input Volt. 36 [V]	Input Volt. 76 [V]																																					
0.000	3	3																																					
0.026	3	3																																					
0.052	3	4																																					
0.078	3	4																																					
0.104	4	4																																					
0.130	4	4																																					
0.143	4	4																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.																																							
Fig. Complex Ripple Wave Form																																							




<p>Model SUS1R54812</p> <p>Item Ripple-Noise</p> <p>Object +12V0.13A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p> —△— Input Volt. 36V - - -○- - - Input Volt. 76V </p> <p>Ripple-Noise [mV]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.026</td><td>5</td><td>6</td></tr> <tr><td>0.052</td><td>6</td><td>6</td></tr> <tr><td>0.078</td><td>7</td><td>7</td></tr> <tr><td>0.104</td><td>8</td><td>8</td></tr> <tr><td>0.130</td><td>8</td><td>8</td></tr> <tr><td>0.143</td><td>9</td><td>9</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.000	5	5	0.026	5	6	0.052	6	6	0.078	7	7	0.104	8	8	0.130	8	8	0.143	9	9	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.000	5	5																																						
0.026	5	6																																						
0.052	6	6																																						
0.078	7	7																																						
0.104	8	8																																						
0.130	8	8																																						
0.143	9	9																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								



Model	SUS1R54812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.13A

Testing Circuitry Figure B

1. Graph



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	6
-40	5	6
-20	5	5
0	4	4
25	3	4
55	2	3
60	2	3
-	-	-
-	-	-
-	-	-
-	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.




Model	SUS1R54812
Item	Ambient Temperature Drift
Object	+12V0.13A

Testing Circuitry Figure A

1.Graph

- △— Input Volt. 36V
- - -□- - - Input Volt. 48V
- · - ○ - · - - Input Volt. 76V



Load 100%

Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	11.993	11.994	11.994
-40	12.002	12.003	12.003
-20	12.007	12.007	12.007
0	12.007	12.007	12.006
25	12.000	11.999	11.999
55	11.986	11.985	11.984
60	11.983	11.982	11.980
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



COSEL		
Model	SUS1R54812	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V0.13A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 0.13A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	0	76	0	12.013	±15	±0.1
Minimum Voltage	55	76	0.13	11.984		




Model		SUS1R54812		Temperature		25°C																							
Item		Time Lapse Drift		Testing Circuitry		Figure A																							
Object		+12V0.13A																											
1.Graph				2.Values																									
<p style="text-align: center;">Time [H]</p> <p>Input Volt. 48V Load 100%</p>				<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.004</td></tr> <tr><td>0.5</td><td>11.999</td></tr> <tr><td>1.0</td><td>11.999</td></tr> <tr><td>2.0</td><td>11.999</td></tr> <tr><td>3.0</td><td>11.999</td></tr> <tr><td>4.0</td><td>11.999</td></tr> <tr><td>5.0</td><td>11.999</td></tr> <tr><td>6.0</td><td>11.999</td></tr> <tr><td>7.0</td><td>11.999</td></tr> <tr><td>8.0</td><td>11.999</td></tr> </tbody> </table>				Time since start [H]	Output Voltage [V]	0.0	12.004	0.5	11.999	1.0	11.999	2.0	11.999	3.0	11.999	4.0	11.999	5.0	11.999	6.0	11.999	7.0	11.999	8.0	11.999
Time since start [H]	Output Voltage [V]																												
0.0	12.004																												
0.5	11.999																												
1.0	11.999																												
2.0	11.999																												
3.0	11.999																												
4.0	11.999																												
5.0	11.999																												
6.0	11.999																												
7.0	11.999																												
8.0	11.999																												




Model	SUS1R54812	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.13A		

1. Graph



2. Values

Load	Time	[mS]				
		Td	Tr	Ts	Th	Tf
50 %		0.1	3.2	3.3	0.1	2.9
100 %		0.1	3.3	3.4	0.1	1.5






Model	SUS1R54812
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.13A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	20.0	20.8
-40	19.7	21.2
-20	19.2	21.6
0	18.7	21.8
25	17.9	22.0
55	17.5	22.6
60	17.2	22.5
-	-	-
-	-	-
-	-	-
-	-	-




Model	SUS1R54812
Item	Overcurrent Protection
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure A

1.Graph

_____ Input Volt. 36V
 _____ Input Volt. 48V
 _____ Input Volt. 76V



Note: Slanted line shows the range of the rated load current.

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
12.0	0.13	0.13	0.13
11.4	0.20	0.19	0.18
10.8	0.21	0.20	0.18
9.6	0.22	0.21	0.19
8.4	0.24	0.23	0.20
7.2	0.26	0.24	0.22
6.0	0.27	0.25	0.23
4.8	0.29	0.26	0.24
3.6	0.30	0.27	0.25
2.4	0.30	0.27	0.25
1.2	0.30	0.26	0.25
0.0	0.35	0.30	0.30




Figure A




Figure B (Ripple and Ripple noise Characteristic)