

# TEST DATA OF SUTS30512

Regulated DC Power Supply  
February 13, 2009

Approved by : Kazunari Asano  
Kazunari Asano Design Manager

Prepared by : Sho Saito Sho Saito Design Engineer

COSEL CO.,LTD.

## CONTENTS

1. Input Current (by Input Voltage) . . . . .	1
2. Input Current (by Load Current) . . . . .	2
3. Input Power (by Load Current) . . . . .	3
4. Efficiency (by Input Voltage) . . . . .	4
5. Efficiency (by Load Current) . . . . .	5
6. Line Regulation . . . . .	6
7. Load Regulation . . . . .	7
8. Dynamic Load Response . . . . .	8
9. Ripple Voltage (by Load Current) . . . . .	9
10. Ripple-Noise . . . . .	10
11. Ripple Voltage (by Ambient Temperature) . . . . .	11
12. Ambient Temperature Drift . . . . .	12
13. Output Voltage Accuracy . . . . .	13
14. Time Lapse Drift . . . . .	14
15. Rise and Fall Time . . . . .	15
16. Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17. Overcurrent Protection . . . . .	17
18. Figure of Testing Circuitry . . . . .	18

(Final Page 18)

Model	SUTS30512	Temperature Testing Circuitry      25°C Figure A																																																																											
Item	Input Current (by Input Voltage)																																																																												
Object	_____	2.Values																																																																											
1.Graph	<p>—△— Load 100%</p> <p>- - -□- - Load 50%</p> <p>- - ○- - Load 0%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>1.70</td><td>0.009</td><td>0.008</td><td>0.009</td></tr> <tr><td>2.00</td><td>0.009</td><td>0.008</td><td>0.009</td></tr> <tr><td>2.66</td><td>0.080</td><td>1.009</td><td>0.019</td></tr> <tr><td>2.83</td><td>0.076</td><td>0.825</td><td>1.735</td></tr> <tr><td>3.00</td><td>0.074</td><td>0.774</td><td>1.543</td></tr> <tr><td>4.00</td><td>0.062</td><td>0.520</td><td>1.020</td></tr> <tr><td>4.50</td><td>0.058</td><td>0.455</td><td>0.906</td></tr> <tr><td>5.00</td><td>0.055</td><td>0.405</td><td>0.802</td></tr> <tr><td>6.00</td><td>0.050</td><td>0.343</td><td>0.645</td></tr> <tr><td>7.00</td><td>0.049</td><td>0.297</td><td>0.551</td></tr> <tr><td>8.00</td><td>0.049</td><td>0.267</td><td>0.487</td></tr> <tr><td>9.00</td><td>0.050</td><td>0.244</td><td>0.436</td></tr> <tr><td>10.00</td><td>0.052</td><td>0.226</td><td>0.397</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0.00	0.000	0.000	0.000	1.70	0.009	0.008	0.009	2.00	0.009	0.008	0.009	2.66	0.080	1.009	0.019	2.83	0.076	0.825	1.735	3.00	0.074	0.774	1.543	4.00	0.062	0.520	1.020	4.50	0.058	0.455	0.906	5.00	0.055	0.405	0.802	6.00	0.050	0.343	0.645	7.00	0.049	0.297	0.551	8.00	0.049	0.267	0.487	9.00	0.050	0.244	0.436	10.00	0.052	0.226	0.397	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																										
0.00	0.000	0.000	0.000																																																																										
1.70	0.009	0.008	0.009																																																																										
2.00	0.009	0.008	0.009																																																																										
2.66	0.080	1.009	0.019																																																																										
2.83	0.076	0.825	1.735																																																																										
3.00	0.074	0.774	1.543																																																																										
4.00	0.062	0.520	1.020																																																																										
4.50	0.058	0.455	0.906																																																																										
5.00	0.055	0.405	0.802																																																																										
6.00	0.050	0.343	0.645																																																																										
7.00	0.049	0.297	0.551																																																																										
8.00	0.049	0.267	0.487																																																																										
9.00	0.050	0.244	0.436																																																																										
10.00	0.052	0.226	0.397																																																																										
--	-	-	-																																																																										
--	-	-	-																																																																										
--	-	-	-																																																																										
--	-	-	-																																																																										

Note: Slanted line shows the range of the rated input voltage.


Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.00	0.000	0.000	0.000
1.70	0.009	0.008	0.009
2.00	0.009	0.008	0.009
2.66	0.080	1.009	0.019
2.83	0.076	0.825	1.735
3.00	0.074	0.774	1.543
4.00	0.062	0.520	1.020
4.50	0.058	0.455	0.906
5.00	0.055	0.405	0.802
6.00	0.050	0.343	0.645
7.00	0.049	0.297	0.551
8.00	0.049	0.267	0.487
9.00	0.050	0.244	0.436
10.00	0.052	0.226	0.397
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Model	SUTS30512	Temperature Testing Circuitry 25°C Figure A																															
Item	Input Current (by Load Current)																																
Object	_____																																
1.Graph		2.Values																															
<p>—△— Input Volt. 4.5V        - -□--- Input Volt. 5V        - -○--- Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Current [A] (4.5V)</th> <th>Input Current [A] (5V)</th> <th>Input Current [A] (9V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.058</td><td>0.055</td><td>0.050</td></tr> <tr><td>0.050</td><td>0.210</td><td>0.195</td><td>0.130</td></tr> <tr><td>0.100</td><td>0.369</td><td>0.329</td><td>0.205</td></tr> <tr><td>0.150</td><td>0.528</td><td>0.473</td><td>0.279</td></tr> <tr><td>0.200</td><td>0.698</td><td>0.627</td><td>0.357</td></tr> <tr><td>0.250</td><td>0.883</td><td>0.779</td><td>0.436</td></tr> <tr><td>0.275</td><td>0.941</td><td>0.844</td><td>0.471</td></tr> </tbody> </table>		Load Current [A]	Input Current [A] (4.5V)	Input Current [A] (5V)	Input Current [A] (9V)	0.00	0.058	0.055	0.050	0.050	0.210	0.195	0.130	0.100	0.369	0.329	0.205	0.150	0.528	0.473	0.279	0.200	0.698	0.627	0.357	0.250	0.883	0.779	0.436	0.275	0.941	0.844	0.471
Load Current [A]	Input Current [A] (4.5V)	Input Current [A] (5V)	Input Current [A] (9V)																														
0.00	0.058	0.055	0.050																														
0.050	0.210	0.195	0.130																														
0.100	0.369	0.329	0.205																														
0.150	0.528	0.473	0.279																														
0.200	0.698	0.627	0.357																														
0.250	0.883	0.779	0.436																														
0.275	0.941	0.844	0.471																														

Note: Slanted line shows the range of the rated load current.


Model	SUTS30512	Temperature Testing Circuitry 25°C Figure A																															
Item	Input Power (by Load Current)																																
Object	_____																																
1.Graph		2.Values																															
<p>—△— Input Volt. 4.5V        - - -□- - Input Volt. 5V        - - ○ - - Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (4.5V)</th> <th>Input Power [W] (5V)</th> <th>Input Power [W] (9V)</th> </tr> </thead> <tbody> <tr><td>0.05</td><td>0.25</td><td>0.27</td><td>0.44</td></tr> <tr><td>0.10</td><td>0.94</td><td>0.95</td><td>1.16</td></tr> <tr><td>0.15</td><td>1.63</td><td>1.64</td><td>1.83</td></tr> <tr><td>0.20</td><td>2.35</td><td>2.35</td><td>2.51</td></tr> <tr><td>0.25</td><td>3.10</td><td>3.08</td><td>3.20</td></tr> <tr><td>0.275</td><td>3.89</td><td>3.84</td><td>3.88</td></tr> <tr><td>0.30</td><td>4.28</td><td>4.21</td><td>4.24</td></tr> </tbody> </table>		Load Current [A]	Input Power [W] (4.5V)	Input Power [W] (5V)	Input Power [W] (9V)	0.05	0.25	0.27	0.44	0.10	0.94	0.95	1.16	0.15	1.63	1.64	1.83	0.20	2.35	2.35	2.51	0.25	3.10	3.08	3.20	0.275	3.89	3.84	3.88	0.30	4.28	4.21	4.24
Load Current [A]	Input Power [W] (4.5V)	Input Power [W] (5V)	Input Power [W] (9V)																														
0.05	0.25	0.27	0.44																														
0.10	0.94	0.95	1.16																														
0.15	1.63	1.64	1.83																														
0.20	2.35	2.35	2.51																														
0.25	3.10	3.08	3.20																														
0.275	3.89	3.84	3.88																														
0.30	4.28	4.21	4.24																														
<p>Note: Slanted line shows the range of the rated load current.</p>																																	

Model	SUTS30512	Temperature Testing Circuitry 25°C Figure A																															
Item	Efficiency (by Input Voltage)																																
Object	—																																
1. Graph		2. Values																															
<p>The graph plots Efficiency [%] on the y-axis (30 to 100) against Input Voltage [V] on the x-axis (3 to 9). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight increase in efficiency from approximately 75% at 4V to about 78% at 7V, followed by a slight decrease to around 75% at 9V. A slanted line on the graph indicates the rated input voltage range.</p>																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>4.0</td> <td>75.3</td> <td>75.4</td> </tr> <tr> <td>4.5</td> <td>75.9</td> <td>77.0</td> </tr> <tr> <td>5.0</td> <td>75.9</td> <td>78.3</td> </tr> <tr> <td>6.0</td> <td>74.8</td> <td>79.4</td> </tr> <tr> <td>7.0</td> <td>73.4</td> <td>79.3</td> </tr> <tr> <td>8.0</td> <td>71.7</td> <td>78.7</td> </tr> <tr> <td>9.0</td> <td>69.4</td> <td>77.6</td> </tr> <tr> <td>9.5</td> <td>68.3</td> <td>77.1</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.0	75.3	75.4	4.5	75.9	77.0	5.0	75.9	78.3	6.0	74.8	79.4	7.0	73.4	79.3	8.0	71.7	78.7	9.0	69.4	77.6	9.5	68.3	77.1	--	-	-
Input Voltage [V]	Efficiency [%]																																
	Load 50%	Load 100%																															
4.0	75.3	75.4																															
4.5	75.9	77.0																															
5.0	75.9	78.3																															
6.0	74.8	79.4																															
7.0	73.4	79.3																															
8.0	71.7	78.7																															
9.0	69.4	77.6																															
9.5	68.3	77.1																															
--	-	-																															
Note: Slanted line shows the range of the rated input voltage.																																	

Model	SUTS30512	Temperature Testing Circuitry 25°C Figure A																																																
Item	Efficiency (by Load Current)																																																	
Object	_____																																																	
1.Graph		2.Values																																																
<p>—△— Input Volt. 4.5V        - - -□- - Input Volt. 5V        - - ○ - - Input Volt. 9V</p>  <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.050</td><td>63.8</td><td>63.0</td><td>51.9</td></tr> <tr><td>0.100</td><td>73.7</td><td>73.4</td><td>65.8</td></tr> <tr><td>0.150</td><td>76.8</td><td>77.0</td><td>71.9</td></tr> <tr><td>0.200</td><td>77.7</td><td>78.3</td><td>75.3</td></tr> <tr><td>0.250</td><td>77.4</td><td>78.5</td><td>77.5</td></tr> <tr><td>0.275</td><td>77.4</td><td>78.6</td><td>78.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	-	-	-	0.050	63.8	63.0	51.9	0.100	73.7	73.4	65.8	0.150	76.8	77.0	71.9	0.200	77.7	78.3	75.3	0.250	77.4	78.5	77.5	0.275	77.4	78.6	78.2	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																															
0.000	-	-	-																																															
0.050	63.8	63.0	51.9																																															
0.100	73.7	73.4	65.8																																															
0.150	76.8	77.0	71.9																																															
0.200	77.7	78.3	75.3																																															
0.250	77.4	78.5	77.5																																															
0.275	77.4	78.6	78.2																																															
--	-	-	-																																															
--	-	-	-																																															
--	-	-	-																																															
--	-	-	-																																															
<p>Note: Slanted line shows the range of the rated load current.</p>																																																		


Model	SUTS30512	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+12V0.25A																																	
1.Graph		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>4.0</td> <td>12.038</td> <td>12.036</td> </tr> <tr> <td>4.5</td> <td>12.038</td> <td>12.036</td> </tr> <tr> <td>5.0</td> <td>12.038</td> <td>12.036</td> </tr> <tr> <td>6.0</td> <td>12.038</td> <td>12.036</td> </tr> <tr> <td>7.0</td> <td>12.038</td> <td>12.036</td> </tr> <tr> <td>8.0</td> <td>12.038</td> <td>12.036</td> </tr> <tr> <td>9.0</td> <td>12.038</td> <td>12.036</td> </tr> <tr> <td>9.5</td> <td>12.038</td> <td>12.036</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	12.038	12.036	4.5	12.038	12.036	5.0	12.038	12.036	6.0	12.038	12.036	7.0	12.038	12.036	8.0	12.038	12.036	9.0	12.038	12.036	9.5	12.038	12.036	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
4.0	12.038	12.036																																
4.5	12.038	12.036																																
5.0	12.038	12.036																																
6.0	12.038	12.036																																
7.0	12.038	12.036																																
8.0	12.038	12.036																																
9.0	12.038	12.036																																
9.5	12.038	12.036																																
--	-	-																																

Note: Slanted line shows the range of the rated input voltage.

Model	SUTS30512	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Load Regulation																																																				
Object	+12V0.25A																																																				
1.Graph	<p>—△— Input Volt. 4.5V        - - -□--- Input Volt. 5V        - - -○--- Input Volt. 9V</p>  <p>The graph plots Output Voltage [V] on the Y-axis (11.60 to 12.30) against Load Current [A] on the X-axis (0.00 to 0.30). Three data series are shown for input voltages of 4.5V, 5V, and 9V. All three series show a horizontal line at approximately 12.04V, indicating excellent load regulation.</p>	2.Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td><td>12.040</td><td>12.040</td><td>12.040</td></tr> <tr> <td>0.050</td><td>12.039</td><td>12.039</td><td>12.039</td></tr> <tr> <td>0.100</td><td>12.038</td><td>12.038</td><td>12.038</td></tr> <tr> <td>0.150</td><td>12.037</td><td>12.037</td><td>12.038</td></tr> <tr> <td>0.200</td><td>12.036</td><td>12.037</td><td>12.037</td></tr> <tr> <td>0.250</td><td>12.036</td><td>12.036</td><td>12.036</td></tr> <tr> <td>0.275</td><td>12.035</td><td>12.036</td><td>12.036</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	12.040	12.040	12.040	0.050	12.039	12.039	12.039	0.100	12.038	12.038	12.038	0.150	12.037	12.037	12.038	0.200	12.036	12.037	12.037	0.250	12.036	12.036	12.036	0.275	12.035	12.036	12.036	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
0.000	12.040	12.040	12.040																																																		
0.050	12.039	12.039	12.039																																																		
0.100	12.038	12.038	12.038																																																		
0.150	12.037	12.037	12.038																																																		
0.200	12.036	12.037	12.037																																																		
0.250	12.036	12.036	12.036																																																		
0.275	12.035	12.036	12.036																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.


**COSEL**



Model	SUTS30512
Item	Ripple Voltage (by Load Current)
Object	+12V0.25A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.000	4	2
0.050	4	2
0.100	5	3
0.150	6	3
0.200	6	3
0.250	7	4
0.275	7	4
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTS30512
Item	Ripple-Noise
Object	+12V0.25A

Temperature 25°C  
Testing Circuitry Figure B

## 1. Graph




Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.


## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.000	5	5
0.050	7	6
0.100	8	7
0.150	10	8
0.200	12	9
0.250	15	11
0.275	17	11
--	-	-
--	-	-
--	-	-
--	-	-



Model	SUTS30512
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.25A

## 1. Graph



Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure B

## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	9
-40	4	9
-20	5	9
0	4	8
25	4	7
55	3	6
60	3	5
--	-	-
--	-	-
--	-	-
--	-	-

Model	SUTS30512
Item	Ambient Temperature Drift
Object	+12V0.25A



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
-60	11.982	11.983	11.984
-40	12.001	12.002	12.003
-20	12.017	12.018	12.018
0	12.028	12.028	12.028
25	12.035	12.035	12.035
55	12.037	12.037	12.037
60	12.037	12.036	12.036
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTS30512	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V0.25A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current : 0 - 0.25A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	9	0	12.042	±21	±0.2
Minimum Voltage	-40	4.5	0.25	12.001		

**COSEL**

Model	SUTS30512
Item	Time Lapse Drift
Object	+12V0.25A

Temperature 25°C  
Testing Circuitry Figure A

1. Graph



2. Values


Time since start [H]	Output Voltage [V]
0.0	12.033
0.5	12.037
1.0	12.037
2.0	12.037
3.0	12.037
4.0	12.037
5.0	12.037
6.0	12.037
7.0	12.037
8.0	12.037

**COSEL**

Model	SUTS30512
Item	Rise and Fall Time
Object	+12V0.25A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.2	6.2	6.4	0.2	3.7	
100 %		0.2	6.3	6.5	0.1	1.8	



Model	SUTS30512
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.25A

Testing Circuitry Figure A

## 1. Graph



## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.1	2.6
-40	2.1	2.8
-20	2.1	2.6
0	2.1	2.7
25	2.1	2.8
55	2.3	2.9
60	2.2	2.9
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	SUTS30512	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection																																																									
Object	+12V0.25A																																																									
1.Graph		2.Values																																																								
<p>The graph plots Output Voltage [V] on the y-axis (0 to 12) against Load Current [A] on the x-axis (0.0 to 0.6). Three curves are shown for Input Voltages of 4.5V, 5V, and 9V. All curves start at 12V for low currents and drop to 0V as current increases. A slanted line highlights the current range from approximately 0.35A to 0.45A.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.25</td><td>0.25</td><td>0.25</td></tr> <tr><td>11.4</td><td>0.39</td><td>0.39</td><td>0.39</td></tr> <tr><td>10.8</td><td>0.40</td><td>0.40</td><td>0.39</td></tr> <tr><td>9.6</td><td>0.41</td><td>0.41</td><td>0.40</td></tr> <tr><td>8.4</td><td>0.43</td><td>0.43</td><td>0.41</td></tr> <tr><td>7.2</td><td>0.45</td><td>0.44</td><td>0.42</td></tr> <tr><td>6.0</td><td>0.46</td><td>0.45</td><td>0.42</td></tr> <tr><td>4.8</td><td>0.47</td><td>0.46</td><td>0.42</td></tr> <tr><td>3.6</td><td>0.47</td><td>0.46</td><td>0.42</td></tr> <tr><td>2.4</td><td>0.46</td><td>0.45</td><td>0.40</td></tr> <tr><td>1.2</td><td>0.42</td><td>0.40</td><td>0.37</td></tr> <tr><td>0.0</td><td>0.36</td><td>0.36</td><td>0.36</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	12.0	0.25	0.25	0.25	11.4	0.39	0.39	0.39	10.8	0.40	0.40	0.39	9.6	0.41	0.41	0.40	8.4	0.43	0.43	0.41	7.2	0.45	0.44	0.42	6.0	0.46	0.45	0.42	4.8	0.47	0.46	0.42	3.6	0.47	0.46	0.42	2.4	0.46	0.45	0.40	1.2	0.42	0.40	0.37	0.0	0.36	0.36	0.36
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
12.0	0.25	0.25	0.25																																																							
11.4	0.39	0.39	0.39																																																							
10.8	0.40	0.40	0.39																																																							
9.6	0.41	0.41	0.40																																																							
8.4	0.43	0.43	0.41																																																							
7.2	0.45	0.44	0.42																																																							
6.0	0.46	0.45	0.42																																																							
4.8	0.47	0.46	0.42																																																							
3.6	0.47	0.46	0.42																																																							
2.4	0.46	0.45	0.40																																																							
1.2	0.42	0.40	0.37																																																							
0.0	0.36	0.36	0.36																																																							

Note: Slanted line shows the range of the rated load current.




Figure A




Figure B (Ripple and Ripple noise Characteristic)