

TEST DATA OF SUTS34815

Regulated DC Power Supply
February 23, 2009

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	9
10.Ripple-Noise · · · · ·	10
11.Ripple Voltage (by Ambient Temperature) · · · · ·	11
12.Ambient Temperature Drift · · · · ·	12
13.Output Voltage Accuracy · · · · ·	13
14.Time Lapse Drift · · · · ·	14
15.Rise and Fall Time · · · · ·	15
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	16
17.Overcurrent Protection · · · · ·	17
18.Figure of Testing Circuitry · · · · ·	18

(Final Page 18)

Model	SUTS34815	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> △ Load 100% □ Load 50% ○ Load 0% </p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.007</td><td>0.007</td><td>0.007</td></tr> <tr><td>16.0</td><td>0.006</td><td>0.006</td><td>0.006</td></tr> <tr><td>19.2</td><td>0.005</td><td>0.005</td><td>0.005</td></tr> <tr><td>21.6</td><td>0.011</td><td>0.092</td><td>0.179</td></tr> <tr><td>24.0</td><td>0.011</td><td>0.083</td><td>0.159</td></tr> <tr><td>33.0</td><td>0.010</td><td>0.061</td><td>0.114</td></tr> <tr><td>36.0</td><td>0.010</td><td>0.056</td><td>0.104</td></tr> <tr><td>40.0</td><td>0.009</td><td>0.050</td><td>0.094</td></tr> <tr><td>48.0</td><td>0.009</td><td>0.043</td><td>0.078</td></tr> <tr><td>60.0</td><td>0.009</td><td>0.036</td><td>0.064</td></tr> <tr><td>70.0</td><td>0.010</td><td>0.032</td><td>0.056</td></tr> <tr><td>76.0</td><td>0.010</td><td>0.031</td><td>0.052</td></tr> <tr><td>80.0</td><td>0.010</td><td>0.030</td><td>0.050</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.007	0.007	0.007	16.0	0.006	0.006	0.006	19.2	0.005	0.005	0.005	21.6	0.011	0.092	0.179	24.0	0.011	0.083	0.159	33.0	0.010	0.061	0.114	36.0	0.010	0.056	0.104	40.0	0.009	0.050	0.094	48.0	0.009	0.043	0.078	60.0	0.009	0.036	0.064	70.0	0.010	0.032	0.056	76.0	0.010	0.031	0.052	80.0	0.010	0.030	0.050	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
8.0	0.007	0.007	0.007																																																																																
16.0	0.006	0.006	0.006																																																																																
19.2	0.005	0.005	0.005																																																																																
21.6	0.011	0.092	0.179																																																																																
24.0	0.011	0.083	0.159																																																																																
33.0	0.010	0.061	0.114																																																																																
36.0	0.010	0.056	0.104																																																																																
40.0	0.009	0.050	0.094																																																																																
48.0	0.009	0.043	0.078																																																																																
60.0	0.009	0.036	0.064																																																																																
70.0	0.010	0.032	0.056																																																																																
76.0	0.010	0.031	0.052																																																																																
80.0	0.010	0.030	0.050																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																


Model	SUTS34815	Temperature Testing Circuitry 25°C Figure A																																														
Item	Input Current (by Load Current)																																															
Object	_____																																															
1.Graph		2.Values																																														
<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.010</td><td>0.009</td><td>0.010</td></tr> <tr><td>0.04</td><td>0.028</td><td>0.022</td><td>0.018</td></tr> <tr><td>0.08</td><td>0.046</td><td>0.036</td><td>0.027</td></tr> <tr><td>0.12</td><td>0.065</td><td>0.050</td><td>0.035</td></tr> <tr><td>0.16</td><td>0.084</td><td>0.064</td><td>0.043</td></tr> <tr><td>0.20</td><td>0.104</td><td>0.079</td><td>0.052</td></tr> <tr><td>0.22</td><td>0.114</td><td>0.086</td><td>0.057</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.010	0.009	0.010	0.04	0.028	0.022	0.018	0.08	0.046	0.036	0.027	0.12	0.065	0.050	0.035	0.16	0.084	0.064	0.043	0.20	0.104	0.079	0.052	0.22	0.114	0.086	0.057	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																													
0.00	0.010	0.009	0.010																																													
0.04	0.028	0.022	0.018																																													
0.08	0.046	0.036	0.027																																													
0.12	0.065	0.050	0.035																																													
0.16	0.084	0.064	0.043																																													
0.20	0.104	0.079	0.052																																													
0.22	0.114	0.086	0.057																																													
--	-	-	-																																													
--	-	-	-																																													
--	-	-	-																																													
--	-	-	-																																													
<p>Note: Slanted line shows the range of the rated load current.</p>																																																

Model	SUTS34815	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Input Power (by Load Current)																																																						
Object	_____																																																						
1.Graph	_____																																																						
	<p>—△— Input Volt. 36V</p> <p>- -□- - Input Volt. 48V</p> <p>- -○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.29</td><td>0.34</td><td>0.58</td></tr> <tr><td>0.04</td><td>0.97</td><td>1.02</td><td>1.25</td></tr> <tr><td>0.08</td><td>1.65</td><td>1.70</td><td>1.91</td></tr> <tr><td>0.12</td><td>2.34</td><td>2.38</td><td>2.58</td></tr> <tr><td>0.16</td><td>3.04</td><td>3.06</td><td>3.25</td></tr> <tr><td>0.20</td><td>3.74</td><td>3.75</td><td>3.93</td></tr> <tr><td>0.22</td><td>4.10</td><td>4.11</td><td>4.27</td></tr> </tbody> </table>	Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0.00	0.29	0.34	0.58	0.04	0.97	1.02	1.25	0.08	1.65	1.70	1.91	0.12	2.34	2.38	2.58	0.16	3.04	3.06	3.25	0.20	3.74	3.75	3.93	0.22	4.10	4.11	4.27																						
Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																																				
0.00	0.29	0.34	0.58																																																				
0.04	0.97	1.02	1.25																																																				
0.08	1.65	1.70	1.91																																																				
0.12	2.34	2.38	2.58																																																				
0.16	3.04	3.06	3.25																																																				
0.20	3.74	3.75	3.93																																																				
0.22	4.10	4.11	4.27																																																				
2.Values																																																							
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.29</td><td>0.34</td><td>0.58</td></tr> <tr><td>0.04</td><td>0.97</td><td>1.02</td><td>1.25</td></tr> <tr><td>0.08</td><td>1.65</td><td>1.70</td><td>1.91</td></tr> <tr><td>0.12</td><td>2.34</td><td>2.38</td><td>2.58</td></tr> <tr><td>0.16</td><td>3.04</td><td>3.06</td><td>3.25</td></tr> <tr><td>0.20</td><td>3.74</td><td>3.75</td><td>3.93</td></tr> <tr><td>0.22</td><td>4.10</td><td>4.11</td><td>4.27</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.29	0.34	0.58	0.04	0.97	1.02	1.25	0.08	1.65	1.70	1.91	0.12	2.34	2.38	2.58	0.16	3.04	3.06	3.25	0.20	3.74	3.75	3.93	0.22	4.10	4.11	4.27	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
0.00	0.29	0.34	0.58																																																				
0.04	0.97	1.02	1.25																																																				
0.08	1.65	1.70	1.91																																																				
0.12	2.34	2.38	2.58																																																				
0.16	3.04	3.06	3.25																																																				
0.20	3.74	3.75	3.93																																																				
0.22	4.10	4.11	4.27																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

Model	SUTS34815
Item	Efficiency (by Input Voltage)
Object	—

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
30	75.9	79.9
36	75.4	80.1
40	74.9	80.4
48	73.8	80.0
55	72.6	79.5
60	71.4	78.8
70	68.8	77.6
76	66.7	76.5
80	65.5	75.6

Note: Slanted line shows the range of the rated input voltage.


Model	SUTS34815	Temperature Testing Circuitry 25°C Figure A																																																																																															
Item	Efficiency (by Load Current)																																																																																																
Object	_____																																																																																																
1.Graph		2.Values																																																																																															
<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [36V] (%)</th> <th>Efficiency [48V] (%)</th> <th>Efficiency [76V] (%)</th> </tr> </thead> <tbody> <tr><td>0.02</td><td>62</td><td>58</td><td>48</td></tr> <tr><td>0.04</td><td>72</td><td>68</td><td>60</td></tr> <tr><td>0.06</td><td>75</td><td>72</td><td>65</td></tr> <tr><td>0.08</td><td>78</td><td>75</td><td>70</td></tr> <tr><td>0.10</td><td>79</td><td>78</td><td>73</td></tr> <tr><td>0.12</td><td>79.1</td><td>78.5</td><td>75.8</td></tr> <tr><td>0.14</td><td>80.3</td><td>80.0</td><td>77.1</td></tr> <tr><td>0.16</td><td>80.6</td><td>80.4</td><td>77.4</td></tr> <tr><td>0.18</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.20</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)	0.02	62	58	48	0.04	72	68	60	0.06	75	72	65	0.08	78	75	70	0.10	79	78	73	0.12	79.1	78.5	75.8	0.14	80.3	80.0	77.1	0.16	80.6	80.4	77.4	0.18	-	-	-	0.20	-	-	-	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.04</td><td>61.9</td><td>58.8</td><td>47.8</td></tr> <tr><td>0.08</td><td>72.8</td><td>70.7</td><td>62.6</td></tr> <tr><td>0.12</td><td>77.1</td><td>75.8</td><td>69.9</td></tr> <tr><td>0.16</td><td>79.1</td><td>78.5</td><td>73.9</td></tr> <tr><td>0.20</td><td>80.3</td><td>80.0</td><td>76.5</td></tr> <tr><td>0.22</td><td>80.6</td><td>80.4</td><td>77.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	0.04	61.9	58.8	47.8	0.08	72.8	70.7	62.6	0.12	77.1	75.8	69.9	0.16	79.1	78.5	73.9	0.20	80.3	80.0	76.5	0.22	80.6	80.4	77.4	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)																																																																																														
0.02	62	58	48																																																																																														
0.04	72	68	60																																																																																														
0.06	75	72	65																																																																																														
0.08	78	75	70																																																																																														
0.10	79	78	73																																																																																														
0.12	79.1	78.5	75.8																																																																																														
0.14	80.3	80.0	77.1																																																																																														
0.16	80.6	80.4	77.4																																																																																														
0.18	-	-	-																																																																																														
0.20	-	-	-																																																																																														
Load Current [A]	Efficiency [%]																																																																																																
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																																														
0.00	-	-	-																																																																																														
0.04	61.9	58.8	47.8																																																																																														
0.08	72.8	70.7	62.6																																																																																														
0.12	77.1	75.8	69.9																																																																																														
0.16	79.1	78.5	73.9																																																																																														
0.20	80.3	80.0	76.5																																																																																														
0.22	80.6	80.4	77.4																																																																																														
--	-	-	-																																																																																														
--	-	-	-																																																																																														
--	-	-	-																																																																																														
--	-	-	-																																																																																														

Note: Slanted line shows the range of the rated load current.

Model	SUTS34815
Item	Line Regulation
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
30	15.025	15.019
36	15.026	15.019
40	15.025	15.019
48	15.025	15.019
55	15.025	15.019
60	15.025	15.019
70	15.025	15.019
76	15.026	15.019
80	15.026	15.020

Note: Slanted line shows the range of the rated input voltage.

Model	SUTS34815	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Load Regulation																																																				
Object	+15V0.2A																																																				
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - -○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>36V [V]</th> <th>48V [V]</th> <th>76V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.036</td><td>15.032</td><td>15.037</td></tr> <tr><td>0.04</td><td>15.030</td><td>15.029</td><td>15.031</td></tr> <tr><td>0.08</td><td>15.027</td><td>15.027</td><td>15.027</td></tr> <tr><td>0.12</td><td>15.025</td><td>15.022</td><td>15.024</td></tr> <tr><td>0.16</td><td>15.022</td><td>15.021</td><td>15.022</td></tr> <tr><td>0.20</td><td>15.019</td><td>15.019</td><td>15.019</td></tr> <tr><td>0.22</td><td>15.018</td><td>15.017</td><td>15.018</td></tr> </tbody> </table>	Load Current [A]	36V [V]	48V [V]	76V [V]	0.00	15.036	15.032	15.037	0.04	15.030	15.029	15.031	0.08	15.027	15.027	15.027	0.12	15.025	15.022	15.024	0.16	15.022	15.021	15.022	0.20	15.019	15.019	15.019	0.22	15.018	15.017	15.018																				
Load Current [A]	36V [V]	48V [V]	76V [V]																																																		
0.00	15.036	15.032	15.037																																																		
0.04	15.030	15.029	15.031																																																		
0.08	15.027	15.027	15.027																																																		
0.12	15.025	15.022	15.024																																																		
0.16	15.022	15.021	15.022																																																		
0.20	15.019	15.019	15.019																																																		
0.22	15.018	15.017	15.018																																																		
2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.036</td><td>15.032</td><td>15.037</td></tr> <tr><td>0.04</td><td>15.030</td><td>15.029</td><td>15.031</td></tr> <tr><td>0.08</td><td>15.027</td><td>15.027</td><td>15.027</td></tr> <tr><td>0.12</td><td>15.025</td><td>15.022</td><td>15.024</td></tr> <tr><td>0.16</td><td>15.022</td><td>15.021</td><td>15.022</td></tr> <tr><td>0.20</td><td>15.019</td><td>15.019</td><td>15.019</td></tr> <tr><td>0.22</td><td>15.018</td><td>15.017</td><td>15.018</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	15.036	15.032	15.037	0.04	15.030	15.029	15.031	0.08	15.027	15.027	15.027	0.12	15.025	15.022	15.024	0.16	15.022	15.021	15.022	0.20	15.019	15.019	15.019	0.22	15.018	15.017	15.018	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.00	15.036	15.032	15.037																																																		
0.04	15.030	15.029	15.031																																																		
0.08	15.027	15.027	15.027																																																		
0.12	15.025	15.022	15.024																																																		
0.16	15.022	15.021	15.022																																																		
0.20	15.019	15.019	15.019																																																		
0.22	15.018	15.017	15.018																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Note:	Slanted line shows the range of the rated load current.																																																				


COSEL



Model	SUTS34815
Item	Ripple Voltage (by Load Current)
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	5	4
0.04	6	4
0.08	7	4
0.12	9	5
0.16	13	7
0.20	14	8
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTS34815
Item	Ripple-Noise
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	6	6
0.04	9	9
0.08	11	10
0.12	13	11
0.16	15	12
0.20	18	13
0.22	20	14
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTS34815
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.2A

1. Graph



Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	7	12
-40	7	12
-20	7	12
0	6	11
25	5	10
55	4	7
60	4	7
--	-	-
--	-	-
--	-	-
--	-	-

Model	SUTS34815
Item	Ambient Temperature Drift
Object	+15V0.2A



Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	14.951	14.952	14.953
-40	14.976	14.976	14.977
-20	14.996	14.996	14.997
0	15.010	15.010	15.010
25	15.018	15.018	15.019
55	15.019	15.019	15.019
60	15.017	15.017	15.017
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTS34815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V0.2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 0.2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	76	0	15.040	±32	±0.2
Minimum Voltage	-40	36	0.2	14.976		

COSEL

Model	SUTS34815
Item	Time Lapse Drift
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



Input Volt. 48V
Load 100%

2.Values


Time since start [H]	Output Voltage [V]
0.0	15.016
0.5	15.018
1.0	15.018
2.0	15.018
3.0	15.019
4.0	15.019
5.0	15.019
6.0	15.019
7.0	15.019
8.0	15.019

COSEL

Model	SUTS34815
Item	Rise and Fall Time
Object	+15V0.2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.1	3.1	3.2	6.4	3.3
100 %		0.1	3.3	3.4	3.1	2.0



Model	SUTS34815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.2A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	12.7	17.3
-40	12.5	17.7
-20	12.3	18.3
0	12.3	18.7
25	12.5	19.5
55	13.1	20.5
60	13.3	20.5
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTS34815	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+15V0.2A																																																								
1.Graph		2.Values																																																							
<p>Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.20</td><td>0.20</td><td>0.20</td></tr> <tr><td>14.3</td><td>0.33</td><td>0.33</td><td>0.34</td></tr> <tr><td>13.5</td><td>0.34</td><td>0.34</td><td>0.36</td></tr> <tr><td>12.0</td><td>0.36</td><td>0.36</td><td>0.37</td></tr> <tr><td>10.5</td><td>0.39</td><td>0.39</td><td>0.39</td></tr> <tr><td>9.0</td><td>0.42</td><td>0.41</td><td>0.41</td></tr> <tr><td>7.5</td><td>0.45</td><td>0.43</td><td>0.43</td></tr> <tr><td>6.0</td><td>0.47</td><td>0.45</td><td>0.44</td></tr> <tr><td>4.5</td><td>0.50</td><td>0.46</td><td>0.45</td></tr> <tr><td>3.0</td><td>0.51</td><td>0.46</td><td>0.45</td></tr> <tr><td>1.5</td><td>0.48</td><td>0.44</td><td>0.43</td></tr> <tr><td>0.0</td><td>0.58</td><td>0.48</td><td>0.57</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	15.0	0.20	0.20	0.20	14.3	0.33	0.33	0.34	13.5	0.34	0.34	0.36	12.0	0.36	0.36	0.37	10.5	0.39	0.39	0.39	9.0	0.42	0.41	0.41	7.5	0.45	0.43	0.43	6.0	0.47	0.45	0.44	4.5	0.50	0.46	0.45	3.0	0.51	0.46	0.45	1.5	0.48	0.44	0.43	0.0	0.58	0.48	0.57
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
15.0	0.20	0.20	0.20																																																						
14.3	0.33	0.33	0.34																																																						
13.5	0.34	0.34	0.36																																																						
12.0	0.36	0.36	0.37																																																						
10.5	0.39	0.39	0.39																																																						
9.0	0.42	0.41	0.41																																																						
7.5	0.45	0.43	0.43																																																						
6.0	0.47	0.45	0.44																																																						
4.5	0.50	0.46	0.45																																																						
3.0	0.51	0.46	0.45																																																						
1.5	0.48	0.44	0.43																																																						
0.0	0.58	0.48	0.57																																																						




Figure A




Figure B (Ripple and Ripple noise Characteristic)