

TEST DATA OF SUTS64812

Regulated DC Power Supply
March 18, 2009

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Figure of Testing Circuitry	18

(Final Page 18)


Model	SUTS64812	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p> <p>The graph plots Input Current [A] on the y-axis (0.00 to 0.50) against Input Voltage [V] on the x-axis (0 to 80). Three data series are shown: Load 100% (solid triangles), Load 50% (dashed squares), and Load 0% (dotted circles). A vertical slanted line indicates the rated input voltage range.</p>																																																																																		
Note:	Slanted line shows the range of the rated input voltage.	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.001</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>28.2</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>29.8</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>31.4</td><td>0.011</td><td>0.116</td><td>0.227</td></tr> <tr><td>33.0</td><td>0.010</td><td>0.110</td><td>0.215</td></tr> <tr><td>36.0</td><td>0.010</td><td>0.101</td><td>0.197</td></tr> <tr><td>40.0</td><td>0.009</td><td>0.091</td><td>0.176</td></tr> <tr><td>48.0</td><td>0.008</td><td>0.077</td><td>0.147</td></tr> <tr><td>60.0</td><td>0.008</td><td>0.063</td><td>0.119</td></tr> <tr><td>70.0</td><td>0.009</td><td>0.056</td><td>0.104</td></tr> <tr><td>76.0</td><td>0.009</td><td>0.053</td><td>0.097</td></tr> <tr><td>80.0</td><td>0.009</td><td>0.051</td><td>0.093</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.001	0.000	0.000	24.0	0.001	0.001	0.001	28.2	0.001	0.001	0.001	29.8	0.001	0.001	0.001	31.4	0.011	0.116	0.227	33.0	0.010	0.110	0.215	36.0	0.010	0.101	0.197	40.0	0.009	0.091	0.176	48.0	0.008	0.077	0.147	60.0	0.008	0.063	0.119	70.0	0.009	0.056	0.104	76.0	0.009	0.053	0.097	80.0	0.009	0.051	0.093	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
8.0	0.000	0.000	0.000																																																																																
16.0	0.001	0.000	0.000																																																																																
24.0	0.001	0.001	0.001																																																																																
28.2	0.001	0.001	0.001																																																																																
29.8	0.001	0.001	0.001																																																																																
31.4	0.011	0.116	0.227																																																																																
33.0	0.010	0.110	0.215																																																																																
36.0	0.010	0.101	0.197																																																																																
40.0	0.009	0.091	0.176																																																																																
48.0	0.008	0.077	0.147																																																																																
60.0	0.008	0.063	0.119																																																																																
70.0	0.009	0.056	0.104																																																																																
76.0	0.009	0.053	0.097																																																																																
80.0	0.009	0.051	0.093																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTS64812	Temperature Testing Circuitry 25°C Figure A																											
Item	Input Current (by Load Current)																												
Object	_____																												
1.Graph		2.Values																											
<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 36V [A]</th> <th>Input Volt. 48V [A]</th> <th>Input Volt. 76V [A]</th> </tr> </thead> <tbody> <tr><td>0.10</td><td>0.046</td><td>0.036</td><td>0.027</td></tr> <tr><td>0.20</td><td>0.083</td><td>0.063</td><td>0.044</td></tr> <tr><td>0.30</td><td>0.120</td><td>0.091</td><td>0.062</td></tr> <tr><td>0.40</td><td>0.158</td><td>0.119</td><td>0.079</td></tr> <tr><td>0.50</td><td>0.197</td><td>0.147</td><td>0.097</td></tr> <tr><td>0.55</td><td>0.216</td><td>0.161</td><td>0.106</td></tr> </tbody> </table>		Load Current [A]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]	0.10	0.046	0.036	0.027	0.20	0.083	0.063	0.044	0.30	0.120	0.091	0.062	0.40	0.158	0.119	0.079	0.50	0.197	0.147	0.097	0.55	0.216	0.161	0.106
Load Current [A]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]																										
0.10	0.046	0.036	0.027																										
0.20	0.083	0.063	0.044																										
0.30	0.120	0.091	0.062																										
0.40	0.158	0.119	0.079																										
0.50	0.197	0.147	0.097																										
0.55	0.216	0.161	0.106																										
<p>Input Current [A]</p>																													
<p>Note: Slanted line shows the range of the rated load current.</p>																													

Model	SUTS64812	Temperature Testing Circuitry 25°C Figure A																																										
Item	Input Power (by Load Current)																																											
Object	_____																																											
1. Graph		2. Values																																										
<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0.10</td><td>0.35</td><td>0.40</td><td>0.68</td></tr> <tr><td>0.20</td><td>1.66</td><td>1.72</td><td>2.05</td></tr> <tr><td>0.30</td><td>2.98</td><td>3.03</td><td>3.37</td></tr> <tr><td>0.40</td><td>4.31</td><td>4.35</td><td>4.68</td></tr> <tr><td>0.50</td><td>5.68</td><td>5.69</td><td>6.01</td></tr> <tr><td>0.55</td><td>7.07</td><td>7.06</td><td>7.35</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0.10	0.35	0.40	0.68	0.20	1.66	1.72	2.05	0.30	2.98	3.03	3.37	0.40	4.31	4.35	4.68	0.50	5.68	5.69	6.01	0.55	7.07	7.06	7.35	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																									
0.10	0.35	0.40	0.68																																									
0.20	1.66	1.72	2.05																																									
0.30	2.98	3.03	3.37																																									
0.40	4.31	4.35	4.68																																									
0.50	5.68	5.69	6.01																																									
0.55	7.07	7.06	7.35																																									
--	-	-	-																																									
--	-	-	-																																									
--	-	-	-																																									
--	-	-	-																																									
<p>Note: Slanted line shows the range of the rated load current.</p>																																												

Model	SUTS64812
Item	Efficiency (by Input Voltage)
Object	—

1. Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
33	83.3	85.3
36	83.2	85.6
40	82.9	85.8
48	82.1	85.8
55	80.8	85.2
60	79.9	84.8
70	77.2	83.3
76	75.4	82.4
80	74.1	81.5


Model	SUTS64812	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
1. Graph		2. Values																																																			
	<p>—△— Input Volt. 36V - - □ - - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [36V] [%]</th> <th>Efficiency [48V] [%]</th> <th>Efficiency [76V] [%]</th> </tr> </thead> <tbody> <tr><td>0.10</td><td>72.9</td><td>70.1</td><td>58.9</td></tr> <tr><td>0.20</td><td>81.4</td><td>79.8</td><td>72.0</td></tr> <tr><td>0.30</td><td>84.2</td><td>83.3</td><td>77.5</td></tr> <tr><td>0.40</td><td>85.3</td><td>85.1</td><td>80.5</td></tr> <tr><td>0.50</td><td>85.6</td><td>85.8</td><td>82.4</td></tr> <tr><td>0.55</td><td>85.7</td><td>86.0</td><td>82.9</td></tr> </tbody> </table>	Load Current [A]	Efficiency [36V] [%]	Efficiency [48V] [%]	Efficiency [76V] [%]	0.10	72.9	70.1	58.9	0.20	81.4	79.8	72.0	0.30	84.2	83.3	77.5	0.40	85.3	85.1	80.5	0.50	85.6	85.8	82.4	0.55	85.7	86.0	82.9																								
Load Current [A]	Efficiency [36V] [%]	Efficiency [48V] [%]	Efficiency [76V] [%]																																																		
0.10	72.9	70.1	58.9																																																		
0.20	81.4	79.8	72.0																																																		
0.30	84.2	83.3	77.5																																																		
0.40	85.3	85.1	80.5																																																		
0.50	85.6	85.8	82.4																																																		
0.55	85.7	86.0	82.9																																																		
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.10</td><td>72.9</td><td>70.1</td><td>58.9</td></tr> <tr><td>0.20</td><td>81.4</td><td>79.8</td><td>72.0</td></tr> <tr><td>0.30</td><td>84.2</td><td>83.3</td><td>77.5</td></tr> <tr><td>0.40</td><td>85.3</td><td>85.1</td><td>80.5</td></tr> <tr><td>0.50</td><td>85.6</td><td>85.8</td><td>82.4</td></tr> <tr><td>0.55</td><td>85.7</td><td>86.0</td><td>82.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	0.10	72.9	70.1	58.9	0.20	81.4	79.8	72.0	0.30	84.2	83.3	77.5	0.40	85.3	85.1	80.5	0.50	85.6	85.8	82.4	0.55	85.7	86.0	82.9	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.00	-	-	-																																																		
0.10	72.9	70.1	58.9																																																		
0.20	81.4	79.8	72.0																																																		
0.30	84.2	83.3	77.5																																																		
0.40	85.3	85.1	80.5																																																		
0.50	85.6	85.8	82.4																																																		
0.55	85.7	86.0	82.9																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

Model	SUTS64812
Item	Line Regulation
Object	+12V0.5A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
33	12.121	12.118
36	12.121	12.118
40	12.121	12.119
48	12.121	12.118
55	12.120	12.118
60	12.120	12.118
70	12.120	12.118
76	12.120	12.118
80	12.120	12.118

Note: Slanted line shows the range of the rated input voltage.

Model	SUTS64812	Temperature Testing Circuitry 25°C Figure A																															
Item	Load Regulation																																
Object	+12V0.5A																																
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - -○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>36V [V]</th> <th>48V [V]</th> <th>76V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.124</td><td>12.125</td><td>12.127</td></tr> <tr><td>0.10</td><td>12.123</td><td>12.123</td><td>12.123</td></tr> <tr><td>0.20</td><td>12.121</td><td>12.121</td><td>12.121</td></tr> <tr><td>0.30</td><td>12.121</td><td>12.120</td><td>12.120</td></tr> <tr><td>0.40</td><td>12.119</td><td>12.119</td><td>12.118</td></tr> <tr><td>0.50</td><td>12.118</td><td>12.118</td><td>12.117</td></tr> <tr><td>0.55</td><td>12.117</td><td>12.117</td><td>12.116</td></tr> </tbody> </table>	Load Current [A]	36V [V]	48V [V]	76V [V]	0.00	12.124	12.125	12.127	0.10	12.123	12.123	12.123	0.20	12.121	12.121	12.121	0.30	12.121	12.120	12.120	0.40	12.119	12.119	12.118	0.50	12.118	12.118	12.117	0.55	12.117	12.117	12.116
Load Current [A]	36V [V]	48V [V]	76V [V]																														
0.00	12.124	12.125	12.127																														
0.10	12.123	12.123	12.123																														
0.20	12.121	12.121	12.121																														
0.30	12.121	12.120	12.120																														
0.40	12.119	12.119	12.118																														
0.50	12.118	12.118	12.117																														
0.55	12.117	12.117	12.116																														
2.Values																																	

Note: Slanted line shows the range of the rated load current.


COSEL



Model	SUTS64812
Item	Ripple Voltage (by Load Current)
Object	+12V0.5A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	6	4
0.10	6	5
0.20	6	5
0.30	6	5
0.40	6	5
0.50	8	5
0.55	10	5
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTS64812
Item	Ripple-Noise
Object	+12V0.5A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	6	4
0.10	14	13
0.20	17	16
0.30	19	20
0.40	23	22
0.50	27	24
0.55	29	25
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTS64812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.5A

1. Graph



Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	7	8
-40	7	8
-20	7	7
0	5	12
25	5	6
55	4	5
60	4	5
--	-	-
--	-	-
--	-	-
--	-	-

Model	SUTS64812
Item	Ambient Temperature Drift
Object	+12V0.5A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	12.053	12.056	12.057
-40	12.075	12.078	12.079
-20	12.092	12.094	12.094
0	12.106	12.107	12.107
25	12.117	12.117	12.117
55	12.121	12.121	12.120
60	12.121	12.120	12.120
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTS64812	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V0.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current : 0 - 0.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	76	0	12.130	±28	±0.2
Minimum Voltage	-40	36	0.5	12.075		

COSEL

Model	SUTS64812
Item	Time Lapse Drift
Object	+12V0.5A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Input Volt. 48V
Load 100%

2. Values


Time since start [H]	Output Voltage [V]
0.0	12.114
0.5	12.119
1.0	12.119
2.0	12.120
3.0	12.119
4.0	12.120
5.0	12.119
6.0	12.119
7.0	12.120
8.0	12.120

COSEL

Model	SUTS64812
Item	Rise and Fall Time
Object	+12V0.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.3	2.4	2.7	0.1	3.1	
100 %		0.3	2.5	2.8	0.1	1.6	



Model	SUTS64812
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.5A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	30.4	30.6
-40	30.4	30.6
-20	30.4	30.4
0	30.4	30.4
25	30.4	30.6
55	30.6	30.6
60	30.4	30.6
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTS64812	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+12V0.5A																																																								
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>	2.Values																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.50</td><td>0.50</td><td>0.50</td></tr> <tr><td>11.4</td><td>0.79</td><td>0.80</td><td>0.76</td></tr> <tr><td>10.8</td><td>0.80</td><td>0.82</td><td>0.77</td></tr> <tr><td>9.6</td><td>0.83</td><td>0.84</td><td>0.79</td></tr> <tr><td>8.4</td><td>0.96</td><td>0.98</td><td>0.90</td></tr> <tr><td>7.2</td><td>1.00</td><td>1.01</td><td>0.93</td></tr> <tr><td>6.0</td><td>1.04</td><td>1.03</td><td>0.95</td></tr> <tr><td>4.8</td><td>1.07</td><td>1.05</td><td>0.96</td></tr> <tr><td>3.6</td><td>1.07</td><td>1.04</td><td>0.96</td></tr> <tr><td>2.4</td><td>1.04</td><td>1.00</td><td>0.93</td></tr> <tr><td>1.2</td><td>0.96</td><td>0.91</td><td>0.87</td></tr> <tr><td>0.0</td><td>0.84</td><td>0.81</td><td>0.82</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	12.0	0.50	0.50	0.50	11.4	0.79	0.80	0.76	10.8	0.80	0.82	0.77	9.6	0.83	0.84	0.79	8.4	0.96	0.98	0.90	7.2	1.00	1.01	0.93	6.0	1.04	1.03	0.95	4.8	1.07	1.05	0.96	3.6	1.07	1.04	0.96	2.4	1.04	1.00	0.93	1.2	0.96	0.91	0.87	0.0	0.84	0.81	0.82
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
12.0	0.50	0.50	0.50																																																						
11.4	0.79	0.80	0.76																																																						
10.8	0.80	0.82	0.77																																																						
9.6	0.83	0.84	0.79																																																						
8.4	0.96	0.98	0.90																																																						
7.2	1.00	1.01	0.93																																																						
6.0	1.04	1.03	0.95																																																						
4.8	1.07	1.05	0.96																																																						
3.6	1.07	1.04	0.96																																																						
2.4	1.04	1.00	0.93																																																						
1.2	0.96	0.91	0.87																																																						
0.0	0.84	0.81	0.82																																																						




Figure A




Figure B (Ripple and Ripple noise Characteristic)