

TEST DATA OF SUTW101212

Regulated DC Power Supply
February 23, 2009

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

Model	SUTW101212	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>5.5</td><td>0.000</td><td>0.000</td><td>2.500</td></tr> <tr><td>6.0</td><td>0.000</td><td>0.000</td><td>2.200</td></tr> <tr><td>7.0</td><td>0.000</td><td>0.000</td><td>1.500</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>1.500</td></tr> <tr><td>10.0</td><td>0.000</td><td>0.000</td><td>1.000</td></tr> <tr><td>12.0</td><td>0.000</td><td>0.000</td><td>0.800</td></tr> <tr><td>14.0</td><td>0.000</td><td>0.000</td><td>0.700</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.600</td></tr> <tr><td>18.0</td><td>0.000</td><td>0.000</td><td>0.500</td></tr> <tr><td>20.0</td><td>0.000</td><td>0.000</td><td>0.500</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	5.5	0.000	0.000	2.500	6.0	0.000	0.000	2.200	7.0	0.000	0.000	1.500	8.0	0.000	0.000	1.500	10.0	0.000	0.000	1.000	12.0	0.000	0.000	0.800	14.0	0.000	0.000	0.700	16.0	0.000	0.000	0.600	18.0	0.000	0.000	0.500	20.0	0.000	0.000	0.500																																						
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																																
5.5	0.000	0.000	2.500																																																																																
6.0	0.000	0.000	2.200																																																																																
7.0	0.000	0.000	1.500																																																																																
8.0	0.000	0.000	1.500																																																																																
10.0	0.000	0.000	1.000																																																																																
12.0	0.000	0.000	0.800																																																																																
14.0	0.000	0.000	0.700																																																																																
16.0	0.000	0.000	0.600																																																																																
18.0	0.000	0.000	0.500																																																																																
20.0	0.000	0.000	0.500																																																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.8</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>5.4</td><td>0.075</td><td>1.185</td><td>2.485</td></tr> <tr><td>6.0</td><td>0.071</td><td>1.060</td><td>2.191</td></tr> <tr><td>8.0</td><td>0.054</td><td>0.800</td><td>1.611</td></tr> <tr><td>9.0</td><td>0.048</td><td>0.702</td><td>1.417</td></tr> <tr><td>10.0</td><td>0.043</td><td>0.637</td><td>1.267</td></tr> <tr><td>12.0</td><td>0.037</td><td>0.532</td><td>1.049</td></tr> <tr><td>14.0</td><td>0.034</td><td>0.458</td><td>0.899</td></tr> <tr><td>16.0</td><td>0.032</td><td>0.400</td><td>0.786</td></tr> <tr><td>18.0</td><td>0.030</td><td>0.351</td><td>0.700</td></tr> <tr><td>20.0</td><td>0.030</td><td>0.319</td><td>0.630</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	4.8	0.000	0.000	0.000	5.4	0.075	1.185	2.485	6.0	0.071	1.060	2.191	8.0	0.054	0.800	1.611	9.0	0.048	0.702	1.417	10.0	0.043	0.637	1.267	12.0	0.037	0.532	1.049	14.0	0.034	0.458	0.899	16.0	0.032	0.400	0.786	18.0	0.030	0.351	0.700	20.0	0.030	0.319	0.630	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
2.0	0.000	0.000	0.000																																																																																
4.0	0.000	0.000	0.000																																																																																
4.8	0.000	0.000	0.000																																																																																
5.4	0.075	1.185	2.485																																																																																
6.0	0.071	1.060	2.191																																																																																
8.0	0.054	0.800	1.611																																																																																
9.0	0.048	0.702	1.417																																																																																
10.0	0.043	0.637	1.267																																																																																
12.0	0.037	0.532	1.049																																																																																
14.0	0.034	0.458	0.899																																																																																
16.0	0.032	0.400	0.786																																																																																
18.0	0.030	0.351	0.700																																																																																
20.0	0.030	0.319	0.630																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
		<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																	


Model	SUTW101212																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 9V - - -□- - Input Volt. 12V - - ○ - - Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [A]</th> <th>12V [A]</th> <th>18V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.048</td><td>0.037</td><td>0.031</td></tr> <tr><td>20</td><td>0.314</td><td>0.232</td><td>0.164</td></tr> <tr><td>40</td><td>0.579</td><td>0.433</td><td>0.295</td></tr> <tr><td>60</td><td>0.841</td><td>0.634</td><td>0.428</td></tr> <tr><td>80</td><td>1.114</td><td>0.836</td><td>0.557</td></tr> <tr><td>100</td><td>1.380</td><td>1.035</td><td>0.695</td></tr> <tr><td>110</td><td>1.562</td><td>1.148</td><td>0.754</td></tr> </tbody> </table>			Load Ration [%]	9V [A]	12V [A]	18V [A]	0	0.048	0.037	0.031	20	0.314	0.232	0.164	40	0.579	0.433	0.295	60	0.841	0.634	0.428	80	1.114	0.836	0.557	100	1.380	1.035	0.695	110	1.562	1.148	0.754																			
Load Ration [%]	9V [A]	12V [A]	18V [A]																																																			
0	0.048	0.037	0.031																																																			
20	0.314	0.232	0.164																																																			
40	0.579	0.433	0.295																																																			
60	0.841	0.634	0.428																																																			
80	1.114	0.836	0.557																																																			
100	1.380	1.035	0.695																																																			
110	1.562	1.148	0.754																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.048</td><td>0.037</td><td>0.031</td></tr> <tr><td>20</td><td>0.314</td><td>0.232</td><td>0.164</td></tr> <tr><td>40</td><td>0.579</td><td>0.433</td><td>0.295</td></tr> <tr><td>60</td><td>0.841</td><td>0.634</td><td>0.428</td></tr> <tr><td>80</td><td>1.114</td><td>0.836</td><td>0.557</td></tr> <tr><td>100</td><td>1.380</td><td>1.035</td><td>0.695</td></tr> <tr><td>110</td><td>1.562</td><td>1.148</td><td>0.754</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	0.048	0.037	0.031	20	0.314	0.232	0.164	40	0.579	0.433	0.295	60	0.841	0.634	0.428	80	1.114	0.836	0.557	100	1.380	1.035	0.695	110	1.562	1.148	0.754	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0	0.048	0.037	0.031																																																			
20	0.314	0.232	0.164																																																			
40	0.579	0.433	0.295																																																			
60	0.841	0.634	0.428																																																			
80	1.114	0.836	0.557																																																			
100	1.380	1.035	0.695																																																			
110	1.562	1.148	0.754																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	SUTW101212																																																						
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																				
Object	<hr/>																																																						
1.Graph	<p>—△— Input Volt. 9V - - -□--- Input Volt. 12V - - -○--- Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [W]</th> <th>12V [W]</th> <th>18V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.43</td><td>0.44</td><td>0.55</td></tr> <tr><td>20</td><td>2.81</td><td>2.77</td><td>2.94</td></tr> <tr><td>40</td><td>5.17</td><td>5.18</td><td>5.30</td></tr> <tr><td>60</td><td>7.54</td><td>7.57</td><td>7.67</td></tr> <tr><td>80</td><td>9.99</td><td>9.94</td><td>10.03</td></tr> <tr><td>100</td><td>12.47</td><td>12.39</td><td>12.42</td></tr> <tr><td>110</td><td>13.76</td><td>13.63</td><td>13.62</td></tr> </tbody> </table>	Load Ration [%]	9V [W]	12V [W]	18V [W]	0	0.43	0.44	0.55	20	2.81	2.77	2.94	40	5.17	5.18	5.30	60	7.54	7.57	7.67	80	9.99	9.94	10.03	100	12.47	12.39	12.42	110	13.76	13.63	13.62	<hr/>																					
Load Ration [%]	9V [W]	12V [W]	18V [W]																																																				
0	0.43	0.44	0.55																																																				
20	2.81	2.77	2.94																																																				
40	5.17	5.18	5.30																																																				
60	7.54	7.57	7.67																																																				
80	9.99	9.94	10.03																																																				
100	12.47	12.39	12.42																																																				
110	13.76	13.63	13.62																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.43</td><td>0.44</td><td>0.55</td></tr> <tr><td>20</td><td>2.81</td><td>2.77</td><td>2.94</td></tr> <tr><td>40</td><td>5.17</td><td>5.18</td><td>5.30</td></tr> <tr><td>60</td><td>7.54</td><td>7.57</td><td>7.67</td></tr> <tr><td>80</td><td>9.99</td><td>9.94</td><td>10.03</td></tr> <tr><td>100</td><td>12.47</td><td>12.39</td><td>12.42</td></tr> <tr><td>110</td><td>13.76</td><td>13.63</td><td>13.62</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Power [W]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	0.43	0.44	0.55	20	2.81	2.77	2.94	40	5.17	5.18	5.30	60	7.54	7.57	7.67	80	9.99	9.94	10.03	100	12.47	12.39	12.42	110	13.76	13.63	13.62	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	<hr/>		
Load Ration [%]	Input Power [W]																																																						
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																				
0	0.43	0.44	0.55																																																				
20	2.81	2.77	2.94																																																				
40	5.17	5.18	5.30																																																				
60	7.54	7.57	7.67																																																				
80	9.99	9.94	10.03																																																				
100	12.47	12.39	12.42																																																				
110	13.76	13.63	13.62																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Model	SUTW101212
Item	Efficiency (by Input Voltage)
Object	—

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
8	85.9	86.7
9	85.8	87.2
10	85.9	87.6
12	85.6	88.1
15	85.1	88.2
18	85.9	87.9
20	85.6	87.6
--	-	-
--	-	-


Note: Slanted line shows the range of the rated input voltage.

Model	SUTW101212	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
1.Graph	<p>—△— Input Volt. 9V - - -□- - Input Volt. 12V - - ○ - - Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Efficiency [9V] (%)</th> <th>Efficiency [12V] (%)</th> <th>Efficiency [18V] (%)</th> </tr> </thead> <tbody> <tr><td>25</td><td>78</td><td>78</td><td>74</td></tr> <tr><td>40</td><td>85</td><td>85</td><td>83</td></tr> <tr><td>50</td><td>87</td><td>87</td><td>86</td></tr> <tr><td>80</td><td>88</td><td>88</td><td>87</td></tr> <tr><td>100</td><td>88</td><td>88</td><td>87</td></tr> <tr><td>110</td><td>88</td><td>88</td><td>87</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [9V] (%)	Efficiency [12V] (%)	Efficiency [18V] (%)	25	78	78	74	40	85	85	83	50	87	87	86	80	88	88	87	100	88	88	87	110	88	88	87																								
Load Ration [%]	Efficiency [9V] (%)	Efficiency [12V] (%)	Efficiency [18V] (%)																																																		
25	78	78	74																																																		
40	85	85	83																																																		
50	87	87	86																																																		
80	88	88	87																																																		
100	88	88	87																																																		
110	88	88	87																																																		
2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>77.6</td><td>78.6</td><td>74.1</td></tr> <tr><td>40</td><td>84.5</td><td>84.3</td><td>82.5</td></tr> <tr><td>60</td><td>86.8</td><td>86.6</td><td>85.4</td></tr> <tr><td>80</td><td>87.3</td><td>87.7</td><td>87.0</td></tr> <tr><td>100</td><td>87.4</td><td>88.1</td><td>87.8</td></tr> <tr><td>110</td><td>87.2</td><td>88.0</td><td>88.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	-	-	-	20	77.6	78.6	74.1	40	84.5	84.3	82.5	60	86.8	86.6	85.4	80	87.3	87.7	87.0	100	87.4	88.1	87.8	110	87.2	88.0	88.1	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																		
0	-	-	-																																																		
20	77.6	78.6	74.1																																																		
40	84.5	84.3	82.5																																																		
60	86.8	86.6	85.4																																																		
80	87.3	87.7	87.0																																																		
100	87.4	88.1	87.8																																																		
110	87.2	88.0	88.1																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Model	SUTW101212
Item	Line Regulation
Object	+12V0.45A

Temperature 25°C
Testing Circuitry Figure A


1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8	12.225	12.125
9	12.220	12.125
10	12.216	12.125
12	12.210	12.125
15	12.205	12.125
18	12.202	12.125
20	12.201	12.125
--	-	-
--	-	-

Object -12V0.45A



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8	-12.216	-12.112
9	-12.210	-12.112
10	-12.207	-12.112
12	-12.200	-12.113
15	-12.194	-12.113
18	-12.191	-12.113
20	-12.191	-12.113
--	-	-
--	-	-


Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	SUTW101212	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+12V0.45A																																																					
1.Graph	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>	2.Values																																																				
	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.521</td><td>12.509</td><td>12.496</td></tr> <tr><td>0.090</td><td>12.287</td><td>12.278</td><td>12.275</td></tr> <tr><td>0.180</td><td>12.240</td><td>12.230</td><td>12.222</td></tr> <tr><td>0.270</td><td>12.201</td><td>12.193</td><td>12.186</td></tr> <tr><td>0.360</td><td>12.163</td><td>12.159</td><td>12.155</td></tr> <tr><td>0.450</td><td>12.125</td><td>12.125</td><td>12.125</td></tr> <tr><td>0.495</td><td>12.106</td><td>12.108</td><td>12.110</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.000	12.521	12.509	12.496	0.090	12.287	12.278	12.275	0.180	12.240	12.230	12.222	0.270	12.201	12.193	12.186	0.360	12.163	12.159	12.155	0.450	12.125	12.125	12.125	0.495	12.106	12.108	12.110	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.000	12.521	12.509	12.496																																																			
0.090	12.287	12.278	12.275																																																			
0.180	12.240	12.230	12.222																																																			
0.270	12.201	12.193	12.186																																																			
0.360	12.163	12.159	12.155																																																			
0.450	12.125	12.125	12.125																																																			
0.495	12.106	12.108	12.110																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V0.45A	2.Values																																																				
1.Graph	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.495</td><td>-12.480</td><td>-12.473</td></tr> <tr><td>0.090</td><td>-12.278</td><td>-12.267</td><td>-12.264</td></tr> <tr><td>0.180</td><td>-12.230</td><td>-12.220</td><td>-12.211</td></tr> <tr><td>0.270</td><td>-12.190</td><td>-12.182</td><td>-12.175</td></tr> <tr><td>0.360</td><td>-12.151</td><td>-12.147</td><td>-12.143</td></tr> <tr><td>0.450</td><td>-12.111</td><td>-12.112</td><td>-12.112</td></tr> <tr><td>0.495</td><td>-12.092</td><td>-12.095</td><td>-12.097</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.000	-12.495	-12.480	-12.473	0.090	-12.278	-12.267	-12.264	0.180	-12.230	-12.220	-12.211	0.270	-12.190	-12.182	-12.175	0.360	-12.151	-12.147	-12.143	0.450	-12.111	-12.112	-12.112	0.495	-12.092	-12.095	-12.097	--	-	-	-	--	-	-	-	--	-	-	-					
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.000	-12.495	-12.480	-12.473																																																			
0.090	-12.278	-12.267	-12.264																																																			
0.180	-12.230	-12.220	-12.211																																																			
0.270	-12.190	-12.182	-12.175																																																			
0.360	-12.151	-12.147	-12.143																																																			
0.450	-12.111	-12.112	-12.112																																																			
0.495	-12.092	-12.095	-12.097																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL




COSEL



Model	SUTW101212
Item	Ripple Voltage (by Load Current)
Object	+12V0.45A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.000	2	2
0.090	3	3
0.180	4	4
0.270	5	5
0.360	7	5
0.450	8	6
0.495	9	7
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW101212
Item	Ripple Voltage (by Load Current)
Object	-12V0.45A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.000	3	5
0.090	6	6
0.180	6	7
0.270	6	7
0.360	7	8
0.450	8	8
0.495	8	10
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form


Model	SUTW101212																																						
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																					
Object	+12V0.45A																																						
1. Graph																																							
		2. Values																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>2</td><td>3</td></tr> <tr><td>0.090</td><td>4</td><td>4</td></tr> <tr><td>0.180</td><td>5</td><td>6</td></tr> <tr><td>0.270</td><td>7</td><td>6</td></tr> <tr><td>0.360</td><td>8</td><td>7</td></tr> <tr><td>0.450</td><td>10</td><td>8</td></tr> <tr><td>0.495</td><td>11</td><td>9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	2	3	0.090	4	4	0.180	5	6	0.270	7	6	0.360	8	7	0.450	10	8	0.495	11	9	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																						
	Input Volt. 9 [V]	Input Volt. 18 [V]																																					
0.000	2	3																																					
0.090	4	4																																					
0.180	5	6																																					
0.270	7	6																																					
0.360	8	7																																					
0.450	10	8																																					
0.495	11	9																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																							
<p>Fig.Complex Ripple Noise Wave Form</p>																																							

Model	SUTW101212																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	-12V0.45A																																							
1. Graph																																								
<p>—△— Input Volt. 9V -·○- Input Volt. 18V</p> <p>Ripple-Noise [mV]</p> <p>Load Current [A]</p>																																								
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
Fig.Complex Ripple Noise Wave Form																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>4</td> <td>6</td> </tr> <tr> <td>0.090</td> <td>6</td> <td>7</td> </tr> <tr> <td>0.180</td> <td>7</td> <td>8</td> </tr> <tr> <td>0.270</td> <td>8</td> <td>9</td> </tr> <tr> <td>0.360</td> <td>8</td> <td>10</td> </tr> <tr> <td>0.450</td> <td>9</td> <td>10</td> </tr> <tr> <td>0.495</td> <td>10</td> <td>10</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	4	6	0.090	6	7	0.180	7	8	0.270	8	9	0.360	8	10	0.450	9	10	0.495	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.000	4	6																																						
0.090	6	7																																						
0.180	7	8																																						
0.270	8	9																																						
0.360	8	10																																						
0.450	9	10																																						
0.495	10	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						

COSEL

Model	SUTW101212
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.45A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	8
-40	5	8
-20	5	8
0	5	8
25	5	7
55	4	6
60	4	6
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph



2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	8	10
-40	8	10
-20	6	9
0	6	9
25	6	8
55	5	6
60	5	6
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	SUTW101212
Item	Ambient Temperature Drift
Object	+12V0.45A

Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	12.071	12.072	12.072
-40	12.090	12.091	12.091
-20	12.105	12.106	12.106
0	12.117	12.117	12.117
25	12.125	12.125	12.125
55	12.128	12.128	12.127
60	12.128	12.128	12.127
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	-12.058	-12.060	-12.061
-40	-12.077	-12.078	-12.079
-20	-12.092	-12.093	-12.094
0	-12.103	-12.104	-12.105
25	-12.111	-12.111	-12.112
55	-12.113	-12.114	-12.114
60	-12.113	-12.113	-12.114
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW101212	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 9 - 18V

Load Current (AVR 1) : 0 - 0.45A (AVR 2) : 0 - 0.45A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.45A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	9	0	12.537	±401	±3.3	
Minimum Voltage	55	9	0.45	11.735			

Object		-12V0.45A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	9	0	-12.511	±401	±3.3	
Minimum Voltage	55	9	0.45	-11.710			

COSEL


Model	SUTW101212	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.45A																								
1.Graph		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 12V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>12.117</td></tr> <tr><td>0.5</td><td>12.121</td></tr> <tr><td>1.0</td><td>12.121</td></tr> <tr><td>2.0</td><td>12.121</td></tr> <tr><td>3.0</td><td>12.121</td></tr> <tr><td>4.0</td><td>12.121</td></tr> <tr><td>5.0</td><td>12.121</td></tr> <tr><td>6.0</td><td>12.121</td></tr> <tr><td>7.0</td><td>12.121</td></tr> <tr><td>8.0</td><td>12.121</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.117	0.5	12.121	1.0	12.121	2.0	12.121	3.0	12.121	4.0	12.121	5.0	12.121	6.0	12.121	7.0	12.121	8.0	12.121
Time since start [H]	Output Voltage [V]																								
0.0	12.117																								
0.5	12.121																								
1.0	12.121																								
2.0	12.121																								
3.0	12.121																								
4.0	12.121																								
5.0	12.121																								
6.0	12.121																								
7.0	12.121																								
8.0	12.121																								
Object		2.Values																							
1.Graph		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>-12.113</td></tr> <tr><td>0.5</td><td>-12.118</td></tr> <tr><td>1.0</td><td>-12.118</td></tr> <tr><td>2.0</td><td>-12.118</td></tr> <tr><td>3.0</td><td>-12.118</td></tr> <tr><td>4.0</td><td>-12.118</td></tr> <tr><td>5.0</td><td>-12.118</td></tr> <tr><td>6.0</td><td>-12.118</td></tr> <tr><td>7.0</td><td>-12.118</td></tr> <tr><td>8.0</td><td>-12.118</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-12.113	0.5	-12.118	1.0	-12.118	2.0	-12.118	3.0	-12.118	4.0	-12.118	5.0	-12.118	6.0	-12.118	7.0	-12.118	8.0	-12.118
Time since start [H]	Output Voltage [V]																								
0.0	-12.113																								
0.5	-12.118																								
1.0	-12.118																								
2.0	-12.118																								
3.0	-12.118																								
4.0	-12.118																								
5.0	-12.118																								
6.0	-12.118																								
7.0	-12.118																								
8.0	-12.118																								
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 12V Load 100%</p>																									

COSEL

Model	SUTW101212
Item	Rise and Fall Time
Object	+12V0.45A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.5	2.9	3.4	0.1	3.3	
100 %		0.5	3.2	3.7	0.1	1.6	




COSEL

Model	SUTW101212
Item	Rise and Fall Time
Object	-12V0.45A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.5	3.0	3.5	0.1	3.5
100 %		0.5	3.3	3.8	0.1	1.7



COSEL


Model SUTW101212

Item Minimum Input Voltage
for Regulated Output Voltage

Object +12V0.45A

1.Graph

---□--- Load 50%
—△— Load 100%



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.7	4.6
-40	4.0	4.8
-20	4.2	5.1
0	4.2	5.3
25	4.6	5.5
55	4.8	5.7
60	4.8	5.9
--	-	-
--	-	-
--	-	-
--	-	-

Object -12V0.45A

1.Graph

---□--- Load 50%
—△— Load 100%



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.6	4.5
-40	3.8	4.7
-20	4.1	4.9
0	4.1	5.2
25	4.5	5.4
55	4.7	5.6
60	4.7	5.8
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW101212	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+12V0.45A																																																								
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V 	2.Values																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.45</td><td>0.45</td><td>0.45</td></tr> <tr><td>11.4</td><td>0.79</td><td>0.88</td><td>0.95</td></tr> <tr><td>10.8</td><td>0.84</td><td>0.93</td><td>1.01</td></tr> <tr><td>9.6</td><td>0.88</td><td>0.98</td><td>1.04</td></tr> <tr><td>8.4</td><td>0.93</td><td>1.01</td><td>1.06</td></tr> <tr><td>7.2</td><td>0.98</td><td>1.05</td><td>1.07</td></tr> <tr><td>6.0</td><td>1.03</td><td>1.09</td><td>1.09</td></tr> <tr><td>4.8</td><td>1.10</td><td>1.15</td><td>1.13</td></tr> <tr><td>3.6</td><td>1.17</td><td>1.21</td><td>1.16</td></tr> <tr><td>2.4</td><td>1.27</td><td>1.28</td><td>1.17</td></tr> <tr><td>1.2</td><td>1.36</td><td>1.32</td><td>1.23</td></tr> <tr><td>0.0</td><td>1.60</td><td>1.57</td><td>1.53</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	12.0	0.45	0.45	0.45	11.4	0.79	0.88	0.95	10.8	0.84	0.93	1.01	9.6	0.88	0.98	1.04	8.4	0.93	1.01	1.06	7.2	0.98	1.05	1.07	6.0	1.03	1.09	1.09	4.8	1.10	1.15	1.13	3.6	1.17	1.21	1.16	2.4	1.27	1.28	1.17	1.2	1.36	1.32	1.23	0.0	1.60	1.57	1.53
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																						
12.0	0.45	0.45	0.45																																																						
11.4	0.79	0.88	0.95																																																						
10.8	0.84	0.93	1.01																																																						
9.6	0.88	0.98	1.04																																																						
8.4	0.93	1.01	1.06																																																						
7.2	0.98	1.05	1.07																																																						
6.0	1.03	1.09	1.09																																																						
4.8	1.10	1.15	1.13																																																						
3.6	1.17	1.21	1.16																																																						
2.4	1.27	1.28	1.17																																																						
1.2	1.36	1.32	1.23																																																						
0.0	1.60	1.57	1.53																																																						
Object	-12V0.45A	2.Values																																																							
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V 	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.45</td><td>0.45</td><td>0.45</td></tr> <tr><td>-11.4</td><td>0.77</td><td>0.88</td><td>0.95</td></tr> <tr><td>-10.8</td><td>0.82</td><td>0.93</td><td>1.01</td></tr> <tr><td>-9.6</td><td>0.87</td><td>0.98</td><td>1.04</td></tr> <tr><td>-8.4</td><td>0.92</td><td>1.01</td><td>1.06</td></tr> <tr><td>-7.2</td><td>0.97</td><td>1.05</td><td>1.07</td></tr> <tr><td>-6.0</td><td>1.02</td><td>1.09</td><td>1.09</td></tr> <tr><td>-4.8</td><td>1.09</td><td>1.14</td><td>1.13</td></tr> <tr><td>-3.6</td><td>1.17</td><td>1.21</td><td>1.16</td></tr> <tr><td>-2.4</td><td>1.27</td><td>1.28</td><td>1.16</td></tr> <tr><td>-1.2</td><td>1.35</td><td>1.32</td><td>1.23</td></tr> <tr><td>0.0</td><td>1.60</td><td>1.57</td><td>1.52</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	-12.0	0.45	0.45	0.45	-11.4	0.77	0.88	0.95	-10.8	0.82	0.93	1.01	-9.6	0.87	0.98	1.04	-8.4	0.92	1.01	1.06	-7.2	0.97	1.05	1.07	-6.0	1.02	1.09	1.09	-4.8	1.09	1.14	1.13	-3.6	1.17	1.21	1.16	-2.4	1.27	1.28	1.16	-1.2	1.35	1.32	1.23	0.0	1.60	1.57	1.52
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																						
-12.0	0.45	0.45	0.45																																																						
-11.4	0.77	0.88	0.95																																																						
-10.8	0.82	0.93	1.01																																																						
-9.6	0.87	0.98	1.04																																																						
-8.4	0.92	1.01	1.06																																																						
-7.2	0.97	1.05	1.07																																																						
-6.0	1.02	1.09	1.09																																																						
-4.8	1.09	1.14	1.13																																																						
-3.6	1.17	1.21	1.16																																																						
-2.4	1.27	1.28	1.16																																																						
-1.2	1.35	1.32	1.23																																																						
0.0	1.60	1.57	1.52																																																						

Note: Slanted line shows the range of the rated load current.




Figure A




Figure B (Ripple and Ripple noise Characteristic)