

TEST DATA OF SUTW104812

Regulated DC Power Supply
February 27, 2009

Approved by : Kazunari Asano
Kazunari Asano Design Manager


Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO., LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

Model	SUTW104812	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;">—△— Load 100% - - -□- - Load 50% - -○--- Load 0%</p>  <p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																		
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24.0</td><td>0.000</td><td>0.001</td><td>0.001</td></tr> <tr><td>26.6</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>29.0</td><td>0.016</td><td>0.221</td><td>0.448</td></tr> <tr><td>33.0</td><td>0.016</td><td>0.195</td><td>0.390</td></tr> <tr><td>36.0</td><td>0.017</td><td>0.180</td><td>0.358</td></tr> <tr><td>36.8</td><td>0.017</td><td>0.176</td><td>0.350</td></tr> <tr><td>40.0</td><td>0.017</td><td>0.163</td><td>0.321</td></tr> <tr><td>48.0</td><td>0.016</td><td>0.137</td><td>0.267</td></tr> <tr><td>60.0</td><td>0.015</td><td>0.112</td><td>0.215</td></tr> <tr><td>70.0</td><td>0.014</td><td>0.097</td><td>0.186</td></tr> <tr><td>76.0</td><td>0.014</td><td>0.089</td><td>0.173</td></tr> <tr><td>80.0</td><td>0.014</td><td>0.085</td><td>0.165</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	16.0	0.000	0.000	0.000	24.0	0.000	0.001	0.001	26.6	0.001	0.001	0.001	29.0	0.016	0.221	0.448	33.0	0.016	0.195	0.390	36.0	0.017	0.180	0.358	36.8	0.017	0.176	0.350	40.0	0.017	0.163	0.321	48.0	0.016	0.137	0.267	60.0	0.015	0.112	0.215	70.0	0.014	0.097	0.186	76.0	0.014	0.089	0.173	80.0	0.014	0.085	0.165	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
8.0	0.000	0.000	0.000																																																																																
16.0	0.000	0.000	0.000																																																																																
24.0	0.000	0.001	0.001																																																																																
26.6	0.001	0.001	0.001																																																																																
29.0	0.016	0.221	0.448																																																																																
33.0	0.016	0.195	0.390																																																																																
36.0	0.017	0.180	0.358																																																																																
36.8	0.017	0.176	0.350																																																																																
40.0	0.017	0.163	0.321																																																																																
48.0	0.016	0.137	0.267																																																																																
60.0	0.015	0.112	0.215																																																																																
70.0	0.014	0.097	0.186																																																																																
76.0	0.014	0.089	0.173																																																																																
80.0	0.014	0.085	0.165																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTW104812	Temperature Testing Circuitry 25°C Figure A																																																		
Item	Input Current (by Load Current)																																																			
Object	_____																																																			
1.Graph		2.Values																																																		
<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 36V [A]</th> <th>Input Volt. 48V [A]</th> <th>Input Volt. 76V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.017</td><td>0.016</td><td>0.014</td></tr> <tr><td>20</td><td>0.081</td><td>0.063</td><td>0.044</td></tr> <tr><td>40</td><td>0.148</td><td>0.113</td><td>0.076</td></tr> <tr><td>60</td><td>0.214</td><td>0.163</td><td>0.107</td></tr> <tr><td>80</td><td>0.283</td><td>0.213</td><td>0.139</td></tr> <tr><td>100</td><td>0.353</td><td>0.264</td><td>0.170</td></tr> <tr><td>110</td><td>0.389</td><td>0.290</td><td>0.186</td></tr> </tbody> </table>		Load Ration [%]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]	0	0.017	0.016	0.014	20	0.081	0.063	0.044	40	0.148	0.113	0.076	60	0.214	0.163	0.107	80	0.283	0.213	0.139	100	0.353	0.264	0.170	110	0.389	0.290	0.186																			
Load Ration [%]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]																																																	
0	0.017	0.016	0.014																																																	
20	0.081	0.063	0.044																																																	
40	0.148	0.113	0.076																																																	
60	0.214	0.163	0.107																																																	
80	0.283	0.213	0.139																																																	
100	0.353	0.264	0.170																																																	
110	0.389	0.290	0.186																																																	
<p>Input Current [A]</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.017</td><td>0.016</td><td>0.014</td></tr> <tr><td>20</td><td>0.081</td><td>0.063</td><td>0.044</td></tr> <tr><td>40</td><td>0.148</td><td>0.113</td><td>0.076</td></tr> <tr><td>60</td><td>0.214</td><td>0.163</td><td>0.107</td></tr> <tr><td>80</td><td>0.283</td><td>0.213</td><td>0.139</td></tr> <tr><td>100</td><td>0.353</td><td>0.264</td><td>0.170</td></tr> <tr><td>110</td><td>0.389</td><td>0.290</td><td>0.186</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.017	0.016	0.014	20	0.081	0.063	0.044	40	0.148	0.113	0.076	60	0.214	0.163	0.107	80	0.283	0.213	0.139	100	0.353	0.264	0.170	110	0.389	0.290	0.186	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																			
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																	
0	0.017	0.016	0.014																																																	
20	0.081	0.063	0.044																																																	
40	0.148	0.113	0.076																																																	
60	0.214	0.163	0.107																																																	
80	0.283	0.213	0.139																																																	
100	0.353	0.264	0.170																																																	
110	0.389	0.290	0.186																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Model	SUTW104812																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>36V [W]</th> <th>48V [W]</th> <th>76V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.61</td><td>0.77</td><td>1.09</td></tr> <tr><td>20</td><td>2.93</td><td>3.04</td><td>3.34</td></tr> <tr><td>40</td><td>5.31</td><td>5.40</td><td>5.74</td></tr> <tr><td>60</td><td>7.71</td><td>7.81</td><td>8.14</td></tr> <tr><td>80</td><td>10.16</td><td>10.20</td><td>10.53</td></tr> <tr><td>100</td><td>12.68</td><td>12.65</td><td>12.93</td></tr> <tr><td>110</td><td>13.97</td><td>13.90</td><td>14.15</td></tr> </tbody> </table>			Load Ration [%]	36V [W]	48V [W]	76V [W]	0	0.61	0.77	1.09	20	2.93	3.04	3.34	40	5.31	5.40	5.74	60	7.71	7.81	8.14	80	10.16	10.20	10.53	100	12.68	12.65	12.93	110	13.97	13.90	14.15																			
Load Ration [%]	36V [W]	48V [W]	76V [W]																																																			
0	0.61	0.77	1.09																																																			
20	2.93	3.04	3.34																																																			
40	5.31	5.40	5.74																																																			
60	7.71	7.81	8.14																																																			
80	10.16	10.20	10.53																																																			
100	12.68	12.65	12.93																																																			
110	13.97	13.90	14.15																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.61</td><td>0.77</td><td>1.09</td></tr> <tr><td>20</td><td>2.93</td><td>3.04</td><td>3.34</td></tr> <tr><td>40</td><td>5.31</td><td>5.40</td><td>5.74</td></tr> <tr><td>60</td><td>7.71</td><td>7.81</td><td>8.14</td></tr> <tr><td>80</td><td>10.16</td><td>10.20</td><td>10.53</td></tr> <tr><td>100</td><td>12.68</td><td>12.65</td><td>12.93</td></tr> <tr><td>110</td><td>13.97</td><td>13.90</td><td>14.15</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.61	0.77	1.09	20	2.93	3.04	3.34	40	5.31	5.40	5.74	60	7.71	7.81	8.14	80	10.16	10.20	10.53	100	12.68	12.65	12.93	110	13.97	13.90	14.15	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	0.61	0.77	1.09																																																			
20	2.93	3.04	3.34																																																			
40	5.31	5.40	5.74																																																			
60	7.71	7.81	8.14																																																			
80	10.16	10.20	10.53																																																			
100	12.68	12.65	12.93																																																			
110	13.97	13.90	14.15																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	SUTW104812	Temperature Testing Circuitry 25°C Figure A																													
Item	Efficiency (by Input Voltage)																														
Object	—																														
1. Graph		2. Values																													
<p>The graph plots Efficiency [%] on the y-axis (40 to 100) against Input Voltage [V] on the x-axis (20 to 80). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight decrease in efficiency as input voltage increases. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>33</td><td>84.7</td><td>86.1</td></tr> <tr><td>36</td><td>84.1</td><td>86.1</td></tr> <tr><td>40</td><td>83.6</td><td>86.2</td></tr> <tr><td>48</td><td>82.7</td><td>86.3</td></tr> <tr><td>55</td><td>81.6</td><td>86.0</td></tr> <tr><td>60</td><td>81.0</td><td>85.8</td></tr> <tr><td>70</td><td>80.6</td><td>85.0</td></tr> <tr><td>76</td><td>80.5</td><td>84.5</td></tr> <tr><td>80</td><td>80.1</td><td>84.0</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	33	84.7	86.1	36	84.1	86.1	40	83.6	86.2	48	82.7	86.3	55	81.6	86.0	60	81.0	85.8	70	80.6	85.0	76	80.5	84.5	80	80.1	84.0
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																													
33	84.7	86.1																													
36	84.1	86.1																													
40	83.6	86.2																													
48	82.7	86.3																													
55	81.6	86.0																													
60	81.0	85.8																													
70	80.6	85.0																													
76	80.5	84.5																													
80	80.1	84.0																													
<p>Note: Slanted line shows the range of the rated input voltage.</p>																															

Model	SUTW104812	Temperature Testing Circuitry 25°C Figure A																																										
Item	Efficiency (by Load Current)																																											
Object	_____																																											
1.Graph		2.Values																																										
<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>20</td><td>74.4</td><td>71.6</td><td>65.3</td></tr> <tr><td>40</td><td>82.2</td><td>80.9</td><td>76.2</td></tr> <tr><td>60</td><td>85.1</td><td>83.9</td><td>80.5</td></tr> <tr><td>80</td><td>86.0</td><td>85.6</td><td>82.9</td></tr> <tr><td>100</td><td>86.1</td><td>86.4</td><td>84.5</td></tr> <tr><td>110</td><td>86.0</td><td>86.4</td><td>84.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	20	74.4	71.6	65.3	40	82.2	80.9	76.2	60	85.1	83.9	80.5	80	86.0	85.6	82.9	100	86.1	86.4	84.5	110	86.0	86.4	84.9	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																									
20	74.4	71.6	65.3																																									
40	82.2	80.9	76.2																																									
60	85.1	83.9	80.5																																									
80	86.0	85.6	82.9																																									
100	86.1	86.4	84.5																																									
110	86.0	86.4	84.9																																									
--	-	-	-																																									
--	-	-	-																																									
--	-	-	-																																									
--	-	-	-																																									


Model	SUTW104812	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+12V0.45A																																	
1.Graph		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>12.217</td><td>12.138</td></tr> <tr><td>36</td><td>12.214</td><td>12.138</td></tr> <tr><td>40</td><td>12.211</td><td>12.138</td></tr> <tr><td>48</td><td>12.207</td><td>12.139</td></tr> <tr><td>55</td><td>12.204</td><td>12.139</td></tr> <tr><td>60</td><td>12.203</td><td>12.139</td></tr> <tr><td>70</td><td>12.201</td><td>12.139</td></tr> <tr><td>76</td><td>12.200</td><td>12.138</td></tr> <tr><td>80</td><td>12.200</td><td>12.138</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	12.217	12.138	36	12.214	12.138	40	12.211	12.138	48	12.207	12.139	55	12.204	12.139	60	12.203	12.139	70	12.201	12.139	76	12.200	12.138	80	12.200	12.138
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	12.217	12.138																																
36	12.214	12.138																																
40	12.211	12.138																																
48	12.207	12.139																																
55	12.204	12.139																																
60	12.203	12.139																																
70	12.201	12.139																																
76	12.200	12.138																																
80	12.200	12.138																																
Object -12V0.45A		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>-12.221</td><td>-12.140</td></tr> <tr><td>36</td><td>-12.219</td><td>-12.140</td></tr> <tr><td>40</td><td>-12.215</td><td>-12.140</td></tr> <tr><td>48</td><td>-12.211</td><td>-12.140</td></tr> <tr><td>55</td><td>-12.209</td><td>-12.140</td></tr> <tr><td>60</td><td>-12.207</td><td>-12.140</td></tr> <tr><td>70</td><td>-12.205</td><td>-12.140</td></tr> <tr><td>76</td><td>-12.203</td><td>-12.140</td></tr> <tr><td>80</td><td>-12.203</td><td>-12.141</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	-12.221	-12.140	36	-12.219	-12.140	40	-12.215	-12.140	48	-12.211	-12.140	55	-12.209	-12.140	60	-12.207	-12.140	70	-12.205	-12.140	76	-12.203	-12.140	80	-12.203	-12.141
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
33	-12.221	-12.140																																
36	-12.219	-12.140																																
40	-12.215	-12.140																																
48	-12.211	-12.140																																
55	-12.209	-12.140																																
60	-12.207	-12.140																																
70	-12.205	-12.140																																
76	-12.203	-12.140																																
80	-12.203	-12.141																																
Note: Slanted line shows the range of the rated input voltage.																																		

COSEL


Model	SUTW104812	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Load Regulation																																																				
Object	+12V0.45A																																																				
1.Graph		<p>—△— Input Volt. 36V - -□--- Input Volt. 48V - -○--- Input Volt. 76V</p>																																																			
2.Values		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.497</td><td>12.476</td><td>12.484</td></tr> <tr><td>0.090</td><td>12.271</td><td>12.263</td><td>12.259</td></tr> <tr><td>0.180</td><td>12.232</td><td>12.224</td><td>12.217</td></tr> <tr><td>0.270</td><td>12.199</td><td>12.194</td><td>12.188</td></tr> <tr><td>0.360</td><td>12.168</td><td>12.166</td><td>12.162</td></tr> <tr><td>0.450</td><td>12.137</td><td>12.138</td><td>12.137</td></tr> <tr><td>0.495</td><td>12.122</td><td>12.125</td><td>12.126</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	12.497	12.476	12.484	0.090	12.271	12.263	12.259	0.180	12.232	12.224	12.217	0.270	12.199	12.194	12.188	0.360	12.168	12.166	12.162	0.450	12.137	12.138	12.137	0.495	12.122	12.125	12.126	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.000	12.497	12.476	12.484																																																		
0.090	12.271	12.263	12.259																																																		
0.180	12.232	12.224	12.217																																																		
0.270	12.199	12.194	12.188																																																		
0.360	12.168	12.166	12.162																																																		
0.450	12.137	12.138	12.137																																																		
0.495	12.122	12.125	12.126																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Object	-12V0.45A	<p>1.Graph</p> <p>—△— Input Volt. 36V - -□--- Input Volt. 48V - -○--- Input Volt. 76V</p>																																																			
2.Values		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.523</td><td>-12.520</td><td>-12.515</td></tr> <tr><td>0.090</td><td>-12.274</td><td>-12.266</td><td>-12.262</td></tr> <tr><td>0.180</td><td>-12.235</td><td>-12.227</td><td>-12.220</td></tr> <tr><td>0.270</td><td>-12.201</td><td>-12.195</td><td>-12.190</td></tr> <tr><td>0.360</td><td>-12.170</td><td>-12.167</td><td>-12.164</td></tr> <tr><td>0.450</td><td>-12.139</td><td>-12.140</td><td>-12.139</td></tr> <tr><td>0.495</td><td>-12.124</td><td>-12.126</td><td>-12.127</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	-12.523	-12.520	-12.515	0.090	-12.274	-12.266	-12.262	0.180	-12.235	-12.227	-12.220	0.270	-12.201	-12.195	-12.190	0.360	-12.170	-12.167	-12.164	0.450	-12.139	-12.140	-12.139	0.495	-12.124	-12.126	-12.127	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.000	-12.523	-12.520	-12.515																																																		
0.090	-12.274	-12.266	-12.262																																																		
0.180	-12.235	-12.227	-12.220																																																		
0.270	-12.201	-12.195	-12.190																																																		
0.360	-12.170	-12.167	-12.164																																																		
0.450	-12.139	-12.140	-12.139																																																		
0.495	-12.124	-12.126	-12.127																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

COSEL




COSEL



Model	SUTW104812
Item	Ripple Voltage (by Load Current)
Object	+12V0.45A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	4	8
0.090	5	8
0.180	6	9
0.270	7	10
0.360	9	10
0.450	10	11
0.495	11	11
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW104812
Item	Ripple Voltage (by Load Current)
Object	-12V0.45A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	8	10
0.090	9	14
0.180	10	15
0.270	11	15
0.360	12	16
0.450	13	16
0.495	14	17
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW104812
Item	Ripple-Noise
Object	+12V0.45A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	6	9
0.070	7	9
0.140	8	10
0.210	9	10
0.280	11	11
0.350	12	12
0.385	13	13
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form

Model	SUTW104812
Item	Ripple-Noise
Object	-12V0.45A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	11	13
0.090	11	16
0.180	11	17
0.270	12	17
0.360	12	18
0.450	14	18
0.495	15	19
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form

Model	SUTW104812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.45A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	8	12
-40	7	10
-20	6	10
0	5	8
25	5	8
55	5	8
60	5	8
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	11	14
-40	11	13
-20	11	13
0	10	11
25	8	11
55	6	9
60	6	9
--	-	-
--	-	-
--	-	-
--	-	-


Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW104812
Item	Ambient Temperature Drift
Object	+12V0.45A

Testing Circuitry Figure A


- 1.Graph
- △— Input Volt. 36V
 - - - □ - - Input Volt. 48V
 - · ○ - - Input Volt. 76V



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	12.056	12.057	12.058
-40	12.083	12.084	12.084
-20	12.106	12.106	12.106
0	12.123	12.124	12.124
25	12.138	12.138	12.138
55	12.147	12.147	12.147
60	12.147	12.148	12.147
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

- 1.Graph
- △— Input Volt. 36V
 - - - □ - - Input Volt. 48V
 - · ○ - - Input Volt. 76V



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	-12.054	-12.056	-12.058
-40	-12.081	-12.083	-12.085
-20	-12.104	-12.105	-12.106
0	-12.122	-12.122	-12.124
25	-12.137	-12.137	-12.138
55	-12.146	-12.147	-12.147
60	-12.147	-12.147	-12.148
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW104812	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 36 - 76V

Load Current (AVR 1) : 0 - 0.45A (AVR 2) : 0 - 0.45A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.45A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	36	0	12.512	±394	±3.3	
Minimum Voltage	-40	36	0.45	11.724			

Object		-12V0.45A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	36	0	-12.538	±395	±3.3	
Minimum Voltage	-40	36	0.45	-11.749			

COSEL


Model	SUTW104812	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift																								
Object	+12V0.45A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.127</td></tr> <tr><td>0.5</td><td>12.138</td></tr> <tr><td>1.0</td><td>12.137</td></tr> <tr><td>2.0</td><td>12.138</td></tr> <tr><td>3.0</td><td>12.138</td></tr> <tr><td>4.0</td><td>12.138</td></tr> <tr><td>5.0</td><td>12.138</td></tr> <tr><td>6.0</td><td>12.138</td></tr> <tr><td>7.0</td><td>12.138</td></tr> <tr><td>8.0</td><td>12.138</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.127	0.5	12.138	1.0	12.137	2.0	12.138	3.0	12.138	4.0	12.138	5.0	12.138	6.0	12.138	7.0	12.138	8.0	12.138
Time since start [H]	Output Voltage [V]																								
0.0	12.127																								
0.5	12.138																								
1.0	12.137																								
2.0	12.138																								
3.0	12.138																								
4.0	12.138																								
5.0	12.138																								
6.0	12.138																								
7.0	12.138																								
8.0	12.138																								
Object			2.Values																						
1.Graph			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.134</td></tr> <tr><td>0.5</td><td>-12.146</td></tr> <tr><td>1.0</td><td>-12.146</td></tr> <tr><td>2.0</td><td>-12.147</td></tr> <tr><td>3.0</td><td>-12.147</td></tr> <tr><td>4.0</td><td>-12.147</td></tr> <tr><td>5.0</td><td>-12.147</td></tr> <tr><td>6.0</td><td>-12.147</td></tr> <tr><td>7.0</td><td>-12.147</td></tr> <tr><td>8.0</td><td>-12.147</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-12.134	0.5	-12.146	1.0	-12.146	2.0	-12.147	3.0	-12.147	4.0	-12.147	5.0	-12.147	6.0	-12.147	7.0	-12.147	8.0	-12.147
Time since start [H]	Output Voltage [V]																								
0.0	-12.134																								
0.5	-12.146																								
1.0	-12.146																								
2.0	-12.147																								
3.0	-12.147																								
4.0	-12.147																								
5.0	-12.147																								
6.0	-12.147																								
7.0	-12.147																								
8.0	-12.147																								
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>																									

COSEL

Model	SUTW104812
Item	Rise and Fall Time
Object	+12V0.45A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		9.0	2.5	11.5	0.1	3.3	
100 %		9.0	2.6	11.6	0.1	1.6	




COSEL

Model	SUTW104812
Item	Rise and Fall Time
Object	-12V0.45A


Temperature 25°C
Testing Circuitry Figure A

1. Graph





2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		9.0	2.4	11.4	0.1	3.5	
100 %		9.0	2.5	11.5	0.1	1.7	





Model	SUTW104812																																								
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																							
Object	+12V0.45A																																								
1.Graph		2.Values																																							
<p>---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>27.7</td><td>27.7</td></tr> <tr><td>-40</td><td>27.7</td><td>27.7</td></tr> <tr><td>-20</td><td>28.1</td><td>28.1</td></tr> <tr><td>0</td><td>28.1</td><td>28.1</td></tr> <tr><td>25</td><td>28.5</td><td>28.4</td></tr> <tr><td>55</td><td>28.5</td><td>28.5</td></tr> <tr><td>60</td><td>28.5</td><td>28.5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	27.7	27.7	-40	27.7	27.7	-20	28.1	28.1	0	28.1	28.1	25	28.5	28.4	55	28.5	28.5	60	28.5	28.5	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	27.7	27.7																																							
-40	27.7	27.7																																							
-20	28.1	28.1																																							
0	28.1	28.1																																							
25	28.5	28.4																																							
55	28.5	28.5																																							
60	28.5	28.5																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
Object		2.Values																																							
<p>---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>27.5</td><td>27.5</td></tr> <tr><td>-40</td><td>27.5</td><td>27.5</td></tr> <tr><td>-20</td><td>27.9</td><td>27.9</td></tr> <tr><td>0</td><td>27.9</td><td>27.9</td></tr> <tr><td>25</td><td>28.3</td><td>28.3</td></tr> <tr><td>55</td><td>28.3</td><td>28.2</td></tr> <tr><td>60</td><td>28.3</td><td>28.3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	27.5	27.5	-40	27.5	27.5	-20	27.9	27.9	0	27.9	27.9	25	28.3	28.3	55	28.3	28.2	60	28.3	28.3	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	27.5	27.5																																							
-40	27.5	27.5																																							
-20	27.9	27.9																																							
0	27.9	27.9																																							
25	28.3	28.3																																							
55	28.3	28.2																																							
60	28.3	28.3																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									

Model	SUTW104812	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+12V0.45A																																																								
1.Graph	<p>— Input Volt. 36V — Input Volt. 48V — Input Volt. 76V</p> 	2.Values																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.45</td><td>0.45</td><td>0.45</td></tr> <tr><td>11.4</td><td>0.75</td><td>0.85</td><td>0.89</td></tr> <tr><td>10.8</td><td>0.81</td><td>0.91</td><td>0.97</td></tr> <tr><td>9.6</td><td>0.96</td><td>1.08</td><td>1.12</td></tr> <tr><td>8.4</td><td>1.10</td><td>1.21</td><td>1.26</td></tr> <tr><td>7.2</td><td>1.19</td><td>1.29</td><td>1.32</td></tr> <tr><td>6.0</td><td>1.27</td><td>1.37</td><td>1.36</td></tr> <tr><td>4.8</td><td>1.36</td><td>1.43</td><td>1.37</td></tr> <tr><td>3.6</td><td>1.46</td><td>1.52</td><td>1.34</td></tr> <tr><td>2.4</td><td>1.60</td><td>1.55</td><td>1.27</td></tr> <tr><td>1.2</td><td>1.66</td><td>1.56</td><td>1.17</td></tr> <tr><td>0.0</td><td>1.69</td><td>1.53</td><td>1.91</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	12.0	0.45	0.45	0.45	11.4	0.75	0.85	0.89	10.8	0.81	0.91	0.97	9.6	0.96	1.08	1.12	8.4	1.10	1.21	1.26	7.2	1.19	1.29	1.32	6.0	1.27	1.37	1.36	4.8	1.36	1.43	1.37	3.6	1.46	1.52	1.34	2.4	1.60	1.55	1.27	1.2	1.66	1.56	1.17	0.0	1.69	1.53	1.91
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
12.0	0.45	0.45	0.45																																																						
11.4	0.75	0.85	0.89																																																						
10.8	0.81	0.91	0.97																																																						
9.6	0.96	1.08	1.12																																																						
8.4	1.10	1.21	1.26																																																						
7.2	1.19	1.29	1.32																																																						
6.0	1.27	1.37	1.36																																																						
4.8	1.36	1.43	1.37																																																						
3.6	1.46	1.52	1.34																																																						
2.4	1.60	1.55	1.27																																																						
1.2	1.66	1.56	1.17																																																						
0.0	1.69	1.53	1.91																																																						
Object	-12V0.45A	2.Values																																																							
1.Graph	<p>— Input Volt. 36V — Input Volt. 48V — Input Volt. 76V</p> 	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.46</td><td>0.46</td><td>0.46</td></tr> <tr><td>-11.4</td><td>0.72</td><td>0.84</td><td>0.89</td></tr> <tr><td>-10.8</td><td>0.79</td><td>0.91</td><td>0.96</td></tr> <tr><td>-9.6</td><td>0.94</td><td>1.07</td><td>1.14</td></tr> <tr><td>-8.4</td><td>1.08</td><td>1.21</td><td>1.26</td></tr> <tr><td>-7.2</td><td>1.18</td><td>1.29</td><td>1.32</td></tr> <tr><td>-6.0</td><td>1.26</td><td>1.36</td><td>1.36</td></tr> <tr><td>-4.8</td><td>1.35</td><td>1.43</td><td>1.37</td></tr> <tr><td>-3.6</td><td>1.46</td><td>1.52</td><td>1.34</td></tr> <tr><td>-2.4</td><td>1.60</td><td>1.55</td><td>1.27</td></tr> <tr><td>-1.2</td><td>1.66</td><td>1.56</td><td>1.17</td></tr> <tr><td>0.0</td><td>1.69</td><td>1.53</td><td>1.91</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-12.0	0.46	0.46	0.46	-11.4	0.72	0.84	0.89	-10.8	0.79	0.91	0.96	-9.6	0.94	1.07	1.14	-8.4	1.08	1.21	1.26	-7.2	1.18	1.29	1.32	-6.0	1.26	1.36	1.36	-4.8	1.35	1.43	1.37	-3.6	1.46	1.52	1.34	-2.4	1.60	1.55	1.27	-1.2	1.66	1.56	1.17	0.0	1.69	1.53	1.91
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
-12.0	0.46	0.46	0.46																																																						
-11.4	0.72	0.84	0.89																																																						
-10.8	0.79	0.91	0.96																																																						
-9.6	0.94	1.07	1.14																																																						
-8.4	1.08	1.21	1.26																																																						
-7.2	1.18	1.29	1.32																																																						
-6.0	1.26	1.36	1.36																																																						
-4.8	1.35	1.43	1.37																																																						
-3.6	1.46	1.52	1.34																																																						
-2.4	1.60	1.55	1.27																																																						
-1.2	1.66	1.56	1.17																																																						
0.0	1.69	1.53	1.91																																																						

Note: Slanted line shows the range of the rated load current.




Figure A




Figure B (Ripple and Ripple noise Characteristic)