

TEST DATA OF SUTW30512

Regulated DC Power Supply

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito Sho Saito Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

Model	SUTW30512	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> △ Load 100% □ Load 50% ○ Load 0% </p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>1.70</td><td>0.008</td><td>0.008</td><td>0.008</td></tr> <tr><td>2.00</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>2.66</td><td>0.127</td><td>0.021</td><td>0.020</td></tr> <tr><td>2.83</td><td>0.120</td><td>0.930</td><td>0.033</td></tr> <tr><td>3.00</td><td>0.112</td><td>0.862</td><td>1.710</td></tr> <tr><td>4.00</td><td>0.091</td><td>0.560</td><td>1.098</td></tr> <tr><td>4.50</td><td>0.084</td><td>0.488</td><td>0.936</td></tr> <tr><td>5.00</td><td>0.077</td><td>0.446</td><td>0.879</td></tr> <tr><td>6.00</td><td>0.067</td><td>0.370</td><td>0.702</td></tr> <tr><td>7.00</td><td>0.062</td><td>0.319</td><td>0.593</td></tr> <tr><td>8.00</td><td>0.058</td><td>0.284</td><td>0.524</td></tr> <tr><td>9.00</td><td>0.057</td><td>0.258</td><td>0.468</td></tr> <tr><td>10.00</td><td>0.056</td><td>0.234</td><td>0.423</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.00	0.000	0.000	0.000	1.70	0.008	0.008	0.008	2.00	0.009	0.009	0.009	2.66	0.127	0.021	0.020	2.83	0.120	0.930	0.033	3.00	0.112	0.862	1.710	4.00	0.091	0.560	1.098	4.50	0.084	0.488	0.936	5.00	0.077	0.446	0.879	6.00	0.067	0.370	0.702	7.00	0.062	0.319	0.593	8.00	0.058	0.284	0.524	9.00	0.057	0.258	0.468	10.00	0.056	0.234	0.423	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.00	0.000	0.000	0.000																																																																																
1.70	0.008	0.008	0.008																																																																																
2.00	0.009	0.009	0.009																																																																																
2.66	0.127	0.021	0.020																																																																																
2.83	0.120	0.930	0.033																																																																																
3.00	0.112	0.862	1.710																																																																																
4.00	0.091	0.560	1.098																																																																																
4.50	0.084	0.488	0.936																																																																																
5.00	0.077	0.446	0.879																																																																																
6.00	0.067	0.370	0.702																																																																																
7.00	0.062	0.319	0.593																																																																																
8.00	0.058	0.284	0.524																																																																																
9.00	0.057	0.258	0.468																																																																																
10.00	0.056	0.234	0.423																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTW30512	Temperature Testing Circuitry 25°C Figure A																															
Item	Input Current (by Load Current)																																
Object	_____																																
1.Graph		2.Values																															
<p>—△— Input Volt. 4.5V - - -□- - Input Volt. 5V - - ○- - Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 4.5V [A]</th> <th>Input Volt. 5V [A]</th> <th>Input Volt. 9V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.080</td><td>0.074</td><td>0.057</td></tr> <tr><td>20</td><td>0.237</td><td>0.215</td><td>0.137</td></tr> <tr><td>40</td><td>0.403</td><td>0.362</td><td>0.220</td></tr> <tr><td>60</td><td>0.570</td><td>0.507</td><td>0.301</td></tr> <tr><td>80</td><td>0.740</td><td>0.670</td><td>0.375</td></tr> <tr><td>100</td><td>0.902</td><td>0.824</td><td>0.459</td></tr> <tr><td>110</td><td>1.000</td><td>0.915</td><td>0.500</td></tr> </tbody> </table>		Load Ration [%]	Input Volt. 4.5V [A]	Input Volt. 5V [A]	Input Volt. 9V [A]	0	0.080	0.074	0.057	20	0.237	0.215	0.137	40	0.403	0.362	0.220	60	0.570	0.507	0.301	80	0.740	0.670	0.375	100	0.902	0.824	0.459	110	1.000	0.915	0.500
Load Ration [%]	Input Volt. 4.5V [A]	Input Volt. 5V [A]	Input Volt. 9V [A]																														
0	0.080	0.074	0.057																														
20	0.237	0.215	0.137																														
40	0.403	0.362	0.220																														
60	0.570	0.507	0.301																														
80	0.740	0.670	0.375																														
100	0.902	0.824	0.459																														
110	1.000	0.915	0.500																														
<p>Input Current [A]</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 4.5V [A]</th> <th>Input Volt. 5V [A]</th> <th>Input Volt. 9V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.080</td><td>0.074</td><td>0.057</td></tr> <tr><td>20</td><td>0.237</td><td>0.215</td><td>0.137</td></tr> <tr><td>40</td><td>0.403</td><td>0.362</td><td>0.220</td></tr> <tr><td>60</td><td>0.570</td><td>0.507</td><td>0.301</td></tr> <tr><td>80</td><td>0.740</td><td>0.670</td><td>0.375</td></tr> <tr><td>100</td><td>0.902</td><td>0.824</td><td>0.459</td></tr> <tr><td>110</td><td>1.000</td><td>0.915</td><td>0.500</td></tr> </tbody> </table>		Load Ration [%]	Input Volt. 4.5V [A]	Input Volt. 5V [A]	Input Volt. 9V [A]	0	0.080	0.074	0.057	20	0.237	0.215	0.137	40	0.403	0.362	0.220	60	0.570	0.507	0.301	80	0.740	0.670	0.375	100	0.902	0.824	0.459	110	1.000	0.915	0.500
Load Ration [%]	Input Volt. 4.5V [A]	Input Volt. 5V [A]	Input Volt. 9V [A]																														
0	0.080	0.074	0.057																														
20	0.237	0.215	0.137																														
40	0.403	0.362	0.220																														
60	0.570	0.507	0.301																														
80	0.740	0.670	0.375																														
100	0.902	0.824	0.459																														
110	1.000	0.915	0.500																														

Model	SUTW30512	Temperature Testing Circuitry 25°C Figure A																															
Item	Input Power (by Load Current)																																
Object	_____																																
1.Graph		2.Values																															
<p>—△— Input Volt. 4.5V - - -□- - Input Volt. 5V - - ○ - - Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>4.5V [W]</th> <th>5V [W]</th> <th>9V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.36</td><td>0.37</td><td>0.50</td></tr> <tr><td>20</td><td>1.07</td><td>1.08</td><td>1.22</td></tr> <tr><td>40</td><td>1.79</td><td>1.80</td><td>1.93</td></tr> <tr><td>60</td><td>2.54</td><td>2.53</td><td>2.69</td></tr> <tr><td>80</td><td>3.33</td><td>3.30</td><td>3.37</td></tr> <tr><td>100</td><td>4.14</td><td>4.09</td><td>4.11</td></tr> <tr><td>110</td><td>4.56</td><td>4.50</td><td>4.46</td></tr> </tbody> </table>		Load Ration [%]	4.5V [W]	5V [W]	9V [W]	0	0.36	0.37	0.50	20	1.07	1.08	1.22	40	1.79	1.80	1.93	60	2.54	2.53	2.69	80	3.33	3.30	3.37	100	4.14	4.09	4.11	110	4.56	4.50	4.46
Load Ration [%]	4.5V [W]	5V [W]	9V [W]																														
0	0.36	0.37	0.50																														
20	1.07	1.08	1.22																														
40	1.79	1.80	1.93																														
60	2.54	2.53	2.69																														
80	3.33	3.30	3.37																														
100	4.14	4.09	4.11																														
110	4.56	4.50	4.46																														
<p>Input Power [W]</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>4.5V [W]</th> <th>5V [W]</th> <th>9V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.36</td><td>0.37</td><td>0.50</td></tr> <tr><td>20</td><td>1.07</td><td>1.08</td><td>1.22</td></tr> <tr><td>40</td><td>1.79</td><td>1.80</td><td>1.93</td></tr> <tr><td>60</td><td>2.54</td><td>2.53</td><td>2.69</td></tr> <tr><td>80</td><td>3.33</td><td>3.30</td><td>3.37</td></tr> <tr><td>100</td><td>4.14</td><td>4.09</td><td>4.11</td></tr> <tr><td>110</td><td>4.56</td><td>4.50</td><td>4.46</td></tr> </tbody> </table>		Load Ration [%]	4.5V [W]	5V [W]	9V [W]	0	0.36	0.37	0.50	20	1.07	1.08	1.22	40	1.79	1.80	1.93	60	2.54	2.53	2.69	80	3.33	3.30	3.37	100	4.14	4.09	4.11	110	4.56	4.50	4.46
Load Ration [%]	4.5V [W]	5V [W]	9V [W]																														
0	0.36	0.37	0.50																														
20	1.07	1.08	1.22																														
40	1.79	1.80	1.93																														
60	2.54	2.53	2.69																														
80	3.33	3.30	3.37																														
100	4.14	4.09	4.11																														
110	4.56	4.50	4.46																														

Model	SUTW30512	Temperature Testing Circuitry 25°C Figure A																																
Item	Efficiency (by Input Voltage)																																	
Object	—																																	
1. Graph		2. Values																																
<p>The graph plots Efficiency [%] on the y-axis (30 to 100) against Input Voltage [V] on the x-axis (3 to 10). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency starting around 72% at 4V, peaking near 77% between 5V and 6V, and then remaining relatively flat up to 10V. A shaded gray area between two slanted lines indicates the rated input voltage range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>4.0</td> <td>72.6</td> <td>74.1</td> </tr> <tr> <td>4.5</td> <td>73.1</td> <td>76.2</td> </tr> <tr> <td>5.0</td> <td>72.7</td> <td>76.9</td> </tr> <tr> <td>6.0</td> <td>72.6</td> <td>78.0</td> </tr> <tr> <td>7.0</td> <td>71.5</td> <td>78.2</td> </tr> <tr> <td>8.0</td> <td>70.5</td> <td>77.8</td> </tr> <tr> <td>9.0</td> <td>69.0</td> <td>77.1</td> </tr> <tr> <td>10.0</td> <td>67.0</td> <td>76.1</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.0	72.6	74.1	4.5	73.1	76.2	5.0	72.7	76.9	6.0	72.6	78.0	7.0	71.5	78.2	8.0	70.5	77.8	9.0	69.0	77.1	10.0	67.0	76.1	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
4.0	72.6	74.1																																
4.5	73.1	76.2																																
5.0	72.7	76.9																																
6.0	72.6	78.0																																
7.0	71.5	78.2																																
8.0	70.5	77.8																																
9.0	69.0	77.1																																
10.0	67.0	76.1																																
--	-	-																																



Note: Slanted line shows the range of the rated input voltage.

Model	SUTW30512	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
1.Graph	<p>—△— Input Volt. 4.5V - - -□- - Input Volt. 5V - - ○ - - Input Volt. 9V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>4.5V [Efficiency %]</th> <th>5V [Efficiency %]</th> <th>9V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>20</td><td>59.2</td><td>58.7</td><td>52.1</td></tr> <tr><td>40</td><td>70.7</td><td>70.3</td><td>65.6</td></tr> <tr><td>60</td><td>74.7</td><td>74.9</td><td>70.5</td></tr> <tr><td>80</td><td>76.1</td><td>76.6</td><td>75.1</td></tr> <tr><td>100</td><td>76.4</td><td>77.3</td><td>76.9</td></tr> <tr><td>110</td><td>76.3</td><td>77.3</td><td>78.0</td></tr> </tbody> </table>	Load Ration [%]	4.5V [Efficiency %]	5V [Efficiency %]	9V [Efficiency %]	20	59.2	58.7	52.1	40	70.7	70.3	65.6	60	74.7	74.9	70.5	80	76.1	76.6	75.1	100	76.4	77.3	76.9	110	76.3	77.3	78.0																								
Load Ration [%]	4.5V [Efficiency %]	5V [Efficiency %]	9V [Efficiency %]																																																		
20	59.2	58.7	52.1																																																		
40	70.7	70.3	65.6																																																		
60	74.7	74.9	70.5																																																		
80	76.1	76.6	75.1																																																		
100	76.4	77.3	76.9																																																		
110	76.3	77.3	78.0																																																		
2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>59.2</td><td>58.7</td><td>52.1</td></tr> <tr><td>40</td><td>70.7</td><td>70.3</td><td>65.6</td></tr> <tr><td>60</td><td>74.7</td><td>74.9</td><td>70.5</td></tr> <tr><td>80</td><td>76.1</td><td>76.6</td><td>75.1</td></tr> <tr><td>100</td><td>76.4</td><td>77.3</td><td>76.9</td></tr> <tr><td>110</td><td>76.3</td><td>77.3</td><td>78.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	-	-	-	20	59.2	58.7	52.1	40	70.7	70.3	65.6	60	74.7	74.9	70.5	80	76.1	76.6	75.1	100	76.4	77.3	76.9	110	76.3	77.3	78.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
0	-	-	-																																																		
20	59.2	58.7	52.1																																																		
40	70.7	70.3	65.6																																																		
60	74.7	74.9	70.5																																																		
80	76.1	76.6	75.1																																																		
100	76.4	77.3	76.9																																																		
110	76.3	77.3	78.0																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		


Model	SUTW30512	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+12V0.13A																																	
1.Graph		2.Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>12.221</td><td>12.160</td></tr> <tr><td>4.5</td><td>12.218</td><td>12.160</td></tr> <tr><td>5.0</td><td>12.216</td><td>12.161</td></tr> <tr><td>6.0</td><td>12.213</td><td>12.161</td></tr> <tr><td>7.0</td><td>12.212</td><td>12.161</td></tr> <tr><td>8.0</td><td>12.210</td><td>12.162</td></tr> <tr><td>9.0</td><td>12.210</td><td>12.162</td></tr> <tr><td>10.0</td><td>12.209</td><td>12.162</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	12.221	12.160	4.5	12.218	12.160	5.0	12.216	12.161	6.0	12.213	12.161	7.0	12.212	12.161	8.0	12.210	12.162	9.0	12.210	12.162	10.0	12.209	12.162	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
4.0	12.221	12.160																																
4.5	12.218	12.160																																
5.0	12.216	12.161																																
6.0	12.213	12.161																																
7.0	12.212	12.161																																
8.0	12.210	12.162																																
9.0	12.210	12.162																																
10.0	12.209	12.162																																
--	-	-																																
Object -12V0.13A		2.Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>-12.218</td><td>-12.155</td></tr> <tr><td>4.5</td><td>-12.214</td><td>-12.156</td></tr> <tr><td>5.0</td><td>-12.212</td><td>-12.156</td></tr> <tr><td>6.0</td><td>-12.208</td><td>-12.156</td></tr> <tr><td>7.0</td><td>-12.207</td><td>-12.156</td></tr> <tr><td>8.0</td><td>-12.205</td><td>-12.156</td></tr> <tr><td>9.0</td><td>-12.204</td><td>-12.156</td></tr> <tr><td>10.0</td><td>-12.204</td><td>-12.156</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	-12.218	-12.155	4.5	-12.214	-12.156	5.0	-12.212	-12.156	6.0	-12.208	-12.156	7.0	-12.207	-12.156	8.0	-12.205	-12.156	9.0	-12.204	-12.156	10.0	-12.204	-12.156	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
4.0	-12.218	-12.155																																
4.5	-12.214	-12.156																																
5.0	-12.212	-12.156																																
6.0	-12.208	-12.156																																
7.0	-12.207	-12.156																																
8.0	-12.205	-12.156																																
9.0	-12.204	-12.156																																
10.0	-12.204	-12.156																																
--	-	-																																

Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	SUTW30512	Temperature Testing Circuitry	25°C Figure A																															
Item	Load Regulation																																	
Object	+12V0.13A																																	
1.Graph	<p>—△— Input Volt. 4.5V - - □ - - Input Volt. 5V - · ○ - - Input Volt. 9V</p>  <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Volt. 4.5V [V]</th> <th>Output Volt. 5V [V]</th> <th>Output Volt. 9V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.376</td><td>12.376</td><td>12.365</td></tr> <tr><td>0.026</td><td>12.270</td><td>12.268</td><td>12.261</td></tr> <tr><td>0.052</td><td>12.232</td><td>12.230</td><td>12.223</td></tr> <tr><td>0.078</td><td>12.205</td><td>12.203</td><td>12.198</td></tr> <tr><td>0.104</td><td>12.181</td><td>12.180</td><td>12.177</td></tr> <tr><td>0.130</td><td>12.158</td><td>12.160</td><td>12.160</td></tr> <tr><td>0.143</td><td>12.147</td><td>12.149</td><td>12.152</td></tr> </tbody> </table>	Load Current [A]	Output Volt. 4.5V [V]	Output Volt. 5V [V]	Output Volt. 9V [V]	0.00	12.376	12.376	12.365	0.026	12.270	12.268	12.261	0.052	12.232	12.230	12.223	0.078	12.205	12.203	12.198	0.104	12.181	12.180	12.177	0.130	12.158	12.160	12.160	0.143	12.147	12.149	12.152	2.Values
Load Current [A]	Output Volt. 4.5V [V]	Output Volt. 5V [V]	Output Volt. 9V [V]																															
0.00	12.376	12.376	12.365																															
0.026	12.270	12.268	12.261																															
0.052	12.232	12.230	12.223																															
0.078	12.205	12.203	12.198																															
0.104	12.181	12.180	12.177																															
0.130	12.158	12.160	12.160																															
0.143	12.147	12.149	12.152																															
Object	-12V0.13A	Load Current [A]	Output Voltage [V]																															
1.Graph	<p>—△— Input Volt. 4.5V - - □ - - Input Volt. 5V - · ○ - - Input Volt. 9V</p>  <table border="1"> <caption>Data points estimated from Graph 2</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Volt. 4.5V [V]</th> <th>Output Volt. 5V [V]</th> <th>Output Volt. 9V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-12.381</td><td>-12.381</td><td>-12.369</td></tr> <tr><td>0.026</td><td>-12.266</td><td>-12.263</td><td>-12.255</td></tr> <tr><td>0.052</td><td>-12.228</td><td>-12.225</td><td>-12.217</td></tr> <tr><td>0.078</td><td>-12.200</td><td>-12.198</td><td>-12.192</td></tr> <tr><td>0.104</td><td>-12.177</td><td>-12.175</td><td>-12.172</td></tr> <tr><td>0.130</td><td>-12.154</td><td>-12.154</td><td>-12.154</td></tr> <tr><td>0.143</td><td>-12.143</td><td>-12.145</td><td>-12.146</td></tr> </tbody> </table>	Load Current [A]	Output Volt. 4.5V [V]	Output Volt. 5V [V]	Output Volt. 9V [V]	0.00	-12.381	-12.381	-12.369	0.026	-12.266	-12.263	-12.255	0.052	-12.228	-12.225	-12.217	0.078	-12.200	-12.198	-12.192	0.104	-12.177	-12.175	-12.172	0.130	-12.154	-12.154	-12.154	0.143	-12.143	-12.145	-12.146	2.Values
Load Current [A]	Output Volt. 4.5V [V]	Output Volt. 5V [V]	Output Volt. 9V [V]																															
0.00	-12.381	-12.381	-12.369																															
0.026	-12.266	-12.263	-12.255																															
0.052	-12.228	-12.225	-12.217																															
0.078	-12.200	-12.198	-12.192																															
0.104	-12.177	-12.175	-12.172																															
0.130	-12.154	-12.154	-12.154																															
0.143	-12.143	-12.145	-12.146																															
Note: Slanted line shows the range of the rated load current.																																		

COSEL




COSEL



Model	SUTW30512
Item	Ripple Voltage (by Load Current)
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.000	3	3
0.026	3	3
0.052	3	3
0.078	4	3
0.104	6	4
0.130	6	5
0.143	7	5
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW30512
Item	Ripple Voltage (by Load Current)
Object	-12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values


Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.000	4	3
0.026	4	3
0.052	4	3
0.078	4	3
0.104	5	4
0.130	8	4
0.143	10	4
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.


Ripple [mVp-p]



Model	SUTW30512
Item	Ripple-Noise
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.000	4	4
0.026	7	6
0.052	7	7
0.078	8	8
0.104	9	9
0.130	13	9
0.143	15	10
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW30512																																							
Item	Ripple-Noise	Temperature Testing Circuitry 25°C Figure B																																						
Object	-12V0.13A																																							
1. Graph																																								
<p>Y-axis: Ripple-Noise [mV] X-axis: Load Current [A]</p> <p>Legend: —△— Input Volt. 4.5V -·○-- Input Volt. 9V </p>																																								
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Y-axis: Ripple Noise[mVp-p]</p>																																								
Fig.Complex Ripple Noise Wave Form																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>7</td><td>8</td></tr> <tr><td>0.026</td><td>9</td><td>10</td></tr> <tr><td>0.052</td><td>10</td><td>10</td></tr> <tr><td>0.078</td><td>10</td><td>11</td></tr> <tr><td>0.104</td><td>10</td><td>11</td></tr> <tr><td>0.130</td><td>11</td><td>11</td></tr> <tr><td>0.143</td><td>12</td><td>11</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	7	8	0.026	9	10	0.052	10	10	0.078	10	11	0.104	10	11	0.130	11	11	0.143	12	11	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	7	8																																						
0.026	9	10																																						
0.052	10	10																																						
0.078	10	11																																						
0.104	10	11																																						
0.130	11	11																																						
0.143	12	11																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						

Model	SUTW30512
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.13A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	4	10
-20	4	10
0	3	6
25	3	6
55	2	5
60	2	5
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph





2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	7	11
-40	6	10
-20	6	10
0	6	8
25	4	7
55	3	5
60	3	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW30512	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+12V0.13A																																																						
1.Graph	<p style="text-align: center;"> —△— Input Volt. 4.5V ---□--- Input Volt. 5V —·○—· Input Volt. 9V </p>  <table border="1"> <caption>Data for +12V0.13A Graph</caption> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>4.5[V] Output [V]</th> <th>5[V] Output [V]</th> <th>9[V] Output [V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.070</td><td>12.072</td><td>12.073</td></tr> <tr><td>-40</td><td>12.098</td><td>12.100</td><td>12.101</td></tr> <tr><td>-20</td><td>12.122</td><td>12.123</td><td>12.124</td></tr> <tr><td>0</td><td>12.142</td><td>12.143</td><td>12.143</td></tr> <tr><td>25</td><td>12.159</td><td>12.159</td><td>12.160</td></tr> <tr><td>55</td><td>12.170</td><td>12.169</td><td>12.170</td></tr> <tr><td>60</td><td>12.171</td><td>12.170</td><td>12.170</td></tr> </tbody> </table>	Ambient Temperature [°C]	4.5[V] Output [V]	5[V] Output [V]	9[V] Output [V]	-60	12.070	12.072	12.073	-40	12.098	12.100	12.101	-20	12.122	12.123	12.124	0	12.142	12.143	12.143	25	12.159	12.159	12.160	55	12.170	12.169	12.170	60	12.171	12.170	12.170																						
Ambient Temperature [°C]	4.5[V] Output [V]	5[V] Output [V]	9[V] Output [V]																																																				
-60	12.070	12.072	12.073																																																				
-40	12.098	12.100	12.101																																																				
-20	12.122	12.123	12.124																																																				
0	12.142	12.143	12.143																																																				
25	12.159	12.159	12.160																																																				
55	12.170	12.169	12.170																																																				
60	12.171	12.170	12.170																																																				
2.Values																																																							
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.070</td><td>12.072</td><td>12.073</td></tr> <tr><td>-40</td><td>12.098</td><td>12.100</td><td>12.101</td></tr> <tr><td>-20</td><td>12.122</td><td>12.123</td><td>12.124</td></tr> <tr><td>0</td><td>12.142</td><td>12.143</td><td>12.143</td></tr> <tr><td>25</td><td>12.159</td><td>12.159</td><td>12.160</td></tr> <tr><td>55</td><td>12.170</td><td>12.169</td><td>12.170</td></tr> <tr><td>60</td><td>12.171</td><td>12.170</td><td>12.170</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	12.070	12.072	12.073	-40	12.098	12.100	12.101	-20	12.122	12.123	12.124	0	12.142	12.143	12.143	25	12.159	12.159	12.160	55	12.170	12.169	12.170	60	12.171	12.170	12.170	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																				
-60	12.070	12.072	12.073																																																				
-40	12.098	12.100	12.101																																																				
-20	12.122	12.123	12.124																																																				
0	12.142	12.143	12.143																																																				
25	12.159	12.159	12.160																																																				
55	12.170	12.169	12.170																																																				
60	12.171	12.170	12.170																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Object	-12V0.13A																																																						
1.Graph	<p style="text-align: center;"> —△— Input Volt. 4.5V ---□--- Input Volt. 5V —·○—· Input Volt. 9V </p>  <table border="1"> <caption>Data for -12V0.13A Graph</caption> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>4.5[V] Output [V]</th> <th>5[V] Output [V]</th> <th>9[V] Output [V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.062</td><td>-12.065</td><td>-12.066</td></tr> <tr><td>-40</td><td>-12.090</td><td>-12.093</td><td>-12.094</td></tr> <tr><td>-20</td><td>-12.115</td><td>-12.117</td><td>-12.117</td></tr> <tr><td>0</td><td>-12.135</td><td>-12.136</td><td>-12.136</td></tr> <tr><td>25</td><td>-12.153</td><td>-12.154</td><td>-12.154</td></tr> <tr><td>55</td><td>-12.163</td><td>-12.164</td><td>-12.164</td></tr> <tr><td>60</td><td>-12.164</td><td>-12.165</td><td>-12.164</td></tr> </tbody> </table>	Ambient Temperature [°C]	4.5[V] Output [V]	5[V] Output [V]	9[V] Output [V]	-60	-12.062	-12.065	-12.066	-40	-12.090	-12.093	-12.094	-20	-12.115	-12.117	-12.117	0	-12.135	-12.136	-12.136	25	-12.153	-12.154	-12.154	55	-12.163	-12.164	-12.164	60	-12.164	-12.165	-12.164																						
Ambient Temperature [°C]	4.5[V] Output [V]	5[V] Output [V]	9[V] Output [V]																																																				
-60	-12.062	-12.065	-12.066																																																				
-40	-12.090	-12.093	-12.094																																																				
-20	-12.115	-12.117	-12.117																																																				
0	-12.135	-12.136	-12.136																																																				
25	-12.153	-12.154	-12.154																																																				
55	-12.163	-12.164	-12.164																																																				
60	-12.164	-12.165	-12.164																																																				
2.Values																																																							
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.062</td><td>-12.065</td><td>-12.066</td></tr> <tr><td>-40</td><td>-12.090</td><td>-12.093</td><td>-12.094</td></tr> <tr><td>-20</td><td>-12.115</td><td>-12.117</td><td>-12.117</td></tr> <tr><td>0</td><td>-12.135</td><td>-12.136</td><td>-12.136</td></tr> <tr><td>25</td><td>-12.153</td><td>-12.154</td><td>-12.154</td></tr> <tr><td>55</td><td>-12.163</td><td>-12.164</td><td>-12.164</td></tr> <tr><td>60</td><td>-12.164</td><td>-12.165</td><td>-12.164</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	-12.062	-12.065	-12.066	-40	-12.090	-12.093	-12.094	-20	-12.115	-12.117	-12.117	0	-12.135	-12.136	-12.136	25	-12.153	-12.154	-12.154	55	-12.163	-12.164	-12.164	60	-12.164	-12.165	-12.164	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																				
-60	-12.062	-12.065	-12.066																																																				
-40	-12.090	-12.093	-12.094																																																				
-20	-12.115	-12.117	-12.117																																																				
0	-12.135	-12.136	-12.136																																																				
25	-12.153	-12.154	-12.154																																																				
55	-12.163	-12.164	-12.164																																																				
60	-12.164	-12.165	-12.164																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						



Model	SUTW30512	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.13A (AVR 2) : 0 - 0.13A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.13A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	4.5	0	12.390	±253	±2.1	
Minimum Voltage	-40	4.5	0.13	11.885			

Object		-12V0.13A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	55	4.5	0	-12.395	±253	±2.1	
Minimum Voltage	-40	4.5	0.13	-11.890			

COSEL


Model	SUTW30512	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift																							
Object	+12V0.13A																							
1.Graph		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.150</td></tr> <tr><td>0.5</td><td>12.160</td></tr> <tr><td>1.0</td><td>12.160</td></tr> <tr><td>2.0</td><td>12.160</td></tr> <tr><td>3.0</td><td>12.160</td></tr> <tr><td>4.0</td><td>12.160</td></tr> <tr><td>5.0</td><td>12.160</td></tr> <tr><td>6.0</td><td>12.160</td></tr> <tr><td>7.0</td><td>12.160</td></tr> <tr><td>8.0</td><td>12.160</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.150	0.5	12.160	1.0	12.160	2.0	12.160	3.0	12.160	4.0	12.160	5.0	12.160	6.0	12.160	7.0	12.160	8.0	12.160
Time since start [H]	Output Voltage [V]																							
0.0	12.150																							
0.5	12.160																							
1.0	12.160																							
2.0	12.160																							
3.0	12.160																							
4.0	12.160																							
5.0	12.160																							
6.0	12.160																							
7.0	12.160																							
8.0	12.160																							
Object -12V0.13A		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.149</td></tr> <tr><td>0.5</td><td>-12.158</td></tr> <tr><td>1.0</td><td>-12.158</td></tr> <tr><td>2.0</td><td>-12.158</td></tr> <tr><td>3.0</td><td>-12.158</td></tr> <tr><td>4.0</td><td>-12.158</td></tr> <tr><td>5.0</td><td>-12.158</td></tr> <tr><td>6.0</td><td>-12.158</td></tr> <tr><td>7.0</td><td>-12.158</td></tr> <tr><td>8.0</td><td>-12.158</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-12.149	0.5	-12.158	1.0	-12.158	2.0	-12.158	3.0	-12.158	4.0	-12.158	5.0	-12.158	6.0	-12.158	7.0	-12.158	8.0	-12.158
Time since start [H]	Output Voltage [V]																							
0.0	-12.149																							
0.5	-12.158																							
1.0	-12.158																							
2.0	-12.158																							
3.0	-12.158																							
4.0	-12.158																							
5.0	-12.158																							
6.0	-12.158																							
7.0	-12.158																							
8.0	-12.158																							

COSEL

Model	SUTW30512
Item	Rise and Fall Time
Object	+12V0.13A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.2	5.0	5.2	0.1	2.4	
100 %		0.2	5.6	5.8	0.1	1.2	




COSEL

Model	SUTW30512
Item	Rise and Fall Time
Object	-12V0.13A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.2	6.1	6.3	0.1	2.8
100 %		0.2	6.7	6.9	0.1	1.4



COSEL

Model	SUTW30512
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.13A

1.Graph




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.0	2.7
-40	2.1	2.7
-20	2.3	2.7
0	1.9	2.7
25	2.2	3.2
55	2.2	2.9
60	2.3	3.0
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.13A
--------	-----------



1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.0	2.7
-40	2.0	2.7
-20	2.0	2.7
0	1.9	2.7
25	2.2	2.9
55	2.2	2.9
60	2.2	2.9
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW30512	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+12V0.13A																																																								
1.Graph	<p>— Input Volt. 4.5V — Input Volt. 5V — Input Volt. 9V</p>  <table border="1"> <caption>Data for +12V0.13A Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>4.5V [V]</th> <th>5V [V]</th> <th>9V [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.0</td><td>12.0</td><td>12.0</td></tr> <tr><td>0.1</td><td>12.0</td><td>12.0</td><td>12.0</td></tr> <tr><td>0.2</td><td>12.0</td><td>12.0</td><td>12.0</td></tr> <tr><td>0.3</td><td>12.0</td><td>12.0</td><td>12.0</td></tr> <tr><td>0.35</td><td>12.0</td><td>11.4</td><td>9.6</td></tr> <tr><td>0.4</td><td>11.4</td><td>8.4</td><td>6.0</td></tr> <tr><td>0.45</td><td>8.4</td><td>5.6</td><td>4.8</td></tr> <tr><td>0.5</td><td>5.6</td><td>3.6</td><td>3.6</td></tr> <tr><td>0.6</td><td>3.6</td><td>0.0</td><td>0.0</td></tr> </tbody> </table>	Load Current [A]	4.5V [V]	5V [V]	9V [V]	0.0	12.0	12.0	12.0	0.1	12.0	12.0	12.0	0.2	12.0	12.0	12.0	0.3	12.0	12.0	12.0	0.35	12.0	11.4	9.6	0.4	11.4	8.4	6.0	0.45	8.4	5.6	4.8	0.5	5.6	3.6	3.6	0.6	3.6	0.0	0.0																
Load Current [A]	4.5V [V]	5V [V]	9V [V]																																																						
0.0	12.0	12.0	12.0																																																						
0.1	12.0	12.0	12.0																																																						
0.2	12.0	12.0	12.0																																																						
0.3	12.0	12.0	12.0																																																						
0.35	12.0	11.4	9.6																																																						
0.4	11.4	8.4	6.0																																																						
0.45	8.4	5.6	4.8																																																						
0.5	5.6	3.6	3.6																																																						
0.6	3.6	0.0	0.0																																																						
2.Values																																																									
	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.13</td><td>0.13</td><td>0.13</td></tr> <tr><td>11.4</td><td>0.28</td><td>0.29</td><td>0.30</td></tr> <tr><td>10.8</td><td>0.29</td><td>0.30</td><td>0.31</td></tr> <tr><td>9.6</td><td>0.32</td><td>0.33</td><td>0.33</td></tr> <tr><td>8.4</td><td>0.36</td><td>0.36</td><td>0.35</td></tr> <tr><td>7.2</td><td>0.38</td><td>0.38</td><td>0.37</td></tr> <tr><td>6.0</td><td>0.41</td><td>0.41</td><td>0.38</td></tr> <tr><td>4.8</td><td>0.43</td><td>0.42</td><td>0.38</td></tr> <tr><td>3.6</td><td>0.44</td><td>0.43</td><td>0.38</td></tr> <tr><td>2.4</td><td>0.45</td><td>0.43</td><td>0.37</td></tr> <tr><td>1.2</td><td>0.41</td><td>0.39</td><td>0.35</td></tr> <tr><td>0.0</td><td>0.36</td><td>0.36</td><td>0.34</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	12.0	0.13	0.13	0.13	11.4	0.28	0.29	0.30	10.8	0.29	0.30	0.31	9.6	0.32	0.33	0.33	8.4	0.36	0.36	0.35	7.2	0.38	0.38	0.37	6.0	0.41	0.41	0.38	4.8	0.43	0.42	0.38	3.6	0.44	0.43	0.38	2.4	0.45	0.43	0.37	1.2	0.41	0.39	0.35	0.0	0.36	0.36	0.34	
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																						
12.0	0.13	0.13	0.13																																																						
11.4	0.28	0.29	0.30																																																						
10.8	0.29	0.30	0.31																																																						
9.6	0.32	0.33	0.33																																																						
8.4	0.36	0.36	0.35																																																						
7.2	0.38	0.38	0.37																																																						
6.0	0.41	0.41	0.38																																																						
4.8	0.43	0.42	0.38																																																						
3.6	0.44	0.43	0.38																																																						
2.4	0.45	0.43	0.37																																																						
1.2	0.41	0.39	0.35																																																						
0.0	0.36	0.36	0.34																																																						
Object	-12V0.13A	2.Values																																																							
1.Graph	<p>— Input Volt. 4.5V — Input Volt. 5V — Input Volt. 9V</p>  <table border="1"> <caption>Data for -12V0.13A Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>4.5V [V]</th> <th>5V [V]</th> <th>9V [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.0</td><td>-12.0</td><td>-12.0</td></tr> <tr><td>0.1</td><td>-12.0</td><td>-12.0</td><td>-12.0</td></tr> <tr><td>0.2</td><td>-12.0</td><td>-12.0</td><td>-12.0</td></tr> <tr><td>0.3</td><td>-12.0</td><td>-12.0</td><td>-12.0</td></tr> <tr><td>0.35</td><td>-12.0</td><td>-11.4</td><td>-9.6</td></tr> <tr><td>0.4</td><td>-11.4</td><td>-8.4</td><td>-6.0</td></tr> <tr><td>0.45</td><td>-8.4</td><td>-5.6</td><td>-4.8</td></tr> <tr><td>0.5</td><td>-5.6</td><td>-3.6</td><td>-3.6</td></tr> <tr><td>0.6</td><td>-3.6</td><td>0.0</td><td>0.0</td></tr> </tbody> </table>		Load Current [A]	4.5V [V]	5V [V]	9V [V]	0.0	-12.0	-12.0	-12.0	0.1	-12.0	-12.0	-12.0	0.2	-12.0	-12.0	-12.0	0.3	-12.0	-12.0	-12.0	0.35	-12.0	-11.4	-9.6	0.4	-11.4	-8.4	-6.0	0.45	-8.4	-5.6	-4.8	0.5	-5.6	-3.6	-3.6	0.6	-3.6	0.0	0.0															
Load Current [A]	4.5V [V]	5V [V]	9V [V]																																																						
0.0	-12.0	-12.0	-12.0																																																						
0.1	-12.0	-12.0	-12.0																																																						
0.2	-12.0	-12.0	-12.0																																																						
0.3	-12.0	-12.0	-12.0																																																						
0.35	-12.0	-11.4	-9.6																																																						
0.4	-11.4	-8.4	-6.0																																																						
0.45	-8.4	-5.6	-4.8																																																						
0.5	-5.6	-3.6	-3.6																																																						
0.6	-3.6	0.0	0.0																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-12.0</td><td>0.13</td><td>0.13</td><td>0.13</td></tr> <tr><td>-11.4</td><td>0.28</td><td>0.29</td><td>0.30</td></tr> <tr><td>-10.8</td><td>0.29</td><td>0.30</td><td>0.31</td></tr> <tr><td>-9.6</td><td>0.33</td><td>0.33</td><td>0.33</td></tr> <tr><td>-8.4</td><td>0.36</td><td>0.36</td><td>0.35</td></tr> <tr><td>-7.2</td><td>0.39</td><td>0.38</td><td>0.37</td></tr> <tr><td>-6.0</td><td>0.41</td><td>0.41</td><td>0.38</td></tr> <tr><td>-4.8</td><td>0.43</td><td>0.43</td><td>0.39</td></tr> <tr><td>-3.6</td><td>0.45</td><td>0.43</td><td>0.38</td></tr> <tr><td>-2.4</td><td>0.44</td><td>0.43</td><td>0.38</td></tr> <tr><td>-1.2</td><td>0.41</td><td>0.39</td><td>0.35</td></tr> <tr><td>0.0</td><td>0.36</td><td>0.36</td><td>0.34</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-12.0	0.13	0.13	0.13	-11.4	0.28	0.29	0.30	-10.8	0.29	0.30	0.31	-9.6	0.33	0.33	0.33	-8.4	0.36	0.36	0.35	-7.2	0.39	0.38	0.37	-6.0	0.41	0.41	0.38	-4.8	0.43	0.43	0.39	-3.6	0.45	0.43	0.38	-2.4	0.44	0.43	0.38	-1.2	0.41	0.39	0.35	0.0	0.36	0.36	0.34	
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																						
-12.0	0.13	0.13	0.13																																																						
-11.4	0.28	0.29	0.30																																																						
-10.8	0.29	0.30	0.31																																																						
-9.6	0.33	0.33	0.33																																																						
-8.4	0.36	0.36	0.35																																																						
-7.2	0.39	0.38	0.37																																																						
-6.0	0.41	0.41	0.38																																																						
-4.8	0.43	0.43	0.39																																																						
-3.6	0.45	0.43	0.38																																																						
-2.4	0.44	0.43	0.38																																																						
-1.2	0.41	0.39	0.35																																																						
0.0	0.36	0.36	0.34																																																						
Note:	Slanted line shows the range of the rated load current.																																																								




Figure A




Figure B (Ripple and Ripple noise Characteristic)