

TEST DATA OF SUTW30515

Regulated DC Power Supply

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.


CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)

Model	SUTW30515	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>1.70</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>2.00</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>2.66</td><td>0.129</td><td>1.024</td><td>1.929</td></tr> <tr><td>3.00</td><td>0.120</td><td>0.805</td><td>1.686</td></tr> <tr><td>4.00</td><td>0.097</td><td>0.548</td><td>1.042</td></tr> <tr><td>4.50</td><td>0.090</td><td>0.480</td><td>0.937</td></tr> <tr><td>5.00</td><td>0.083</td><td>0.430</td><td>0.817</td></tr> <tr><td>6.00</td><td>0.075</td><td>0.359</td><td>0.675</td></tr> <tr><td>7.00</td><td>0.068</td><td>0.312</td><td>0.573</td></tr> <tr><td>8.00</td><td>0.064</td><td>0.277</td><td>0.501</td></tr> <tr><td>9.00</td><td>0.062</td><td>0.251</td><td>0.448</td></tr> <tr><td>10.00</td><td>0.062</td><td>0.235</td><td>0.407</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.00	0.000	0.000	0.000	1.70	0.009	0.009	0.009	2.00	0.009	0.009	0.009	2.66	0.129	1.024	1.929	3.00	0.120	0.805	1.686	4.00	0.097	0.548	1.042	4.50	0.090	0.480	0.937	5.00	0.083	0.430	0.817	6.00	0.075	0.359	0.675	7.00	0.068	0.312	0.573	8.00	0.064	0.277	0.501	9.00	0.062	0.251	0.448	10.00	0.062	0.235	0.407	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.00	0.000	0.000	0.000																																																																																
1.70	0.009	0.009	0.009																																																																																
2.00	0.009	0.009	0.009																																																																																
2.66	0.129	1.024	1.929																																																																																
3.00	0.120	0.805	1.686																																																																																
4.00	0.097	0.548	1.042																																																																																
4.50	0.090	0.480	0.937																																																																																
5.00	0.083	0.430	0.817																																																																																
6.00	0.075	0.359	0.675																																																																																
7.00	0.068	0.312	0.573																																																																																
8.00	0.064	0.277	0.501																																																																																
9.00	0.062	0.251	0.448																																																																																
10.00	0.062	0.235	0.407																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																


Model	SUTW30515	Temperature Testing Circuitry 25°C Figure A																																														
Item	Input Current (by Load Current)																																															
Object	_____																																															
1.Graph		2.Values																																														
<p>—△— Input Volt. 4.5V - - -□- - Input Volt. 5V - - ○- - Input Volt. 9V</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 4.5V [A]</th> <th>Input Volt. 5V [A]</th> <th>Input Volt. 9V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.088</td><td>0.082</td><td>0.061</td></tr> <tr><td>20</td><td>0.233</td><td>0.214</td><td>0.143</td></tr> <tr><td>40</td><td>0.391</td><td>0.351</td><td>0.213</td></tr> <tr><td>60</td><td>0.556</td><td>0.497</td><td>0.289</td></tr> <tr><td>80</td><td>0.718</td><td>0.638</td><td>0.368</td></tr> <tr><td>100</td><td>0.881</td><td>0.796</td><td>0.444</td></tr> <tr><td>110</td><td>0.935</td><td>0.858</td><td>0.482</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Volt. 4.5V [A]	Input Volt. 5V [A]	Input Volt. 9V [A]	0	0.088	0.082	0.061	20	0.233	0.214	0.143	40	0.391	0.351	0.213	60	0.556	0.497	0.289	80	0.718	0.638	0.368	100	0.881	0.796	0.444	110	0.935	0.858	0.482	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Volt. 4.5V [A]	Input Volt. 5V [A]	Input Volt. 9V [A]																																													
0	0.088	0.082	0.061																																													
20	0.233	0.214	0.143																																													
40	0.391	0.351	0.213																																													
60	0.556	0.497	0.289																																													
80	0.718	0.638	0.368																																													
100	0.881	0.796	0.444																																													
110	0.935	0.858	0.482																																													
--	-	-	-																																													
--	-	-	-																																													
--	-	-	-																																													
--	-	-	-																																													

Model	SUTW30515	Temperature Testing Circuitry 25°C Figure A																																																
Item	Input Power (by Load Current)																																																	
Object	_____																																																	
1.Graph		2.Values																																																
<p>—△— Input Volt. 4.5V - - -□- - Input Volt. 5V - - ○ - - Input Volt. 9V</p>  <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (4.5V)</th> <th>Input Power [W] (5V)</th> <th>Input Power [W] (9V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.38</td><td>0.40</td><td>0.53</td></tr> <tr><td>20</td><td>1.06</td><td>1.08</td><td>1.24</td></tr> <tr><td>40</td><td>1.75</td><td>1.77</td><td>1.93</td></tr> <tr><td>60</td><td>2.46</td><td>2.45</td><td>2.60</td></tr> <tr><td>80</td><td>3.19</td><td>3.17</td><td>3.27</td></tr> <tr><td>100</td><td>3.96</td><td>3.92</td><td>3.99</td></tr> <tr><td>110</td><td>4.33</td><td>4.29</td><td>4.31</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Power [W] (4.5V)	Input Power [W] (5V)	Input Power [W] (9V)	0	0.38	0.40	0.53	20	1.06	1.08	1.24	40	1.75	1.77	1.93	60	2.46	2.45	2.60	80	3.19	3.17	3.27	100	3.96	3.92	3.99	110	4.33	4.29	4.31	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Ration [%]	Input Power [W] (4.5V)	Input Power [W] (5V)	Input Power [W] (9V)																																															
0	0.38	0.40	0.53																																															
20	1.06	1.08	1.24																																															
40	1.75	1.77	1.93																																															
60	2.46	2.45	2.60																																															
80	3.19	3.17	3.27																																															
100	3.96	3.92	3.99																																															
110	4.33	4.29	4.31																																															
--	-	-	-																																															
--	-	-	-																																															
--	-	-	-																																															
--	-	-	-																																															

Model	SUTW30515
Item	Efficiency (by Input Voltage)
Object	—

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
4.0	71.5	74.0
4.5	71.8	75.7
5.0	71.8	76.7
6.0	70.9	77.6
7.0	69.8	77.4
8.0	68.3	77.0
9.0	66.8	76.2
10.0	65.2	75.2
--	-	-


Note: Slanted line shows the range of the rated input voltage.

Model	SUTW30515	Temperature Testing Circuitry 25°C Figure A																																																		
Item	Efficiency (by Load Current)																																																			
Object	_____																																																			
1.Graph		2.Values																																																		
<p>—△— Input Volt. 4.5V - - -□- - Input Volt. 5V - - ○ - - Input Volt. 9V</p>																																																				
<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>20</td><td>57.1</td><td>56.0</td><td>48.8</td></tr> <tr> <td>40</td><td>69.0</td><td>68.5</td><td>62.5</td></tr> <tr> <td>60</td><td>73.7</td><td>74.0</td><td>69.8</td></tr> <tr> <td>80</td><td>75.7</td><td>76.1</td><td>73.9</td></tr> <tr> <td>100</td><td>76.2</td><td>77.0</td><td>75.6</td></tr> <tr> <td>110</td><td>76.7</td><td>77.5</td><td>77.1</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	-	-	-	20	57.1	56.0	48.8	40	69.0	68.5	62.5	60	73.7	74.0	69.8	80	75.7	76.1	73.9	100	76.2	77.0	75.6	110	76.7	77.5	77.1	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																			
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																	
0	-	-	-																																																	
20	57.1	56.0	48.8																																																	
40	69.0	68.5	62.5																																																	
60	73.7	74.0	69.8																																																	
80	75.7	76.1	73.9																																																	
100	76.2	77.0	75.6																																																	
110	76.7	77.5	77.1																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Model	SUTW30515
Item	Line Regulation
Object	+15V0.1A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.0	15.134	15.073
4.5	15.131	15.073
5.0	15.129	15.073
6.0	15.126	15.073
7.0	15.123	15.072
8.0	15.122	15.072
9.0	15.121	15.072
10.0	15.120	15.072
--	-	-

Object -15V0.1A

1.Graph





2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.0	-15.152	-15.088
4.5	-15.149	-15.089
5.0	-15.148	-15.090
6.0	-15.146	-15.091
7.0	-15.144	-15.091
8.0	-15.143	-15.091
9.0	-15.142	-15.091
10.0	-15.142	-15.092
--	-	-

Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	SUTW30515	Temperature Testing Circuitry	25°C Figure A																															
Item	Load Regulation																																	
Object	+15V0.1A																																	
1.Graph	<p>—△— Input Volt. 4.5V - - -□- - Input Volt. 5V - · -○- - Input Volt. 9V</p>  <table border="1"> <caption>Data for +15V0.1A Object</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Volt. 4.5[V]</th> <th>Output Volt. 5[V]</th> <th>Output Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.286</td><td>15.284</td><td>15.270</td></tr> <tr><td>0.02</td><td>15.183</td><td>15.181</td><td>15.172</td></tr> <tr><td>0.04</td><td>15.145</td><td>15.142</td><td>15.134</td></tr> <tr><td>0.06</td><td>15.117</td><td>15.115</td><td>15.109</td></tr> <tr><td>0.08</td><td>15.094</td><td>15.092</td><td>15.088</td></tr> <tr><td>0.10</td><td>15.073</td><td>15.073</td><td>15.071</td></tr> <tr><td>0.11</td><td>15.062</td><td>15.063</td><td>15.063</td></tr> </tbody> </table>	Load Current [A]	Output Volt. 4.5[V]	Output Volt. 5[V]	Output Volt. 9[V]	0.00	15.286	15.284	15.270	0.02	15.183	15.181	15.172	0.04	15.145	15.142	15.134	0.06	15.117	15.115	15.109	0.08	15.094	15.092	15.088	0.10	15.073	15.073	15.071	0.11	15.062	15.063	15.063	2.Values
Load Current [A]	Output Volt. 4.5[V]	Output Volt. 5[V]	Output Volt. 9[V]																															
0.00	15.286	15.284	15.270																															
0.02	15.183	15.181	15.172																															
0.04	15.145	15.142	15.134																															
0.06	15.117	15.115	15.109																															
0.08	15.094	15.092	15.088																															
0.10	15.073	15.073	15.071																															
0.11	15.062	15.063	15.063																															
Object	-15V0.1A	Load Current [A]	Output Voltage [V]																															
1.Graph	<p>—△— Input Volt. 4.5V - - -□- - Input Volt. 5V - · -○- - Input Volt. 9V</p>  <table border="1"> <caption>Data for -15V0.1A Object</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Volt. 4.5[V]</th> <th>Output Volt. 5[V]</th> <th>Output Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.335</td><td>-15.330</td><td>-15.309</td></tr> <tr><td>0.02</td><td>-15.207</td><td>-15.205</td><td>-15.198</td></tr> <tr><td>0.04</td><td>-15.164</td><td>-15.162</td><td>-15.156</td></tr> <tr><td>0.06</td><td>-15.134</td><td>-15.133</td><td>-15.129</td></tr> <tr><td>0.08</td><td>-15.110</td><td>-15.110</td><td>-15.108</td></tr> <tr><td>0.10</td><td>-15.088</td><td>-15.088</td><td>-15.090</td></tr> <tr><td>0.11</td><td>-15.077</td><td>-15.078</td><td>-15.082</td></tr> </tbody> </table>	Load Current [A]	Output Volt. 4.5[V]	Output Volt. 5[V]	Output Volt. 9[V]	0.00	-15.335	-15.330	-15.309	0.02	-15.207	-15.205	-15.198	0.04	-15.164	-15.162	-15.156	0.06	-15.134	-15.133	-15.129	0.08	-15.110	-15.110	-15.108	0.10	-15.088	-15.088	-15.090	0.11	-15.077	-15.078	-15.082	2.Values
Load Current [A]	Output Volt. 4.5[V]	Output Volt. 5[V]	Output Volt. 9[V]																															
0.00	-15.335	-15.330	-15.309																															
0.02	-15.207	-15.205	-15.198																															
0.04	-15.164	-15.162	-15.156																															
0.06	-15.134	-15.133	-15.129																															
0.08	-15.110	-15.110	-15.108																															
0.10	-15.088	-15.088	-15.090																															
0.11	-15.077	-15.078	-15.082																															
Note: Slanted line shows the range of the rated load current.																																		

COSEL




COSEL



Model	SUTW30515
Item	Ripple Voltage (by Load Current)
Object	+15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.00	3	3
0.02	3	3
0.04	3	3
0.06	4	3
0.08	7	3
0.10	7	4
0.11	8	5
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW30515
Item	Ripple Voltage (by Load Current)
Object	-15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.00	3	2
0.02	3	2
0.04	3	2
0.06	4	2
0.08	4	2
0.10	5	2
0.11	5	2
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW30515
Item	Ripple-Noise
Object	+15V0.1A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.00	3	5
0.02	5	5
0.04	5	5
0.06	7	6
0.08	9	6
0.10	12	7
0.11	14	7
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW30515	Temperature Testing Circuitry 25°C Figure B
Item	Ripple-Noise	
Object	-15V0.1A	

1. Graph




Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values


Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.00	3	3
0.02	5	5
0.04	5	5
0.06	6	5
0.08	8	6
0.10	12	6
0.11	14	6
--	-	-
--	-	-
--	-	-
--	-	-



Model	SUTW30515
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.1A

1.Graph

---□--- Load 50%
—△— Load 100%




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	8	10
-40	8	10
-20	8	10
0	8	8
25	5	6
55	2	6
60	2	6
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph

---□--- Load 50%
—△— Load 100%



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	3	3
-40	2	3
-20	2	3
0	2	3
25	2	3
55	2	3
60	2	3
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW30515
Item	Ambient Temperature Drift
Object	+15V0.1A

Testing Circuitry Figure A

1.Graph

- △— Input Volt. 4.5V
- - - □ - - Input Volt. 5V
- · ○ - - Input Volt. 9V




2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
-60	14.985	14.986	14.985
-40	15.013	15.014	15.013
-20	15.037	15.037	15.036
0	15.056	15.056	15.054
25	15.071	15.071	15.070
55	15.079	15.079	15.077
60	15.079	15.079	15.077
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

1.Graph

- △— Input Volt. 4.5V
- - - □ - - Input Volt. 5V
- · ○ - - Input Volt. 9V



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
-60	-14.999	-15.003	-15.006
-40	-15.028	-15.031	-15.034
-20	-15.052	-15.054	-15.057
0	-15.071	-15.073	-15.075
25	-15.086	-15.087	-15.089
55	-15.094	-15.094	-15.096
60	-15.094	-15.095	-15.097
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW30515	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.1A (AVR 2) : 0 - 0.1A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+15V0.1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	4.5		0	15.294	
Minimum Voltage	-40	4.5	0.1	14.776	±259	±1.7

Object	-15V0.1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	4.5		0	-15.343	
Minimum Voltage	-40	4.5	0.1	-14.836	±254	±1.7

COSEL


Model	SUTW30515	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V0.1A																								
1.Graph		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>15.063</td></tr> <tr><td>0.5</td><td>15.071</td></tr> <tr><td>1.0</td><td>15.071</td></tr> <tr><td>2.0</td><td>15.071</td></tr> <tr><td>3.0</td><td>15.071</td></tr> <tr><td>4.0</td><td>15.071</td></tr> <tr><td>5.0</td><td>15.071</td></tr> <tr><td>6.0</td><td>15.071</td></tr> <tr><td>7.0</td><td>15.071</td></tr> <tr><td>8.0</td><td>15.071</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	15.063	0.5	15.071	1.0	15.071	2.0	15.071	3.0	15.071	4.0	15.071	5.0	15.071	6.0	15.071	7.0	15.071	8.0	15.071
Time since start [H]	Output Voltage [V]																								
0.0	15.063																								
0.5	15.071																								
1.0	15.071																								
2.0	15.071																								
3.0	15.071																								
4.0	15.071																								
5.0	15.071																								
6.0	15.071																								
7.0	15.071																								
8.0	15.071																								
Object		2.Values																							
1.Graph		 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V</p> <p>Load 100%</p>																							
<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>-15.085</td></tr> <tr><td>0.5</td><td>-15.092</td></tr> <tr><td>1.0</td><td>-15.092</td></tr> <tr><td>2.0</td><td>-15.092</td></tr> <tr><td>3.0</td><td>-15.092</td></tr> <tr><td>4.0</td><td>-15.092</td></tr> <tr><td>5.0</td><td>-15.092</td></tr> <tr><td>6.0</td><td>-15.092</td></tr> <tr><td>7.0</td><td>-15.091</td></tr> <tr><td>8.0</td><td>-15.092</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-15.085	0.5	-15.092	1.0	-15.092	2.0	-15.092	3.0	-15.092	4.0	-15.092	5.0	-15.092	6.0	-15.092	7.0	-15.091	8.0	-15.092		
Time since start [H]	Output Voltage [V]																								
0.0	-15.085																								
0.5	-15.092																								
1.0	-15.092																								
2.0	-15.092																								
3.0	-15.092																								
4.0	-15.092																								
5.0	-15.092																								
6.0	-15.092																								
7.0	-15.091																								
8.0	-15.092																								

COSEL

Model	SUTW30515
Item	Rise and Fall Time
Object	+15V0.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.2	5.4	5.6	0.1	2.5
100 %		0.2	5.6	5.8	0.1	1.2




COSEL

Model	SUTW30515
Item	Rise and Fall Time
Object	-15V0.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph







2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.2	5.4	5.6	0.1	3.3	
100 %		0.2	5.7	5.9	0.1	1.6	



COSEL

Model SUTW30515 Item Minimum Input Voltage for Regulated Output Voltage Object +15V0.1A	Testing Circuitry Figure A																																						
	2.Values																																						
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>2.1</td><td>2.6</td></tr> <tr><td>-40</td><td>2.1</td><td>2.8</td></tr> <tr><td>-20</td><td>2.1</td><td>2.8</td></tr> <tr><td>0</td><td>2.1</td><td>2.8</td></tr> <tr><td>25</td><td>2.0</td><td>2.8</td></tr> <tr><td>55</td><td>2.3</td><td>3.0</td></tr> <tr><td>60</td><td>2.3</td><td>3.0</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	2.1	2.6	-40	2.1	2.8	-20	2.1	2.8	0	2.1	2.8	25	2.0	2.8	55	2.3	3.0	60	2.3	3.0	--	-	-	--	-	-	--	-	-	--	-
Ambient Temperature [°C]	Input Voltage [V]																																						
	Load 50%	Load 100%																																					
-60	2.1	2.6																																					
-40	2.1	2.8																																					
-20	2.1	2.8																																					
0	2.1	2.8																																					
25	2.0	2.8																																					
55	2.3	3.0																																					
60	2.3	3.0																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
1.Graph 																																							
Object -15V0.1A																																							
1.Graph 																																							
Note: Slanted line shows the range of the rated ambient temperature.																																							
- 20 -																																							
BC-10243																																							

Model	SUTW30515			Temperature 25°C																																																							
Item	Overcurrent Protection			Testing Circuitry Figure A																																																							
Object	+15V0.1A																																																										
1.Graph		————— Input Volt. 4.5V ———— Input Volt. 5V ———— Input Volt. 9V																																																									
		2.Values																																																									
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr> <tr> <th>Input Volt. 4.5[V]</th><th>Input Volt. 5[V]</th><th>Input Volt. 9[V]</th></tr> </thead> <tbody> <tr><td>15.0</td><td>0.10</td><td>0.10</td><td>0.10</td></tr> <tr><td>14.3</td><td>0.20</td><td>0.20</td><td>0.22</td></tr> <tr><td>13.5</td><td>0.21</td><td>0.21</td><td>0.23</td></tr> <tr><td>12.0</td><td>0.24</td><td>0.24</td><td>0.25</td></tr> <tr><td>10.5</td><td>0.27</td><td>0.27</td><td>0.27</td></tr> <tr><td>9.0</td><td>0.29</td><td>0.30</td><td>0.29</td></tr> <tr><td>7.5</td><td>0.32</td><td>0.32</td><td>0.31</td></tr> <tr><td>6.0</td><td>0.35</td><td>0.35</td><td>0.32</td></tr> <tr><td>4.5</td><td>0.37</td><td>0.36</td><td>0.33</td></tr> <tr><td>3.0</td><td>0.38</td><td>0.37</td><td>0.33</td></tr> <tr><td>1.5</td><td>0.36</td><td>0.35</td><td>0.32</td></tr> <tr><td>0.0</td><td>0.32</td><td>0.32</td><td>0.38</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	15.0	0.10	0.10	0.10	14.3	0.20	0.20	0.22	13.5	0.21	0.21	0.23	12.0	0.24	0.24	0.25	10.5	0.27	0.27	0.27	9.0	0.29	0.30	0.29	7.5	0.32	0.32	0.31	6.0	0.35	0.35	0.32	4.5	0.37	0.36	0.33	3.0	0.38	0.37	0.33	1.5	0.36	0.35	0.32	0.0	0.32	0.32	0.38
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																								
15.0	0.10	0.10	0.10																																																								
14.3	0.20	0.20	0.22																																																								
13.5	0.21	0.21	0.23																																																								
12.0	0.24	0.24	0.25																																																								
10.5	0.27	0.27	0.27																																																								
9.0	0.29	0.30	0.29																																																								
7.5	0.32	0.32	0.31																																																								
6.0	0.35	0.35	0.32																																																								
4.5	0.37	0.36	0.33																																																								
3.0	0.38	0.37	0.33																																																								
1.5	0.36	0.35	0.32																																																								
0.0	0.32	0.32	0.38																																																								
Object		-15V0.1A																																																									
1.Graph		————— Input Volt. 4.5V ———— Input Volt. 5V ———— Input Volt. 9V																																																									
		2.Values																																																									
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr> <tr> <th>Input Volt. 4.5[V]</th><th>Input Volt. 5[V]</th><th>Input Volt. 9[V]</th></tr> </thead> <tbody> <tr><td>-15.00</td><td>0.10</td><td>0.10</td><td>0.10</td></tr> <tr><td>-14.25</td><td>0.19</td><td>0.20</td><td>0.22</td></tr> <tr><td>-13.50</td><td>0.21</td><td>0.22</td><td>0.23</td></tr> <tr><td>-12.00</td><td>0.24</td><td>0.24</td><td>0.25</td></tr> <tr><td>-10.50</td><td>0.26</td><td>0.27</td><td>0.27</td></tr> <tr><td>-9.00</td><td>0.29</td><td>0.30</td><td>0.29</td></tr> <tr><td>-7.50</td><td>0.32</td><td>0.32</td><td>0.31</td></tr> <tr><td>-6.00</td><td>0.35</td><td>0.35</td><td>0.32</td></tr> <tr><td>-4.50</td><td>0.37</td><td>0.37</td><td>0.33</td></tr> <tr><td>-3.00</td><td>0.38</td><td>0.37</td><td>0.33</td></tr> <tr><td>-1.50</td><td>0.36</td><td>0.35</td><td>0.32</td></tr> <tr><td>0.00</td><td>0.32</td><td>0.32</td><td>0.38</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-15.00	0.10	0.10	0.10	-14.25	0.19	0.20	0.22	-13.50	0.21	0.22	0.23	-12.00	0.24	0.24	0.25	-10.50	0.26	0.27	0.27	-9.00	0.29	0.30	0.29	-7.50	0.32	0.32	0.31	-6.00	0.35	0.35	0.32	-4.50	0.37	0.37	0.33	-3.00	0.38	0.37	0.33	-1.50	0.36	0.35	0.32	0.00	0.32	0.32	0.38
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																								
-15.00	0.10	0.10	0.10																																																								
-14.25	0.19	0.20	0.22																																																								
-13.50	0.21	0.22	0.23																																																								
-12.00	0.24	0.24	0.25																																																								
-10.50	0.26	0.27	0.27																																																								
-9.00	0.29	0.30	0.29																																																								
-7.50	0.32	0.32	0.31																																																								
-6.00	0.35	0.35	0.32																																																								
-4.50	0.37	0.37	0.33																																																								
-3.00	0.38	0.37	0.33																																																								
-1.50	0.36	0.35	0.32																																																								
0.00	0.32	0.32	0.38																																																								
Note: Slanted line shows the range of the rated load current.																																																											




Figure A




Figure B (Ripple and Ripple noise Characteristic)