

TEST DATA OF SUTW61215

Regulated DC Power Supply
March 17, 2009

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Figure of Testing Circuitry	22

(Final Page 22)


Model	SUTW61215	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.009</td><td>0.009</td><td>0.009</td></tr> <tr><td>4.0</td><td>0.009</td><td>0.010</td><td>0.010</td></tr> <tr><td>6.0</td><td>0.008</td><td>0.009</td><td>0.009</td></tr> <tr><td>6.8</td><td>0.009</td><td>0.008</td><td>0.009</td></tr> <tr><td>7.4</td><td>0.064</td><td>0.025</td><td>0.023</td></tr> <tr><td>7.6</td><td>0.062</td><td>0.489</td><td>0.949</td></tr> <tr><td>8.0</td><td>0.059</td><td>0.462</td><td>0.915</td></tr> <tr><td>9.0</td><td>0.056</td><td>0.409</td><td>0.800</td></tr> <tr><td>10.0</td><td>0.052</td><td>0.370</td><td>0.717</td></tr> <tr><td>12.0</td><td>0.051</td><td>0.309</td><td>0.590</td></tr> <tr><td>14.0</td><td>0.046</td><td>0.273</td><td>0.508</td></tr> <tr><td>16.0</td><td>0.045</td><td>0.244</td><td>0.449</td></tr> <tr><td>18.0</td><td>0.045</td><td>0.222</td><td>0.400</td></tr> <tr><td>20.0</td><td>0.049</td><td>0.205</td><td>0.366</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.009	0.009	0.009	4.0	0.009	0.010	0.010	6.0	0.008	0.009	0.009	6.8	0.009	0.008	0.009	7.4	0.064	0.025	0.023	7.6	0.062	0.489	0.949	8.0	0.059	0.462	0.915	9.0	0.056	0.409	0.800	10.0	0.052	0.370	0.717	12.0	0.051	0.309	0.590	14.0	0.046	0.273	0.508	16.0	0.045	0.244	0.449	18.0	0.045	0.222	0.400	20.0	0.049	0.205	0.366	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
2.0	0.009	0.009	0.009																																																																																
4.0	0.009	0.010	0.010																																																																																
6.0	0.008	0.009	0.009																																																																																
6.8	0.009	0.008	0.009																																																																																
7.4	0.064	0.025	0.023																																																																																
7.6	0.062	0.489	0.949																																																																																
8.0	0.059	0.462	0.915																																																																																
9.0	0.056	0.409	0.800																																																																																
10.0	0.052	0.370	0.717																																																																																
12.0	0.051	0.309	0.590																																																																																
14.0	0.046	0.273	0.508																																																																																
16.0	0.045	0.244	0.449																																																																																
18.0	0.045	0.222	0.400																																																																																
20.0	0.049	0.205	0.366																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	SUTW61215	Temperature Testing Circuitry 25°C Figure A																															
Item	Input Current (by Load Current)																																
Object	_____																																
1.Graph		2.Values																															
<p>—△— Input Volt. 9V - - -□- - Input Volt. 12V - - ○- - Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [A]</th> <th>12V [A]</th> <th>18V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.055</td><td>0.048</td><td>0.046</td></tr> <tr><td>20</td><td>0.196</td><td>0.153</td><td>0.118</td></tr> <tr><td>40</td><td>0.336</td><td>0.259</td><td>0.187</td></tr> <tr><td>60</td><td>0.483</td><td>0.363</td><td>0.257</td></tr> <tr><td>80</td><td>0.628</td><td>0.474</td><td>0.328</td></tr> <tr><td>100</td><td>0.785</td><td>0.580</td><td>0.398</td></tr> <tr><td>110</td><td>0.854</td><td>0.636</td><td>0.434</td></tr> </tbody> </table>		Load Ration [%]	9V [A]	12V [A]	18V [A]	0	0.055	0.048	0.046	20	0.196	0.153	0.118	40	0.336	0.259	0.187	60	0.483	0.363	0.257	80	0.628	0.474	0.328	100	0.785	0.580	0.398	110	0.854	0.636	0.434
Load Ration [%]	9V [A]	12V [A]	18V [A]																														
0	0.055	0.048	0.046																														
20	0.196	0.153	0.118																														
40	0.336	0.259	0.187																														
60	0.483	0.363	0.257																														
80	0.628	0.474	0.328																														
100	0.785	0.580	0.398																														
110	0.854	0.636	0.434																														

Model	SUTW61215																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 9V - - -□--- Input Volt. 12V - - ○--- Input Volt. 18V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>0.49</td><td>0.56</td><td>0.83</td></tr> <tr> <td>20</td><td>1.74</td><td>1.83</td><td>2.11</td></tr> <tr> <td>40</td><td>3.02</td><td>3.10</td><td>3.36</td></tr> <tr> <td>60</td><td>4.32</td><td>4.36</td><td>4.62</td></tr> <tr> <td>80</td><td>5.65</td><td>5.66</td><td>5.87</td></tr> <tr> <td>100</td><td>7.00</td><td>6.96</td><td>7.16</td></tr> <tr> <td>110</td><td>7.70</td><td>7.62</td><td>7.80</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	0.49	0.56	0.83	20	1.74	1.83	2.11	40	3.02	3.10	3.36	60	4.32	4.36	4.62	80	5.65	5.66	5.87	100	7.00	6.96	7.16	110	7.70	7.62	7.80	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0	0.49	0.56	0.83																																																			
20	1.74	1.83	2.11																																																			
40	3.02	3.10	3.36																																																			
60	4.32	4.36	4.62																																																			
80	5.65	5.66	5.87																																																			
100	7.00	6.96	7.16																																																			
110	7.70	7.62	7.80																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	SUTW61215	Temperature	25°C
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A
Object	—		

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values


Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
8	81.9	84.6
9	81.7	85.5
10	81.6	85.9
12	80.6	85.8
15	78.0	85.3
18	74.6	84.4
20	72.5	82.8
--	-	-
--	-	-

Model	SUTW61215	Temperature Testing Circuitry 25°C Figure A																																																		
Item	Efficiency (by Load Current)																																																			
Object	_____																																																			
1.Graph		2.Values																																																		
<p>—△— Input Volt. 9V - - -□- - Input Volt. 12V - - ○- - Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Efficiency [9V] (%)</th> <th>Efficiency [12V] (%)</th> <th>Efficiency [18V] (%)</th> </tr> </thead> <tbody> <tr><td>25</td><td>68</td><td>65</td><td>57</td></tr> <tr><td>40</td><td>78</td><td>75</td><td>72</td></tr> <tr><td>50</td><td>82</td><td>80</td><td>78</td></tr> <tr><td>80</td><td>85</td><td>84</td><td>82</td></tr> <tr><td>110</td><td>86</td><td>86</td><td>85</td></tr> </tbody> </table>		Load Ration [%]	Efficiency [9V] (%)	Efficiency [12V] (%)	Efficiency [18V] (%)	25	68	65	57	40	78	75	72	50	82	80	78	80	85	84	82	110	86	86	85																											
Load Ration [%]	Efficiency [9V] (%)	Efficiency [12V] (%)	Efficiency [18V] (%)																																																	
25	68	65	57																																																	
40	78	75	72																																																	
50	82	80	78																																																	
80	85	84	82																																																	
110	86	86	85																																																	
<table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Efficiency [9V] (%)</th> <th>Efficiency [12V] (%)</th> <th>Efficiency [18V] (%)</th> </tr> </thead> <tbody> <tr><td>25</td><td>68</td><td>65</td><td>57</td></tr> <tr><td>40</td><td>78</td><td>75</td><td>72</td></tr> <tr><td>50</td><td>82</td><td>80</td><td>78</td></tr> <tr><td>80</td><td>85</td><td>84</td><td>82</td></tr> <tr><td>110</td><td>86</td><td>86</td><td>85</td></tr> </tbody> </table>		Load Ration [%]	Efficiency [9V] (%)	Efficiency [12V] (%)	Efficiency [18V] (%)	25	68	65	57	40	78	75	72	50	82	80	78	80	85	84	82	110	86	86	85																											
Load Ration [%]	Efficiency [9V] (%)	Efficiency [12V] (%)	Efficiency [18V] (%)																																																	
25	68	65	57																																																	
40	78	75	72																																																	
50	82	80	78																																																	
80	85	84	82																																																	
110	86	86	85																																																	
<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>68.8</td><td>65.5</td><td>56.8</td></tr> <tr><td>40</td><td>79.4</td><td>77.5</td><td>71.3</td></tr> <tr><td>60</td><td>83.4</td><td>82.5</td><td>77.9</td></tr> <tr><td>80</td><td>84.9</td><td>84.8</td><td>81.8</td></tr> <tr><td>100</td><td>85.6</td><td>86.2</td><td>83.8</td></tr> <tr><td>110</td><td>85.7</td><td>86.6</td><td>84.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	-	-	-	20	68.8	65.5	56.8	40	79.4	77.5	71.3	60	83.4	82.5	77.9	80	84.9	84.8	81.8	100	85.6	86.2	83.8	110	85.7	86.6	84.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																			
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																	
0	-	-	-																																																	
20	68.8	65.5	56.8																																																	
40	79.4	77.5	71.3																																																	
60	83.4	82.5	77.9																																																	
80	84.9	84.8	81.8																																																	
100	85.6	86.2	83.8																																																	
110	85.7	86.6	84.6																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Model	SUTW61215
Item	Line Regulation
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8	15.047	14.986
9	15.045	14.987
10	15.043	14.987
12	15.041	14.988
15	15.038	14.988
18	15.037	14.987
20	15.036	14.988
--	-	-
--	-	-

Object -15V0.2A

1.Graph





2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8	-15.040	-14.979
9	-15.038	-14.979
10	-15.036	-14.979
12	-15.033	-14.979
15	-15.030	-14.978
18	-15.028	-14.978
20	-15.027	-14.978
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	SUTW61215	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V0.2A																																																					
1.Graph	—△— Input Volt. 9V - - □ - - Input Volt. 12V - · ○ - - Input Volt. 18V																																																					
																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.222</td><td>15.210</td><td>15.190</td></tr> <tr><td>0.04</td><td>15.100</td><td>15.095</td><td>15.087</td></tr> <tr><td>0.08</td><td>15.059</td><td>15.054</td><td>15.050</td></tr> <tr><td>0.12</td><td>15.032</td><td>15.028</td><td>15.025</td></tr> <tr><td>0.16</td><td>15.008</td><td>15.007</td><td>15.005</td></tr> <tr><td>0.20</td><td>14.987</td><td>14.987</td><td>14.987</td></tr> <tr><td>0.22</td><td>14.976</td><td>14.978</td><td>14.979</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	15.222	15.210	15.190	0.04	15.100	15.095	15.087	0.08	15.059	15.054	15.050	0.12	15.032	15.028	15.025	0.16	15.008	15.007	15.005	0.20	14.987	14.987	14.987	0.22	14.976	14.978	14.979	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	15.222	15.210	15.190																																																			
0.04	15.100	15.095	15.087																																																			
0.08	15.059	15.054	15.050																																																			
0.12	15.032	15.028	15.025																																																			
0.16	15.008	15.007	15.005																																																			
0.20	14.987	14.987	14.987																																																			
0.22	14.976	14.978	14.979																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-15V0.2A																																																					
1.Graph	—△— Input Volt. 9V - - □ - - Input Volt. 12V - · ○ - - Input Volt. 18V																																																					
																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.231</td><td>-15.215</td><td>-15.195</td></tr> <tr><td>0.04</td><td>-15.094</td><td>-15.090</td><td>-15.083</td></tr> <tr><td>0.08</td><td>-15.051</td><td>-15.047</td><td>-15.042</td></tr> <tr><td>0.12</td><td>-15.024</td><td>-15.020</td><td>-15.016</td></tr> <tr><td>0.16</td><td>-15.000</td><td>-14.998</td><td>-14.996</td></tr> <tr><td>0.20</td><td>-14.979</td><td>-14.979</td><td>-14.978</td></tr> <tr><td>0.22</td><td>-14.969</td><td>-14.969</td><td>-14.969</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	-15.231	-15.215	-15.195	0.04	-15.094	-15.090	-15.083	0.08	-15.051	-15.047	-15.042	0.12	-15.024	-15.020	-15.016	0.16	-15.000	-14.998	-14.996	0.20	-14.979	-14.979	-14.978	0.22	-14.969	-14.969	-14.969	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	-15.231	-15.215	-15.195																																																			
0.04	-15.094	-15.090	-15.083																																																			
0.08	-15.051	-15.047	-15.042																																																			
0.12	-15.024	-15.020	-15.016																																																			
0.16	-15.000	-14.998	-14.996																																																			
0.20	-14.979	-14.979	-14.978																																																			
0.22	-14.969	-14.969	-14.969																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL




COSEL



Model	SUTW61215
Item	Ripple Voltage (by Load Current)
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.00	2	3
0.04	4	3
0.08	5	4
0.12	7	5
0.16	8	6
0.20	11	7
0.22	13	8
--	-	-
--	-	-
--	-	-
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW61215
Item	Ripple Voltage (by Load Current)
Object	-15V0.2A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.00	2	3
0.04	3	3
0.08	4	3
0.12	4	4
0.16	5	4
0.20	7	4
0.22	9	4
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

Model	SUTW61215
Item	Ripple-Noise
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.00	2	3
0.04	4	3
0.08	5	4
0.12	7	5
0.16	9	6
0.20	12	7
0.22	14	8
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SUTW61215																																							
Item	Ripple-Noise	Temperature Testing Circuitry 25°C Figure B																																						
Object	-15V0.2A																																							
1. Graph																																								
<p>Graph showing Ripple-Noise [mV] vs Load Current [A]. The Y-axis ranges from 0 to 80 mV, and the X-axis ranges from 0.00 to 0.20 A. Two curves are shown: one for Input Volt. 9V (solid line with triangle markers) and one for Input Volt. 18V (dashed line with circle markers). Both curves show a slight increase in noise as load current increases. A slanted line indicates the range of the rated load current.</p>																																								
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>2</td> <td>3</td> </tr> <tr> <td>0.04</td> <td>3</td> <td>3</td> </tr> <tr> <td>0.08</td> <td>4</td> <td>3</td> </tr> <tr> <td>0.12</td> <td>5</td> <td>4</td> </tr> <tr> <td>0.16</td> <td>6</td> <td>5</td> </tr> <tr> <td>0.20</td> <td>9</td> <td>6</td> </tr> <tr> <td>0.22</td> <td>11</td> <td>6</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	2	3	0.04	3	3	0.08	4	3	0.12	5	4	0.16	6	5	0.20	9	6	0.22	11	6	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.00	2	3																																						
0.04	3	3																																						
0.08	4	3																																						
0.12	5	4																																						
0.16	6	5																																						
0.20	9	6																																						
0.22	11	6																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						

Model	SUTW61215
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.2A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	9
-40	5	9
-20	5	9
0	5	8
25	4	8
55	4	8
60	4	8
--	-	-
--	-	-
--	-	-
--	-	-

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	4	6
-40	4	6
-20	4	6
0	4	6
25	4	5
55	4	5
60	4	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	SUTW61215
Item	Ambient Temperature Drift
Object	+15V0.2A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	14.900	14.901	14.901
-40	14.929	14.930	14.930
-20	14.952	14.953	14.953
0	14.971	14.971	14.971
25	14.986	14.986	14.986
55	14.993	14.994	14.994
60	14.993	14.994	14.994
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	-14.892	-14.892	-14.892
-40	-14.921	-14.921	-14.920
-20	-14.944	-14.944	-14.943
0	-14.962	-14.962	-14.962
25	-14.977	-14.977	-14.976
55	-14.985	-14.985	-14.984
60	-14.985	-14.985	-14.984
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	SUTW61215	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 9 - 18V

Load Current (AVR 1) : 0 - 0.2A (AVR 2) : 0 - 0.2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Object	+15V0.2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	9		0	15.236	
Minimum Voltage	-40	9	0.2	14.708	±264	±1.8

Object	-15V0.2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	9		0	-15.245	
Minimum Voltage	-40	9	0.2	-14.723	±261	±1.7

COSEL

Model	SUTW61215
Item	Time Lapse Drift
Object	+15V0.2A


1.Graph



Input Volt. 12V
Load 100%

Object	-15V0.2A
--------	----------

1.Graph



Input Volt. 12V
Load 100%

Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	14.980
0.5	14.986
1.0	14.986
2.0	14.986
3.0	14.986
4.0	14.986
5.0	14.986
6.0	14.986
7.0	14.986
8.0	14.985

2.Values


Time since start [H]	Output Voltage [V]
0.0	-14.976
0.5	-14.981
1.0	-14.981
2.0	-14.981
3.0	-14.981
4.0	-14.981
5.0	-14.981
6.0	-14.981
7.0	-14.981
8.0	-14.981

COSEL

Model	SUTW61215
Item	Rise and Fall Time
Object	+15V0.2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.3	3.6	3.9	0.3	3.8	
100 %		0.3	3.7	4.0	0.2	1.9	




COSEL

Model	SUTW61215
Item	Rise and Fall Time
Object	-15V0.2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[mS]
50 %		0.3	3.6	3.9	0.3	4.3	
100 %		0.3	3.7	4.0	0.2	2.1	




COSEL

Model	SUTW61215
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.2A

1.Graph

---□--- Load 50%
—△— Load 100%



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.0	8.1
-40	7.8	8.1
-20	7.8	7.9
0	7.6	7.7
25	7.4	7.5
55	7.2	7.3
60	7.2	7.3
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.2A
--------	----------

1.Graph

---□--- Load 50%
—△— Load 100%



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.0	8.1
-40	7.8	7.9
-20	7.8	7.9
0	7.6	7.7
25	7.4	7.5
55	7.2	7.3
60	7.2	7.3
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	SUTW61215	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+15V0.2A																																																								
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>	2.Values																																																							
Object	-15V0.2A	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.20</td><td>0.20</td><td>0.20</td></tr> <tr><td>14.3</td><td>0.35</td><td>0.40</td><td>0.41</td></tr> <tr><td>13.5</td><td>0.38</td><td>0.42</td><td>0.43</td></tr> <tr><td>12.0</td><td>0.42</td><td>0.47</td><td>0.46</td></tr> <tr><td>10.5</td><td>0.48</td><td>0.53</td><td>0.53</td></tr> <tr><td>9.0</td><td>0.53</td><td>0.57</td><td>0.57</td></tr> <tr><td>7.5</td><td>0.58</td><td>0.61</td><td>0.61</td></tr> <tr><td>6.0</td><td>0.63</td><td>0.65</td><td>0.64</td></tr> <tr><td>4.5</td><td>0.67</td><td>0.68</td><td>0.67</td></tr> <tr><td>3.0</td><td>0.68</td><td>0.68</td><td>0.67</td></tr> <tr><td>1.5</td><td>0.66</td><td>0.65</td><td>0.64</td></tr> <tr><td>0.0</td><td>0.99</td><td>0.97</td><td>0.99</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	15.0	0.20	0.20	0.20	14.3	0.35	0.40	0.41	13.5	0.38	0.42	0.43	12.0	0.42	0.47	0.46	10.5	0.48	0.53	0.53	9.0	0.53	0.57	0.57	7.5	0.58	0.61	0.61	6.0	0.63	0.65	0.64	4.5	0.67	0.68	0.67	3.0	0.68	0.68	0.67	1.5	0.66	0.65	0.64	0.0	0.99	0.97	0.99
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																						
15.0	0.20	0.20	0.20																																																						
14.3	0.35	0.40	0.41																																																						
13.5	0.38	0.42	0.43																																																						
12.0	0.42	0.47	0.46																																																						
10.5	0.48	0.53	0.53																																																						
9.0	0.53	0.57	0.57																																																						
7.5	0.58	0.61	0.61																																																						
6.0	0.63	0.65	0.64																																																						
4.5	0.67	0.68	0.67																																																						
3.0	0.68	0.68	0.67																																																						
1.5	0.66	0.65	0.64																																																						
0.0	0.99	0.97	0.99																																																						
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>	2.Values																																																							

Note: Slanted line shows the range of the rated load current.




Figure A




Figure B (Ripple and Ripple noise Characteristic)