



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|-----------|
| Model | TUHS10F24 |
|-------|-----------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|------------|----------------|------------------------------------|-------------------|
| 1 | I C | Monolithic | 2 | 0.0980 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | Transistors | | 2 | 0.1980 | |
| 4 | Diodes | | 11 | 0.1865 | |
| 5 | LED•Optocouplers | | 1 | 0.0700 | |
| 6 | Resistors | | 25 | 0.0050 | |
| 7 | Capacitors | | 19 | 0.1406 | |
| 8 | Transformer•Choke Coil | | 3 | 0.0690 | |
| 9 | Connectors | | 155 | 0.0213 | |
| 10 | Others | | 1 | 0.1100 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 0.8984 | |

| | | |
|---------------------|-----|-----------|
| M T B F | [H] | 1,120,000 |
| Ambient Temperature | [℃] | — |
| Load Factor | [%] | — |