

TEST DATA OF TUHS3F24

Regulated DC Power Supply
February 28, 2014

Approved by : Nobuyuki Shiraishi
Nobuyuki Shiraishi Design Manager

Prepared by : Takayuki Yamamoto
Takayuki Yamamoto Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Overvoltage Protection	23
24.Figure of Testing Circuitry	24


(Final Page 25)

Model	TUHS3F24																																																						
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																				
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○- - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.009</td><td>0.004</td><td>0.003</td></tr> <tr><td>0.02</td><td>0.021</td><td>0.014</td><td>0.014</td></tr> <tr><td>0.04</td><td>0.032</td><td>0.022</td><td>0.020</td></tr> <tr><td>0.06</td><td>0.043</td><td>0.028</td><td>0.026</td></tr> <tr><td>0.08</td><td>0.053</td><td>0.035</td><td>0.032</td></tr> <tr><td>0.10</td><td>0.063</td><td>0.041</td><td>0.037</td></tr> <tr><td>0.12</td><td>0.073</td><td>0.047</td><td>0.043</td></tr> <tr><td>0.13</td><td>0.077</td><td>0.050</td><td>0.046</td></tr> <tr><td>0.14</td><td>0.083</td><td>0.053</td><td>0.049</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]	0.00	0.009	0.004	0.003	0.02	0.021	0.014	0.014	0.04	0.032	0.022	0.020	0.06	0.043	0.028	0.026	0.08	0.053	0.035	0.032	0.10	0.063	0.041	0.037	0.12	0.073	0.047	0.043	0.13	0.077	0.050	0.046	0.14	0.083	0.053	0.049														
Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]																																																				
0.00	0.009	0.004	0.003																																																				
0.02	0.021	0.014	0.014																																																				
0.04	0.032	0.022	0.020																																																				
0.06	0.043	0.028	0.026																																																				
0.08	0.053	0.035	0.032																																																				
0.10	0.063	0.041	0.037																																																				
0.12	0.073	0.047	0.043																																																				
0.13	0.077	0.050	0.046																																																				
0.14	0.083	0.053	0.049																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.009</td><td>0.004</td><td>0.003</td></tr> <tr><td>0.02</td><td>0.021</td><td>0.014</td><td>0.014</td></tr> <tr><td>0.04</td><td>0.032</td><td>0.022</td><td>0.020</td></tr> <tr><td>0.06</td><td>0.043</td><td>0.028</td><td>0.026</td></tr> <tr><td>0.08</td><td>0.053</td><td>0.035</td><td>0.032</td></tr> <tr><td>0.10</td><td>0.063</td><td>0.041</td><td>0.037</td></tr> <tr><td>0.12</td><td>0.073</td><td>0.047</td><td>0.043</td></tr> <tr><td>0.13</td><td>0.077</td><td>0.050</td><td>0.046</td></tr> <tr><td>0.14</td><td>0.083</td><td>0.053</td><td>0.049</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.009	0.004	0.003	0.02	0.021	0.014	0.014	0.04	0.032	0.022	0.020	0.06	0.043	0.028	0.026	0.08	0.053	0.035	0.032	0.10	0.063	0.041	0.037	0.12	0.073	0.047	0.043	0.13	0.077	0.050	0.046	0.14	0.083	0.053	0.049	--	-	-	-	--	-	-	-			
Load Current [A]	Input Current [A]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	0.009	0.004	0.003																																																				
0.02	0.021	0.014	0.014																																																				
0.04	0.032	0.022	0.020																																																				
0.06	0.043	0.028	0.026																																																				
0.08	0.053	0.035	0.032																																																				
0.10	0.063	0.041	0.037																																																				
0.12	0.073	0.047	0.043																																																				
0.13	0.077	0.050	0.046																																																				
0.14	0.083	0.053	0.049																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

Model	TUHS3F24																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p>  <p>The graph plots Input Power [W] on the y-axis (0.0 to 5.0) against Load Current [A] on the x-axis (0.00 to 0.15). Three data series are shown: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All curves show a linear increase in power with load current. A diagonal hatched line represents the rated load current range, which is approximately between 0.08A and 0.13A.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.29</td><td>0.21</td><td>0.21</td></tr> <tr> <td>0.02</td><td>0.82</td><td>0.91</td><td>0.95</td></tr> <tr> <td>0.04</td><td>1.36</td><td>1.46</td><td>1.49</td></tr> <tr> <td>0.06</td><td>1.91</td><td>2.00</td><td>2.03</td></tr> <tr> <td>0.08</td><td>2.46</td><td>2.54</td><td>2.58</td></tr> <tr> <td>0.10</td><td>3.01</td><td>3.08</td><td>3.12</td></tr> <tr> <td>0.12</td><td>3.57</td><td>3.63</td><td>3.67</td></tr> <tr> <td>0.13</td><td>3.85</td><td>3.90</td><td>3.94</td></tr> <tr> <td>0.14</td><td>4.23</td><td>4.26</td><td>4.30</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.29	0.21	0.21	0.02	0.82	0.91	0.95	0.04	1.36	1.46	1.49	0.06	1.91	2.00	2.03	0.08	2.46	2.54	2.58	0.10	3.01	3.08	3.12	0.12	3.57	3.63	3.67	0.13	3.85	3.90	3.94	0.14	4.23	4.26	4.30	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.29	0.21	0.21																																																			
0.02	0.82	0.91	0.95																																																			
0.04	1.36	1.46	1.49																																																			
0.06	1.91	2.00	2.03																																																			
0.08	2.46	2.54	2.58																																																			
0.10	3.01	3.08	3.12																																																			
0.12	3.57	3.63	3.67																																																			
0.13	3.85	3.90	3.94																																																			
0.14	4.23	4.26	4.30																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	TUHS3F24	Temperature	25°C
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A
Object	—		


1. Graph



2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	77.2	80.7
85	77.0	81.1
100	76.8	81.4
120	76.4	81.5
200	73.6	80.3
230	72.2	79.5
264	69.9	78.2
280	68.4	77.2
--	-	-

Note: Slanted line shows the range of the rated input voltage.




Model	TUHS3F24	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p>  <p>The graph plots Efficiency [%] on the y-axis (30 to 90) against Load Current [A] on the x-axis (0.00 to 0.15). Three data series are shown: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All three curves show efficiency increasing with load current. A slanted line is drawn across the graph, starting from approximately (0.02, 55) and ending at (0.12, 85), indicating the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.02</td><td>58.8</td><td>52.9</td><td>50.8</td></tr> <tr> <td>0.04</td><td>71.1</td><td>66.3</td><td>64.5</td></tr> <tr> <td>0.06</td><td>76.0</td><td>72.6</td><td>71.1</td></tr> <tr> <td>0.08</td><td>78.7</td><td>76.1</td><td>74.9</td></tr> <tr> <td>0.10</td><td>80.2</td><td>78.4</td><td>77.4</td></tr> <tr> <td>0.12</td><td>81.1</td><td>79.8</td><td>79.0</td></tr> <tr> <td>0.13</td><td>81.4</td><td>80.3</td><td>79.5</td></tr> <tr> <td>0.14</td><td>81.7</td><td>81.0</td><td>80.2</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.02	58.8	52.9	50.8	0.04	71.1	66.3	64.5	0.06	76.0	72.6	71.1	0.08	78.7	76.1	74.9	0.10	80.2	78.4	77.4	0.12	81.1	79.8	79.0	0.13	81.4	80.3	79.5	0.14	81.7	81.0	80.2	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.02	58.8	52.9	50.8																																																			
0.04	71.1	66.3	64.5																																																			
0.06	76.0	72.6	71.1																																																			
0.08	78.7	76.1	74.9																																																			
0.10	80.2	78.4	77.4																																																			
0.12	81.1	79.8	79.0																																																			
0.13	81.4	80.3	79.5																																																			
0.14	81.7	81.0	80.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	TUHS3F24																																
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																															
Object	—	—																															
1. Graph																																	
		2. Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>0.473</td><td>0.522</td></tr> <tr> <td>85</td><td>0.455</td><td>0.503</td></tr> <tr> <td>100</td><td>0.431</td><td>0.476</td></tr> <tr> <td>120</td><td>0.408</td><td>0.450</td></tr> <tr> <td>200</td><td>0.347</td><td>0.381</td></tr> <tr> <td>230</td><td>0.331</td><td>0.365</td></tr> <tr> <td>264</td><td>0.319</td><td>0.348</td></tr> <tr> <td>280</td><td>0.314</td><td>0.342</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.473	0.522	85	0.455	0.503	100	0.431	0.476	120	0.408	0.450	200	0.347	0.381	230	0.331	0.365	264	0.319	0.348	280	0.314	0.342	--	-	-
Input Voltage [V]	Power Factor																																
	Load 50%	Load 100%																															
75	0.473	0.522																															
85	0.455	0.503																															
100	0.431	0.476																															
120	0.408	0.450																															
200	0.347	0.381																															
230	0.331	0.365																															
264	0.319	0.348																															
280	0.314	0.342																															
--	-	-																															
Note: Slanted line shows the range of the rated input voltage.																																	

Model	TUHS3F24	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Power Factor (by Load Current)																																																						
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V</th> <th>Input Volt. 200V</th> <th>Input Volt. 230V</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.32</td><td>0.25</td><td>0.25</td></tr> <tr><td>0.03</td><td>0.38</td><td>0.30</td><td>0.28</td></tr> <tr><td>0.06</td><td>0.42</td><td>0.34</td><td>0.33</td></tr> <tr><td>0.09</td><td>0.45</td><td>0.36</td><td>0.35</td></tr> <tr><td>0.12</td><td>0.48</td><td>0.38</td><td>0.37</td></tr> <tr><td>0.15</td><td>0.49</td><td>0.39</td><td>0.38</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V	0.00	0.32	0.25	0.25	0.03	0.38	0.30	0.28	0.06	0.42	0.34	0.33	0.09	0.45	0.36	0.35	0.12	0.48	0.38	0.37	0.15	0.49	0.39	0.38	2.Values																									
Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V																																																				
0.00	0.32	0.25	0.25																																																				
0.03	0.38	0.30	0.28																																																				
0.06	0.42	0.34	0.33																																																				
0.09	0.45	0.36	0.35																																																				
0.12	0.48	0.38	0.37																																																				
0.15	0.49	0.39	0.38																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.323</td><td>0.247</td><td>0.256</td></tr> <tr><td>0.02</td><td>0.376</td><td>0.308</td><td>0.292</td></tr> <tr><td>0.04</td><td>0.406</td><td>0.326</td><td>0.314</td></tr> <tr><td>0.06</td><td>0.428</td><td>0.344</td><td>0.329</td></tr> <tr><td>0.08</td><td>0.444</td><td>0.356</td><td>0.341</td></tr> <tr><td>0.10</td><td>0.459</td><td>0.368</td><td>0.353</td></tr> <tr><td>0.12</td><td>0.471</td><td>0.377</td><td>0.360</td></tr> <tr><td>0.13</td><td>0.476</td><td>0.381</td><td>0.365</td></tr> <tr><td>0.14</td><td>0.484</td><td>0.386</td><td>0.371</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.323	0.247	0.256	0.02	0.376	0.308	0.292	0.04	0.406	0.326	0.314	0.06	0.428	0.344	0.329	0.08	0.444	0.356	0.341	0.10	0.459	0.368	0.353	0.12	0.471	0.377	0.360	0.13	0.476	0.381	0.365	0.14	0.484	0.386	0.371	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	0.323	0.247	0.256																																																				
0.02	0.376	0.308	0.292																																																				
0.04	0.406	0.326	0.314																																																				
0.06	0.428	0.344	0.329																																																				
0.08	0.444	0.356	0.341																																																				
0.10	0.459	0.368	0.353																																																				
0.12	0.471	0.377	0.360																																																				
0.13	0.476	0.381	0.365																																																				
0.14	0.484	0.386	0.371																																																				
--	-	-	-																																																				
--	-	-	-																																																				
		<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

COSEL

Model	TUHS3F24	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current		
Object	_____		





Model	TUHS3F24	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object	_____		

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	230 [V]	
DEN-AN	Both phases	0.003	0.004	0.004	Operation
	One of phases	0.003	0.005	0.006	Stand by
IEC60950-1	Both phases	0.002	0.005	0.005	Operation
	One of phases	0.003	0.005	0.005	Stand by


The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.
 There is no FG in TUHS series and it is a reinforced insulation power supply of the class 2.

Model	TUHS3F24	Temperature Testing Circuitry 25°C Figure A
Item	Line Regulation	
Object	+24V0.13A	

1. Graph




Note: Slanted line shows the range of the rated input voltage.

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	24.103	24.095
85	24.103	24.095
100	24.104	24.095
120	24.104	24.096
200	24.108	24.100
230	24.107	24.099
264	24.106	24.098
280	24.106	24.097
--	-	-

Model	TUHS3F24	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Load Regulation																																																						
Object	+24V0.13A																																																						
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 200V - - -○--- Input Volt. 230V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>24.110</td><td>24.111</td><td>24.107</td></tr> <tr><td>0.02</td><td>24.108</td><td>24.111</td><td>24.109</td></tr> <tr><td>0.04</td><td>24.106</td><td>24.110</td><td>24.108</td></tr> <tr><td>0.06</td><td>24.104</td><td>24.108</td><td>24.107</td></tr> <tr><td>0.08</td><td>24.102</td><td>24.106</td><td>24.105</td></tr> <tr><td>0.10</td><td>24.099</td><td>24.103</td><td>24.103</td></tr> <tr><td>0.12</td><td>24.097</td><td>24.101</td><td>24.101</td></tr> <tr><td>0.13</td><td>24.095</td><td>24.100</td><td>24.099</td></tr> <tr><td>0.14</td><td>24.094</td><td>24.098</td><td>24.098</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	24.110	24.111	24.107	0.02	24.108	24.111	24.109	0.04	24.106	24.110	24.108	0.06	24.104	24.108	24.107	0.08	24.102	24.106	24.105	0.10	24.099	24.103	24.103	0.12	24.097	24.101	24.101	0.13	24.095	24.100	24.099	0.14	24.094	24.098	24.098	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	24.110	24.111	24.107																																																				
0.02	24.108	24.111	24.109																																																				
0.04	24.106	24.110	24.108																																																				
0.06	24.104	24.108	24.107																																																				
0.08	24.102	24.106	24.105																																																				
0.10	24.099	24.103	24.103																																																				
0.12	24.097	24.101	24.101																																																				
0.13	24.095	24.100	24.099																																																				
0.14	24.094	24.098	24.098																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated load current.																																																							

COSEL




COSEL

Model	TUHS3F24
Item	Ripple Voltage (by Load Current)
Object	+24V0.13A

Temperature 25°C
Testing Circuitry Figure C

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0	5	200
0.02	5	5
0.04	10	5
0.06	15	10
0.08	20	10
0.10	20	10
0.12	25	10
0.13	30	10
0.14	40	10
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line
T2: Due to Switching




Fig. Complex Ripple Wave Form

COSEL


Model	TUHS3F24																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure C																																						
Object	+24V0.13A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph shows two sets of data points: Input Volt. 100V (solid line with triangle markers) and Input Volt. 230V (dashed line with circle markers). The x-axis represents Load Current [A] from 0.00 to 0.15. The y-axis represents Ripple Voltage [mV] from 0 to 400. A slanted line indicates the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 230V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>220</td></tr> <tr><td>0.02</td><td>10</td><td>15</td></tr> <tr><td>0.04</td><td>10</td><td>15</td></tr> <tr><td>0.06</td><td>15</td><td>15</td></tr> <tr><td>0.08</td><td>15</td><td>15</td></tr> <tr><td>0.10</td><td>20</td><td>15</td></tr> <tr><td>0.12</td><td>25</td><td>15</td></tr> <tr><td>0.13</td><td>35</td><td>15</td></tr> <tr><td>0.14</td><td>40</td><td>15</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 230V)	0.00	5	220	0.02	10	15	0.04	10	15	0.06	15	15	0.08	15	15	0.10	20	15	0.12	25	15	0.13	35	15	0.14	40	15	--	-	-	--	-	-		
Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 230V)																																						
0.00	5	220																																						
0.02	10	15																																						
0.04	10	15																																						
0.06	15	15																																						
0.08	15	15																																						
0.10	20	15																																						
0.12	25	15																																						
0.13	35	15																																						
0.14	40	15																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 230 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>5</td><td>220</td></tr> <tr><td>0.02</td><td>10</td><td>15</td></tr> <tr><td>0.04</td><td>10</td><td>15</td></tr> <tr><td>0.06</td><td>15</td><td>15</td></tr> <tr><td>0.08</td><td>15</td><td>15</td></tr> <tr><td>0.10</td><td>20</td><td>15</td></tr> <tr><td>0.12</td><td>25</td><td>15</td></tr> <tr><td>0.13</td><td>35</td><td>15</td></tr> <tr><td>0.14</td><td>40</td><td>15</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 230 [V]	0	5	220	0.02	10	15	0.04	10	15	0.06	15	15	0.08	15	15	0.10	20	15	0.12	25	15	0.13	35	15	0.14	40	15	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 100 [V]	Input Volt. 230 [V]																																						
0	5	220																																						
0.02	10	15																																						
0.04	10	15																																						
0.06	15	15																																						
0.08	15	15																																						
0.10	20	15																																						
0.12	25	15																																						
0.13	35	15																																						
0.14	40	15																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form</p>																																								

Model	TUHS3F24	Testing Circuitry Figure C																																			
Item	Ripple Voltage (by Ambient Temp.)																																				
Object	+24V0.13A																																				
1. Graph		2. Values																																			
<p>Graph showing Ripple Voltage [mV] vs Ambient Temperature [°C] for TUHS3F24 at Load 100%.</p> <p>Legend:</p> <ul style="list-style-type: none"> - - - □ - - - Input Volt. 100V — △ — Input Volt. 200V <table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>-45</td><td>25</td><td>10</td></tr> <tr><td>-40</td><td>20</td><td>10</td></tr> <tr><td>-20</td><td>25</td><td>10</td></tr> <tr><td>0</td><td>25</td><td>10</td></tr> <tr><td>25</td><td>30</td><td>10</td></tr> <tr><td>50</td><td>35</td><td>10</td></tr> <tr><td>70</td><td>40</td><td>10</td></tr> <tr><td>85</td><td>45</td><td>10</td></tr> <tr><td>90</td><td>45</td><td>15</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	-45	25	10	-40	20	10	-20	25	10	0	25	10	25	30	10	50	35	10	70	40	10	85	45	10	90	45	15	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																																			
-45	25	10																																			
-40	20	10																																			
-20	25	10																																			
0	25	10																																			
25	30	10																																			
50	35	10																																			
70	40	10																																			
85	45	10																																			
90	45	15																																			
--	-	-																																			
--	-	-																																			
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																					

Model TUHS3F24

Item Ambient Temperature Drift

Object +24V0.13A



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-45	24.186	24.189	24.189
-40	24.187	24.189	24.190
-20	24.177	24.180	24.181
0	24.151	24.155	24.155
25	24.095	24.100	24.099
50	24.027	24.034	24.034
70	23.951	23.959	23.959
85	23.899	23.909	23.910
90	23.848	23.859	23.861
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	TUHS3F24	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+24V0.13A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 85 - 264V

Load Current : 0 - 0.13A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	85	0	24.195	±148	±0.6
Minimum Voltage	85	85	0.13	23.899		

COSEL

Model	TUHS3F24
Item	Time Lapse Drift
Object	+24V0.13A

1.Graph



2.Values

Time since start [H]	Output Voltage [V]
0.0	24.095
0.5	24.083
1.0	24.082
2.0	24.082
3.0	24.082
4.0	24.082
5.0	24.082
6.0	24.082
7.0	24.082
8.0	24.082


* The characteristic of AC230V is equal.

COSSEL

Model	TUHS3F24
Item	Rise and Fall Time
Object	+24V0.13A


Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		29.3	1.0	30.3	35.3	20.8	
230 V		28.8	1.0	29.8	251.0	21.3	



Model	TUHS3F24
Item	Hold-Up Time
Object	+24V0.13A

1. Graph



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	39	14
85	54	22
100	79	35
120	120	56
200	360	185
230	482	251
264	642	337
280	724	383
--	-	-


Model	TUHS3F24	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Instantaneous Interruption Compensation																																																				
Object	+24V0.13A																																																				
1.Graph	<p>—△— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>200V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>0.03</td><td>100</td><td>300</td><td>500</td></tr> <tr><td>0.05</td><td>80</td><td>250</td><td>400</td></tr> <tr><td>0.08</td><td>60</td><td>200</td><td>350</td></tr> <tr><td>0.10</td><td>50</td><td>180</td><td>300</td></tr> <tr><td>0.13</td><td>40</td><td>150</td><td>250</td></tr> <tr><td>0.15</td><td>35</td><td>130</td><td>220</td></tr> </tbody> </table>	Load Current [A]	100V [ms]	200V [ms]	230V [ms]	0.03	100	300	500	0.05	80	250	400	0.08	60	200	350	0.10	50	180	300	0.13	40	150	250	0.15	35	130	220																								
Load Current [A]	100V [ms]	200V [ms]	230V [ms]																																																		
0.03	100	300	500																																																		
0.05	80	250	400																																																		
0.08	60	200	350																																																		
0.10	50	180	300																																																		
0.13	40	150	250																																																		
0.15	35	130	220																																																		
2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.02</td><td>105</td><td>460</td><td>614</td></tr> <tr><td>0.04</td><td>92</td><td>410</td><td>548</td></tr> <tr><td>0.06</td><td>79</td><td>360</td><td>482</td></tr> <tr><td>0.08</td><td>67</td><td>310</td><td>416</td></tr> <tr><td>0.10</td><td>54</td><td>260</td><td>350</td></tr> <tr><td>0.12</td><td>41</td><td>210</td><td>284</td></tr> <tr><td>0.13</td><td>35</td><td>185</td><td>251</td></tr> <tr><td>0.14</td><td>27</td><td>152</td><td>208</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.02	105	460	614	0.04	92	410	548	0.06	79	360	482	0.08	67	310	416	0.10	54	260	350	0.12	41	210	284	0.13	35	185	251	0.14	27	152	208	--	-	-	-	--	-	-	-	
Load Current [A]	Time [ms]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.00	-	-	-																																																		
0.02	105	460	614																																																		
0.04	92	410	548																																																		
0.06	79	360	482																																																		
0.08	67	310	416																																																		
0.10	54	260	350																																																		
0.12	41	210	284																																																		
0.13	35	185	251																																																		
0.14	27	152	208																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

Model	TUHS3F24
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+24V0.13A

Testing Circuitry Figure A

1.Graph



2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-45	37	59
-40	35	57
-20	33	53
0	33	53
25	33	53
50	33	52
70	33	52
85	33	53
90	33	54
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	TUHS3F24	Temperature Testing Circuitry Figure A	25°C																																																					
Item	Overcurrent Protection																																																							
Object	+24V0.13A																																																							
1. Graph		2. Values																																																						
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>24</td><td>0.20</td><td>0.26</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	24	0.20	0.26	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																																							
	Input Volt. 100[V]	Input Volt. 230[V]																																																						
24	0.20	0.26																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						
--	-	-																																																						

Model	TUHS3F24
Item	Oversupply Protection
Object	+24V0.13A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-45	29.18	29.18
-40	29.23	29.23
-20	29.46	29.47
0	29.79	29.81
25	30.41	30.63
50	30.90	31.05
75	31.32	31.35
85	31.42	31.42
90	31.52	31.49
--	-	-
--	-	-




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)




Figure C