

TEST DATA OF TUNS500F12

Regulated DC Power Supply
October 1, 2014

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Kosuke Takarada
Kosuke Takarada Design Engineer

COSEL CO.,LTD.


CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Ovvervoltage Protection	23
24.Figure of Testing Circuitry	24,25

(Final Page 25)

COSEL

Model	TUNS500F12
Item	Input Current (by Load Current)
Object	—




Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	0.161	0.334	0.384
8.4	1.282	0.713	0.674
16.8	2.451	1.258	1.129
25.2	3.634	1.817	1.606
33.6	4.868	2.394	2.099
42.0	6.130	2.982	2.606
46.2	6.776	3.283	2.864
—	-	-	-
—	-	-	-
—	-	-	-
—	-	-	-


COSEL

Model	TUNS500F12	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>—▲— Input Volt. 100V ---□--- Input Volt. 200V -○--- Input Volt. 230V</p>  <p>The graph plots Input Power [W] on the Y-axis (0 to 1000) against Load Current [A] on the X-axis (0 to 50). Three curves are shown for different input voltages: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All curves show a linear increase in power with load current. A slanted line is drawn across the graph, starting from approximately (10, 100) and ending at (40, 600), indicating the range of the rated load current.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>100[V]</th> <th>200[V]</th> <th>230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.1</td><td>2.9</td><td>2.9</td></tr> <tr><td>8.4</td><td>123.2</td><td>120.4</td><td>120.0</td></tr> <tr><td>16.8</td><td>240.4</td><td>235.2</td><td>234.2</td></tr> <tr><td>25.2</td><td>357.6</td><td>349.8</td><td>348.2</td></tr> <tr><td>33.6</td><td>477.5</td><td>466.4</td><td>464.3</td></tr> <tr><td>42.0</td><td>599.9</td><td>584.7</td><td>582.0</td></tr> <tr><td>46.2</td><td>662.4</td><td>644.6</td><td>641.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			100[V]	200[V]	230[V]	0.0	3.1	2.9	2.9	8.4	123.2	120.4	120.0	16.8	240.4	235.2	234.2	25.2	357.6	349.8	348.2	33.6	477.5	466.4	464.3	42.0	599.9	584.7	582.0	46.2	662.4	644.6	641.5	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	100[V]	200[V]	230[V]																																																			
0.0	3.1	2.9	2.9																																																			
8.4	123.2	120.4	120.0																																																			
16.8	240.4	235.2	234.2																																																			
25.2	357.6	349.8	348.2																																																			
33.6	477.5	466.4	464.3																																																			
42.0	599.9	584.7	582.0																																																			
46.2	662.4	644.6	641.5																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	TUNS500F12																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>84.3</td> <td>83.3</td> </tr> <tr> <td>85</td> <td>84.6</td> <td>83.8</td> </tr> <tr> <td>100</td> <td>85.1</td> <td>84.7</td> </tr> <tr> <td>120</td> <td>85.6</td> <td>85.5</td> </tr> <tr> <td>200</td> <td>87.0</td> <td>86.9</td> </tr> <tr> <td>230</td> <td>87.3</td> <td>87.3</td> </tr> <tr> <td>264</td> <td>87.7</td> <td>87.7</td> </tr> <tr> <td>280</td> <td>88.5</td> <td>88.2</td> </tr> <tr> <td>—</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	80	84.3	83.3	85	84.6	83.8	100	85.1	84.7	120	85.6	85.5	200	87.0	86.9	230	87.3	87.3	264	87.7	87.7	280	88.5	88.2	—	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
80	84.3	83.3																																
85	84.6	83.8																																
100	85.1	84.7																																
120	85.6	85.5																																
200	87.0	86.9																																
230	87.3	87.3																																
264	87.7	87.7																																
280	88.5	88.2																																
—	-	-																																

COSEL

Model	TUNS500F12	Temperature	25°C																																																					
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																					
Object	<hr/>																																																							
1. Graph																																																								
—△— Input Volt. 100V - - + - - Input Volt. 200V - - ○ - - Input Volt. 230V																																																								
																																																								
Note: Slanted line shows the range of the rated load current.																																																								
2. Values																																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>8.4</td><td>82.5</td><td>84.5</td><td>84.7</td></tr> <tr> <td>16.8</td><td>84.5</td><td>86.5</td><td>86.8</td></tr> <tr> <td>25.2</td><td>85.3</td><td>87.2</td><td>87.6</td></tr> <tr> <td>33.6</td><td>85.2</td><td>87.2</td><td>87.6</td></tr> <tr> <td>42.0</td><td>84.7</td><td>86.9</td><td>87.3</td></tr> <tr> <td>46.2</td><td>84.4</td><td>86.7</td><td>87.1</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	8.4	82.5	84.5	84.7	16.8	84.5	86.5	86.8	25.2	85.3	87.2	87.6	33.6	85.2	87.2	87.6	42.0	84.7	86.9	87.3	46.2	84.4	86.7	87.1	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	-	-	-																																																					
8.4	82.5	84.5	84.7																																																					
16.8	84.5	86.5	86.8																																																					
25.2	85.3	87.2	87.6																																																					
33.6	85.2	87.2	87.6																																																					
42.0	84.7	86.9	87.3																																																					
46.2	84.4	86.7	87.1																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					


COSEL

Model TUNS500F12

Item Power Factor (by Input Voltage)

Object

1. Graph



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
80	0.990	0.995
85	0.990	0.995
100	0.989	0.994
120	0.985	0.993
200	0.952	0.982
230	0.927	0.971
264	0.889	0.956
270	0.882	0.953
280	0.400	0.447




COSEL

Model	TUNS500F12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Power Factor (by Load Current)																																																					
Object																																																						
1. Graph		2. Values																																																				
<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○- - Input Volt. 230V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.190</td><td>0.044</td><td>0.033</td></tr> <tr><td>4.2</td><td>0.915</td><td>0.675</td><td>0.574</td></tr> <tr><td>8.4</td><td>0.962</td><td>0.843</td><td>0.773</td></tr> <tr><td>16.8</td><td>0.985</td><td>0.934</td><td>0.901</td></tr> <tr><td>25.2</td><td>0.991</td><td>0.962</td><td>0.942</td></tr> <tr><td>33.6</td><td>0.992</td><td>0.975</td><td>0.962</td></tr> <tr><td>42.0</td><td>0.994</td><td>0.982</td><td>0.971</td></tr> <tr><td>46.2</td><td>0.994</td><td>0.984</td><td>0.975</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.190	0.044	0.033	4.2	0.915	0.675	0.574	8.4	0.962	0.843	0.773	16.8	0.985	0.934	0.901	25.2	0.991	0.962	0.942	33.6	0.992	0.975	0.962	42.0	0.994	0.982	0.971	46.2	0.994	0.984	0.975	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.190	0.044	0.033																																																			
4.2	0.915	0.675	0.574																																																			
8.4	0.962	0.843	0.773																																																			
16.8	0.985	0.934	0.901																																																			
25.2	0.991	0.962	0.942																																																			
33.6	0.992	0.975	0.962																																																			
42.0	0.994	0.982	0.971																																																			
46.2	0.994	0.984	0.975																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	TUNS500F12	Temperature Testing Circuitry Figure A
Item	Inrush Current	
Object	—	





Model	TUNS500F12	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240[V]	
IEC60950-1	Both phases	0.16	0.33	0.40	Operation
	One of phase	0.30	0.63	0.77	stand by

The value for "One phase" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	TUNS500F12
Item	Line Regulation
Object	+12V42A

1.Graph

Output Voltage [V]

Input Voltage [V]

Legend:

- Load 50% (Dashed line)
- Load 100% (Solid line)

Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	12.089	12.088
85	12.089	12.088
100	12.089	12.089
120	12.089	12.089
200	12.089	12.089
230	12.089	12.089
264	12.089	12.089
280	12.089	12.089
--	-	-

COSEL

Model	TUNS500F12																																																						
Item	Load Regulation																																																						
Object	+12V42A																																																						
1.Graph																																																							
<p style="text-align: center;"> —▲— Input Volt. 100V ---■--- Input Volt. 200V ---○--- Input Volt. 230V </p> <p>The graph plots Output Voltage [V] on the Y-axis (from 11.80 to 12.40) against Load Current [A] on the X-axis (from 0 to 50). Three data series are shown for different input voltages: 100V (solid line with triangle markers), 200V (dashed line with square markers), and 230V (dash-dot line with circle markers). All three series show a slight decrease in output voltage as load current increases, with the 100V series being the most stable. A horizontal line is drawn at approximately 12.10V, and a slanted line extends from the origin through the data points at higher currents.</p>																																																							
2.Values																																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.093</td><td>12.093</td><td>12.093</td></tr> <tr><td>8.4</td><td>12.091</td><td>12.091</td><td>12.091</td></tr> <tr><td>16.8</td><td>12.090</td><td>12.090</td><td>12.090</td></tr> <tr><td>25.2</td><td>12.090</td><td>12.090</td><td>12.090</td></tr> <tr><td>33.6</td><td>12.089</td><td>12.089</td><td>12.089</td></tr> <tr><td>42.0</td><td>12.089</td><td>12.089</td><td>12.089</td></tr> <tr><td>46.2</td><td>12.088</td><td>12.088</td><td>12.088</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	12.093	12.093	12.093	8.4	12.091	12.091	12.091	16.8	12.090	12.090	12.090	25.2	12.090	12.090	12.090	33.6	12.089	12.089	12.089	42.0	12.089	12.089	12.089	46.2	12.088	12.088	12.088	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.0	12.093	12.093	12.093																																																				
8.4	12.091	12.091	12.091																																																				
16.8	12.090	12.090	12.090																																																				
25.2	12.090	12.090	12.090																																																				
33.6	12.089	12.089	12.089																																																				
42.0	12.089	12.089	12.089																																																				
46.2	12.088	12.088	12.088																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
<p>Note: Slanted line shows the range of the rated load current.</p>																																																							

COSEL

Model	TUNS500F12
Item	Dynamic Load Response
Object	+12V 42A


Temperature
Testing Circuitry 25°C
Figure AInput Volt. 100V
Cycle 1000ms

Load Current


42A / 50us

Min.Load (0A)↔
Load 100%(42A)

200 mV/div




200 us/div




10 ms/div

Min.Load (0A)↔
Load 50%(21A)

200 mV/div




200 us/div




10 ms/div

Load 10% (4.2A)↔
Load 100% (42A)

200 mV/div



200 us/div




10 ms/div

COSEL

Model	TUNS500F12
Item	Ripple Voltage (by Load Current)
Object	+12V42A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



Measured by 100 MHz Oscilloscope.
 Ripple Voltage is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	45	45
8.4	85	85
16.8	90	90
25.2	90	90
33.6	90	90
42.0	90	90
46.2	90	90
--	-	-
--	-	-
--	-	-
--	-	-





Fig. Complex Ripple Wave Form

COSEL

Model	TUNS500F12
Item	Ripple-Noise
Object	+12V42A

Temperature 25°C
 Testing Circuitry Figure C

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	50	50
8.4	85	85
16.8	95	95
25.2	95	95
33.6	95	95
42.0	95	95
46.2	95	95
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.
 Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.





Fig. Complex Ripple Wave Form

Model	TUNS500F12
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V42A

1.Graph




Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	115	115
-40	105	110
-20	100	100
0	105	105
25	90	90
50	90	90
75	85	85
85	85	85
100	85	85
105	85	85
--	-	-



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-50	12.019	12.020	12.020
-40	12.032	12.032	12.032
-20	12.053	12.054	12.054
0	12.072	12.072	12.072
25	12.089	12.089	12.089
50	12.093	12.093	12.093
75	12.097	12.097	12.097
85	12.098	12.099	12.099
100	12.104	12.104	12.104
105	12.107	12.108	12.108
—	-	-	-



Model	TUNS500F12	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V42A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 100°C

Input Voltage : 85 - 264V

Load Current : 0 - 42A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	100	85	0	12.109		
Minimum Voltage	-40	85	42	12.030	±40	±0.3


COSEL

Model	TUNS500F12
-------	------------

Item	Time Lapse Drift
------	------------------

Object	+12V42A
--------	---------

1. Graph



* The characteristic of AC200V is equal.

Temperature	25°C
Testing Circuitry	Figure A


2. Values

Time since start [H]	Output Voltage [V]
0.0	12.087
0.5	12.090
1.0	12.090
2.0	12.090
3.0	12.090
4.0	12.090
5.0	12.090
6.0	12.090
7.0	12.090
8.0	12.090

COSEL


Model	TUNS500F12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V42A		

1.Graph



2.Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		529.0	11.0	540.0	50.7	4.9	
200 V		490.0	11.0	501.0	50.9	4.9	




COSEL

Model TUNS500F12

Item Hold-Up Time

Object +12V42A

1. Graph



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
80	89	41
85	89	41
100	89	41
120	89	41
200	89	41
230	89	41
264	89	41
280	96	43
--	-	-

COSEL


Model	TUNS500F12	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Instantaneous Interruption Compensation																																																						
Object	+12V42A	2.Values																																																					
1.Graph																																																							
<p>—△— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>200V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>10</td><td>~150</td><td>~150</td><td>~150</td></tr> <tr><td>15</td><td>~120</td><td>~120</td><td>~120</td></tr> <tr><td>20</td><td>~100</td><td>~100</td><td>~100</td></tr> <tr><td>25</td><td>~80</td><td>~80</td><td>~80</td></tr> <tr><td>30</td><td>~70</td><td>~70</td><td>~70</td></tr> <tr><td>35</td><td>~60</td><td>~60</td><td>~60</td></tr> <tr><td>40</td><td>~50</td><td>~50</td><td>~50</td></tr> <tr><td>45</td><td>~40</td><td>~40</td><td>~40</td></tr> </tbody> </table>				Load Current [A]	100V [ms]	200V [ms]	230V [ms]	10	~150	~150	~150	15	~120	~120	~120	20	~100	~100	~100	25	~80	~80	~80	30	~70	~70	~70	35	~60	~60	~60	40	~50	~50	~50	45	~40	~40	~40																
Load Current [A]	100V [ms]	200V [ms]	230V [ms]																																																				
10	~150	~150	~150																																																				
15	~120	~120	~120																																																				
20	~100	~100	~100																																																				
25	~80	~80	~80																																																				
30	~70	~70	~70																																																				
35	~60	~60	~60																																																				
40	~50	~50	~50																																																				
45	~40	~40	~40																																																				
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.4</td><td>214</td><td>214</td><td>214</td></tr> <tr><td>16.8</td><td>111</td><td>111</td><td>111</td></tr> <tr><td>25.2</td><td>72</td><td>72</td><td>72</td></tr> <tr><td>33.6</td><td>51</td><td>51</td><td>51</td></tr> <tr><td>42.0</td><td>39</td><td>39</td><td>39</td></tr> <tr><td>46.2</td><td>37</td><td>37</td><td>37</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	8.4	214	214	214	16.8	111	111	111	25.2	72	72	72	33.6	51	51	51	42.0	39	39	39	46.2	37	37	37	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.0	-	-	-																																																				
8.4	214	214	214																																																				
16.8	111	111	111																																																				
25.2	72	72	72																																																				
33.6	51	51	51																																																				
42.0	39	39	39																																																				
46.2	37	37	37																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
<p>Note: Slanted line shows the range of the rated load current.</p>																																																							

Model TUNS500F12 Item Minimum Input Voltage for Regulated Output Voltage Object +12V42A	Testing Circuitry Figure A																																						
	2.Values																																						
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-50</td><td>72</td><td>71</td></tr> <tr> <td>-40</td><td>72</td><td>72</td></tr> <tr> <td>-20</td><td>72</td><td>72</td></tr> <tr> <td>0</td><td>72</td><td>72</td></tr> <tr> <td>25</td><td>72</td><td>72</td></tr> <tr> <td>50</td><td>71</td><td>72</td></tr> <tr> <td>75</td><td>71</td><td>72</td></tr> <tr> <td>85</td><td>71</td><td>71</td></tr> <tr> <td>100</td><td>71</td><td>72</td></tr> <tr> <td>105</td><td>72</td><td>73</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-50	72	71	-40	72	72	-20	72	72	0	72	72	25	72	72	50	71	72	75	71	72	85	71	71	100	71	72	105	72	73	--	-
Ambient Temperature [°C]	Input Voltage [V]																																						
	Load 50%	Load 100%																																					
-50	72	71																																					
-40	72	72																																					
-20	72	72																																					
0	72	72																																					
25	72	72																																					
50	71	72																																					
75	71	72																																					
85	71	71																																					
100	71	72																																					
105	72	73																																					
--	-	-																																					
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p>																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																							

COSEL

Model	TUNS500F12
Item	Overcurrent Protection
Object	+12V42A

1.Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 6V to 0V.

Temperature 25°C
Testing Circuitry Figure A


2.Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
12.0	42.56	42.39
11.4	57.72	57.82
10.8	58.22	58.32
9.6	59.40	59.47
8.4	60.97	60.89
7.2	62.74	62.72
6.0	64.90	64.97
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	TUNS500F12
Item	Overvoltage Protection
Object	+12V42A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-50	15.77	15.77
-40	15.77	15.77
-20	15.83	15.83
0	15.82	15.82
25	15.82	15.82
50	15.82	15.82
75	15.82	15.82
85	15.82	15.82
100	15.82	15.82
105	15.82	15.82
...	-	-





Figure B (DEN-AN)






Figure B (IEC60950-1)



C10	: TUNS500F12	2200 μ F	(0 \leq Tc \leq 100)	C11	: TUNS500F12	10 μ F
		2200 μ F \times 3	(-40 \leq Tc < 0)			TUNS500F28 4.7 μ F
	TUNS500F28	1000 μ F	(0 \leq Tc \leq 100)			TUNS500F48 2.2 μ F
		1000 μ F \times 3	(-40 \leq Tc < 0)			
	TUNS500F48	470 μ F	(0 \leq Tc \leq 100)			
		470 μ F \times 3	(-40 \leq Tc < 0)			

Tc:Base Plate Temp.

Figure C



L1,L2	: SC-15-200(NEC TOKIN)	C1
C1,C2	: $0.68\ \mu F$ 310V Film Capacitor × 2	
C3	: $1.0\ \mu F$ 310V Film Capacitor × 2	
C4,C5,C9	: 2200pF Ceramic Capacitor	
C6,C7	: $0.68\ \mu F$ 450V Film Capacitor × 2	
C8	: $390\ \mu F$ 450V Electrolytic Capacitor × 2	
C10	: TUNS500F12 $2200\ \mu F$ 25V Electrolytic Capacitor	
	TUNS500F28 $1000\ \mu F$ 50V Electrolytic Capacitor	
	TUNS500F48 $470\ \mu F$ 63V Electrolytic Capacitor	

C11 : TUNS500F12 10 μ F Ceramic Capacitor
TUNS500F28 4.7 μ F Ceramic Capacitor
TUNS500F48 2.2 μ F Ceramic Capacitor

Figure D