



DATA SHEET		Date	12-Sep-23
Model	UMA60F-36	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	A.Mukai




Frequency	Line	Level		Limit		Margin		Pass/Fail	Remark
MHz		dB(μV)		dB(μV)		dB			
		QP	AV	QP	AV	QP	AV		
0.199	N	54.7	37.5	63.6	53.6	8.9	16.1	Pass	
0.205	L1	55.2	37.9	63.4	53.4	8.2	15.5	Pass	




Frequency	Polarization	Stability	Level	Limit	Margin	Pass/Fail	Height	Angle	Remark
MHz			dB(μV/m)	dB(μV/m)	dB		cm	deg	
			QP	QP	QP				
179.651	H	Stable	31	40	9	Pass	200	168.8	

DATA SHEET		Date	12-Sep-23
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	A.Mukai

1. Line conduction



2. Radiated emission




Conditions

Test : EMI
Model Name: UMA60F-36

○Photographs of Test Set-Up

1. LINE CONDUCTION



2. RADIATED EMISSION

