



TEST DATA OF UMA60F-5

Regulated DC Power Supply
January 16, 2023

Approved by : Takashi Kajii
Design Manager

Prepared by : Jeonghoon Yi
Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)

COSEL

Model	UMA60F-5
Item	Input Current (by Load Current)
Object	+5V6A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]
0.0	0.013	0.025	0.028
1.2	0.139	0.091	0.084
2.4	0.251	0.157	0.142
3.6	0.361	0.220	0.201
4.8	0.474	0.287	0.260
6.0	0.587	0.354	0.321
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL


Model	UMA60F-5	Temperature	25°C																																																																											
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																																											
Object	+5V6A																																																																													
1.Graph		2.Values																																																																												
<p>The graph plots Efficiency [%] on the y-axis (70 to 100) against Load Current [A] on the x-axis (0 to 8). Three data series are shown: Input Volt. 115V (solid line with open triangle markers), Input Volt. 230V (dashed line with open square markers), and Input Volt. 264V (dash-dot line with open circle markers). All series show a slight decrease in efficiency as load current increases from 1.2A to 6.0A.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 115V [%]</th> <th>Input Volt. 230V [%]</th> <th>Input Volt. 264V [%]</th> </tr> </thead> <tbody> <tr><td>1.2</td><td>84.9</td><td>83.1</td><td>82.0</td></tr> <tr><td>2.4</td><td>84.0</td><td>83.6</td><td>83.0</td></tr> <tr><td>3.6</td><td>83.5</td><td>83.6</td><td>82.1</td></tr> <tr><td>4.8</td><td>82.8</td><td>82.3</td><td>81.8</td></tr> <tr><td>6.0</td><td>82.2</td><td>81.7</td><td>81.0</td></tr> </tbody> </table>		Load Current [A]	Input Volt. 115V [%]	Input Volt. 230V [%]	Input Volt. 264V [%]	1.2	84.9	83.1	82.0	2.4	84.0	83.6	83.0	3.6	83.5	83.6	82.1	4.8	82.8	82.3	81.8	6.0	82.2	81.7	81.0	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.2</td><td>84.9</td><td>83.1</td><td>82.0</td></tr> <tr><td>2.4</td><td>84.0</td><td>83.6</td><td>83.0</td></tr> <tr><td>3.6</td><td>83.5</td><td>83.6</td><td>82.1</td></tr> <tr><td>4.8</td><td>82.8</td><td>82.3</td><td>81.8</td></tr> <tr><td>6.0</td><td>82.2</td><td>81.7</td><td>81.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]	0.0	-	-	-	1.2	84.9	83.1	82.0	2.4	84.0	83.6	83.0	3.6	83.5	83.6	82.1	4.8	82.8	82.3	81.8	6.0	82.2	81.7	81.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Volt. 115V [%]	Input Volt. 230V [%]	Input Volt. 264V [%]																																																																											
1.2	84.9	83.1	82.0																																																																											
2.4	84.0	83.6	83.0																																																																											
3.6	83.5	83.6	82.1																																																																											
4.8	82.8	82.3	81.8																																																																											
6.0	82.2	81.7	81.0																																																																											
Load Current [A]	Efficiency [%]																																																																													
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]																																																																											
0.0	-	-	-																																																																											
1.2	84.9	83.1	82.0																																																																											
2.4	84.0	83.6	83.0																																																																											
3.6	83.5	83.6	82.1																																																																											
4.8	82.8	82.3	81.8																																																																											
6.0	82.2	81.7	81.0																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											

COSEL

Model	UMA60F-5
Item	Power Factor (by Load Current)
Object	+5V6A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Load Current [A]	Power Factor		
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]
0.0	0.033	0.023	0.022
1.2	0.456	0.357	0.343
2.4	0.510	0.410	0.396
3.6	0.533	0.438	0.424
4.8	0.546	0.454	0.438
6.0	0.554	0.462	0.447
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


COSEL

Model	UMA60F-5	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current		
Object	+5V6A		



Input Voltage	230 V
Frequency	50 Hz
Load	100 %

Primary inrush current	48.0 A
Secondary inrush current	2.0 A





Model	UMA60F-5	Temperature Testing Circuitry Figure C	25°C
Item	Leakage Current		
Object	+5V6A		

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			115 [V]	230 [V]	264 [V]	
IEC60601-1	Figure C-1	Both phases	0.05	0.11	0.13	Operation
		One of phases	0.10	0.21	0.25	Stand by
IEC62368-1	Figure C-2	Both phases	0.05	0.11	0.13	Operation
		One of phases	0.10	0.21	0.25	Stand by
	Figure C-3	Both phases	0.05	0.11	0.13	Operation
		One of phases	0.10	0.21	0.25	Stand by

The value for "One of phases" is the reference value only.



2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	UMA60F-5	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+5V6A																																		
1. Graph			2. Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> --□-- Load 50% —△— Load 100% 			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>5.134</td> <td>-</td> </tr> <tr> <td>100</td> <td>5.135</td> <td>-</td> </tr> <tr> <td>115</td> <td>5.135</td> <td>5.110</td> </tr> <tr> <td>132</td> <td>5.135</td> <td>5.110</td> </tr> <tr> <td>170</td> <td>5.135</td> <td>5.111</td> </tr> <tr> <td>200</td> <td>5.135</td> <td>5.111</td> </tr> <tr> <td>230</td> <td>5.135</td> <td>5.111</td> </tr> <tr> <td>264</td> <td>5.135</td> <td>5.112</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	5.134	-	100	5.135	-	115	5.135	5.110	132	5.135	5.110	170	5.135	5.111	200	5.135	5.111	230	5.135	5.111	264	5.135	5.112	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	5.134	-																																	
100	5.135	-																																	
115	5.135	5.110																																	
132	5.135	5.110																																	
170	5.135	5.111																																	
200	5.135	5.111																																	
230	5.135	5.111																																	
264	5.135	5.112																																	
--	-	-																																	



COSEL

Model	UMA60F-5	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+5V6A																																																					
1.Graph		2.Values																																																				
<p>—△— Input Volt. 115V - - -□- - Input Volt. 230V - - -○- - Input Volt. 264V</p> 		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.137</td><td>5.138</td><td>5.138</td></tr> <tr><td>1.2</td><td>5.130</td><td>5.130</td><td>5.130</td></tr> <tr><td>2.4</td><td>5.121</td><td>5.121</td><td>5.121</td></tr> <tr><td>3.6</td><td>5.112</td><td>5.112</td><td>5.112</td></tr> <tr><td>4.8</td><td>5.100</td><td>5.102</td><td>5.103</td></tr> <tr><td>6.0</td><td>5.090</td><td>5.091</td><td>5.091</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]	0.0	5.137	5.138	5.138	1.2	5.130	5.130	5.130	2.4	5.121	5.121	5.121	3.6	5.112	5.112	5.112	4.8	5.100	5.102	5.103	6.0	5.090	5.091	5.091	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]																																																			
0.0	5.137	5.138	5.138																																																			
1.2	5.130	5.130	5.130																																																			
2.4	5.121	5.121	5.121																																																			
3.6	5.112	5.112	5.112																																																			
4.8	5.100	5.102	5.103																																																			
6.0	5.090	5.091	5.091																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+5V6A	Testing Circuitry	Figure B																																																			
1.Graph																																																						
<p>Input Voltage 230V Load 100%</p> 																																																						

COSEL

Model	UMA60F-5	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+5V6A		


Input Volt. 230 V
 Cycle 1000 ms



COSEL


Model	UMA60F-5	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V6A		

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		27.8	4.3	32.1	346.0	7.8	
100 %		27.8	6.5	34.3	166.5	5.3	



COSEL

Model	UMA60F-5	Temperature	25°C
Item	Hold-Up Time	Testing Circuitry	Figure A
Object	+5V6A		

1.Graph



2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	40	-
100	58	-
115	79	35
132	107	48
170	184	86
200	260	123
230	349	167
264	467	225
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

COSEL

Model	UMA60F-5	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+5V6A																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 115V (solid line with open triangle) Input Volt. 230V (dashed line with open square) Input Volt. 264V (dash-dot line with open circle) <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>115[V] [ms]</th> <th>230[V] [ms]</th> <th>264[V] [ms]</th> </tr> </thead> <tbody> <tr> <td>1.2</td> <td>209</td> <td>908</td> <td>1210</td> </tr> <tr> <td>2.4</td> <td>102</td> <td>446</td> <td>605</td> </tr> <tr> <td>3.6</td> <td>66</td> <td>294</td> <td>393</td> </tr> <tr> <td>4.8</td> <td>47</td> <td>217</td> <td>291</td> </tr> <tr> <td>6.0</td> <td>35</td> <td>168</td> <td>227</td> </tr> </tbody> </table>			Load Current [A]	115[V] [ms]	230[V] [ms]	264[V] [ms]	1.2	209	908	1210	2.4	102	446	605	3.6	66	294	393	4.8	47	217	291	6.0	35	168	227																											
Load Current [A]	115[V] [ms]	230[V] [ms]	264[V] [ms]																																																			
1.2	209	908	1210																																																			
2.4	102	446	605																																																			
3.6	66	294	393																																																			
4.8	47	217	291																																																			
6.0	35	168	227																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.2</td> <td>209</td> <td>908</td> <td>1210</td> </tr> <tr> <td>2.4</td> <td>102</td> <td>446</td> <td>605</td> </tr> <tr> <td>3.6</td> <td>66</td> <td>294</td> <td>393</td> </tr> <tr> <td>4.8</td> <td>47</td> <td>217</td> <td>291</td> </tr> <tr> <td>6.0</td> <td>35</td> <td>168</td> <td>227</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]	0.0	-	-	-	1.2	209	908	1210	2.4	102	446	605	3.6	66	294	393	4.8	47	217	291	6.0	35	168	227	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]																																																			
0.0	-	-	-																																																			
1.2	209	908	1210																																																			
2.4	102	446	605																																																			
3.6	66	294	393																																																			
4.8	47	217	291																																																			
6.0	35	168	227																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	UMA60F-5	Temperature	25°C																																																																											
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																																											
Object	+5V6A																																																																													
1.Graph		2.Values																																																																												
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Overcurrent protection is Hiccup mode.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>5</td><td>9.61</td><td>9.98</td><td>10.31</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]	5	9.61	9.98	10.31	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																																													
	Input Volt. 115[V]	Input Volt. 230[V]	Input Volt. 264[V]																																																																											
5	9.61	9.98	10.31																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											

COSEL

Model	UMA60F-5	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+5V6A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 115V	Input Volt. 230V	Input Volt. 264V
-20	5.098	5.100	5.101
25	5.110	5.112	5.112
40	5.111	5.113	5.113

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+5V6A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	30	46
25	29	45
40	28	45

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+5V6A	

1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 115V	Input Volt. 264V
-20	6.62	6.62
25	6.62	6.61
40	6.62	6.61

COSEL






Figure C-1 (IEC60601-1)

COSEL




Figure C-2 (IEC62368-1 refer to IEC60990 Fig.4)




Figure C-3 (IEC62368-1 refer to IEC60990 Fig.5)