

COSEL

TEST DATA OF VAF1005
(100V INPUT)

Regulated DC Power Supply

Date : May 28. 1999

Approved by : T. Yoneda
Design Manager

Prepared by : Y. Hirose
Design Engineer

コーセル株式会社
COSEL CO., LTD.



C O N T E N T S

1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Power Factor (by Input Voltage)	6
力率 (入力電圧特性)	
7. Power Factor (by Load Current)	7
力率 (負荷特性)	
8. Hold-Up Time	8
出力保持時間	
9. Instantaneous Interruption Compensation	9
瞬時停電保障	
10. Load Regulation	10
静的負荷変動	
11. Ripple Voltage (by Load Current)	11
リップル電圧 (負荷特性)	
12. Ripple-Noise	12
リップルノイズ	
13. Overcurrent Protection	13
過電流保護	
14. Inrush Current	14
突入電流	
15. Dynamic Load Response	15
動的負荷変動	
16. Rise and Fall Time	16
立上り、立下がり時間	
17. Ambient Temperature Drift	17
周囲温度変動	
18. Minimum Input Voltage for Regulated Output Voltage	18
最低レギュレーション電圧	
19. Ripple Voltage (by Ambient Temperature)	19
リップル電圧 (周囲温度特性)	
20. Time Lapse Drift	20
経時ドリフト	
21. Output Voltage Accuracy	21
定電圧精度	
22. Oscillator Frequency	22
発振周波数	
23. Condensation	23
結露特性	
24. Leakage Current	24
漏洩電流	
25. Line Noise Tolerance	25
入力雑音耐量	
26. Conducted Emission	26
雑音端子電圧	
27. Figure of Testing Circuitry	27
測定回路図	

(Final Page 28)

COSEL

Model	VAF1005	Temperature	25°C																																
Item	Line Regulation 静的入力変動	Testing Circuitry	Figure A																																
Object	+5.0V2A																																		
1. Graph																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>5.113</td><td>5.111</td></tr> <tr><td>80</td><td>5.113</td><td>5.111</td></tr> <tr><td>85</td><td>5.113</td><td>5.111</td></tr> <tr><td>90</td><td>5.113</td><td>5.111</td></tr> <tr><td>100</td><td>5.113</td><td>5.112</td></tr> <tr><td>110</td><td>5.113</td><td>5.112</td></tr> <tr><td>120</td><td>5.113</td><td>5.112</td></tr> <tr><td>132</td><td>5.113</td><td>5.112</td></tr> <tr><td>140</td><td>5.113</td><td>5.112</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	5.113	5.111	80	5.113	5.111	85	5.113	5.111	90	5.113	5.111	100	5.113	5.112	110	5.113	5.112	120	5.113	5.112	132	5.113	5.112	140	5.113	5.112
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	5.113	5.111																																	
80	5.113	5.111																																	
85	5.113	5.111																																	
90	5.113	5.111																																	
100	5.113	5.112																																	
110	5.113	5.112																																	
120	5.113	5.112																																	
132	5.113	5.112																																	
140	5.113	5.112																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL


Model	VAF1005	Temperature	25°C																																																							
Item	Input Current (by Load Current) 入力電流（負荷特性）	Testing Circuitry	Figure A																																																							
Output	_____																																																									
1. Graph																																																										
<p>The graph plots Input Current [A] on the y-axis (0 to 0.5) against Load Current [A] on the x-axis (0 to 2.5). Three curves are shown for different input voltages: 85V (triangles), 100V (squares), and 132V (circles). All curves show a positive linear relationship. A slanted line is drawn across the graph, representing the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85V [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 132V [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.012</td><td>0.013</td><td>0.014</td></tr> <tr><td>0.4</td><td>0.071</td><td>0.064</td><td>0.054</td></tr> <tr><td>0.8</td><td>0.122</td><td>0.110</td><td>0.092</td></tr> <tr><td>1.2</td><td>0.172</td><td>0.152</td><td>0.129</td></tr> <tr><td>1.6</td><td>0.221</td><td>0.196</td><td>0.161</td></tr> <tr><td>2.0</td><td>0.270</td><td>0.238</td><td>0.196</td></tr> <tr><td>2.2</td><td>0.296</td><td>0.259</td><td>0.212</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85V [A]	Input Volt. 100V [A]	Input Volt. 132V [A]	0.0	0.012	0.013	0.014	0.4	0.071	0.064	0.054	0.8	0.122	0.110	0.092	1.2	0.172	0.152	0.129	1.6	0.221	0.196	0.161	2.0	0.270	0.238	0.196	2.2	0.296	0.259	0.212																								
Load Current [A]	Input Volt. 85V [A]	Input Volt. 100V [A]	Input Volt. 132V [A]																																																							
0.0	0.012	0.013	0.014																																																							
0.4	0.071	0.064	0.054																																																							
0.8	0.122	0.110	0.092																																																							
1.2	0.172	0.152	0.129																																																							
1.6	0.221	0.196	0.161																																																							
2.0	0.270	0.238	0.196																																																							
2.2	0.296	0.259	0.212																																																							
2. Values																																																										
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.012</td><td>0.013</td><td>0.014</td></tr> <tr><td>0.4</td><td>0.071</td><td>0.064</td><td>0.054</td></tr> <tr><td>0.8</td><td>0.122</td><td>0.110</td><td>0.092</td></tr> <tr><td>1.2</td><td>0.172</td><td>0.152</td><td>0.129</td></tr> <tr><td>1.6</td><td>0.221</td><td>0.196</td><td>0.161</td></tr> <tr><td>2.0</td><td>0.270</td><td>0.238</td><td>0.196</td></tr> <tr><td>2.2</td><td>0.296</td><td>0.259</td><td>0.212</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	0.012	0.013	0.014	0.4	0.071	0.064	0.054	0.8	0.122	0.110	0.092	1.2	0.172	0.152	0.129	1.6	0.221	0.196	0.161	2.0	0.270	0.238	0.196	2.2	0.296	0.259	0.212	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0.0	0.012	0.013	0.014																																																							
0.4	0.071	0.064	0.054																																																							
0.8	0.122	0.110	0.092																																																							
1.2	0.172	0.152	0.129																																																							
1.6	0.221	0.196	0.161																																																							
2.0	0.270	0.238	0.196																																																							
2.2	0.296	0.259	0.212																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	VAF1005
Item	Input Power (by Load Current) 入力電力（負荷特性）
Output	_____



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	0.33	0.41	0.57
0.4	2.84	2.86	2.87
0.8	5.42	5.44	5.46
1.2	8.14	8.02	8.16
1.6	10.97	10.86	10.66
2.0	13.94	13.68	13.50
2.2	15.52	15.15	14.88
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	VAF1005	Temperature Testing Circuitry	25°C Figure A																							
Item	Efficiency 効率																									
Object	<hr/>																									
<p>1. Graph</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p> <table> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% [%]</th> <th>Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>80</td><td>75.5</td><td>71.8</td></tr> <tr><td>90</td><td>75.5</td><td>72.7</td></tr> <tr><td>100</td><td>75.5</td><td>73.4</td></tr> <tr><td>110</td><td>75.4</td><td>74.0</td></tr> <tr><td>120</td><td>75.4</td><td>74.8</td></tr> <tr><td>130</td><td>75.5</td><td>75.3</td></tr> <tr><td>140</td><td>75.5</td><td>75.9</td></tr> </tbody> </table>			Input Voltage [V]	Load 50% [%]	Load 100% [%]	80	75.5	71.8	90	75.5	72.7	100	75.5	73.4	110	75.4	74.0	120	75.4	74.8	130	75.5	75.3	140	75.5	75.9
Input Voltage [V]	Load 50% [%]	Load 100% [%]																								
80	75.5	71.8																								
90	75.5	72.7																								
100	75.5	73.4																								
110	75.4	74.0																								
120	75.4	74.8																								
130	75.5	75.3																								
140	75.5	75.9																								

2. Values


Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	75.5	71.8
80	76.0	72.7
85	76.3	73.4
90	76.4	74.0
100	76.0	74.8
110	75.4	75.3
120	75.3	75.6
132	75.8	75.9
140	76.2	76.0

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	VAF1005
Item	Efficiency (by Load Current) 効率(負荷電流特性)
Output	—



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.4	72.0	71.5	71.2
0.8	75.7	75.4	75.1
1.2	75.5	76.6	75.3
1.6	74.7	75.5	76.9
2.0	73.5	74.9	75.9
2.2	72.5	74.3	75.7
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

COSEL


Model	VAF1005	Temperature	25°C																																
Item	Power Factor (by Input Voltage) 力率 (入力電圧特性)	Testing Circuitry	Figure A																																
Object																																			
1. Graph	<p style="text-align: center;">-----□----- Load 50% -----△----- Load 100%</p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.56</td><td>0.63</td></tr> <tr><td>80</td><td>0.55</td><td>0.62</td></tr> <tr><td>85</td><td>0.54</td><td>0.61</td></tr> <tr><td>90</td><td>0.53</td><td>0.60</td></tr> <tr><td>100</td><td>0.51</td><td>0.58</td></tr> <tr><td>110</td><td>0.49</td><td>0.56</td></tr> <tr><td>120</td><td>0.48</td><td>0.54</td></tr> <tr><td>132</td><td>0.46</td><td>0.52</td></tr> <tr><td>140</td><td>0.45</td><td>0.51</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.56	0.63	80	0.55	0.62	85	0.54	0.61	90	0.53	0.60	100	0.51	0.58	110	0.49	0.56	120	0.48	0.54	132	0.46	0.52	140	0.45	0.51
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
75	0.56	0.63																																	
80	0.55	0.62																																	
85	0.54	0.61																																	
90	0.53	0.60																																	
100	0.51	0.58																																	
110	0.49	0.56																																	
120	0.48	0.54																																	
132	0.46	0.52																																	
140	0.45	0.51																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	VAF1005
Item	Power Factor (by Load Current) 力率 (負荷電流特性)
Output	—

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Power Factor		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	0.34	0.33	0.31
0.4	0.47	0.44	0.40
0.8	0.52	0.49	0.45
1.2	0.56	0.53	0.48
1.6	0.58	0.55	0.50
2.0	0.61	0.57	0.52
2.2	0.62	0.58	0.53
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	VAF1005	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+5.0V2A																																		
1. Graph			2. Values																																
<p style="text-align: center;">—□— Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>21</td><td>7</td></tr> <tr><td>80</td><td>25</td><td>9</td></tr> <tr><td>85</td><td>29</td><td>11</td></tr> <tr><td>90</td><td>33</td><td>13</td></tr> <tr><td>100</td><td>43</td><td>18</td></tr> <tr><td>110</td><td>53</td><td>23</td></tr> <tr><td>120</td><td>64</td><td>28</td></tr> <tr><td>132</td><td>79</td><td>35</td></tr> <tr><td>140</td><td>90</td><td>41</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	21	7	80	25	9	85	29	11	90	33	13	100	43	18	110	53	23	120	64	28	132	79	35	140	90	41
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	21	7																																	
80	25	9																																	
85	29	11																																	
90	33	13																																	
100	43	18																																	
110	53	23																																	
120	64	28																																	
132	79	35																																	
140	90	41																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。


COSEL

Model	VAF1005	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																						
Object	+5.0V2A																																																						
1. Graph																																																							
<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85 V (open triangle) Input Volt. 100 V (open square) Input Volt. 132 V (open circle) 			2. Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>0.4</td><td>71</td><td>102</td><td>188</td></tr> <tr><td>0.8</td><td>31</td><td>48</td><td>90</td></tr> <tr><td>1.2</td><td>19</td><td>30</td><td>59</td></tr> <tr><td>1.6</td><td>13</td><td>21</td><td>42</td></tr> <tr><td>2.0</td><td>6</td><td>14</td><td>32</td></tr> <tr><td>2.2</td><td>6</td><td>13</td><td>28</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	—	—	—	0.4	71	102	188	0.8	31	48	90	1.2	19	30	59	1.6	13	21	42	2.0	6	14	32	2.2	6	13	28	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Time [mS]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
0.0	—	—	—																																																				
0.4	71	102	188																																																				
0.8	31	48	90																																																				
1.2	19	30	59																																																				
1.6	13	21	42																																																				
2.0	6	14	32																																																				
2.2	6	13	28																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.																																																							
Note: Slanted line shows the range of the rated load current.																																																							
瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。																																																							
(注) 斜線は定格負荷電流範囲を示す。																																																							

COSEL

Model	VAF1005
Item	Load Regulation 靜的負荷變動
Object	+5.0V 2A

Temperature 25°C
Testing Circuitry Figure A



2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	5.115	5.115	5.115
0.4	5.115	5.115	5.115
0.8	5.114	5.114	5.114
1.2	5.113	5.114	5.114
1.6	5.112	5.113	5.113
2.0	5.112	5.112	5.112
2.2	5.111	5.112	5.112
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSSEL

Model	VAF1005	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)	Testing Circuitry	Figure A																																						
Object	+5.0V2A																																								
1. Graph	<p>---□--- Input Volt. 85V [mV] ---△--- Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Graph 1.1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage 85V [mV]</th> <th>Ripple Voltage 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0.4</td><td>10</td><td>10</td></tr> <tr><td>0.8</td><td>10</td><td>10</td></tr> <tr><td>1.2</td><td>10</td><td>10</td></tr> <tr><td>1.6</td><td>15</td><td>10</td></tr> <tr><td>2.0</td><td>20</td><td>20</td></tr> <tr><td>2.2</td><td>20</td><td>20</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage 85V [mV]	Ripple Voltage 132V [mV]	0.4	10	10	0.8	10	10	1.2	10	10	1.6	15	10	2.0	20	20	2.2	20	20																	
Load Current [A]	Ripple Voltage 85V [mV]	Ripple Voltage 132V [mV]																																							
0.4	10	10																																							
0.8	10	10																																							
1.2	10	10																																							
1.6	15	10																																							
2.0	20	20																																							
2.2	20	20																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.4</td><td>10</td><td>10</td></tr> <tr><td>0.8</td><td>10</td><td>10</td></tr> <tr><td>1.2</td><td>10</td><td>10</td></tr> <tr><td>1.6</td><td>15</td><td>10</td></tr> <tr><td>2.0</td><td>20</td><td>20</td></tr> <tr><td>2.2</td><td>20</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	5	5	0.4	10	10	0.8	10	10	1.2	10	10	1.6	15	10	2.0	20	20	2.2	20	20	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
0.0	5	5																																							
0.4	10	10																																							
0.8	10	10																																							
1.2	10	10																																							
1.6	15	10																																							
2.0	20	20																																							
2.2	20	20																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL


Model	VAF1005	Temperature Testing Circuitry	25°C Figure A																																							
Item	Ripple-Noise リップルノイズ																																									
Object	+5.0V2A	2. Values																																								
1. Graph																																										
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>0.4</td><td>15</td><td>15</td></tr> <tr><td>0.8</td><td>20</td><td>20</td></tr> <tr><td>1.2</td><td>20</td><td>20</td></tr> <tr><td>1.6</td><td>25</td><td>20</td></tr> <tr><td>2.0</td><td>30</td><td>30</td></tr> <tr><td>2.2</td><td>35</td><td>30</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	10	10	0.4	15	15	0.8	20	20	1.2	20	20	1.6	25	20	2.0	30	30	2.2	35	30	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																									
	Input Volt. 85 [V]	Input Volt. 132 [V]																																								
0.0	10	10																																								
0.4	15	15																																								
0.8	20	20																																								
1.2	20	20																																								
1.6	25	20																																								
2.0	30	30																																								
2.2	35	30																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
		<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																								
		<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSEL

Model	VAF1005	Temperature 25°C Testing Circuitry Figure A																																																									
Item	Overcurrent Protection 過電流保護																																																										
Object	+5.0V2A																																																										
1. Graph	<p>[V] Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>5.00</td><td>3.30</td><td>3.70</td><td>4.20</td></tr> <tr> <td>4.75</td><td>3.35</td><td>3.82</td><td>4.26</td></tr> <tr> <td>4.50</td><td>3.40</td><td>4.02</td><td>4.40</td></tr> <tr> <td>4.00</td><td>3.75</td><td>4.28</td><td>4.63</td></tr> <tr> <td>3.50</td><td>4.00</td><td>4.56</td><td>4.94</td></tr> <tr> <td>3.00</td><td>4.20</td><td>5.00</td><td>5.37</td></tr> <tr> <td>2.50</td><td>4.78</td><td>5.21</td><td>5.64</td></tr> <tr> <td>2.00</td><td>5.12</td><td>5.66</td><td>6.10</td></tr> <tr> <td>1.50</td><td>5.78</td><td>6.16</td><td>6.50</td></tr> <tr> <td>1.00</td><td>6.36</td><td>6.76</td><td>7.31</td></tr> <tr> <td>0.50</td><td>—</td><td>—</td><td>—</td></tr> <tr> <td>0.00</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	5.00	3.30	3.70	4.20	4.75	3.35	3.82	4.26	4.50	3.40	4.02	4.40	4.00	3.75	4.28	4.63	3.50	4.00	4.56	4.94	3.00	4.20	5.00	5.37	2.50	4.78	5.21	5.64	2.00	5.12	5.66	6.10	1.50	5.78	6.16	6.50	1.00	6.36	6.76	7.31	0.50	—	—	—	0.00	—	—	—
Output Voltage [V]	Load Current [A]																																																										
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																								
5.00	3.30	3.70	4.20																																																								
4.75	3.35	3.82	4.26																																																								
4.50	3.40	4.02	4.40																																																								
4.00	3.75	4.28	4.63																																																								
3.50	4.00	4.56	4.94																																																								
3.00	4.20	5.00	5.37																																																								
2.50	4.78	5.21	5.64																																																								
2.00	5.12	5.66	6.10																																																								
1.50	5.78	6.16	6.50																																																								
1.00	6.36	6.76	7.31																																																								
0.50	—	—	—																																																								
0.00	—	—	—																																																								
Note1:	The graph shows the relationship between Output Voltage and Load Current for three different input voltages. A horizontal line at 5.0V represents the rated output voltage. A diagonal line from (0, 5) to (2, 5) indicates the range of rated load current. Three curves show the output voltage decreasing as load current increases for each input voltage. The 85V curve is the highest, followed by 100V, and then 132V.																																																										
Note2:	The graph shows the relationship between Output Voltage and Load Current for three different input voltages. A horizontal line at 5.0V represents the rated output voltage. A diagonal line from (0, 5) to (2, 5) indicates the range of rated load current. Three curves show the output voltage decreasing as load current increases for each input voltage. The 85V curve is the highest, followed by 100V, and then 132V.																																																										
(注1)	(注1) 斜線は定格負荷電流範囲を示す。																																																										
(注2)	(注2) 垂下部分は間欠モード時のピーク電流を示す。																																																										

COSEL

Model	VAF1005	Temperature Testing Circuitry	25°C
Item	Inrush Current 突入電流		Figure A
Object	_____		



Input Voltage 100 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 9.01 [A]

② 2.21 [A]



COSEL



Model	VAF1005	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response 動的負荷變動		
Object	+5.0V2A		

Input Volt. 100 V
 Cycle 1000 mS


Load Current




Min. Load ↔
 Load 100 %



Min. Load ↔
 Load 50 %



100 mV/div




20 mS/div

COSEL

Model	VAF1005
Item	Rise and Fall Time 立上り、立下り時間
Object	+5.0V2A


Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		170.3	3.8	174.0	29.1	39.3	
100 %		170.3	4.0	174.3	11.2	20.9	



COSEL


COSEL

Model VAF1005

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +5.0V2A

1. Graph



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	42	55
-20	41	55
-10	41	55
0	40	55
10	40	55
25	40	55
30	40	55
40	40	55
55	40	56
60	40	56
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model

VAF1005


Item

Ripple Voltage (by Ambient Temp.)
リップル電圧 (周囲温度特性)

Object

+5.0V2A

1. Graph



Input Volt. 100 V

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

Testing Circuitry

Figure A


2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	40	60
-10	30	55
0	20	30
10	20	25
20	15	25
25	10	20
30	10	15
40	10	15
55	10	15
60	10	15
-	-	-

COSEL

Model	VAF1005
Item	Time Lapse Drift 経時ドリフト
Object	+5.0V2A

1. Graph



Temperature 25 °C
Testing Circuitry Figure A

2. Values

Time since start [H]	Output Voltage [V]
0.0	5.112
0.5	5.111
1.0	5.111
2.0	5.111
3.0	5.112
4.0	5.112
5.0	5.111
6.0	5.112
7.0	5.112
8.0	5.112



Model	VAF1005
Item	Output Voltage Accuracy 定電圧精度
Object	+5.0V2A

Testing Circuitry Figure A

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~55 °C

Input Voltage : 85~132 V

Load Current : 0~2A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~55 °C

入力電圧 85~132 V

負荷電流 0~2A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	132	0	5.115	± 5	± 0.1
Minimum Voltage	55	100	2	5.106		


COSEL

Model	VAF1005
Item	Oscillator Frequency 発振周波数
Object	+5.0V2A

Temperature 25°C
 Testing Circuitry Figure A

1. Graph

—△— Input Volt. 85 V
 -□- Input Volt. 100 V
 -○- Input Volt. 132 V



Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

2. Values

Load Current [A]	Oscillator Frequency [KHz]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	100	101	101
0.4	101	101	101
0.8	101	101	101
1.2	101	101	101
1.6	101	101	101
2.0	101	101	101
2.2	101	101	101
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—



Model	VAF1005		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+5.0V2A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.101	Input Volt.: 100V, Load Current:2A
Line Regulation [mV]	3	Input Volt.: 85~132V, Load Current:2A
Load Regulation [mV]	7	Input Volt.: 100V, Load Current:0~2A



Model	VAF1005	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.07	0.09	0.11
(B) IEC60950	0.07	0.09	0.11

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—



Model	VAF1005	Temperature Testing Circuitry	25°C Figure C
Item	Line Noise Tolerance 入力雑音耐量		
Object	+5.0V2A		

1. Results

Pulse Width [nS]	MODE	No protection failure should occur 保護回路の誤動作がない	DC-like Regulation of Output Voltage 出力電圧の直流的変動
50	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation
1000	COMMON	OK	no fluctuation
	NORMAL	OK	no fluctuation

2. Conditions

Input Voltage : 100 V
 Pulse Voltage : 2000 V
 Pulse Cycle : 10 mS
 Pulse Input Duration : 1 min. or more
 Load : 100 %

COSEL

Model	VAF1005	Temperature Testing Circuitry	25°C
Item	Conducted Emission 雜音端子電壓		
Object	<hr/>		

1. Graph

Remarks


Input Volt. 100 V (VCCI Class B)

120 V (FCC Class B)


Load 100 %

Limit1: [VCCI] Class B(QP)

Limit2: [VCCI] Class B(Ave.)



Limit1: [FCC Part15] Class B



COSEL






Figure B (I E C 6 0 9 5 0)

COSEL




Figure C




Figure D




Figure E