



M T B F

(MIL-HDBK217F NOTICE 2)

Model	WBA35B-5
-------	----------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	0.3710	
2		Hybrid	0	0.0000	
3	Transistors		2	0.9570	
4	Diodes		11	0.4020	
5	LED•Optocouplers		2	0.4040	
6	Resistors		40	0.1810	
7	Capacitors		23	2.7620	
8	Transformer•Choke Coil		3	0.3630	
9	Connectors		207	0.3200	
10	Others		2	0.0100	
Total Failure Rate [10 ⁻⁶ /H]				5.7700	

M T B F	[H]	173,300
Ambient Temperature	[°C]	40.0
Load Factor	[%]	100



M T B F

(E I A J R C R - 9 1 0 2)

Model	WBA35B-5
-------	----------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	0.0980	
2		Hybrid	0	0.0000	
3	T r a n s i s t o r s		2	0.1980	
4	D i o d e s		11	0.2660	
5	LED•Optocouplers		2	0.0712	
6	R e s i s t o r s		40	0.4276	
7	C a p a c i t o r s		23	0.2850	
8	Transformer•Choke Coil		3	0.0690	
9	C o n n e c t o r s		207	0.0787	
10	O t h e r s		2	0.0230	
Total Failure Rate [10 ⁻⁶ /H]				1.5165	

M T B F	[H]	659,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—