



# TEST DATA OF WBA35B-5

Regulated DC Power Supply  
May 24, 2021

Approved by : Takeshi Kojii  
Design Manager

Prepared by : Takeshi Naganuma  
Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Load Current) .....	1
2.Efficiency (by Load Current) .....	2
3.Power Factor (by Load Current) .....	3
4.Inrush Current .....	4
5.Leakage Current .....	5
6.Line Regulation .....	6
7.Load Regulation .....	7
8.Ripple-Noise .....	7
9.Dynamic Load Response .....	8
10.Rise and Fall Time .....	9
11.Hold-Up Time .....	10
12.Instantaneous Interruption Compensation .....	11
13.Overcurrent Protection .....	12
14.Ambient Temperature Drift .....	13
15.Minimum Input Voltage for Regulated Output Voltage .....	13
16.Overvoltage Protection .....	13
17.Figure of Testing Circuitry .....	14

(Final Page 15)


**COSEL**

Model	WBA35B-5
Item	Input Current (by Load Current)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph

—△— Input Volt. 170V  
 - -□--- Input Volt. 277V  
 - -⊖--- Input Volt. 305V




## 2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 170[V]	Input Volt. 277[V]	Input Volt. 305[V]
0.0	0.017	0.025	0.022
1.4	0.124	0.096	0.088
2.8	0.214	0.160	0.148
4.2	0.302	0.221	0.205
5.6	0.388	0.281	0.259
7.0	0.477	0.341	0.314
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	WBA35B-5
Item	Efficiency (by Load Current)
Object	_____



 Temperature 25°C  
 Testing Circuitry Figure A

## 2.Values

Load Current [A]	Efficiency [%]		
	Input Volt. 170[V]	Input Volt. 277[V]	Input Volt. 305[V]
0.0	-	-	-
1.4	80.6	74.3	71.9
2.8	82.8	79.9	78.7
4.2	82.6	81.2	80.5
5.6	82.0	81.6	81.2
7.0	81.0	81.5	81.4
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	WBA35B-5
Item	Power Factor (by Load Current)
Object	_____



 Temperature 25°C  
 Testing Circuitry Figure A

## 2.Values

Load Current [A]	Power Factor		
	Input Volt. 170[V]	Input Volt. 277[V]	Input Volt. 305[V]
0.0	0.129	0.088	0.098
1.4	0.417	0.357	0.367
2.8	0.470	0.402	0.407
4.2	0.501	0.428	0.428
5.6	0.523	0.447	0.441
7.0	0.539	0.460	0.457
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


# COSEL

Model	WBA35B-5	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	<hr/>		



Input Voltage      277 V  
 Frequency            60 Hz  
 Load                100 %

Primary inrush current    43.1 A  
 Secondary inrush current   2.2 A





Model	WBA35B-5	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure C
Object	_____		

### 1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			170 [V]	277 [V]	305 [V]	
DEN-AN	Figure C-1	Both phases	0.21	0.36	0.40	Operation
		One of phases	0.40	0.68	0.75	Stand by
IEC62368-1	Figure C-2	Both phases	0.21	0.36	0.40	Operation
		One of phases	0.40	0.67	0.75	Stand by
	Figure C-3	Both phases	0.21	0.36	0.39	Operation
		One of phases	0.40	0.67	0.74	Stand by

The value for "One of phases" is the reference value only.

### 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	WBA35B-5
Item	Line Regulation
Object	+5V7A

 Temperature 25°C  
 Testing Circuitry Figure A



## 1.Graph



## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
170	5.058	5.054
200	5.058	5.055
230	5.058	5.054
277	5.058	5.054
305	5.058	5.054
--	-	-
--	-	-
--	-	-
--	-	-

# COSEL

Model	WBA35B-5	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+5V7A																																																					
1.Graph		2.Values																																																				
<p>—△— Input Volt. 170V        - - - □ - - Input Volt. 277V        - - Θ - - Input Volt. 305V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 277[V]</th> <th>Input Volt. 305[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.064</td><td>5.061</td><td>5.061</td></tr> <tr><td>1.4</td><td>5.060</td><td>5.060</td><td>5.060</td></tr> <tr><td>2.8</td><td>5.059</td><td>5.059</td><td>5.059</td></tr> <tr><td>4.2</td><td>5.057</td><td>5.057</td><td>5.057</td></tr> <tr><td>5.6</td><td>5.056</td><td>5.056</td><td>5.056</td></tr> <tr><td>7.0</td><td>5.055</td><td>5.054</td><td>5.054</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 277[V]	Input Volt. 305[V]	0.0	5.064	5.061	5.061	1.4	5.060	5.060	5.060	2.8	5.059	5.059	5.059	4.2	5.057	5.057	5.057	5.6	5.056	5.056	5.056	7.0	5.055	5.054	5.054	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 170[V]	Input Volt. 277[V]	Input Volt. 305[V]																																																			
0.0	5.064	5.061	5.061																																																			
1.4	5.060	5.060	5.060																																																			
2.8	5.059	5.059	5.059																																																			
4.2	5.057	5.057	5.057																																																			
5.6	5.056	5.056	5.056																																																			
7.0	5.055	5.054	5.054																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Item		Temperature	25°C																																																			
Object		Testing Circuitry	Figure B																																																			
1.Graph																																																						
<p>Input Voltage 277V        Load 100%</p>  <p>20[mV/div]</p> <p>20[ms/div]</p>																																																						

# COSEL

Model	WBA35B-5
Item	Dynamic Load Response
Object	+5V7A

Temperature 25°C  
Testing Circuitry Figure A



Input Volt.

277 V

Response.  $t_1=t_2=50\mu s$ . Typ

Cycle

1000 ms



Load 0%(0A)  $\longleftrightarrow$   
Load 100%(7A)

200[mV/div]

20[ms/div]

20[ms/div]

Load 50%(3.5A)  $\longleftrightarrow$   
Load 100%(7A)

200[mV/div]

20[ms/div]


20[ms/div]

**COSEL**

Model	WBA35B-5
Item	Rise and Fall Time
Object	+5V7A

Temperature  
Testing Circuitry  
25°C  
Figure A


## 1.Graph



## 2.Values

[ms]

Load	Time	Td	Tr	Ts	Th	Tf
50 %		68.0	2.8	70.8	162.3	21.3
100 %		67.5	3.5	71.0	77.3	12.0




**COSEL**

Model	WBA35B-5
Item	Hold-Up Time
Object	+5V7A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph




## 2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
170	57	22
200	81	34
230	110	49
277	163	75
305	200	95
--	-	-
--	-	-
--	-	-
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

**COSEL**

Model	WBA35B-5
Item	Instantaneous Interruption Compensation
Object	+5V7A


 Temperature 25°C  
 Testing Circuitry Figure A

## 2. Values

Load Current [A]	Time [ms]		
	Input Volt. 170[V]	Input Volt. 277[V]	Input Volt. 305[V]
0.0	-	-	-
1.4	151	407	555
2.8	73	206	254
4.2	47	137	170
5.6	32	100	125
7.0	23	76	98
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-





Model	WBA35B-5	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+5V7A	

## 1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 170V	Input Volt. 277V	Input Volt. 305V
-20	5.042	5.042	5.042
25	5.055	5.054	5.054
50	5.056	5.056	5.056

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+5V7A	

## 1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	44	97
25	42	93
40	42	91

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+5V7A	

## 1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 170V	Input Volt. 305V
-20	5.93	5.92
25	6.18	6.18
40	6.26	6.32

**COSEL**





Figure A



C<sub>1</sub>= 0.1  $\mu$  F  
(Ceramic capacitor)

C<sub>2</sub>= 47  $\mu$  F  
(Electrolytic capacitor)

Figure B




Figure C-1 ( DEN-AN )




Figure C-2 ( IEC62368-1 refer to IEC60990 Fig.4 )




Figure C-3 ( IEC62368-1 refer to IEC60990 Fig.5 )