



M T B F

(MIL-HDBK217F NOTICE 2)

Model	WBA75B-24
-------	-----------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	1.4270	
2		Hybrid	0	0.0000	
3	T r a n s i s t o r s		2	1.6270	
4	D i o d e s		11	0.3430	
5	LED•Optocouplers		2	0.5860	
6	R e s i s t o r s		43	0.2750	
7	C a p a c i t o r s		23	3.8490	
8	Transformer•Choke Coil		4	0.4850	
9	C o n n e c t o r s		206	0.3200	
10	O t h e r s		2	0.0100	
Total Failure Rate [10 ⁻⁶ /H]				8.9220	

M T B F	[H]	112,100
Ambient Temperature	[°C]	50.0
Load Factor	[%]	100



M T B F

(E I A J R C R - 9 1 0 2)

Model	WBA75B-24
-------	-----------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	0.0980	
2		Hybrid	0	0.0000	
3	T r a n s i s t o r s		2	0.1980	
4	D i o d e s		11	0.2660	
5	LED•Optocouplers		2	0.0712	
6	R e s i s t o r s		43	0.4282	
7	C a p a c i t o r s		23	0.2624	
8	Transformer•Choke Coil		4	0.0713	
9	C o n n e c t o r s		206	0.0789	
10	O t h e r s		2	0.0230	
Total Failure Rate [10 ⁻⁶ /H]				1.4970	

M T B F	[H]	668,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—