



M T B F

(MIL-HDBK217F NOTICE 2)

Model	WDA30F-24
-------	-----------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	4.1860	
2		Hybrid	0	0.0000	
3	T r a n s i s t o r s		2	1.6470	
4	D i o d e s		11	0.9870	
5	LED•Optocouplers		2	0.5050	
6	R e s i s t o r s		40	0.1980	
7	C a p a c i t o r s		25	3.3100	
8	Transformer•Choke Coil		3	0.4320	
9	C o n n e c t o r s		218	0.4440	
10	O t h e r s		4	0.0200	
Total Failure Rate [10 ⁻⁶ /H]				11.7290	

M T B F	[H]	85,300
Ambient Temperature	[°C]	50.0
Load Factor	[%]	100



M T B F

(E I A J R C R - 9 1 0 2)

Model	WDA30F-24
-------	-----------

No.	P a r t s		Q' ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	M o n o l i t h i c	2	0.0980	
2		H y b r i d	0	0.0000	
3	T r a n s i s t o r s		2	0.1980	
4	D i o d e s		11	0.2660	
5	LED・Optocouplers		2	0.0712	
6	R e s i s t o r s		40	0.4276	
7	C a p a c i t o r s		25	0.2555	
8	Transformer・Choke Coil		3	0.0690	
9	C o n n e c t o r s		218	0.0810	
1 0	O t h e r s		4	0.1470	
Total Failure Rate [10 ⁻⁶ /H]				1.6133	

M T B F	[H]	620,000
Ambient Temperature	[°C]	—
Load Factor	[%]	—