



M T B F

(M I L - H D B K 2 1 7 F N O T I C E 2)

Model	WMA150H-48
-------	------------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	1.4140	
2		Hybrid	0	0.0000	
3	T r a n s i s t o r s		2	1.5880	
4	D i o d e s		10	0.7410	
5	LED•Optocouplers		3	0.6340	
6	R e s i s t o r s		63	0.2890	
7	C a p a c i t o r s		27	2.7290	
8	Transformer•Choke Coil		3	0.3900	
9	C o n n e c t o r s		348	0.4760	
10	O t h e r s		4	0.0430	
Total Failure Rate [10 ⁻⁶ /H]				8.3040	

M T B F	[H]	120, 400
Ambient Temperature	[℃]	50. 0
Load Factor	[%]	100



M T B F

(E I A J R C R - 9 1 0 2)

Model	WMA150H-48
-------	------------

No.	P a r t s		Q'ty of Device	Failure rate [10 ⁻⁶ /H]	R e f e r e n c e
1	I C	Monolithic	2	0.0980	
2		Hybrid	0	0.0000	
3	Transistors		2	0.1001	
4	Diodes		10	0.2835	
5	LED•Optocouplers		3	0.1412	
6	Resistors		63	0.7520	
7	Capacitors		27	0.3381	
8	Transformer•Choke Coil		3	0.0690	
9	Connectors		348	0.2493	
10	Others		4	0.0460	
Total Failure Rate [10 ⁻⁶ /H]				2.0772	

M T B F	[H]	481,000
Ambient Temperature	[℃]	—
Load Factor	[%]	—