



DATA SHEET		Date	25-Nov-19
Model	WMA350H-24	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	A.Nishikawa




Frequency	Line	Level		Limit		Margin		Pass/Fail	Remark
MHz		dB(μV)		dB(μV)		dB			
		QP	AV	QP	AV	QP	AV		
0.19	N	55	44.4	64	54	9	9.6	Pass	
0.187	L1	52	45.9	64.2	54.2	12.2	8.3	Pass	




Frequency	Polarization	Stability	Level	Limit	Margin	Pass/Fail	Height	Angle	Remark
MHz			dB(μV/m)	dB(μV/m)	dB		cm	deg	
			QP	QP	QP				
43.261	V	Stable	31.7	40	8.3	Pass	100	351.7	
165.415	V	Stable	33.6	40	6.4	Pass	100.2	101.1	

DATA SHEET		Date	25-Nov-19
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	A.Nishikawa

1. Line conduction



2. Radiated emission




Conditions

Test : EMI
Model Name: WMA350H-24

Photographs of Test Set-Up

1. LINE CONDUCTION



2. RADIATED EMISSION

