

TEST DATA OF WMA350H-48

(115V INPUT)

Regulated DC Power Supply
December 5, 2019

Approved by :


Takashi Kajii
Design Manager

Prepared by :


Ryo Takahashi
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple-Noise (by Load Current)	12
13.Ripple-Noise (by Ambient Temperature)	13
14.Ambient Temperature Drift	14
15.Output Voltage Accuracy	15
16.Time Lapse Drift	16
17.Rise and Fall Time	17
18.Hold-Up Time	18
19.Instantaneous Interruption Compensation	19
20.Minimum Input Voltage for Regulated Output Voltage	20
21.Overcurrent Protection	21
22.Overvoltage Protection	22
23.Figure of Testing Circuitry	23

(Final Page 23)

COSEL


Model WMA350H-48

Item Input Current (by Load Current)

Object _____

1.Graph

—△— Input Volt. 100V
 - - -□- - Input Volt. 115V
 - ·○· - Input Volt. 132V

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 132[V]
0.00	0.073	0.077	0.082
1.46	1.601	1.439	1.287
2.92	2.817	2.519	2.250
4.38	4.000	3.580	3.198
5.84	5.220	4.640	4.150
7.30	-	5.740	5.130
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL


Model WMA350H-48

Item Input Power (by Load Current)

Object _____

1. Graph

—△— Input Volt. 100V
 - - - □ - - Input Volt. 115V
 - · ○ - - Input Volt. 132V


 Temperature 25°C
 Testing Circuitry Figure A

2. Values


Load Current [A]	Input Power [W]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 132[V]
0.00	1.0	1.0	1.1
1.46	78.7	79.4	80.5
2.92	156.4	156.8	157.5
4.38	236.0	236.0	235.6
5.84	318.0	316.0	315.0
7.30	-	398.0	396.0
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	WMA350H-48
Item	Efficiency (by Input Voltage)
Object	+48V7.3A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
85	89.2	-
100	89.6	-
115	89.8	88.6
132	89.8	88.6
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-


COSEL

Model	WMA350H-48																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	_____		2.Values																																																			
<p>—△— Input Volt. 100V - - - □ - - Input Volt. 115V - · ○ - - Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [115V] (%)</th> <th>Efficiency [132V] (%)</th> </tr> </thead> <tbody> <tr><td>1.46</td><td>89.0</td><td>88.2</td><td>87.0</td></tr> <tr><td>2.92</td><td>90.0</td><td>89.8</td><td>89.4</td></tr> <tr><td>4.38</td><td>89.3</td><td>89.3</td><td>89.5</td></tr> <tr><td>5.84</td><td>88.3</td><td>88.9</td><td>89.1</td></tr> <tr><td>7.30</td><td>-</td><td>88.1</td><td>88.6</td></tr> </tbody> </table>				Load Current [A]	Efficiency [100V] (%)	Efficiency [115V] (%)	Efficiency [132V] (%)	1.46	89.0	88.2	87.0	2.92	90.0	89.8	89.4	4.38	89.3	89.3	89.5	5.84	88.3	88.9	89.1	7.30	-	88.1	88.6																											
Load Current [A]	Efficiency [100V] (%)	Efficiency [115V] (%)	Efficiency [132V] (%)																																																			
1.46	89.0	88.2	87.0																																																			
2.92	90.0	89.8	89.4																																																			
4.38	89.3	89.3	89.5																																																			
5.84	88.3	88.9	89.1																																																			
7.30	-	88.1	88.6																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.46</td><td>89.0</td><td>88.2</td><td>87.0</td></tr> <tr><td>2.92</td><td>90.0</td><td>89.8</td><td>89.4</td></tr> <tr><td>4.38</td><td>89.3</td><td>89.3</td><td>89.5</td></tr> <tr><td>5.84</td><td>88.3</td><td>88.9</td><td>89.1</td></tr> <tr><td>7.30</td><td>-</td><td>88.1</td><td>88.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 132[V]	0.00	-	-	-	1.46	89.0	88.2	87.0	2.92	90.0	89.8	89.4	4.38	89.3	89.3	89.5	5.84	88.3	88.9	89.1	7.30	-	88.1	88.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 132[V]																																																			
0.00	-	-	-																																																			
1.46	89.0	88.2	87.0																																																			
2.92	90.0	89.8	89.4																																																			
4.38	89.3	89.3	89.5																																																			
5.84	88.3	88.9	89.1																																																			
7.30	-	88.1	88.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	WMA350H-48
Item	Power Factor (by Input Voltage)
Object	+48V7.3A

1. Graph


 Temperature 25°C
 Testing Circuitry Figure A

2. Values


Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
85	0.608	-
100	0.580	-
115	0.558	0.588
132	0.539	0.567
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	WMA350H-48																																																	
Item	Power Factor (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																															
Object	_____																																																	
1.Graph	<p>—△— Input Volt. 100V - - □ - - Input Volt. 115V - · ○ - - Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Power Factor (100V)</th> <th>Power Factor (115V)</th> <th>Power Factor (132V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.141</td><td>0.115</td><td>0.104</td></tr> <tr><td>1.46</td><td>0.491</td><td>0.479</td><td>0.474</td></tr> <tr><td>2.92</td><td>0.555</td><td>0.541</td><td>0.530</td></tr> <tr><td>4.38</td><td>0.590</td><td>0.574</td><td>0.558</td></tr> <tr><td>5.84</td><td>0.609</td><td>0.593</td><td>0.575</td></tr> <tr><td>7.30</td><td>-</td><td>0.604</td><td>0.585</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor (100V)	Power Factor (115V)	Power Factor (132V)	0.00	0.141	0.115	0.104	1.46	0.491	0.479	0.474	2.92	0.555	0.541	0.530	4.38	0.590	0.574	0.558	5.84	0.609	0.593	0.575	7.30	-	0.604	0.585	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	2. Values
Load Current [A]	Power Factor (100V)	Power Factor (115V)	Power Factor (132V)																																															
0.00	0.141	0.115	0.104																																															
1.46	0.491	0.479	0.474																																															
2.92	0.555	0.541	0.530																																															
4.38	0.590	0.574	0.558																																															
5.84	0.609	0.593	0.575																																															
7.30	-	0.604	0.585																																															
--	-	-	-																																															
--	-	-	-																																															
--	-	-	-																																															
--	-	-	-																																															
--	-	-	-																																															


COSEL

Model	WMA350H-48	Temperature Testing Circuitry	25°C
Item	Inrush Current		Figure A
Object	_____		



Input Voltage 115 V
 Frequency 60 Hz
 Load 100 %

Primary inrush current 33.5 A
 Secondary inrush current 2.3 A





Model	WMA350H-48	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards		Input Volt.			Note
		100 [V]	115 [V]	132 [V]	
IEC60601-1	Both phases	0.15	0.18	0.20	Operation
	One of phases	0.24	0.27	0.31	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	WMA350H-48
Item	Line Regulation
Object	+48V7.3A

1. Graph

- - - □ - - - Load 50%
 — △ — Load 100%


 Temperature 25°C
 Testing Circuitry Figure A

2. Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	48.048	-
100	48.047	-
115	48.048	48.046
132	48.047	48.047
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	WMA350H-48	Temperature 25°C Testing Circuitry Figure A																																																	
Item	Load Regulation																																																		
Object	+48V7.3A																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — △ — Input Volt. 100V - - □ - - Input Volt. 115V - · ○ - - Input Volt. 132V 																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>48.059</td> <td>48.058</td> <td>48.059</td> </tr> <tr> <td>1.46</td> <td>48.057</td> <td>48.057</td> <td>48.058</td> </tr> <tr> <td>2.92</td> <td>48.057</td> <td>48.057</td> <td>48.057</td> </tr> <tr> <td>4.38</td> <td>48.056</td> <td>48.056</td> <td>48.056</td> </tr> <tr> <td>5.84</td> <td>48.055</td> <td>48.056</td> <td>48.056</td> </tr> <tr> <td>7.30</td> <td>-</td> <td>48.053</td> <td>48.054</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 132[V]	0.00	48.059	48.058	48.059	1.46	48.057	48.057	48.058	2.92	48.057	48.057	48.057	4.38	48.056	48.056	48.056	5.84	48.055	48.056	48.056	7.30	-	48.053	48.054	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 132[V]																																																
0.00	48.059	48.058	48.059																																																
1.46	48.057	48.057	48.058																																																
2.92	48.057	48.057	48.057																																																
4.38	48.056	48.056	48.056																																																
5.84	48.055	48.056	48.056																																																
7.30	-	48.053	48.054																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																



COSEL

Model	WMA350H-48
Item	Dynamic Load Response
Object	+48V7.3A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 115 V
Cycle 1000 msMin.Load (0A)↔
Load 100% (7.3A)



500 mV/div

200 us/div

Min.Load (0A)↔
Load 50% (3.65A)



500 mV/div

200 us/div

Load 50% (3.65A)↔
Load 100% (7.3A)

500 mV/div


200 us/div



COSEL

Model	WMA350H-48
Item	Ripple Noise(by Load Current)
Object	+48V7.3A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

 Temperature 25°C
 Testing Circuitry Figure C

2. Values

Load Current [A]	Ripple Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 132 [V]
0.00	30	50
1.46	50	50
2.92	55	60
4.38	65	70
5.84	75	80
7.30	-	95
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-



 T1: Due to AC Input Line
 T2: Due to Switching


Fig. Complex Ripple Wave Form

COSEL

Model	WMA350H-48
Item	Ripple Noise (by Ambient Temp.)
Object	+48V7.3A

1. Graph



Measured by 20 MHz Oscilloscope.

Testing Circuitry Figure C

2. Values

Ambient Temperature [°C]	Ripple Noise [mV]	
	Load 50%	Load 100%
-20	245	360
-10	155	240
0	110	160
25	65	90
50	50	70
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL


Model WMA350H-48

Item Ambient Temperature Drift

Object +48V7.3A

1.Graph

—△— Input Volt. 100V
 - - - □ - - Input Volt. 115V
 - · ○ - - Input Volt. 132V



Load 100%

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 132[V]
-20	-	47.895	47.895
-10	-	47.941	47.941
0	-	47.977	47.977
25	-	48.040	48.040
50	-	48.077	48.078
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	WMA350H-48
Item	Output Voltage Accuracy
Object	+48V7.3A

Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 100 - 132V

Load Current : 0 - 7.3A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	115	0	48.082	±71	±0.1
Minimum Voltage	-10	115	7.3	47.941		

COSEL

Model	WMA350H-48
Item	Time Lapse Drift
Object	+48V7.3A

1.Graph


 Temperature 25°C
 Testing Circuitry Figure A

2.Values


Time since start [H]	Output Voltage [V]
0.0	48.391
0.5	48.464
1.0	48.466
2.0	48.467
3.0	48.468
4.0	48.468
5.0	48.468
6.0	48.468
7.0	48.470
8.0	48.470

COSEL

Model	WMA350H-48
Item	Rise and Fall Time
Object	+48V7.3A

Temperature
Testing Circuitry
25°C
Figure A


1. Graph



2. Values

[ms]


Load	Time	Td	Tr	Ts	Th	Tf
50 %		626.0	4.0	630.0	45.1	47.1
100 %		670.0	4.0	674.0	17.9	31.7



COSEL

Model	WMA350H-48
Item	Hold-Up Time
Object	+48V7.3A

1. Graph



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	12	-
100	26	-
115	42	17
132	63	27
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	WMA350H-48
Item	Instantaneous Interruption Compensation
Object	+48V7.3A


 Temperature 25°C
 Testing Circuitry Figure A


2. Values

Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 132[V]
0.00	-	-	-
1.46	78	119	173
2.92	36	56	84
4.38	21	35	54
5.84	13	24	38
7.30	-	17	28
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	WMA350H-48
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+48V7.3A

1. Graph




Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	67	81
-10	67	81
0	67	81
25	66	80
50	66	80
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-



Model	WMA350H-48
Item	Overcurrent Protection
Object	+48V7.3A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 132[V]
48	8.68	8.87	9.01
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	WMA350H-48
Item	Oversupply Protection
Object	+48V7.3A

1. Graph



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 85[V]	Input Volt. 132[V]
-20	59.64	59.70
-10	59.04	58.98
0	59.34	59.57
25	59.63	59.74
50	60.40	60.39
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL




Figure A




Figure B (IEC60601-1)




Figure C