

TEST DATA OF WMA75F-24

Regulated DC Power Supply
November 9, 2020

Approved by : Takeshi Kajii
Design Manager

Prepared by : Takeshi Nakano
Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple-Noise (by Load Current)	12
13.Ripple-Noise (by Ambient Temperature)	13
14.Ambient Temperature Drift	14
15.Output Voltage Accuracy	15
16.Time Lapse Drift	16
17.Rise and Fall Time	17
18.Hold-Up Time	18
19.Instantaneous Interruption Compensation	19
20.Minimum Input Voltage for Regulated Output Voltage	20
21.Overcurrent Protection	21
22.Overvoltage Protection	22
23.Figure of Testing Circuitry	23

(Final Page 23)

COSEL

Model	WMA75F-24
Item	Input Current (by Load Current)
Object	_____



 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.0	0.026	0.028	0.049
0.6	0.326	0.310	0.200
1.2	0.587	0.543	0.334
1.8	0.845	0.772	0.469
2.4	1.109	0.998	0.605
3.0	-	1.227	0.742
3.2	-	1.307	0.792
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	WMA75F-24
Item	Input Power (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.0	0.37	0.40	0.74
0.6	16.66	16.57	18.20
1.2	32.96	32.67	33.63
1.8	49.56	49.01	49.90
2.4	66.47	65.66	65.58
3.0	-	82.55	81.63
3.2	-	88.15	86.85
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	WMA75F-24	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	—																																		
1.Graph			2.Values																																
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 50% (Dashed line with squares) Load 100% (Solid line with triangles) 			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>86.6</td> <td>-</td> </tr> <tr> <td>100</td> <td>87.6</td> <td>-</td> </tr> <tr> <td>115</td> <td>88.0</td> <td>87.5</td> </tr> <tr> <td>200</td> <td>88.1</td> <td>89.1</td> </tr> <tr> <td>230</td> <td>87.5</td> <td>88.9</td> </tr> <tr> <td>240</td> <td>87.2</td> <td>88.8</td> </tr> <tr> <td>264</td> <td>86.6</td> <td>88.5</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	86.6	-	100	87.6	-	115	88.0	87.5	200	88.1	89.1	230	87.5	88.9	240	87.2	88.8	264	86.6	88.5	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
85	86.6	-																																	
100	87.6	-																																	
115	88.0	87.5																																	
200	88.1	89.1																																	
230	87.5	88.9																																	
240	87.2	88.8																																	
264	86.6	88.5																																	
--	-	-																																	
--	-	-																																	

COSEL


Model	WMA75F-24																																																					
Item	Efficiency (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph																																																						
<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 115V Input Volt. 230V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>100[V]</th> <th>115[V]</th> <th>230[V]</th> </tr> </thead> <tbody> <tr><td>0.6</td><td>86.7</td><td>87.1</td><td>81.9</td></tr> <tr><td>1.2</td><td>87.3</td><td>88.1</td><td>86.3</td></tr> <tr><td>1.8</td><td>87.2</td><td>88.1</td><td>87.5</td></tr> <tr><td>2.4</td><td>86.6</td><td>87.7</td><td>88.3</td></tr> <tr><td>3.0</td><td>-</td><td>87.2</td><td>88.7</td></tr> </tbody> </table>				Load Current [A]	100[V]	115[V]	230[V]	0.6	86.7	87.1	81.9	1.2	87.3	88.1	86.3	1.8	87.2	88.1	87.5	2.4	86.6	87.7	88.3	3.0	-	87.2	88.7																											
Load Current [A]	100[V]	115[V]	230[V]																																																			
0.6	86.7	87.1	81.9																																																			
1.2	87.3	88.1	86.3																																																			
1.8	87.2	88.1	87.5																																																			
2.4	86.6	87.7	88.3																																																			
3.0	-	87.2	88.7																																																			
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.6</td><td>86.7</td><td>87.1</td><td>81.9</td></tr> <tr><td>1.2</td><td>87.3</td><td>88.1</td><td>86.3</td></tr> <tr><td>1.8</td><td>87.2</td><td>88.1</td><td>87.5</td></tr> <tr><td>2.4</td><td>86.6</td><td>87.7</td><td>88.3</td></tr> <tr><td>3.0</td><td>-</td><td>87.2</td><td>88.7</td></tr> <tr><td>3.2</td><td>-</td><td>87.1</td><td>88.8</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.0	-	-	-	0.6	86.7	87.1	81.9	1.2	87.3	88.1	86.3	1.8	87.2	88.1	87.5	2.4	86.6	87.7	88.3	3.0	-	87.2	88.7	3.2	-	87.1	88.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
0.6	86.7	87.1	81.9																																																			
1.2	87.3	88.1	86.3																																																			
1.8	87.2	88.1	87.5																																																			
2.4	86.6	87.7	88.3																																																			
3.0	-	87.2	88.7																																																			
3.2	-	87.1	88.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	WMA75F-24																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	_____	_____																																
1.Graph																																		
<p>Graph showing Power Factor vs Input Voltage for WMA75F-24 at 25°C. The x-axis is Input Voltage [V] from 50 to 300. The y-axis is Power Factor from 0.2 to 0.8. Two curves are shown: Load 50% (dashed line with squares) and Load 100% (solid line with triangles). Both curves show a decreasing trend as input voltage increases.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% Power Factor</th> <th>Load 100% Power Factor</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>0.594</td> <td>-</td> </tr> <tr> <td>100</td> <td>0.563</td> <td>-</td> </tr> <tr> <td>115</td> <td>0.538</td> <td>0.575</td> </tr> <tr> <td>200</td> <td>0.462</td> <td>0.486</td> </tr> <tr> <td>230</td> <td>0.444</td> <td>0.465</td> </tr> <tr> <td>240</td> <td>0.439</td> <td>0.460</td> </tr> <tr> <td>264</td> <td>0.427</td> <td>0.447</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Load 50% Power Factor	Load 100% Power Factor	85	0.594	-	100	0.563	-	115	0.538	0.575	200	0.462	0.486	230	0.444	0.465	240	0.439	0.460	264	0.427	0.447	--	-	-	--	-	-		
Input Voltage [V]	Load 50% Power Factor	Load 100% Power Factor																																
85	0.594	-																																
100	0.563	-																																
115	0.538	0.575																																
200	0.462	0.486																																
230	0.444	0.465																																
240	0.439	0.460																																
264	0.427	0.447																																
--	-	-																																
--	-	-																																
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>0.594</td> <td>-</td> </tr> <tr> <td>100</td> <td>0.563</td> <td>-</td> </tr> <tr> <td>115</td> <td>0.538</td> <td>0.575</td> </tr> <tr> <td>200</td> <td>0.462</td> <td>0.486</td> </tr> <tr> <td>230</td> <td>0.444</td> <td>0.465</td> </tr> <tr> <td>240</td> <td>0.439</td> <td>0.460</td> </tr> <tr> <td>264</td> <td>0.427</td> <td>0.447</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.594	-	100	0.563	-	115	0.538	0.575	200	0.462	0.486	230	0.444	0.465	240	0.439	0.460	264	0.427	0.447	--	-	-	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
85	0.594	-																																
100	0.563	-																																
115	0.538	0.575																																
200	0.462	0.486																																
230	0.444	0.465																																
240	0.439	0.460																																
264	0.427	0.447																																
--	-	-																																
--	-	-																																

COSEL

Model	WMA75F-24
Item	Power Factor (by Load Current)
Object	_____






Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Power Factor		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.0	0.145	0.122	0.050
0.6	0.510	0.464	0.367
1.2	0.559	0.522	0.417
1.8	0.584	0.551	0.440
2.4	0.598	0.570	0.450
3.0	-	0.583	0.457
3.2	-	0.585	0.455
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	WMA75F-24	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	WMA75F-24	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

[mA]

Standards	Measuring Method	Input Volt.			Note
		100 [V]	115 [V]	230 [V]	
IEC60601-1	Both phases	0.14	0.16	0.35	Operation
	One of phases	0.22	0.25	0.57	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	WMA75F-24
Item	Line Regulation
Object	+24V3.2A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	23.998	-
100	23.998	-
115	23.997	23.997
200	23.994	23.993
230	23.990	23.988
240	23.989	23.986
264	23.985	23.982
--	-	-
--	-	-

COSEL

Model	WMA75F-24
Item	Load Regulation
Object	+24V3.2A

 Temperature 25°C
 Testing Circuitry Figure A





2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.0	24.001	24.005	24.003
0.6	24.002	24.002	23.997
1.2	24.001	24.002	23.995
1.8	24.000	24.001	23.991
2.4	24.000	24.000	23.991
3.0	-	23.997	23.989
3.2	-	23.997	23.990
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	WMA75F-24	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+24V3.2A		

Input Volt. 230 V
 Cycle 1000 ms




COSEL

Model	WMA75F-24
Item	Ripple-Noise (by Load Current)
Object	+24V3.2A

Temperature 25°C
Testing Circuitry Figure C

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0.00	73	118
0.64	20	19
1.28	20	19
1.92	22	20
2.56	27	21
3.20	36	23
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.





Fig. Complex Ripple Wave Form

COSEL

Model	WMA75F-24
Item	Ripple-Noise (by Ambient Temp.)
Object	+24V3.2A

1. Graph



Measured by 20 MHz Oscilloscope.


Testing Circuitry Figure C

2. Values

Ambient Temperature [°C]	Ripple-Noise [mV]	
	Input Volt. 115[V]	Input Volt. 230[V]
-20	81	57
-10	52	36
25	36	23
50	37	19
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	WMA75F-24
Item	Ambient Temperature Drift
Object	+24V3.2A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
-20	-	23.915	23.909
-10	-	23.942	23.934
0	-	23.961	23.951
25	-	23.998	23.991
50	-	24.015	24.008
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	WMA75F-24	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+24V3.2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 100 - 230V

Load Current : 0 - 3.2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	230	0	24.027	±57	±0.2
Minimum Voltage	-20	100	3.2	23.914		

COSEL

Model	WMA75F-24
Item	Time Lapse Drift
Object	+24V3.2A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Time since start [H]	Output Voltage [V]
0.0	24.011
0.2	24.025
0.5	24.027
1.0	24.025
2.0	24.028
3.0	24.027
4.0	24.024
8.0	24.027

COSEL


Model	WMA75F-24	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+24V3.2A		

1. Graph



2. Values

Input Volt	Time	Td	Tr	Ts	Th	Tf	[ms]
115 V		98.5	9.8	108.3	15.2	22.7	
230 V		89.0	9.5	98.5	78.7	22.8	




COSEL

Model	WMA75F-24
Item	Hold-Up Time
Object	+24V3.2A

Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	16	-
100	25	-
115	35	14
200	120	57
230	162	78
240	178	86
264	218	106
--	-	-
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

COSEL

Model	WMA75F-24
Item	Instantaneous Interruption Compensation
Object	+24V3.2A



Temperature 25°C
Testing Circuitry Figure A

2.Values


Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.0	-	-	-
0.6	76	103	575
1.2	37	50	297
1.8	23	32	197
2.4	16	22	146
3.0	-	17	116
3.2	-	15	107
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	WMA75F-24
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+24V3.2A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	39	69
-10	39	69
0	39	68
25	39	69
50	39	70
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-



COSEL


Model WMA75F-24

Item Overvoltage Protection

Object +24V3.2A

1. Graph

—△— Input Volt. 115V
 - - □ - - Input Volt. 230V



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 115[V]	Input Volt. 230[V]
-20	30.07	30.07
-10	30.30	30.37
0	30.51	30.51
25	31.10	31.10
50	31.76	31.76
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL




Figure A

Data Acquisition/Control Unit





Figure B (IEC60601-1)



(Ceramic capacitor)
C1= 0.1 µF

(Electrolytic capacitor)
C2= 47 µF

Figure C