

# TEST DATA OF WXA150H-48

(115V INPUT)

Regulated DC Power Supply  
March 20, 2019

Approved by : Takashi Kajii  
Takashi Kajii Design Manager

Prepared by : Yoji Kawagishi  
Yoji Kawagishi Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Input Power (by Load Current) . . . . .	2
3.Efficiency (by Input Voltage) . . . . .	3
4.Efficiency (by Load Current) . . . . .	4
5.Power Factor (by Input Voltage) . . . . .	5
6.Power Factor (by Load Current) . . . . .	6
7.Inrush Current . . . . .	7
8.Leakage Current . . . . .	8
9.Line Regulation . . . . .	9
10.Load Regulation . . . . .	10
11.Dynamic Load Response . . . . .	11
12.Ripple-Noise (by Load Current) . . . . .	12
13.Ripple-Noise (by Ambient Temperature) . . . . .	13
14.Ambient Temperature Drift . . . . .	14
15.Output Voltage Accuracy . . . . .	15
16.Time Lapse Drift . . . . .	16
17.Rise and Fall Time . . . . .	17
18.Hold-Up Time . . . . .	18
19.Instantaneous Interruption Compensation . . . . .	19
20.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
21.Overcurrent Protection . . . . .	21
22.Overvoltage Protection . . . . .	22
23.Figure of Testing Circuitry . . . . .	23


(Final Page 23)

**COSEL**

Model	WXA150H-48
Item	Input Current (by Load Current)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]
0.0	0.045	0.054	0.061
0.6	0.690	0.589	0.532
1.2	1.263	1.059	0.956
1.8	1.841	1.528	1.372
2.4	2.427	2.000	1.782
3.0	3.024	2.466	2.203
3.3	3.329	2.705	2.418
3.6	-	2.965	2.648
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	WXA150H-48
Item	Input Power (by Load Current)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]
0.0	0.6	0.7	0.7
0.6	33.8	33.5	33.8
1.2	66.4	66.3	66.9
1.8	98.9	98.5	98.9
2.4	131.5	130.7	130.6
3.0	165.1	162.9	162.6
3.3	181.9	179.2	178.6
3.6	-	197.8	196.4
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	WXA150H-48
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	88.3	86.0
80	88.7	87.1
85	88.9	87.9
90	89.0	88.4
100	88.9	89.1
115	88.4	89.9
120	88.2	89.9
132	88.4	90.1
140	88.1	90.1

Note: Slanted line shows the range of the rated input voltage.

**COSEL**


Model	WXA150H-48	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>Graph showing Efficiency [%] vs Load Current [A]. The Y-axis ranges from 44 to 100 in increments of 8. The X-axis ranges from 0.0 to 4.0 in increments of 1.0. Three data series are plotted: Input Volt. 90V (solid line with triangle markers), Input Volt. 115V (dashed line with square markers), and Input Volt. 132V (dash-dot line with circle markers). All curves show efficiency increasing slightly with load current. A slanted line is drawn across the graph, starting from approximately (0.7, 85) and ending at (3.3, 90), indicating the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.6</td><td>86.9</td><td>87.3</td><td>86.5</td></tr> <tr> <td>1.2</td><td>88.1</td><td>88.2</td><td>87.3</td></tr> <tr> <td>1.8</td><td>88.7</td><td>89.0</td><td>88.7</td></tr> <tr> <td>2.4</td><td>88.9</td><td>89.5</td><td>89.5</td></tr> <tr> <td>3.0</td><td>88.5</td><td>89.7</td><td>89.8</td></tr> <tr> <td>3.3</td><td>88.4</td><td>89.7</td><td>89.9</td></tr> <tr> <td>3.6</td><td>-</td><td>89.3</td><td>89.9</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]	0.0	-	-	-	0.6	86.9	87.3	86.5	1.2	88.1	88.2	87.3	1.8	88.7	89.0	88.7	2.4	88.9	89.5	89.5	3.0	88.5	89.7	89.8	3.3	88.4	89.7	89.9	3.6	-	89.3	89.9	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]																																																			
0.0	-	-	-																																																			
0.6	86.9	87.3	86.5																																																			
1.2	88.1	88.2	87.3																																																			
1.8	88.7	89.0	88.7																																																			
2.4	88.9	89.5	89.5																																																			
3.0	88.5	89.7	89.8																																																			
3.3	88.4	89.7	89.9																																																			
3.6	-	89.3	89.9																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	WXA150H-48
Item	Power Factor (by Input Voltage)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
75	0.611	0.617
80	0.599	0.615
85	0.591	0.611
90	0.583	0.604
100	0.569	0.591
115	0.549	0.571
120	0.545	0.566
132	0.533	0.552
140	0.526	0.544


Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	WXA150H-48	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 90V</li> <li>Input Volt. 115V</li> <li>Input Volt. 132V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.150</td><td>0.109</td><td>0.093</td></tr> <tr> <td>0.6</td><td>0.544</td><td>0.494</td><td>0.480</td></tr> <tr> <td>1.2</td><td>0.584</td><td>0.545</td><td>0.530</td></tr> <tr> <td>1.8</td><td>0.598</td><td>0.561</td><td>0.546</td></tr> <tr> <td>2.4</td><td>0.602</td><td>0.569</td><td>0.555</td></tr> <tr> <td>3.0</td><td>0.607</td><td>0.575</td><td>0.559</td></tr> <tr> <td>3.3</td><td>0.608</td><td>0.576</td><td>0.560</td></tr> <tr> <td>3.6</td><td>-</td><td>0.581</td><td>0.562</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]	0.0	0.150	0.109	0.093	0.6	0.544	0.494	0.480	1.2	0.584	0.545	0.530	1.8	0.598	0.561	0.546	2.4	0.602	0.569	0.555	3.0	0.607	0.575	0.559	3.3	0.608	0.576	0.560	3.6	-	0.581	0.562	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]																																																			
0.0	0.150	0.109	0.093																																																			
0.6	0.544	0.494	0.480																																																			
1.2	0.584	0.545	0.530																																																			
1.8	0.598	0.561	0.546																																																			
2.4	0.602	0.569	0.555																																																			
3.0	0.607	0.575	0.559																																																			
3.3	0.608	0.576	0.560																																																			
3.6	-	0.581	0.562																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						


**COSEL**

Model	WXA150H-48	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		



Input Voltage      115 V  
 Frequency          50 Hz  
 Load                100 %

Primary inrush current    31.1 A  
 Secondary inrush current    0.0A





Model	WXA150H-48	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

### 1. Results

Standards		Input Volt.			Note
		90 [V]	115 [V]	132 [V]	
IEC60950-1	Both phases	0.24	0.30	0.35	Operation
	One of phases	0.48	0.60	0.70	Stand by

The value for "One of phases" is the reference value only.

### 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	WXA150H-48
Item	Line Regulation
Object	+48V3.3A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	48.684	48.685
80	48.684	48.685
85	48.684	48.685
90	48.683	48.686
100	48.679	48.684
115	48.664	48.675
120	48.658	48.672
132	48.652	48.661
140	48.642	48.652

Note: Slanted line shows the range of the rated input voltage.




**COSEL**

Model	WXA150H-48	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+48V3.3A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> <li>— ▲ — Input Volt. 90V</li> <li>- - □ - - Input Volt. 115V</li> <li>- - ○ - - Input Volt. 132V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>48.701</td> <td>48.696</td> <td>48.698</td> </tr> <tr> <td>0.6</td> <td>48.693</td> <td>48.684</td> <td>48.675</td> </tr> <tr> <td>1.2</td> <td>48.693</td> <td>48.673</td> <td>48.660</td> </tr> <tr> <td>1.8</td> <td>48.693</td> <td>48.677</td> <td>48.659</td> </tr> <tr> <td>2.4</td> <td>48.692</td> <td>48.676</td> <td>48.662</td> </tr> <tr> <td>3.0</td> <td>48.690</td> <td>48.677</td> <td>48.661</td> </tr> <tr> <td>3.3</td> <td>48.689</td> <td>48.678</td> <td>48.662</td> </tr> <tr> <td>3.6</td> <td>-</td> <td>48.677</td> <td>48.663</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]	0.0	48.701	48.696	48.698	0.6	48.693	48.684	48.675	1.2	48.693	48.673	48.660	1.8	48.693	48.677	48.659	2.4	48.692	48.676	48.662	3.0	48.690	48.677	48.661	3.3	48.689	48.678	48.662	3.6	-	48.677	48.663	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]																																																			
0.0	48.701	48.696	48.698																																																			
0.6	48.693	48.684	48.675																																																			
1.2	48.693	48.673	48.660																																																			
1.8	48.693	48.677	48.659																																																			
2.4	48.692	48.676	48.662																																																			
3.0	48.690	48.677	48.661																																																			
3.3	48.689	48.678	48.662																																																			
3.6	-	48.677	48.663																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	WXA150H-48	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+48V3.3A		

Input Volt. 115 V  
 Cycle 1000 ms




# COSEL

Model	WXA150H-48
Item	Ripple-Noise (by Load Current)
Object	+48V3.3A

Temperature 25°C  
Testing Circuitry Figure C

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 132 [V]
0.0	145	150
0.3	165	165
1.0	20	25
1.5	25	20
2.0	30	25
2.5	40	30
3.3	50	35
--	-	-
--	-	-
--	-	-
--	-	-





Fig. Complex Ripple Wave Form

**COSEL**

Model	WXA150H-48	Testing Circuitry	Figure C																																						
Item	Ripple Noise (by Ambient Temp.)																																								
Object	+48V3.3A																																								
1.Graph			2.Values																																						
<p>Ambient Temperature [°C]</p> <p>Input Volt. 115V</p>			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-30</td><td>65</td><td>135</td> </tr> <tr> <td>-20</td><td>60</td><td>100</td> </tr> <tr> <td>-10</td><td>35</td><td>70</td> </tr> <tr> <td>0</td><td>35</td><td>55</td> </tr> <tr> <td>10</td><td>30</td><td>60</td> </tr> <tr> <td>25</td><td>25</td><td>45</td> </tr> <tr> <td>30</td><td>25</td><td>40</td> </tr> <tr> <td>40</td><td>30</td><td>45</td> </tr> <tr> <td>50</td><td>30</td><td>45</td> </tr> <tr> <td>60</td><td>25</td><td>50</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-30	65	135	-20	60	100	-10	35	70	0	35	55	10	30	60	25	25	45	30	25	40	40	30	45	50	30	45	60	25	50	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																								
	Load 50%	Load 100%																																							
-30	65	135																																							
-20	60	100																																							
-10	35	70																																							
0	35	55																																							
10	30	60																																							
25	25	45																																							
30	25	40																																							
40	30	45																																							
50	30	45																																							
60	25	50																																							
--	-	-																																							

**COSEL**

Model	WXA150H-48
Item	Ambient Temperature Drift
Object	+48V3.3A



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]
-30	48.331	48.324	48.313
-20	48.417	48.409	48.397
-10	48.490	48.481	48.470
0	48.536	48.527	48.513
10	48.597	48.588	48.575
25	48.674	48.664	48.650
30	48.697	48.686	48.671
40	48.734	48.723	48.707
50	48.767	48.755	48.739
60	48.808	48.797	48.780
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	WXA150H-48	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+48V3.3A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 90 - 132V

Load Current : 0 - 3.3A


\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	132	0	48.824	$\pm 214$	$\pm 0.4$
Minimum Voltage	-20	132	3.3	48.397		


**COSEL**

Model	WXA150H-48	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+48V3.3A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 115V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>48.652</td></tr> <tr><td>0.5</td><td>48.681</td></tr> <tr><td>1.0</td><td>48.681</td></tr> <tr><td>2.0</td><td>48.681</td></tr> <tr><td>3.0</td><td>48.681</td></tr> <tr><td>4.0</td><td>48.681</td></tr> <tr><td>5.0</td><td>48.681</td></tr> <tr><td>6.0</td><td>48.681</td></tr> <tr><td>7.0</td><td>48.682</td></tr> <tr><td>8.0</td><td>48.681</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	48.652	0.5	48.681	1.0	48.681	2.0	48.681	3.0	48.681	4.0	48.681	5.0	48.681	6.0	48.681	7.0	48.682	8.0	48.681
Time since start [H]	Output Voltage [V]																								
0.0	48.652																								
0.5	48.681																								
1.0	48.681																								
2.0	48.681																								
3.0	48.681																								
4.0	48.681																								
5.0	48.681																								
6.0	48.681																								
7.0	48.682																								
8.0	48.681																								

**COSEL**


Model	WXA150H-48	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+48V3.3A		

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		102.5	68.8	171.3	84.8	89.0	
100 %		102.8	69.3	172.1	38.5	45.5	




**COSEL**

Model	WXA150H-48
Item	Hold-Up Time
Object	+48V3.3A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph



## 2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	27	6
80	33	9
85	38	12
90	44	15
100	57	21
115	80	33
120	88	37
132	109	48
140	125	56


This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	WXA150H-48
Item	Instantaneous Interruption Compensation
Object	+48V3.3A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



Note: Slanted line shows the range of the rated load current.

## 2.Values


Load Current [A]	Time [ms]		
	Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]
0.0	-	-	-
0.6	141	240	323
1.2	67	117	158
1.8	42	75	103
2.4	28	54	75
3.0	20	40	57
3.3	14	34	49
3.6	-	28	42
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	WXA150H-48
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+48V3.3A

Testing Circuitry Figure A

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	41	68
-20	41	68
-10	41	68
0	41	67
10	41	66
25	40	66
30	40	66
40	40	67
50	40	67
60	40	66
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	WXA150H-48	Temperature	25°C																																																																											
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																																											
Object	+48V3.3A																																																																													
1.Graph		<p>The graph plots Output Voltage [V] on the y-axis (0 to 60) against Load Current [A] on the x-axis (0 to 6). Three horizontal lines represent different input voltages: 90V (blue), 115V (red), and 132V (green). A slanted line indicates the range of the rated load current.</p>																																																																												
<p>Note: Slanted line shows the range of the rated load current.</p>		2.Values																																																																												
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 90[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>48</td><td>4.02</td><td>4.21</td><td>4.59</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]	48	4.02	4.21	4.59	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																																													
	Input Volt. 90[V]	Input Volt. 115[V]	Input Volt. 132[V]																																																																											
48	4.02	4.21	4.59																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											
--	-	-	-																																																																											


**COSEL**

Model WXA150H-48

Item Overvoltage Protection

Object +48V3.3A

## 1.Graph




Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 90[V]	Input Volt. 132[V]
-30	56.81	56.96
-20	57.33	57.33
-10	58.21	58.21
0	58.72	58.79
10	59.30	59.30
25	60.11	60.11
30	60.40	60.40
40	60.99	60.99
50	61.58	61.58
60	62.17	62.17
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

**coSEL**



Data Acquisition/Control Unit

Figure A





Figure B ( IEC60950-1 )



C1= 0.1 μF  
(Ceramic capacitor)

C2= 47 μF  
(Electrolytic capacitor)

Figure C