



TEST DATA OF ZUS61205

(12.0V INPUT)

Regulated DC Power Supply

Date : Sep. 23. 1996

Approved by : T. Sugimori
Design Manager

Prepared by : H. Ise
Design Engineer

コーセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	5
リップルノイズ	
6. Overcurrent Protection	6
過電流保護	
7. Dynamic Load Responce	7
動的負荷変動	
8. Rise and Fall Time	8
立上り、立下がり時間	
9. Ambient Temperature Drift	9
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage . . .	10
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	11
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	12
経時ドリフト	
13. Output Voltage Accuracy	13
定電圧精度	
14. Condensation	14
結露特性	
15. Figure of Testing Circuitry	15
測定回路図	

(Final Page 15)

COSEL

Model		ZUS61205	Temperature		25℃																																							
Item		Line Regulation 静的入力変動	Testing Circuitry		Figure A																																							
Object		+5V1.2A																																										
1. Graph			2. Values																																									
<div><div>-----□----- Load 50%</div><div>-----△----- Load 100%</div><div><div>[V]</div><div><div>Output Voltage</div><div>Input Voltage [V]</div></div></div></div>			<table><tr><th>Input Voltage [V]</th><th>Load 50% Output Volt. [V]</th><th>Load 100% Output Volt. [V]</th></tr><tr><td>8.0</td><td>5.062</td><td>5.059</td></tr><tr><td>9.0</td><td>5.062</td><td>5.059</td></tr><tr><td>10.0</td><td>5.062</td><td>5.059</td></tr><tr><td>12.0</td><td>5.062</td><td>5.059</td></tr><tr><td>15.0</td><td>5.062</td><td>5.059</td></tr><tr><td>18.0</td><td>5.062</td><td>5.059</td></tr><tr><td>20.0</td><td>5.061</td><td>5.059</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>			Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	8.0	5.062	5.059	9.0	5.062	5.059	10.0	5.062	5.059	12.0	5.062	5.059	15.0	5.062	5.059	18.0	5.062	5.059	20.0	5.061	5.059	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																																										
8.0	5.062	5.059																																										
9.0	5.062	5.059																																										
10.0	5.062	5.059																																										
12.0	5.062	5.059																																										
15.0	5.062	5.059																																										
18.0	5.062	5.059																																										
20.0	5.061	5.059																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										
<div>Note: Slanted line shows the range of the rated input voltage.</div> <div>(注)斜線は定格入力電圧範囲を示す。</div>																																												

COSEL

Model

ZUS61205

Item

Efficiency 効率

Temperature


25°C

Testing Circuitry

Figure A

Object

1. Graph



Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。


2. Values

Input Voltage [V]	Load 50%	Load 100%
	Efficiency [%]	Efficiency [%]
8.0	75.7	73.5
9.0	75.8	74.9
10.0	76.2	76.1
12.0	75.8	77.1
15.0	73.9	77.2
18.0	72.0	76.6
20.0	70.3	76.0
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—

COSEL

COSEL																																																		
Model	ZUS61205	Temperature 25℃ Testing Circuitry Figure A																																																
Item	Load Regulation 静的負荷変動																																																	
Object	+5V1.2A																																																	
1. Graph		2. Values																																																
<div><div><div>—△—</div><div>Input Volt. 9.0V</div></div><div><div>---□---</div><div>Input Volt. 12.0V</div></div><div><div>---○---</div><div>Input Volt. 18.0V</div></div></div> <div><div>Output Voltage [V]</div><div>Load Current [A]</div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th>Input Volt. 9.0[V]</th><th>Input Volt. 12.0[V]</th><th>Input Volt. 18.0[V]</th></tr><tr><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr><tr><td>0.00</td><td>5.063</td><td>5.063</td><td>5.063</td></tr><tr><td>0.20</td><td>5.063</td><td>5.063</td><td>5.062</td></tr><tr><td>0.40</td><td>5.062</td><td>5.062</td><td>5.062</td></tr><tr><td>0.60</td><td>5.062</td><td>5.062</td><td>5.061</td></tr><tr><td>0.80</td><td>5.061</td><td>5.061</td><td>5.061</td></tr><tr><td>1.00</td><td>5.060</td><td>5.060</td><td>5.060</td></tr><tr><td>1.20</td><td>5.060</td><td>5.060</td><td>5.060</td></tr><tr><td>1.20</td><td>5.060</td><td>5.060</td><td>5.060</td></tr><tr><td>1.32</td><td>5.060</td><td>5.060</td><td>5.059</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>		Load Current [A]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	0.00	5.063	5.063	5.063	0.20	5.063	5.063	5.062	0.40	5.062	5.062	5.062	0.60	5.062	5.062	5.061	0.80	5.061	5.061	5.061	1.00	5.060	5.060	5.060	1.20	5.060	5.060	5.060	1.20	5.060	5.060	5.060	1.32	5.060	5.060	5.059	—	—	—	—
Load Current [A]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]																																															
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																															
0.00	5.063	5.063	5.063																																															
0.20	5.063	5.063	5.062																																															
0.40	5.062	5.062	5.062																																															
0.60	5.062	5.062	5.061																																															
0.80	5.061	5.061	5.061																																															
1.00	5.060	5.060	5.060																																															
1.20	5.060	5.060	5.060																																															
1.20	5.060	5.060	5.060																																															
1.32	5.060	5.060	5.059																																															
—	—	—	—																																															
Note: Slanted line shows the range of the rated load current.																																																		
(注)斜線は定格負荷電流範囲を示す。																																																		

COSEL



COSEL

Model		ZUS61205	
Item		Ripple-Noise リップルノイズ	
Object		+5V1.2A	

1. Graph

-----□----- Input Volt. 9.0V

-----△----- Input Volt. 18.0V

Ripple-Noise

[mV]

250

200

150

100

50

0

0

0.5

1

1.5

Load Current

[A]

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p-p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line

入力商用周期

T2: Due to Switching

スイッチング周期

T2

Ripple-Noise

[mVp-p]

T1

Fig. Complex Ripple Wave Form

図 リップル波形詳細図

2. Values

Load current	Input Volt.	Input Volt.
	9.0 [V]	18.0 [V]
[A]	Ripple-Noise	Ripple-Noise
	[mV]	[mV]
0.00	15	15
0.20	30	20
0.40	40	30
0.60	45	35
0.80	50	45
1.00	65	50
1.20	70	60
1.32	70	65
—	—	—
—	—	—
—	—	—

COSEL


Model ZUS61205

Item Overcurrent Protection
過電流保護

Object +5V1.2A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

2. Values

Output Voltage [V]	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]
5.00	1.66	1.82	1.68
4.75	1.69	1.84	1.68
4.50	1.71	1.86	1.68
4.00	1.76	1.88	1.68
3.50	1.81	1.90	1.66
3.00	1.84	1.90	1.63
2.50	1.87	1.89	1.58
2.00	1.86	1.85	1.52
1.50	1.82	1.76	1.41
1.00	1.75	1.67	1.32
0.50	1.73	1.61	1.26
0.00	1.73	1.64	1.34

COSEL

Model	ZUS61205	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Responce 動的負荷変動	
Object	+5V1.2A	

Input Volt. 12.0 V


Cycle 100 mS

Load Current

Min. Load ↔

Load 100 %


200 mV/div



Min. Load ↔

Load 50 %


200 mV/div



Load 50% ↔

Load 100 %

200 mV/div




1 mS/div

COSEL

Model	ZUS61205	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+5V1.2A		

1. Graph


Input Volt. 9.0 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	0.05	2.35	2.40	0.19	2.15
100 %	0.05	2.55	2.60	0.09	1.05



COSEL


Model ZUS61205

Item Ambient Temperature Drift
周囲温度変動

Object +5V1.2A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

2. Values

Temperature	Input Volt. 9.0[V]	Input Volt. 12.0[V]	Input Volt. 18.0[V]
[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
-30	5.061	5.061	5.061
-20	5.061	5.061	5.061
-10	5.060	5.060	5.060
0	5.060	5.060	5.060
10	5.060	5.060	5.060
25	5.059	5.060	5.059
30	5.059	5.059	5.059
40	5.058	5.058	5.058
55	5.056	5.056	5.055
60	5.055	5.054	5.054
—	—	—	—

COSEL

Model

ZUS61205

Item

Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object


+5V1.2A

Testing Circuitry Figure A

1. Graph

[V]

-----□----- Load 50%
 -----△----- Load 100%



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-30	4.5	5.8
-20	4.4	5.7
-10	4.4	5.6
0	4.2	5.6
10	4.1	5.6
25	4.0	5.7
30	3.9	5.8
40	3.9	6.0
55	3.8	6.2
60	3.8	6.3
—	—	—

COSEL

Model ZUS61205


Item Ripple Voltage (by Ambient Temp.)
リップル電圧 (周囲温度特性)

Object +5V1.2A

Testing Circuitry Figure A

1. Graph

-----□----- Load 50%
 -----△----- Load 100%



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-30	10	20
-20	10	20
-10	5	15
0	5	15
10	5	15
25	5	10
30	5	10
40	5	10
55	5	10
60	5	10
—	—	—

COSEL

Model	ZUS61205	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+5V1.2A	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~55 °C

Input Voltage : 9.0~18.0 V

Load Current : 0.0~1.2 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 : -20~55 °C

入力電圧 : 9.0~18.0 V

負荷電流 : 0.0~1.2 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

* 定電圧精度(変動率) = $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy (Ration) [%]
Maximum Voltage	-20	18.0	0.0	5.065	±5	±0.2
Minimum Voltage	55	18.0	1.2	5.055		

COSEL

COLTEL

Model	ZUS61205
Item	Condensation 結露特性
Object	+5V 1.2A

Testing Circuitry Figure A

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 26°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で -10°C に冷却しておき、約1時間後に恒温槽から取り出し、室温 26°C 、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	5.061	5	45
	2	5.062	5	45
	3	5.062	5	50
Load 100 %	1	5.059	15	75
	2	5.060	15	75
	3	5.059	15	75

Input Volt. 12.0 V

COSEL




Figure A