



TEST DATA OF ZUW1R50515 (5.0V INPUT)

Regulated DC Power Supply

Date : June 14. 1996

Approved by : T. Sugimori
Design Manager

Prepared by : K. Shimano
Design Engineer

コーセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency	2
効率	
3. Load Regulation	3
静的負荷変動	
4. Ripple Voltage (by Load Current)	4
リップル電圧(負荷電流特性)	
5. Ripple-Noise	6
リップルノイズ	
6. Overcurrent Protection	8
過電流保護	
7. Dynamic Load Responce	9
動的負荷変動	
8. Rise and Fall Time	11
立ち上り、立下がり時間	
9. Ambient Temperature Drift	13
周囲温度変動	
10. Minimum Input Voltage for Regulated Output Voltage	14
最低レギュレーション電圧	
11. Ripple Voltage (by Ambient Temperature)	15
リップル電圧(周囲温度特性)	
12. Time Lapse Drift	16
経時ドリフト	
13. Output Voltage Accuracy	17
定電圧精度	
14. Condensation	18
結露特性	
15. Figure of Testing Circuitry	20
測定回路図	



(Final Page 20)

COSEL

Model	ZUW1R50515	Temperature Testing Circuitry	25°C Figure A																																										
Item	Line Regulation 静的入力変動																																												
Object	+15V 0.05A																																												
1. Graph	<p style="text-align: center;">-----□----- Load 50% -----△----- Load 100%</p>																																												
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>15.381</td><td>15.239</td></tr> <tr><td>4.5</td><td>15.374</td><td>15.242</td></tr> <tr><td>5.0</td><td>15.369</td><td>15.243</td></tr> <tr><td>6.0</td><td>15.360</td><td>15.244</td></tr> <tr><td>7.0</td><td>15.354</td><td>15.243</td></tr> <tr><td>8.0</td><td>15.350</td><td>15.242</td></tr> <tr><td>9.0</td><td>15.346</td><td>15.242</td></tr> <tr><td>9.5</td><td>15.345</td><td>15.242</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	4.0	15.381	15.239	4.5	15.374	15.242	5.0	15.369	15.243	6.0	15.360	15.244	7.0	15.354	15.243	8.0	15.350	15.242	9.0	15.346	15.242	9.5	15.345	15.242	-	-	-	-	-	-	-	-	-	-	-	-	
Input Voltage [V]	Load 50%	Load 100%																																											
	Output Volt. [V]	Output Volt. [V]																																											
4.0	15.381	15.239																																											
4.5	15.374	15.242																																											
5.0	15.369	15.243																																											
6.0	15.360	15.244																																											
7.0	15.354	15.243																																											
8.0	15.350	15.242																																											
9.0	15.346	15.242																																											
9.5	15.345	15.242																																											
-	-	-																																											
-	-	-																																											
-	-	-																																											
-	-	-																																											
Object	-15V 0.05A	<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>-15.346</td><td>-15.205</td></tr> <tr><td>4.5</td><td>-15.339</td><td>-15.208</td></tr> <tr><td>5.0</td><td>-15.333</td><td>-15.210</td></tr> <tr><td>6.0</td><td>-15.325</td><td>-15.210</td></tr> <tr><td>7.0</td><td>-15.319</td><td>-15.209</td></tr> <tr><td>8.0</td><td>-15.315</td><td>-15.208</td></tr> <tr><td>9.0</td><td>-15.311</td><td>-15.208</td></tr> <tr><td>9.5</td><td>-15.310</td><td>-15.208</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	4.0	-15.346	-15.205	4.5	-15.339	-15.208	5.0	-15.333	-15.210	6.0	-15.325	-15.210	7.0	-15.319	-15.209	8.0	-15.315	-15.208	9.0	-15.311	-15.208	9.5	-15.310	-15.208	-	-	-	-	-	-	-	-	-	-	-	-
Input Voltage [V]	Load 50%	Load 100%																																											
	Output Volt. [V]	Output Volt. [V]																																											
4.0	-15.346	-15.205																																											
4.5	-15.339	-15.208																																											
5.0	-15.333	-15.210																																											
6.0	-15.325	-15.210																																											
7.0	-15.319	-15.209																																											
8.0	-15.315	-15.208																																											
9.0	-15.311	-15.208																																											
9.5	-15.310	-15.208																																											
-	-	-																																											
-	-	-																																											
-	-	-																																											
-	-	-																																											
1. Graph	<p style="text-align: center;">-----□----- Load 50% -----△----- Load 100%</p>																																												
2. Values																																													
Note:	Slanted line shows the range of the rated input voltage.																																												
(注)	(注) 斜線は定格入力電圧範囲を示す。																																												

COSEL

Model	ZUW1R50515																																										
Item	Efficiency 効率																																										
Object																																											
1. Graph																																											
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																											
<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注) 斜線は定格入力電圧範囲を示す。</p>																																											
Temperature 25°C Testing Circuitry Figure A																																											
2. Values																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Efficiency [%]</th> <th>Efficiency [%]</th> </tr> </thead> <tbody> <tr><td>4.0</td><td>57.2</td><td>64.4</td></tr> <tr><td>4.5</td><td>56.1</td><td>65.6</td></tr> <tr><td>5.0</td><td>55.7</td><td>65.3</td></tr> <tr><td>6.0</td><td>52.2</td><td>64.2</td></tr> <tr><td>7.0</td><td>49.8</td><td>62.3</td></tr> <tr><td>8.0</td><td>46.3</td><td>60.1</td></tr> <tr><td>9.0</td><td>43.7</td><td>58.1</td></tr> <tr><td>9.5</td><td>42.4</td><td>56.9</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Efficiency [%]	Efficiency [%]	4.0	57.2	64.4	4.5	56.1	65.6	5.0	55.7	65.3	6.0	52.2	64.2	7.0	49.8	62.3	8.0	46.3	60.1	9.0	43.7	58.1	9.5	42.4	56.9	—	—	—	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50%	Load 100%																																									
	Efficiency [%]	Efficiency [%]																																									
4.0	57.2	64.4																																									
4.5	56.1	65.6																																									
5.0	55.7	65.3																																									
6.0	52.2	64.2																																									
7.0	49.8	62.3																																									
8.0	46.3	60.1																																									
9.0	43.7	58.1																																									
9.5	42.4	56.9																																									
—	—	—																																									
—	—	—																																									
—	—	—																																									
—	—	—																																									

COSELTemperature 25°C
Testing Circuitry Figure A

COSEL

Model ZUW1R50515

Item Ripple Voltage(by Load Current)
リップル電圧(負荷電流特性)


Object +15V 0.05A

1. Graph

-----□----- Input Volt. 4.5V

[mV]

-----△----- Input Volt. 9.0V

Temperature
Testing Circuitry 25°C
Figure A

2. Values

Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.000	5	5
0.008	5	5
0.016	5	5
0.024	5	5
0.032	10	5
0.040	15	5
0.048	15	5
0.050	18	5
0.055	20	5
-	-	-
-	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期

T2: Due to Switching
スイッチング周期




Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL

Model ZUW1R50515

Item Ripple Voltage(by Load Current)
リップル電圧(負荷電流特性)

Object -15V 0.05A


Temperature
Testing Circuitry25°C
Figure A

1. Graph

-----□----- Input Volt. 4.5V

[mV]

-----△----- Input Volt. 9.0V



2. Values

Load Current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
0.000	5	5
0.008	5	5
0.016	10	5
0.024	10	5
0.032	15	5
0.040	18	5
0.048	18	5
0.050	18	5
0.055	20	5
-	-	-
-	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期

T2: Due to Switching
スイッチング周期

→ ← T2





Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL

Model	ZUW1R50515
Item	Ripple-Noise リップルノイズ
Object	+15V 0.05A

Temperature 25°C
Testing Circuitry Figure A



2. Values

Load current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.000	15	15
0.008	15	15
0.016	15	20
0.024	20	20
0.032	20	20
0.040	20	20
0.048	20	20
0.050	20	20
0.055	25	20
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line 入力商用周期

T2: Due to Switching スイッチング周期





Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL

Model	ZUW1R50515
Item	Ripple-Noise リップルノイズ
Object	-15V 0.05A

Temperature
Testing Circuitry 25°C
Figure A

2. Values

Load current [A]	Input Volt. 4.5 [V]	Input Volt. 9.0 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.000	20	25
0.008	20	30
0.016	20	30
0.024	25	30
0.032	30	30
0.040	30	30
0.048	35	30
0.050	35	30
0.055	35	30
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

- T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期




Fig. Complex Ripple Wave Form


図 リップル波形詳細図

COSEL

Model ZUW1R50515

Item Overcurrent Protection
過電流保護


Object +15V 0.05 A

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]
15.00	0.086	0.089	0.109
14.25	0.114	0.118	0.113
13.50	0.120	0.123	0.117
12.00	0.131	0.134	0.124
10.50	0.142	0.144	0.129
9.00	0.154	0.155	0.135
7.50	0.166	0.165	0.140
6.00	0.176	0.173	0.143
4.50	0.186	0.178	0.145
3.00	0.193	0.183	0.147
1.50	0.203	0.190	0.155
0.00	0.145	0.134	0.161

Object -15V 0.05 A



2. Values

Output Voltage [V]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]
-15.00	0.094	0.101	0.089
-14.25	0.119	0.121	0.116
-13.50	0.124	0.126	0.120
-12.00	0.136	0.136	0.126
-10.50	0.147	0.147	0.133
-9.00	0.159	0.158	0.139
-7.50	0.171	0.168	0.144
-6.00	0.182	0.177	0.148
-4.50	0.191	0.183	0.150
-3.00	0.199	0.189	0.152
-1.50	0.209	0.196	0.160
0.00	0.171	0.139	0.200

Note: Slanted line shows the range of the rated load current.


(注)斜線は定格負荷電流範囲を示す。

COSEL


Model	ZUW1R50515
Item	Dynamic Load Response 動的負荷變動
Object	+15V 0.05A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 5.0 V
Cycle 100 mSLoad CurrentMin. Load ←→
Load 100 %


200 mV/div

Min. Load ←→
Load 50 %

200 mV/div

Load 50% ←→
Load 100 %

200 mV/div



1 mS/div

COSEL

Model	ZUW1R50515
Item	Dynamic Load Response 動的負荷變動
Object	-15V 0.05A

Temperature 25°C
Testing Circuitry Figure A

Input Volt. 5.0 V



Cycle 100 mS

Load Current

Min. Load →

Load 100 %



200 mV/div



Min. Load →

Load 50 %



200 mV/div



Load 50%→

Load 100 %

200 mV/div




1 mS/div

COSEL

Model	ZUW1R50515
Item	Rise and Fall Time 立上り、立下り時間
Object	+15V 0.05A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		0.10	1.55	1.65	0.59	2.56	
100 %		0.10	1.60	1.70	0.39	1.43	




COSEL

Model	ZUW1R50515
Item	Rise and Fall Time 立上り、立下り時間
Object	-15V 0.05A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		0.65	1.00	1.65	0.57	1.44	
100 %		0.65	1.05	1.70	0.37	1.25	



COSEL


Model	ZUW1R50515
Item	Ambient Temperature Drift 周囲温度変動
Object	+15V 0.05A

Testing Circuitry Figure A



2. Values

Temperature [°C]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
-30	15.264	15.264	15.260
-20	15.259	15.260	15.256
-10	15.256	15.256	15.253
0	15.252	15.253	15.250
10	15.250	15.251	15.248
25	15.247	15.248	15.246
30	15.246	15.247	15.246
40	15.244	15.245	15.244
55	15.239	15.241	15.242
60	15.237	15.239	15.241
—	—	—	—



2. Values

Temperature [°C]	Input Volt. 4.5[V]	Input Volt. 5.0[V]	Input Volt. 9.0[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
-30	-15.227	-15.228	-15.225
-20	-15.224	-15.225	-15.222
-10	-15.221	-15.221	-15.218
0	-15.218	-15.219	-15.216
10	-15.215	-15.216	-15.213
25	-15.212	-15.213	-15.211
30	-15.211	-15.212	-15.210
40	-15.209	-15.210	-15.209
55	-15.205	-15.206	-15.207
60	-15.203	-15.204	-15.206
—	—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL


Model ZUW1R50515

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +15V 0.05A

1. Graph

[V]

Load 50%
Load 100%


Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-30	3.1	3.6
-20	3.0	3.5
-10	2.9	3.4
0	2.9	3.3
10	2.8	3.3
25	2.8	3.2
30	2.8	3.2
40	2.7	3.1
55	2.7	3.1
60	2.7	3.0
—	—	—

Object -15V 0.05A

[V]

Load 50%
Load 100%

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-30	3.1	3.6
-20	3.0	3.5
-10	2.9	3.4
0	2.9	3.3
10	2.8	3.3
25	2.8	3.2
30	2.8	3.2
40	2.7	3.1
55	2.7	3.1
60	2.7	3.0
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL


Model	ZUW1R50515
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)
Object	+15V 0.05A

Testing Circuitry

Figure A

1. Graph

-----□----- Load 50%
-----△----- Load 100%




2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-30	20	45
-20	10	30
-10	10	25
0	10	25
10	10	25
25	10	25
30	10	25
40	10	25
55	10	20
60	10	20
-	-	-

1. Graph

-----□----- Load 50%
-----△----- Load 100%



2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-30	20	40
-20	10	30
-10	10	25
0	10	25
10	10	25
25	10	25
30	10	20
40	10	20
55	10	20
60	10	20
-	-	-

Note: Slanted line shows the range of the rated ambient temperature.


(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	ZUW1R50515
Item	Time Lapse Drift 経時ドリフト
Object	+15V 0.05A

Temperature 25 °C
Testing Circuitry Figure A

1. Graph




2. Values

Time since start [H]	Output Voltage [V]
0.0	15.262
0.5	15.259
1.0	15.259
2.0	15.258
3.0	15.258
4.0	15.258
5.0	15.258
6.0	15.258
7.0	15.258
8.0	15.258

Object	-15V 0.05A
--------	------------

1. Graph



2. Values

Time since start [H]	Output Voltage [V]
0.0	-15.215
0.5	-15.201
1.0	-15.201
2.0	-15.201
3.0	-15.201
4.0	-15.202
5.0	-15.202
6.0	-15.202
7.0	-15.201
8.0	-15.202



Model	ZUW1R50515	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20~55 °C

Input Voltage : 4.5~9.0 V

Load Current (AVR 1) : 0.00~0.05 A

(AVR 2) : 0.00~0.05 A

* Output Voltage Accuracy = $\pm (\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -20~55 °C

入力電圧 4.5~9.0 V

負荷電流 (AVR 1) 0.00~0.05 A

(AVR 2) 0.00~0.05 A

* 定電圧精度(変動値) = $\pm (\text{出力電圧の最高値} - \text{出力電圧の最低値}) / 2$

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Object	+15V 0.05A
--------	------------

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	5.0	0.05	15.257		
Minimum Voltage	25	4.5	0.00	14.948	±155	±1.1

Object	-15V 0.05A
--------	------------

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-20	5.0	0.05	-15.223		
Minimum Voltage	55	4.5	0.00	-14.902	±161	±1.1



Model	ZUW1R50515		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+15V 0.05A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	15.102	5	15
	2	15.111	5	15
	3	15.097	5	15
Load 100 %	1	15.021	20	20
	2	15.063	20	20
	3	15.005	20	20

Input Volt. 5.0 V



Model	ZUW1R50515		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	-15V 0.05A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.
- ④ Repeating ①, ② and ③ three times.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を3度行い、異常のないことを確認する。

2. Values

	Times	Output Voltage [V]	Ripple Voltage [mV]	Ripple Noise [mV]
Load 50 %	1	-14.887	10	25
	2	-14.935	10	25
	3	-14.876	10	25
Load 100 %	1	-14.847	20	35
	2	-14.893	20	35
	3	-14.841	20	35

Input Volt. 5.0 V

